

# SPECIFICATIONS

System CPU /Chipset	VIA Eden ULV Processor 1GHz VIA CN896 + VT8237S
System Memory	256MB (CE), 512MB (LX & XP) Expandable up to 2GB DDR2 667MHz SDRAM
Flash Memory	256MB (CE), 512MB (LX & XP) Expandable up to 8GB
I/O Peripheral	1 x VGA (DB-15) 1 x DVI 1 x RJ-45 Giga LAN (available in 2 <sup>nd</sup> LAN) 2 x PS/2 4 x USB 2.0 (2 front, 2 rear) Key Lock DC Power Jack Antenna Jack 1 x Line-out 1 x MIC-in Smart Card Reader (Optional)
Networking	10/100/1000 Mbps (Gigabit LAN) 2 <sup>nd</sup> Gigabit LAN (option) 802.11b/g/n Wireless (Optional)
Audio	Output : 1/8-inch mini, 2 Channel Stereo Input : 1/8-inch, 8-bit mini Microphone
Graphic Resolution	Up to 1920 x 1200 @75Hz
Dimensions	Device : 5.90 x 8.22 x 1.56 (inch) 150 x 209 x 39.8 (mm) Packaging Box : 355 x 220 x 95 (mm) Carton : 500 x 360 x 240 (mm), 5 units/CTN
Weight	Device : 0.86kg (net) Packaging Box : 1.3kg (net) / 1.35kg (gross) Carton : 9.5kg (net) / 10kg (gross)
Power Requirement	External Power Supply : 100~240VAC DC +12V/50W Max. Power Consumption : < 30W
Temperature	Operating : 0~40°C (32~104°F)
Relative Humidity	20% to 80% Non-condensing
Expansions	(a) 2 <sup>nd</sup> Gigabit LAN (Build to Order) (b) Smart Card Reader (c) 802.11b/g/n Wireless (d) VESA Mounting Kit (e) 2.5" HDD Kit (HDD Not Included) * HDD Side Cover / Screws /Bracket



PN	A3500	A3520	A3560	A3580
OS	None	Linux	Win CE	Win XPe

