

L700

Valuable thin client with VIA Eden X2 Dual Core 1GHz / Nano 1GHz CPU + VX900 Chipset, 1 x LAN, 5 x USB, Dual DVI, and optional WLAN module.



Feature

- VIA Eden X2 Dual Core 1GHz / Nano 1GHz CPU with VX900 chipset
- Dual DVI (alternative to serial port)
- 5 USB ports + upper USB chamber with security design
- Optional wireless device (internal WLAN module and WiFi USB adapter)
- Metal VESA Mounting Bracket (optional)
- Label card slot + withdrawable label card (optional)
- Customized side plates and logo clip (optional)



Specification	Model	L700	
Processor	CPU / Chipset	VIA Eden X2 Dual Core 1.0 GHz or Nano 1.0 GHz + VX900	
Memory	RAM	One SO-DIMM socket supports DDR3 800/1066 MHz from 1GB to 4GB	
Display	Resolution	up to 1920x1200x32bit color	
	Video Memory	Supports up to 512MB frame buffer size using system memory	
	Display Data Control	Integrated in VX900	
Audio	Speaker	x 1 (Build-in 1W internal speaker)	
Storage		x 2 (7 pin and 22 pin SATA conn. for DOM)	
I/O Physical	PS/2	x 1 (For K/B or Y cable for mouse and K/B)	
	USB (1.1/2.0)	Front	x 2
		Rear	x 2
		Top	x 1 (within the upper USB chamber)
	Video	DVI-I	x 1 (optional DVI-to-VGA adapter)
		DVI-D	x 1 (alternative to serial port)
	Audio	Mic-in	x 1
Line-out		x 1 (Speaker-out jack)	
Networking	LAN	x 1 (RJ-45, 10/100/1000 Base-T)	
	WLAN	Optional (x 1 Internal USB header for WLAN module) (x 1 Mini PCIe socket as a reserved manufacturing option)	
Environment	Temperature	Operation	32° to 95° F (0° to 35° C)
		Storage	-4° to 140° F (-20° to 60° C)
	Relative Humidity		20% to 80% non-condensing
Power	Power Supply		36W, DC 12V/3A external power adapter
Mounting	Foot Stand	H or V	Vertical
	Metal VESA Mounting Bracket		Optional
Security	Kensington Lock		Yes
OS Support			Linux / Windows CE / Windows XP Embedded / Windows Embedded Standard 7
Physical Characteristics	Chassis Housing		Plastic and metal
	Dimension	Terminal	42 (W) x 198 (H) x 140 (D) mm, N.W.: 1.15 Kg
		Packing : Single Box	85 (W) x 303 (H) x 295 (D) mm
		Packing : Carton	628 (W) x 330 (H) x 455 (D) mm, 10 boxes in one carton
Regulatory Compliance			CE/ FCC

Specifications subject to change without notice.

Mechanical Layout/ Drawing

Front Side View

Rear Side View



Front Side View

1. Power button
2. HDD LED
3. USB 2.0 ports x 2
4. Audio port (MIC-in)
5. Audio port (Line-out)

Rear Side View

6. USB 2.0 ports x 1 (within the upper USB chamber)
7. USB 2.0 ports x 2
8. RJ-45 LAN port
9. PS/2 port
10. Label card slot
11. DVI-D port (alternative to serial port)
12. DVI-I port
13. DC jack
14. Kensington Lock