

L810

High performance Thin Client with Intel® Celeron processor,
1 x LAN, 5 x USB 2.0, 2 x USB 3.0, 1 x DVI-D and 1 x DVI-I



Feature

- Powered by the next generation Intel® Celeron® J1900 Quad-Core 2GHz SoC processor
- Supports dual displays DVI-D & DVI-I
- Supports two USB 3.0 ports and five USB 2.0 ports
- One mPCIe slot for WiFi module


Specification

Processor	CPU	Intel® Celeron® J1900 Quad-Core 2GHz	
Memory	RAM	X 1 SO-DIMM socket for DDR3L 1333MHz RAM up to 8GB	
Display	Resolution	Up to 1920 X 1200	
	Graphic Engine	Intel Gen7	
Audio	Speaker	X 1 (Built-in 1W internal speaker)	
Storage		X 1 22pin SATA conn. for DOM/SSD , Storage active LED	
I/O Physical	DVI-I	X 1(Alternative to Display port , Connect to DP 1.1a device)	
	DVI-D	X 1(Alternative to Display port , Connect to DP 1.1a device)	
	USB 3.0	X 2 (rear)	
	USB 2.0	X 5 (rear X 2 + front X 2 + top X 1)	
	Mic-in	X 1	
	Line-out	X 1	
Networking	LAN	X 1 (RJ-45, 10/100/1000 Base-T)	
	WLAN	(Optional, mPCIe interface)	
Other Expansion	mPCIe Slot	X 1	
Environment	Temperature	Operation	32° to 95° F (0° to 35° C)
		Storage	-4° to 140° F (-20° to 60° C)
	Relative Humidity		20% to 80% non-condensing
Power	Power Supply	36W, DC 12V/3A external power adapter	
Mounting	Foot Stand	Vertical	
	VESA Bracket	(Optional)	
Security	Kensington Lock	Yes	
OS support		Windows Embedded Standard 7 / Win10 IoT Enterprise / Linux per request	
Physical Characteristics	Chassis Housing	Plastic and metal	
	Dimension	Terminal	43 (W) X 196 (H) X 142 (D) mm, N.W.: 1.15 Kg
		Packing : Single Box	85 (W) X 303 (H) X 295 (D) mm
		Packing : Carton	628 (W) X 330 (H) X 455 (D) mm, 10 boxes in one carton
Regulatory Compliance		CE / FCC	


Specifications subject to change without notice.

Drawing

Front View



Rear View



Front View

1. Power button/Power LED
2. HDD LED
3. USB 2.0
4. Mic-in
5. Line-out
6. Cradle

Rear View

7. USB 2.0
8. RJ45
9. USB 2.0
10. USB 3.0
11. Label card slot
12. DVI-I
13. DVI-D
14. DC jack
15. Kensington lock