

Contents

Summary of Changes	1	ThinkCentre M92z (3291) - 20" (TopSeller) - Win 8	70
ThinkCentre M32 Thin Client	2	ThinkCentre M92z (3296) - 20"	71
ThinkCentre M32 (10BV) - Thin Client (TopSeller) - 3-year onsite	3	ThinkCentre M92z (3296) - 20" (Win 8)	72
ThinkCentre M32 (10BM) - Thin Client (GMP)	4	ThinkCentre M92z (3298) - 20" (GMP)	73
ThinkCentre M53 Tiny	5	ThinkCentre M92z (3298) - 20" (GMP) - Win 8	74
ThinkCentre M53 Tiny Platform Specifications	6	ThinkCentre M92z (3318) - 23" (TopSeller)	75
ThinkCentre M53 Tiny (10DC) - TopSeller	7	ThinkCentre M92z (3318) - 23" (TopSeller) - Win 8	76
ThinkCentre M73 Tiny, Small, Mini Tower	8	ThinkCentre M92z (3322) - 23"	77
ThinkCentre M73 Tiny, Small, Mini Tower II	9	ThinkCentre M92z (3325) - 23"	78
ThinkCentre M73 Tiny (10AY) - TopSeller	10	ThinkCentre M92z (3325) - 23" (Win 8)	79
ThinkCentre M73 Tiny (10AX) - GMP	11	ThinkCentre M92z (3327) - 23" (GMP)	80
ThinkCentre M73 Small (10B4) - ES 6.0 (GMP)	12	ThinkCentre M92z (3327) - 23" (GMP) - Win 8	81
ThinkCentre M73 Mini Tower (10B1) - ES 6.0 (GMP)	13	ThinkCentre M92z (3311) - 23" (Multi-touch) - TopSeller	82
ThinkCentre M72z All-In-One	14	ThinkCentre M92z (3314) - 23" (Multi-touch)	83
ThinkCentre M72z (3543) - TopSeller (Win 8)	15	ThinkCentre M92z (3329) - 23" Multi-touch (GMP)	84
ThinkCentre M72z (3549)	16	ThinkCentre M93z All-In-One	85
ThinkCentre M72z (3554)	17	ThinkCentre M93z (10AF) - TopSeller	86
ThinkCentre M72z (3554) - Windows 8	18	ThinkCentre M93z (10AE) - GMP	87
ThinkCentre M72z (3558) - GMP	19	ThinkCentre M93z (10AE) - GMP (Windows 8/8.1)	88
ThinkCentre M72z (3558) - GMP (Thin Client)	20	ThinkCentre M93z (10AD) - Multi-touch (TopSeller)	89
ThinkCentre M72z (3558) - GMP (Win 8)	21	ThinkCentre M93z (10AD) - Multi-touch (TopSeller) - Win 8/8.1	90
ThinkCentre M72z (3512) - Multi-touch (TopSeller)	22	ThinkCentre M93z (10AC) - Multi-touch (GMP)	91
ThinkCentre M72z (3528) - Multi-touch (TopSeller)	23	ThinkCentre M93z (10AC) - Multi-touch (GMP) - Win 8/8.1	92
ThinkCentre M72z (3535) - Multi-touch	24	ThinkCentre Edge 62z	93
ThinkCentre M72z (3535) - Multi-touch - II	25	ThinkCentre Edge 62z (2117) - TopSeller	94
ThinkCentre M72z (3538) - Multi-touch (GMP)	26	ThinkCentre E73 SFF and Tower	95
ThinkCentre M72z (3538) - Multi-touch (GMP) - Thin Client	27	ThinkCentre E73 SFF (10AU) - TopSeller	96
ThinkCentre M73z All-In-One	28	ThinkCentre E73 SFF (10AU) - TopSeller - II	97
ThinkCentre M73z (10BC) - TopSeller (1-year Onsite)	29	ThinkCentre E73 SFF (10AU) - TopSeller - III	98
ThinkCentre M73z (10BC) - TopSeller	30	ThinkCentre E73 SFF (10AW) - ES 6.0 (TopSeller)	99
ThinkCentre M73z (10BB) - GMP	31	ThinkCentre E73 SFF (10AW) - ES 6.0 (TopSeller) - II	100
ThinkCentre M73z (10BB) - GMP (Win8/8.1)	32	ThinkCentre E73 Tower (10AS) - TopSeller	101
ThinkCentre M78 Small and Tower	33	ThinkCentre E73 Tower (10AS) - TopSeller - II	102
ThinkCentre M78 Small (10BS) - ES 5.2 (GMP)	34	ThinkCentre E73 Tower (10AS) - TopSeller - III	103
ThinkCentre M78 Tower (10BN) - ES 5.2	35	ThinkCentre E73 Tower (10AS) - TopSeller - IV	104
ThinkCentre M78 Tower (10BN) - ES 5.2 (GMP)	36	ThinkCentre E73 Tower (10DR) - ES 6.0 (TopSeller)	105
ThinkCentre M79 SFF and Tower	37	ThinkCentre E73 Tower (10DR) - ES 6.0 (TopSeller) - II	106
ThinkCentre M79 SFF Platform Specifications	38	ThinkCentre E73 Tower (10DR) - ES 6.0 (TopSeller) - III	107
ThinkCentre M79 Tower Platform Specifications	39	ThinkCentre E73 Tower (10DR) - ES 6.0 (TopSeller) - IV	108
ThinkCentre M79 SFF (10CU) - TopSeller	40	ThinkCentre E73 Tower (10DR) - TopSeller	109
ThinkCentre M79 SFF (10CT)	41	ThinkCentre E73 Tower (10DR) - TopSeller - II	110
ThinkCentre M79 Tower (10CR) - TopSeller	42	ThinkCentre E93z All-In-One	111
ThinkCentre M79 Tower (10CQ)	43	ThinkCentre E93z All-In-One II	112
Lenovo ThinkCentre M83 Small Pro, Mini Tower	44	ThinkCentre E93z (10B8) - TopSeller	113
ThinkCentre M83 SFF Pro (10AJ) - ES 6.0 (TopSeller)	45	ThinkCentre E93z (10B8) - TopSeller (3-year Onsite)	114
ThinkCentre M83 SFF Pro (10AJ) - ES 6.0 (TopSeller) - II	46	ThinkCentre E93z (10B8) - TopSeller (3-year Onsite) - Win8	115
ThinkCentre M83 SFF Pro (10AH) - ES 6.0 (GMP)	47	ThinkCentre E93z (10B9) - NVIDIA (TopSeller)	116
ThinkCentre M83 Mini Tower (10BE) - ES 6.0 (TopSeller)	48	ThinkCentre E93z (10B9) - NVIDIA (TopSeller) - 3-year (Win8)	117
ThinkCentre M83 Mini Tower (10BE) - ES 6.0 (TopSeller) - II	49	ThinkCentre E93z (10CX) - Touch (TopSeller) - Windows 8.1	118
ThinkCentre M83 Mini Tower (10AG) - ES 6.0 (GMP)	50	ThinkCentre E93z (10BA) - Touch (NVIDIA) - TopSeller	119
ThinkCentre M83z All-In-One	51	ThinkCentre E93z (10BA) - Touch (NVIDIA) - TopSeller (3-year)	120
ThinkCentre M83z Platform Specifications	52	ThinkCentre E93z (10BA) - Touch (NVIDIA) - TopSeller (Win8)	121
ThinkCentre M83z (10C2) - TopSeller	53	ThinkCentre E93z (10BA) - Touch (NVIDIA) - TS (Win8) - 3-year	122
ThinkCentre M83z (10C3)	54	ThinkCentre E93z (10B8) - 3-year Onsite	123
ThinkCentre M93/M93p Tiny, Small Pro, Mini Tower	55	ThinkCentre E93z (10BA) - Touch (NVIDIA) - (Win8.1) - 3-year	124
ThinkCentre M93/M93p Tiny, Small Pro, Mini Tower II	56	Withdrawn Product Books	125
ThinkCentre M93 Tiny (10A5) - TopSeller	57	Legal Information and Trademarks	126
ThinkCentre M93 Mini Tower (10A1) - TopSeller	58		
ThinkCentre M93p Tiny (10AB) - TopSeller	59		
ThinkCentre M93p Tiny (10AA) - GMP	60		
ThinkCentre M93p Tiny (10AA) - GMP - II	61		
ThinkCentre M93p SFF Pro (10A9) - TopSeller	62		
ThinkCentre M93p SFF Pro (10A8)	63		
ThinkCentre M93p SFF Pro (10A8) - GMP	64		
ThinkCentre M93p Mini Tower (10A7) - TopSeller	65		
ThinkCentre M93p Mini Tower (10A6)	66		
ThinkCentre M93p Mini Tower (10A6) - GMP	67		
ThinkCentre M92z All-In-One	68		
ThinkCentre M92z (3280) - 20" (TopSeller) - Win 8	69		

Summary of Changes

This section describes the technical changes made in this edition.

This edition might also include minor corrections and editorial changes which are not identified.

September 9, 2014 - Version 459

Additions in this update

► **New product(s)**

ThinkCentre M53 Tiny announced August 2014 (G-MSL1-P, G-MSL1-Spec, G-MSL1-1)


ThinkCentre M32 Thin Client



Lenovo ThinkCentre M32 Thin Client with Lenovo ThinkVision Monitor



Lenovo ThinkCentre M32 Thin Client



Lenovo ThinkCentre M32 Thin Client



Lenovo ThinkCentre M32 Thin Client



Lenovo ThinkCentre M32 Thin Client (inside view)



Lenovo ThinkCentre M32 Thin Client

ThinkCentre M32 (10BV) - Thin Client (TopSeller) - 3-year onsite

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ⁸	Flash Memory	Optical	Graphics	DP to DVI dongle	Floor stand	Key-board/ Mouse	ENERGY STAR 6.0	Global (G) GMP (P)	OS preload	Ann date (mm/dd/yy)
10BV000C++	Celeron 847	2GBx1	8G DOM Card	None	Intel HD Graphics	None	Floor stand	USB	ES6.0	None	WES 7	12/10/13
10BV000G++	Celeron 847	2GBx1	1G DOM Card	None	Intel HD Graphics	None	Floor stand	USB	None	None	LeTOS	12/10/13

Country Code"++": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)
 Note: models listed above might not be available in all WE countries

- Small and medium business (SMB) model(s), part of the Western Europe TopSeller™ Program
- 3-year limited warranty

Positioning	<i>Mainstream Thin Client with better security and manageability for the enterprise</i>							Preloaded operating system				
Processor	Intel® Celeron® Processor 847 (2 cores / 2 threads, 1.1GHz, 2MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology							Some: Genuine Windows® Embedded Standard 7 (WES 7) Some: LeTOS (Lenovo Terminal Operating System, Linux-based)				
Memory	4GB max, PC3-12800 1600MHz DDR3*, one 204-pin SODIMM socket (notebook) * System automatically clocks down for processors with 1333MHz DDR3 memory controller							Preloaded applications (only some listed)				
Graphics	Intel HD Graphics in processor, uses main memory, DirectX® 10.1, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x2048 (DisplayPort)@60Hz; 2560x1600 (VGA)@60Hz Optional DisplayPort to Single-link DVI-D dongle							- WES 7 only:				
DP dongle								<ul style="list-style-type: none"> • Intel Management Engine Components • RDP Client • Citrix Client • VMware Client • Internet Explorer 9 • Java • Flash • .Net Framework • Microsoft® Silverlight • Echo Agent • Ultra VNC • Adobe Reader • Intel Manageability Engine Firmware Recovery Agent 				
Flash Memory	1GB (LeTOS models) or 8GB (WES 7 models) / DOM (Disk On Module) Card							- LeTOS only:				
Optical	None							<ul style="list-style-type: none"> • xFreeRDP • Citrix ICA Client • VMware View Client • Java • Mozilla Firefox • NX NoMachine Client • X11 Client • VDI-In-A-Box Java Client • AnyConnect VPN Client 				
SATA controller	Serial ATA, SATA 3.0Gb/s support, integrated in chipset							Network-based Thin Client Management Tool - Lenovo Thin Client Manager (LTM)*				
Onboard SATA	one SATA 3.0Gb/s connector for DOM Card							*A license is included with the purchase of M32 and the utility is downloadable from website				
eSATA port	None							Security				
Chipset	Mobile Intel NM70 Express Chipset							<ul style="list-style-type: none"> • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement • Serial port and parallel port disablement 				
Front ports	Four USB 2.0, microphone (3.5mm), headphone (3.5mm)							EPEAT™ Gold rating (WES models)				
Rear ports	Two USB 2.0, ethernet (RJ-45), two PS/2 ports (keyboard and mouse), one parallel, four serial ports (Customizable Pin definition for serial port 2, 3, and 4), one VGA, one DisplayPort							ENERGY STAR® 6.0 (WES models)				
PCIe Mini Card	None							GREENGUARD® certified				
PCIe WLAN	None							RoHS-compliant				
Bluetooth	None							WEEE				
Audio	High Definition (HD) Audio, Realtek® ALC662-VD codec							REACH				
Speaker	None							VMWare Ready Certification				
IEEE 1394	None							Citrix Ready/HDX Ready Certification				
Ethernet	One gigabit ethernet port, Realtek RTL8111F, Wake on LAN®							MS RemoteFX Certification (WES models)				
Intel AMT	None											
Modem	None											
Security chip	None											
Keyboard	Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo											
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo											
Floor Stand	System floor stand for vertical orientation											
VESA mount	Supports VESA 100mm mount standard											
Power supply	65 watts adapter, autosensing 100-240V, 85% PSU											
Machine	<ul style="list-style-type: none"> • Business black color; USFF (2L) • Fan-less, Cable-less Design • (Without stand) 2.2" W X 6.7" D X 8.7" H • (Without stand) 55mm W X 170mm D X 220mm H • (Without stand) 3.3 lb (1.48 kg) in maximum configuration 											
Protocols	Citrix:	ICA, HDX (compatible with XenDesktop and XenApp)										
	Microsoft:	RDP, RemoteFX (WES 7 models only), RDS										
	VMWare:	VMware Horizon View through RDP VMware Horizon View through PCoIP										
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											

See footnotes for important warranty information
 WE model(s) announced December 10, 2013

©Lenovo
 (G-CLVL1-2) December 2013

ThinkCentre M32 (10BM) - Thin Client (GMP)

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ⁸	Flash Memory	Optical	Graphics	DP to DVI dongle	Floor stand	Key-board/ Mouse	ENERGY STAR 6.0	Global (G) GMP (P)	OS preload	Ann date (mm/dd/yy)
10BM0009++	Celeron 807	2GBx1	1G DOM Card	None	Intel HD Graphics	DP to DVI	Floor stand	USB	None	G P	LeTOS	09/03/13
10BM000A++	Celeron 807	2GBx1	8G DOM Card	None	Intel HD Graphics	DP to DVI	Floor stand	USB	ES6.0	G P	WES 7	09/03/13
10BM000B++	Celeron 807	4GBx1	8G DOM Card	None	Intel HD Graphics	DP to DVI	Floor stand	USB	ES6.0	G P	WES 7	09/03/13
10BM0017++	Celeron 847	2GBx1	1G DOM Card	None	Intel HD Graphics	DP to DVI	Floor stand	USB	None	G P	LeTOS	12/24/13
10BM0018++	Celeron 847	2GBx1	8G DOM Card	None	Intel HD Graphics	DP to DVI	Floor stand	USB	ES6.0	G P	WES 7	12/24/13
10BM0019++	Celeron 847	4GBx1	8G DOM Card	None	Intel HD Graphics	DP to DVI	Floor stand	USB	ES6.0	G P	WES 7	12/24/13

Country Code⁹++ : AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)

Note: models listed above might not be available in all WE countries

- Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty
- 3-year limited warranty

Positioning	<i>Mainstream Thin Client with better security and manageability for the enterprise</i>							Preloaded operating system				
Processor	Intel® Celeron® Processor 807 (1 cores / 2 threads, 1.5GHz, 1.5MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Celeron Processor 847 (2 cores / 2 threads, 1.1GHz, 2MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology							Some: Genuine Windows® Embedded Standard 7 (WES 7) Some: LeTOS (Lenovo Terminal Operating System, Linux-based)				
Memory	4GB max, PC3-12800 1600MHz DDR3* , one 204-pin SODIMM socket (notebook) * System automatically clocks down for processors with 1333MHz DDR3 memory controller							Preloaded applications (only some listed)				
Graphics	Intel HD Graphics in processor, uses main memory, DirectX® 10.1, one VGA, one DisplayPort™, supports dual independent display; <i>Maximum resolution:</i> 2560x2048 (DisplayPort)@60Hz; 2560x1600 (VGA)@60Hz Optional DisplayPort to Single-link DVI-D dongle							- WES 7 only: <ul style="list-style-type: none"> ● Intel Management Engine Components ● RDP Client ● Citrix Client ● VMware Client ● Internet Explorer 9 ● Java ● Flash ● .Net Framework ● Microsoft® Silverlight ● Echo Agent ● Ultra VNC ● Adobe Reader ● Intel Manageability Engine Firmware Recovery Agent 				
DP dongle	Optional DisplayPort to Single-link DVI-D dongle							- LeTOS only: <ul style="list-style-type: none"> ● xFreeRDP ● Citrix ICA Client ● VMware View Client ● Java ● Mozilla Firefox ● NX NoMachine Client ● X11 Client ● VDI-In-A-Box Java Client ● AnyConnect VPN Client 				
Flash Memory	1GB (LeTOS models) or 8GB (WES 7 models) / DOM (Disk On Module) Card							Network-based Thin Client Management Tool - Lenovo Thin Client Manager (LTM)* *A license is included with the purchase of M32 and the utility is downloadable from website				
Optical	None											
SATA controller	Serial ATA, SATA 3.0Gb/s support, integrated in chipset											
Onboard SATA	one SATA 3.0Gb/s connector for DOM Card											
eSATA port	None											
Chipset	Mobile Intel NM70 Express Chipset											
Front ports	Four USB 2.0, microphone (3.5mm), headphone (3.5mm)											
Rear ports	Two USB 2.0, ethernet (RJ-45), two PS/2 ports (keyboard and mouse), one parallel, four serial ports (Customizable Pin definition for serial port 2, 3, and 4), one VGA, one DisplayPort											
PCIe Mini Card	None											
PCIe WLAN	None											
Bluetooth	None											
Audio	High Definition (HD) Audio, Realtek® ALC662-VD codec											
Speaker	None											
IEEE 1394	None											
Ethernet	One gigabit ethernet port, Realtek RTL8111F, Wake on LAN®											
Intel AMT	None											
Modem	None											
Security chip	None											
Keyboard	Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo											
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo											
Floor Stand	System floor stand for vertical orientation											
VESA mount	Supports VESA 100mm mount standard											
Power supply	65 watts adapter, autosensing 100-240V, 85% PSU											
Machine	<ul style="list-style-type: none"> ● Business black color; USFF (2L) ● Fan-less, Cable-less Design ● (Without stand) 2.2" W X 6.7" D X 8.7" H ● (Without stand) 55mm W X 170mm D X 220mm H ● (Without stand) 3.3 lb (1.48 kg) in maximum configuration 							Security <ul style="list-style-type: none"> ● Security slot (in rear for attachment of optional Kensington® MicroSaver® cable) ● Power-on password ● Administrator password ● Boot sequence control ● Boot without keyboard and mouse ● Individual USB port disablement ● Serial port and parallel port disablement 				
Protocols	Citrix: Microsoft: VMWare:	ICA, HDX (compatible with XenDesktop and XenApp) RDP, RemoteFX (WES 7 models only), RDS VMware Horizon View through RDP VMware Horizon View through PCoIP					EPEAT™ Gold rating (WES models) ENERGY STAR® 6.0 (WES models) GREENGUARD® certified RoHS-compliant WEEE REACH VMWare Ready Certification Citrix Ready/HDX Ready Certification MS RemoteFX Certification (WES models)					
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											

See footnotes for important warranty information

WE model(s) announced September 3, 2013 or December 24, 2013

©Lenovo

(G-CLVL1-1) January 2014



ThinkCentre M53 Tiny with optional floor stand, wireless keyboard/mouse, and monitor



ThinkCentre M53 Tiny with optional floor stand



ThinkCentre M53 Tiny with optional VESA mount kit



ThinkCentre M53 Tiny with optional optical box



ThinkCentre M53 Tiny with optional I/O box



ThinkCentre M53 Tiny

ThinkCentre M53 Tiny Platform Specifications

Product Specifications Reference (PSREF)

Processor	Intel® Celeron® Processor J1000 Series* for Desktop or Intel Pentium® Processor J2000 Series* for Desktop						Keyboard	<i>Some:</i> Preferred Pro USB Keyboard (USB connector), Lenovo logo <i>Some:</i> Lenovo Slim USB Keyboard (USB connector), black, Lenovo logo <i>Some:</i> Ultralim Plus Wireless Keyboard (2.4GHz via USB receiver), black <i>Some:</i> Enhanced Optical USB Mouse, black, Lenovo logo <i>Some:</i> Ultralim Plus Wireless Mouse (2.4GHz via USB receiver), black	
	Processor	Cores / Threads	Frequency (Max/Base)	Cache	Memory Types	Integrated Graphics	Mouse		
	Celeron J1800	2 / 2	2.58 / 2.41 GHz	1MB	DDR3L-1333	Intel HD			
	Pentium J2900	4 / 4	2.58 / 2.41 GHz	2MB	DDR3L-1333	Intel HD			
	* System-on-Chip (SoC) solution, integrates Intel processor core, Graphics, Memory Controller, and I/O interfaces						Mechanical	<ul style="list-style-type: none"> Tiny (1L), business black color; metal case M53 Tiny only: 7.0" W X 7.2" D X 1.4" H 179mm W X 182mm D X 34.5mm H 2.9 lb (1.3 kg), weight may vary by configuration With VESA mount & optical box: 7.2" W X 7.2" D X 2.55" H 184mm W X 182mm D X 65mm H 4.6 lb (2.1 kg), weight may vary by configuration Optional VESA mount bracket kit, supports VESA 75mm and 100mm Optional system floor stand for vertical orientation 	
Memory	8GB max / DDR3 Low Voltage, DDR3L-1600*, non-parity, one 204-pin SO-DIMM socket * System automatically clocks down for processors with 1333MHz DDR3 memory controller						VESA mount		
Disk	<i>Some:</i> SATA 3.0Gb/s, 2.5" Wide, 5400 or 7200 rpm <i>Some:</i> 500GB (5400 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 3.0Gb/s, 2.5" wide <i>Some:</i> Solid State Drive (SSD) / SATA 3.0Gb/s, 2.5" Wide <i>Some:</i> external optical box with slim DVD-ROM, 12.7mm high, tray-in, via USB <i>Some:</i> external optical box with slim DVD±RW, 12.7mm high, tray-in, via USB						Floor Stand		
Optical	SATA 3.0Gb/s controller, one connectors on planar						Power supply	65 watts AC/DC adapter, autosensing, 88% PSU	
Onboard SATA Media reader	None						Limited warranty ³	<i>Some:</i> 3-years, limited onsite service / service upgrades available <i>Some:</i> 3-years, limited onsite service, IWS (International Warranty Service ⁹) / service upgrades available <i>For Lenovo service upgrade options, please go to S-TC sheet</i>	
Graphics	Intel HD Graphics in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort)@60Hz; 1920x1200 (VGA)@60Hz Optional DisplayPort to DVI-D or DisplayPort to HDMI monitor cable						Preload	<i>Some:</i> Windows® 7 Professional 32/64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit <i>Some:</i> Windows 7 Professional 64-bit Ready to install applications (only some listed) <ul style="list-style-type: none"> Rescue and Recovery™ Password Manager Preloaded applications (only some listed) <ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage System Update ThinkVantage Communication Utility ThinkVantage Device Experience Desktop Power Manager View Management Utility Lenovo Solution Center Lenovo Message Center Plus Lenovo SHAREit Norton™ Internet Security (30 days of virus definitions) Adobe® Reader® Skype™ Microsoft Office preloaded; purchase a product key to activate Cyberlink Power2Go (DVD±RW) Cyberlink PowerProducer (DVD±RW) Evernote® Nitro Pro 	
DP cable	Optional DisplayPort to DVI-D or DisplayPort to HDMI monitor cable							<i>Some:</i> Windows 8.1 64-bit <i>Some:</i> Windows 8.1 Pro 64-bit Web install applications (only some listed) <ul style="list-style-type: none"> Password Manager Preloaded applications (only some listed) <ul style="list-style-type: none"> ThinkVantage System Update Desktop Power Manager Lenovo Solution Center Lenovo Support Lenovo Companion Lenovo SHAREit Lenovo Reach Norton Internet Security (30 days of virus definitions) Skype™ Microsoft Office preloaded; purchase a product key to activate Cyberlink PowerDVD (DVD±RW, DVD) Cyberlink Power2Go (DVD±RW) Cyberlink PowerProducer (DVD±RW) Evernote® Nitro Pro AccuWeather Norton™ Studio Pokki Hightail 	
Chipset	Intel System-on-Chip (SoC) platform								
Front ports	One USB 3.0 (Always On / Powered), one USB 2.0, one microphone (stereo, 3.5mm), one headphone / microphone combo jack (stereo, 3.5mm)								
Rear ports	Three USB 2.0 (optional external optical box or external I/O box occupies one specific USB 2.0 on some models), ethernet (RJ-45), VGA DB-15, DisplayPort, one optional port (USB 2.0 or serial on selected models)								
I/O box	Optional external I/O box, extends four USB 2.0 (two on front and two on rear), one serial, and two PS/2 (for keyboard and mouse), via USB 2.0 port								
Audio support	High Definition (HD) Audio, Realtek ALC283 / optional internal speaker (1.5 watt)								
WLAN ¹³	<i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Realtek RTL8723BE, Wi-Fi + Bluetooth 4.0 combo adapter, 1x1 <i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Realtek RTL8192EE, Wi-Fi + Bluetooth 4.0 combo adapter, 2x2 <i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 7260, Wi-Fi + Bluetooth combo adapter, 2x2								
Bluetooth™	<i>Some:</i> Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter								
Ethernet Modem	One gigabit ethernet port, Realtek RTL8111GN, Wake on LAN® None								
Manageability	None								
Security chip	None								
Security features	<ul style="list-style-type: none"> Security slot (in rear for optional Kensington® MicroSaver® cable) Smart USB protection, allows keyboard/mouse only, blocks all storage devices Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse Individual USB port disablement Optional <i>Chassis intrusion switch</i> 								
Environment	ENERGY STAR® 6.0 (for Windows models only); GREENGUARD®; RoHS-compliant; Cisco EnergyWise compatible; ErP Lot 3								
Accessories	For compatible accessories, please go to TC-AQP sheet								

See footnotes for more detailed information

ThinkCentre M53 Tiny (10DC) - TopSeller

Product Specifications Reference (PSREF)

Type-model	Processor	Memory	Graphics	Storage	External optical / I/O box	WLAN	Optional port	DP Cable	Chassis intrusion switch	Floor Stand	VESA mount	Keyboard/ Mouse	Internal Speaker	Preload	Base Warranty (year)	Global	Ann Date (mm/yy)
10DC0005++	Pentium J2900	4GBx1	Intel HD	500G 5400	None	8723BE	None	None	None	None	Mount	USB	Speaker	Win7 P64 DG Win8.1	3-onsite	No	08/14

Country Code"+": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)

Note: models listed above might not be available in all WE countries

- For detailed platform specifications, please see [ThinkCentre M53 Tiny Platform Specifications sheet](#)

Processor	Intel® Celeron® Processor J1000 Series* for Desktop or Intel Pentium® Processor J2000 Series* for Desktop	Manageability Security chip	None None																		
	<table border="1"> <thead> <tr> <th>Processor</th> <th>Cores / Threads</th> <th>Frequency (Max/Base)</th> <th>Cache</th> <th>Memory Types</th> <th>Integrated Graphics</th> </tr> </thead> <tbody> <tr> <td>Celeron J1800</td> <td>2 / 2</td> <td>2.58 / 2.41 GHz</td> <td>1MB</td> <td>DDR3L-1333</td> <td>Intel HD</td> </tr> <tr> <td>Pentium J2900</td> <td>4 / 4</td> <td>2.58 / 2.41 GHz</td> <td>2MB</td> <td>DDR3L-1333</td> <td>Intel HD</td> </tr> </tbody> </table> <p>* System-on-Chip (SoC) solution, integrates Intel processor core, Graphics, Memory Controller, and I/O interfaces</p>	Processor	Cores / Threads	Frequency (Max/Base)	Cache	Memory Types	Integrated Graphics	Celeron J1800	2 / 2	2.58 / 2.41 GHz	1MB	DDR3L-1333	Intel HD	Pentium J2900	4 / 4	2.58 / 2.41 GHz	2MB	DDR3L-1333	Intel HD	Security features	<ul style="list-style-type: none"> • Security slot (in rear for optional Kensington® MicroSaver® cable) • Smart USB protection, allows keyboard/ mouse only, blocks all storage devices • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement • Optional Chassis intrusion switch
Processor	Cores / Threads	Frequency (Max/Base)	Cache	Memory Types	Integrated Graphics																
Celeron J1800	2 / 2	2.58 / 2.41 GHz	1MB	DDR3L-1333	Intel HD																
Pentium J2900	4 / 4	2.58 / 2.41 GHz	2MB	DDR3L-1333	Intel HD																
Memory	8GB max / DDR3 Low Voltage, DDR3L-1600*, non-parity, one 204-pin SO-DIMM socket * System automatically clocks down for processors with 1333MHz DDR3 memory controller	Keyboard	<p>USB: Preferred Pro USB Keyboard (USB connector), Lenovo logo</p> <p>USB(Slim): Lenovo Slim USB Keyboard (USB connector), black, Lenovo logo</p> <p>2.4G: Ultralim Plus Wireless Keyboard (2.4GHz via USB receiver), black</p>																		
Disk	<p>Some: SATA 3.0Gb/s, 2.5" Wide, 5400 or 7200 rpm</p> <p>Some: 500GB (5400 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 3.0Gb/s, 2.5" wide</p> <p>Some: Solid State Drive (SSD) / SATA 3.0Gb/s, 2.5" Wide</p>	Mouse	<p>USB: Enhanced Optical USB Mouse, black, Lenovo logo</p> <p>2.4G: Ultralim Plus Wireless Mouse (2.4GHz via USB receiver), black</p>																		
Optical	<p>Some: external optical box with slim DVD-ROM, 12.7mm high, tray-in, via USB</p> <p>Some: external optical box with slim DVD±RW, 12.7mm high, tray-in, via USB</p>	Mechanical	<ul style="list-style-type: none"> • Tiny (1L), business black color; metal case M53 Tiny only: 7.0" W X 7.2" D X 1.4" H 179mm W X 182mm D X 34.5mm H 2.9 lb (1.3 kg), weight may vary by configuration With VESA mount & optical box: 7.2" W X 7.2" D X 2.55" H 184mm W X 182mm D X 65mm H 4.6 lb (2.1 kg), weight may vary by configuration 																		
Onboard SATA Media reader	SATA 3.0Gb/s controller, one connectors on planar None	VESA mount	Optional VESA mount bracket kit, supports VESA 75mm and 100mm																		
Graphics	Intel HD Graphics in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort) @60Hz; 1920x1200 (VGA) @60Hz	Floor Stand	Optional system floor stand for vertical orientation																		
DP cable	Optional DisplayPort to DVI-D or DisplayPort to HDMI monitor cable	Power supply	65 watts AC/DC adapter, autosensing, 88% PSU																		
Chipset	Intel System-on-Chip (SoC) platform	Limited warranty ³	<p>Some: 3-years, limited onsite service / service upgrades available</p> <p>Some: 3-years, limited onsite service, IWS (International Warranty Service⁹) / service upgrades available</p> <p>For Lenovo service upgrade options, please go to S-TC sheet</p>																		
Front ports	One USB 3.0 (Always On / Powered), one USB 2.0, one microphone (stereo, 3.5mm), one headphone / microphone combo jack (stereo, 3.5mm)	Preload	<p>Some: Windows® 7 Professional 32/64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit</p> <p>Some: Windows 7 Professional 64</p> <p>Some: Windows 8.1 64-bit</p> <p>Some: Windows 8.1 Pro 64-bit</p> <p>Some: Windows 8.1 with Bing 64-bit</p>																		
Rear ports	Three USB 2.0 (optional external optical box or external I/O box occupies one specific USB 2.0 on some models), ethernet (RJ-45), VGA DB-15, DisplayPort, one optional port (USB 2.0 or serial on selected models)	Environment	ENERGY STAR® 6.0 (for Windows models only); GREENGUARD®; RoHS-compliant; Cisco EnergyWise compatible; ErP Lot 3																		
I/O box	Optional external I/O box, extends four USB 2.0 (two on front and two on rear), one serial, and two PS/2 (for keyboard and mouse), via USB 2.0 port	Accessories	For compatible accessories, please go to TC-AQP sheet																		
Audio support	High Definition (HD) Audio, Realtek ALC283 / optional internal speaker (1.5 watt)																				
WLAN ¹³	<p>Some: 11b/g/n wireless, Realtek RTL8723BE, Wi-Fi + BT 4.0 combo, 1x1</p> <p>Some: 11b/g/n wireless, Realtek RTL8192EE, Wi-Fi + BT 4.0 combo, 2x2</p> <p>Some: 11b/g/n, Intel Centrino® Wireless-N 7260, Wi-Fi + BT combo</p>																				
Bluetooth™	Some: Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter																				
Ethernet	One gigabit ethernet port, Realtek RTL8111GN, Wake on LAN®																				
Modem	None																				

See footnotes for more detailed information

ThinkCentre M73 Tiny, Small, Mini Tower



ThinkCentre M73 Tiny with Optional WLAN



ThinkCentre M73 Tiny with ThinkVision Monitor



ThinkCentre M73 Tiny with optional I/O Box



ThinkCentre M73 Tiny with ThinkVision Monitor



ThinkCentre M73 Tiny with optional External Optical Box



ThinkCentre M73 Tiny

ThinkCentre M73 Tiny, Small, Mini Tower II

ThinkCentre®



ThinkCentre M73 Small and Mini Tower



ThinkCentre M73 Small with ThinkVision Monitor



ThinkCentre M73 Small



ThinkCentre M73 Mini Tower with ThinkVision Monitor



ThinkCentre M73 Mini Tower



ThinkCentre M73 Mini Tower

ThinkCentre M73 Tiny (10AY) - TopSeller

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ^a	SATA disk GB rpm	External optical / I/O box	Graphics	PCIe Mini Card WLAN / BT	Optional port	Chassis intrusion switch	Floor stand	VESA mount	Keyboard / mouse	Preload	Ann date (mm/dd/yy)
10AY000A++	i3-4130T	4GBx1	500G Hybrid	DVD±RW	HD 4400	Intel 2230	None	Switch	None	Mount	USB	Win7 Pro64 (DG)	10/01/13
10AY000B++	i3-4130T	4GBx1	500G Hybrid	None	HD 4400	Intel 2230	None	Switch	Stand	None	USB	Win7 Pro64 (DG)	10/01/13
10AY000C++	G3220T	4GBx1	500G 7200	None	Intel HD	Intel 2230	None	Switch	Stand	None	USB	Win7 Pro64 (DG)	10/01/13
10AY000D++	G3220T	4GBx1	500G 7200	DVD±RW	Intel HD	Intel 2230	None	Switch	None	Mount	USB	Win7 Pro64 (DG)	10/01/13
10AY000E++	G3220T	4GBx1	500G 7200	None	Intel HD	Intel 2230	None	Switch	None	Mount	USB	Win7 Pro64 (DG)	10/01/13
10AY002R++	G3220T	4GBx1	500G 7200	None	Intel HD	Intel 2230	Serial	Switch	Stand	None	USB	Win7 Pro64 (DG)	12/10/13
10AY003S++	G3240T	4GBx1	500G 7200	None	Intel HD	7260 b/g/n	None	Switch	None	Mount	USB	Win7 P64 DG Win8.1	07/08/14
10AY003T++	G3240T	4GBx1	500G 7200	None	Intel HD	7260 b/g/n	Serial	Switch	Stand	None	USB	Win7 P64 DG Win8.1	07/08/14
10AY003U++	G3240T	4GBx1	500G 7200	None	Intel HD	7260 b/g/n	None	Switch	Stand	None	USB	Win7 P64 DG Win8.1	07/08/14
10AY003V++	i3-4150T	4GBx1	500G Hybrid	DVD±RW	HD 4400	7260 b/g/n	None	Switch	None	Mount	USB	Win7 P64 DG Win8.1	07/08/14
10AY003W++	i3-4150T	4GBx1	500G Hybrid	None	HD 4400	7260 b/g/n	None	Switch	Stand	None	USB	Win7 P64 DG Win8.1	07/08/14

Positioning	<i>Essential business features, exceptional value</i>										
Processor	Intel® Pentium® G3220T Processor (2 cores / 2 threads, 2.6GHz, 3MB cache), Intel HD Graphics, 1333MHz DDR3 memory controller Intel Pentium G3240T Processor (2 cores / 2 threads, 2.7GHz, 3MB cache), Intel HD Graphics, 1333MHz DDR3 memory controller Intel Core™ i3-4130T Processor (2 cores / 4 threads, 2.9GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller Intel Core i3-4150T Processor (2 cores / 4 threads, 3.0GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller										
Implementation	Processor in LGA1150 socket										
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook), <i>System automatically clocks down for processors with 1333MHz DDR3 memory controller</i>										
Graphics	Intel HD Graphics or Intel HD Graphics 4400/4600 in processor, uses main memory, one VGA, one DisplayPort™, supports up to dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking)</i>										
DP dongle	None										
Disk	<i>Some: SATA 6.0Gb/s, 2.5" Wide, 7200 rpm</i> <i>Some: 500GB (5400 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 2.5" wide</i>										
External optical	<i>Some: Slim DVD burner box, SATA 1.5Gb/s, 12.7mm high, tray-in, via USB 2.0</i>										
SATA controller	Serial ATA, SATA 6.0Gb/s support, integrated in chipset										
Onboard SATA	One SATA cable (1-drop to device), one SATA 6.0Gb/s connector on planar										
eSATA port	None										
Chipset	Intel H81 Express Chipset										
Front ports	Two USB 3.0 (one Always On / Powered), one microphone (stereo, 3.5mm), one headphone / microphone combo jack (stereo, 3.5mm)										
Rear ports	Three USB 2.0 (optional external optical box or external I/O box occupies one specific USB 2.0 on some models), ethernet (RJ-45), VGA DB-15, DisplayPort connector, one optional port (USB 2.0 / serial on selected models)										
I/O box	Optional external I/O box, extends four USB 2.0 (two on front and two on rear), one serial, and two PS/2 (for keyboard and mouse), via USB 2.0 port										
PCIe Mini Card	One PCI Express® Mini Card slot										
PCIe WLAN	<i>Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2</i> <i>Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Wireless-N 7260, Wi-Fi + Bluetooth combo adapter, 2x2</i>										
Bluetooth	<i>Some: Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter</i>										
Audio	High Definition (HD) Audio, Realtek® ALC283 codec										
Speaker	Internal speaker for business audio (1.5 watt)										
Ethernet	Gigabit ethernet port, Intel I217-V, Wake on LAN®										
Intel AMT	None										
Modem	None										
Security chip	None										
Keyboard	Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo										
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo										
Floor Stand	Optional System floor stand for vertical orientation										
VESA mount	Optional VESA mount bracket kit, supports VESA 75mm and 100mm mount standard										
Power supply	65 watts AC/DC adapter, autosensing, 88% PSU										
Mechanical	<ul style="list-style-type: none"> Tiny (1L), business black color; metal case <i>M73 Tiny only:</i> 7.0" W X 7.2" D X 1.4" H 179mm W X 182mm D X 34.5mm H 2.9 lb (1.3 kg), weight may vary by configuration <i>With VESA mount & optical box:</i> 7.2" W X 7.2" D X 2.55" H 184mm W X 182mm D X 65mm H 5.1lb (2.3 kg), weight may vary by configuration 										
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available										
	Preloaded operating system <i>Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit</i> <i>Some: Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit</i> Ready to install applications (only some listed) <ul style="list-style-type: none"> Rescue and Recovery™ Password Manager Preloaded applications (only some listed) <ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage System Update ThinkVantage Communication Utility ThinkVantage Power Manager View Management Utility PC Device Stage Lenovo Cloud Storage by SugarSync Lenovo Solution Center Lenovo Message Center Plus Norton™ Internet Security (30 days of virus definitions) Adobe® Reader® Skype™ Evernote® Microsoft® Office preloaded; purchase a product key to activate Cyberlink Power2Go (DVD±RW) Cyberlink PowerProducer (DVD±RW) Nitro Pro 										
	Security <ul style="list-style-type: none"> Security slot (in rear for attachment of optional Kensington® MicroSaver® cable) Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse Individual USB port disablement Chassis intrusion switch on selected model(s) 										
	EPEAT™ Gold rating ENERGY STAR® 6.0-compliant Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies										

See footnotes for important warranty information

©Lenovo
(G-MLM1N-1) July 2014

ThinkCentre M73 Tiny (10AX) - GMP

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ^a	SATA disk GB rpm	External optical / I/O box	Graphics	PCIe Mini Card WLAN / BT	Optional port	Chassis intrusion switch	Floor stand	VESA mount	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)
10AX002U++	G3420T	2GBx1	320G 5400	None	Intel HD	Intel 105	None	None	Stand	None	G P	Win7 Pro64	10/01/13
10AX002V++	i3-4130T	4GBx1	500G 5400	None	HD 4400	Intel 2230	None	None	Stand	None	G P	Win7 Pro64 (DG)	10/01/13
10AX003D++	i5-4570T	4GBx1	128G SSD	DVD±RW	HD 4600	Intel 2230	USB	Switch	None	Mount	G P	Win7 Pro64 (DG)	10/01/13
10AX0044++	i5-4570T	4GBx1	500G 7200	None	HD 4600	Intel 2230	None	None	Stand	None	G P	Win7 Pro64 (DG)	10/22/13
10AX0045++	i3-4130T	4GBx1	500G 7200	None	HD 4400	Intel 105	None	None	Stand	None	G P	Win7 Pro64 (DG)	10/22/13
10AX007W++	i5-4590T	4GBx1	128G SSD	DVD±RW	HD 4600	7260 b/g/n	USB	Switch	None	Mount	G P	Win7 P64 DG Win8.1	07/08/14
10AX007X++	i3-4150T	4GBx1	500G 5400	None	HD 4400	7260 b/g/n	None	None	Stand	None	G P	Win7 P64 DG Win8.1	07/08/14

Country Code"+": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)

Note: models listed above might not be available in all WE countries

● Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning	<i>Essential business features, exceptional value</i>										Preloaded operating system		
Processor	Intel® Pentium® G3420T Processor (2 cores / 2 threads, 2.7GHz, 3MB cache), Intel HD Graphics, 1600MHz DDR3 memory controller Intel Core™ i3-4130T Processor (2 cores / 4 threads, 2.9GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller Intel Core i3-4150T Processor (2 cores / 4 threads, 3.0GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller Intel Core i5-4570T Processor (2 cores / 4 threads, 2.9GHz, 4MB cache), Turbo Boost 2.0 (3.6GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i5-4590T Processor (4 cores / 4 threads, 2.0GHz, 4MB cache), Turbo Boost 2.0 (3.0GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Processor in LGA1150 socket										Some: Windows® 7 Professional 64 Some: Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit		
Implementation	Processor in LGA1150 socket										Ready to install applications (only some listed)		
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook), System automatically clocks down for processors with 1333MHz DDR3 memory controller										<ul style="list-style-type: none"> Rescue and Recovery™ Password Manager 		
Graphics	Intel HD Graphics or Intel HD Graphics 4400/4600 in processor, uses main memory, one VGA, one DisplayPort™, supports up to dual independent display; Maximum resolution: 2560x1600 (DisplayPort)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking)										Preloaded applications (only some listed)		
DP dongle	None										<ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage System Update ThinkVantage Communication Utility ThinkVantage Power Manager View Management Utility PC Device Stage Lenovo Cloud Storage by SugarSync Lenovo Solution Center Lenovo Message Center Plus Norton™ Internet Security (30 days of virus definitions) Adobe® Reader® Skype™ Evernote® Microsoft® Office preloaded; purchase a product key to activate Cyberlink Power2Go (DVD±RW) Cyberlink PowerProducer (DVD±RW) Nitro Pro 		
Disk	Some: SATA 3.0Gb/s, 2.5" Wide, 5400 rpm or 7200 rpm Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide												
External optical	Some: Slim DVD burner box, SATA 1.5Gb/s, 12.7mm high, tray-in, via USB 2.0												
SATA controller	Serial ATA, SATA 6.0Gb/s support, integrated in chipset												
Onboard SATA	One SATA cable (1-drop to device), one SATA 6.0Gb/s connector on planar												
eSATA port	None												
Chipset	Intel H81 Express Chipset												
Front ports	Two USB 3.0 (one Always On / Powered), one microphone (stereo, 3.5mm), one headphone / microphone combo jack (stereo, 3.5mm)												
Rear ports	Three USB 2.0 (optional external optical box or external I/O box occupies one specific USB 2.0 on some models), ethernet (RJ-45), VGA DB-15, DisplayPort connector, one optional port (USB 2.0 / serial on selected models)												
I/O box	Optional external I/O box, extends four USB 2.0 (two on front and two on rear), one serial, and two PS/2 (for keyboard and mouse), via USB 2.0 port												
PCIe Mini Card	One PCI Express® Mini Card slot												
PCIe WLAN	Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2 Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 105, 1x1 Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Wireless-N 7260, Wi-Fi + Bluetooth combo adapter, 2x2												
Bluetooth	Some: Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter												
Audio	High Definition (HD) Audio, Realtek® ALC283 codec												
Speaker	Internal speaker for business audio (1.5 watt)												
Ethernet	Gigabit ethernet port, Intel I217-V, Wake on LAN®												
Intel AMT	None												
Modem	None												
Security chip	None										Security		
Keyboard	Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo										<ul style="list-style-type: none"> Security slot (in rear for attachment of optional Kensington® MicroSaver® cable) Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse Individual USB port disablement Chassis intrusion switch on selected model(s) 		
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo												
Floor Stand	Optional System floor stand for vertical orientation												
VESA mount	Optional VESA mount bracket kit, supports VESA 75mm and 100mm mount standard												
Power supply	65 watts AC/DC adapter, autosensing, 88% PSU												
Mechanical	<ul style="list-style-type: none"> Tiny (1L), business black color; metal case M73 Tiny only: <ul style="list-style-type: none"> 7.0" W X 7.2" D X 1.4" H 179mm W X 182mm D X 34.5mm H 2.9 lb (1.3 kg), weight may vary by configuration With VESA mount & optical box: <ul style="list-style-type: none"> 7.2" W X 7.2" D X 2.55" H 184mm W X 182mm D X 65mm H 5.1lb (2.3 kg), weight may vary by configuration 										EPEAT™ Gold rating ENERGY STAR® 6.0-compliant Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant		
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available										Supports ThinkVantage Technologies		

See footnotes for important warranty information

ThinkCentre M73 Small (10B4) - ES 6.0 (GMP)

Product Specifications Reference (PSREF)


Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	PCIe WLAN	Media reader	Graphics	Chassis Intrusion switch	2nd Serial/ Parallel	Optional Rear USB	Floor stand	ENERGY STAR 6.0	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)
10B4001F++	3x4	G3420	2GBx1	500G 7200	DVD	None	None	Intel HD	None	None	None	None	ES6.0	G P	Win7 Pro64	10/01/13
10B4001G++	3x4	i3-4130	4GBx1	500G 7200	DVD±RW	None	None	HD 4400	None	None	None	Stand	ES6.0	G P	Win7 Pro64 (DG)	10/01/13
10B4001H++	3x4	i5-4570	4GBx1	1TB 7200	DVD±RW	N105	Media	HD 8470	Switch	None	None	None	ES6.0	G P	Win7 Pro64 (DG)	10/01/13
10B40020++	3x4	i3-4130	4GBx1	500G 7200	DVD±RW	None	None	HD 4400	None	None	None	Stand	ES6.0	G P	Win7 Pro64	02/04/14
10B4002L++	3x4	G3440	2GBx1	500G 7200	DVD	None	None	Intel HD	None	None	None	None	ES6.0	G P	Win7 Pro64	06/24/14
10B4002M++	3x4	i3-4150	4GBx1	500G 7200	DVD±RW	None	None	HD 4400	None	None	None	Stand	ES6.0	G P	Win7 P64 DG Win8.1	07/08/14
10B4002N++	3x4	i5-4590	4GBx1	1TB 7200	DVD±RW	8723BE	None	GT 620	Switch	None	None	None	ES6.0	G P	Win7 P64 DG Win8.1	07/08/14
Positioning	<i>Essential business features, exceptional value</i>												Preloaded operating system			
Processor	Intel® Pentium® G3420 Processor (2 cores / 2 threads, 3.2GHz, 3MB cache), Intel HD Graphics, 1600MHz DDR3 memory controller Intel® Pentium G3440 Processor (2 cores / 2 threads, 3.3GHz, 3MB cache), Intel HD Graphics, 1600MHz DDR3 memory controller Intel Core™ i3-4130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller Intel® Core™ i3-4150 Processor (2 cores / 4 threads, 3.5GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller Intel Core i5-4570 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i5-4590 Processor (4 cores / 4 threads, 3.3GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller												<i>Some:</i> Windows® 7 Professional 64 <i>Some:</i> Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit <i>Some:</i> Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit			
Implementation	Processor in LGA1150 socket												Ready to install applications (only some listed)			
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets *System automatically clocks down for processors with 1333MHz memory controller												<ul style="list-style-type: none"> Rescue and Recovery™ Password Manager 			
Graphics	Intel HD Graphics or Intel HD Graphics 4400/4600 in processor, uses main memory, one VGA, one DisplayPort™, supports dual independent display, works along with discrete graphics to support up to four independent monitors; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz;</i> 1920x1200 (VGA)@60Hz (Reduced Blanking) <i>Some:</i> AMD Radeon™ HD 8470 , DirectX 11, 3D Hardware Acceleration, 512MB, PCI Express® 2.0 x16 adapter, one VGA, one DisplayPort, 25 watts, <i>Max resolution: 2560x1600 (DisplayPort)@60Hz; 2048x1536 (VGA)@85Hz</i> <i>Some:</i> NVIDIA® GeForce® GT 620 , DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express 2.0 x16 adapter, one VGA, one DisplayPort, 30 watts; <i>Max resolution: 2560x1600 (DisplayPort)@60Hz; 2048x1536 (VGA)@85Hz</i>												Preloaded applications (only some listed) <ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage System Update ThinkVantage Communication Utility ThinkVantage Power Manager View Management Utility PC Device Stage Lenovo Cloud Storage by SugarSync Lenovo Solution Center Lenovo Message Center Plus Norton™ Internet Security (30 days of virus definitions) Adobe® Reader® Skype™ Evernote® Microsoft® Office preloaded; purchase a product key to activate Cyberlink Power2Go (DVD±RW) Cyberlink PowerProducer (DVD±RW) Nitro Pro 			
Disk	<i>Some:</i> SATA 6.0Gb/s, 3.5" Wide, 7200 rpm															
Optical	<i>Some:</i> DVD-ROM DL SATA 1.5Gb/s Drive <i>Some:</i> Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive															
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset															
Onboard SATA	SATA cables match SATA devices (each 1-drop to device), one SATA 3.0Gb/s connector (for optical) and two SATA 6.0Gb/s connectors (for HDD/SSD) on planar															
eSATA port	None															
Media reader	Optional 9-in-1 media reader, internal USB 2.0															
Chipset	Intel H81 Express Chipset															
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)															
Rear ports	Two USB 3.0, two USB 2.0, two optional USB 2.0, serial (9-pin), optional 2nd serial (9-pin), optional parallel (9-pin), keyboard (PS/2), mouse (PS/2), ethernet (RJ-45), VGA DB-15, DisplayPort															
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)															
Audio	High Definition (HD) Audio, Realtek® ALC662 codec															
PCIe WLAN ⁴	<i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 105, 1x1 <i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Realtek RTL8723BE, Wi-Fi/BT 4.0, 1x1 <i>Some:</i> Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter															
Bluetooth	None															
Speaker	Internal speaker for business audio (1 watt)															
IEEE 1394	None															
Ethernet	Gigabit ethernet port, Realtek RTL8111GN, Wake on LAN®															
Manageability	None															
Security chip	None															
Keyboard	Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo												Security <ul style="list-style-type: none"> One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse Serial port I/O control Individual USB port disablement Chassis intrusion switch on selected model(s) 			
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo															
Floor Stand	Optional system floor stand for vertical orientation															
Power supply	<i>Some:</i> 240 watts, autosensing, active PFC, 85% PSU															
Machine	<ul style="list-style-type: none"> Business black color; metal case 13.2" W X 15.0" D X 3.9" H 335mm W X 382mm D X 101mm H 14.6 lb (6.6 kg) in maximum configuration Highlighted optical drive button for easy access 															
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 2.5", N/A, no access, opt 2nd SSD* Bay 4: 1.5", .35" high, access, opt reader* *bay only available on models with HDD/SSD/reader installed															
Slot	Slot 1: Low Profile, PCIe 3.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, PCIe 2.0 x1												EPEAT™ Gold rating ENERGY STAR® 6.0-compliant Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant			
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available												Supports ThinkVantage Technologies			

See footnotes for important warranty information

ThinkCentre M73 Mini Tower (10B1) - ES 6.0 (GMP)

Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory ^a	SATA disk GB rpm	SATA optical	PCIe WLAN	Media reader	Graphics	Chassis Intrusion switch	2nd Serial / Parallel	Optional Rear USB	ENERGY STAR 6.0	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)
10B10011++	3x4	G3420	2GBx1	500G 7200	DVD	None	None	Intel HD	None	None	None	ES6.0	G P	Win7 Pro64	10/01/13
10B10012++	3x4	i3-4130	4GBx1	500G 7200	DVD±RW	None	None	HD 4400	None	None	None	ES6.0	G P	Win7 Pro64 (DG)	10/01/13
10B10017++	3x4	i5-4570	4GBx1	1TB 7200	DVD±RW	N105	Media	HD 8470	Switch	None	None	ES6.0	G P	Win7 Pro64 (DG)	10/01/13
10B1001K++	3x4	i3-4130	4GBx1	500G 7200	DVD±RW	None	None	HD 4400	None	None	None	ES6.0	G P	Win7 Pro64	02/04/14
10B10029US	3x4	i3-4150	4GBx1	500G 7200	DVD±RW	None	None	HD 4400	None	None	None	ES6.0	G P	Win7 P64 DG Win8.1	07/08/14
10B1002AUS	3x4	i5-4590	4GBx1	1TB 7200	DVD±RW	8723BE	None	GT 620	Switch	None	None	ES6.0	G P	Win7 P64 DG Win8.1	07/08/14

Positioning Processor	<i>Essential business features, exceptional value</i> Intel® Pentium® G3420 Processor (2 cores / 2 threads, 3.2GHz, 3MB cache), Intel HD Graphics, 1600MHz DDR3 memory controller Intel Core™ i3-4130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller Intel Core i3-4150 Processor (2 cores / 4 threads, 3.5GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller Intel Core i5-4570 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i5-4590 Processor (4 cores / 4 threads, 3.3GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Processor in LGA1150 socket											Preloaded operating system <i>Some:</i> Windows® 7 Professional 64 <i>Some:</i> Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit <i>Some:</i> Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit			
Implementation Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets *System automatically clocks down for processors with 1333MHz memory controller											Ready to install applications (only some listed) • Rescue and Recovery™ • Password Manager			
Graphics	Intel HD Graphics or Intel HD Graphics 4400/4600 in processor, uses main memory, one VGA, one DisplayPort™, supports dual independent display, works along with discrete graphics to support up to four independent monitors; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking)</i> <i>Some: AMD Radeon™ HD 8470, DirectX 11, 3D Hardware Acceleration, 512MB, PCI Express® 2.0 x16 adapter, one VGA, one DisplayPort, 25 watts, Max resolution: 2560x1600 (DisplayPort)@60Hz; 2048x1536 (VGA)@85Hz</i> <i>Some: NVIDIA® GeForce® GT 620, DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express 2.0 x16 adapter, one VGA, one DisplayPort, 30 watts; Max resolution: 2560x1600 (DisplayPort)@60Hz; 2048x1536 (VGA)@85Hz</i>											Preloaded applications (only some listed) • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Power Manager • View Management Utility • PC Device Stage • Lenovo Cloud Storage by SugarSync • Lenovo Solution Center • Lenovo Message Center Plus • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ • Evernote® • Microsoft® Office preloaded; purchase a product key to activate • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) • Nitro Pro			
Disk Optical	<i>Some:</i> SATA 6.0Gb/s, 3.5" Wide, 7200 rpm <i>Some:</i> DVD-ROM DL SATA 1.5Gb/s Drive <i>Some:</i> Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive														
SATA controller Onboard SATA	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset SATA cables match SATA devices (each 1-drop to device), one SATA 3.0Gb/s connector (for optical) and two SATA 6.0Gb/s connectors (for HDD/SSD) on planar														
eSATA port	None														
Media reader	Optional 9-in-1 media reader, internal USB 2.0														
Chipset	Intel H81 Express Chipset														
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
Rear ports	Two USB 3.0, two USB 2.0, two optional USB 2.0, serial (9-pin), optional 2nd serial (9-pin), optional parallel (9-pin), keyboard (PS/2), mouse (PS/2), ethernet (RJ-45), VGA DB-15, DisplayPort														
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)														
Audio	High Definition (HD) Audio, Realtek® ALC662 codec														
PCIe WLAN ⁴	<i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 105, 1x1 <i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Realtek RTL8723BE, Wi-Fi/BT 4.0, 1x1 <i>Some:</i> Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter														
Bluetooth	None														
Speaker	Internal speaker for business audio (1.5 watt)														
IEEE 1394	None														
Ethernet	Gigabit ethernet port, Realtek RTL8111GN, Wake on LAN®														
Manageability	None														
Modem	None														
Security chip	None														
Keyboard	Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo														
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo														
Power supply	<i>Some:</i> 280 watts, autosensing, active PFC, 85% PSU														
Mechanical	<ul style="list-style-type: none"> • Business black color; metal case • 6.3" W X 16.6" D X 15.3" H (with handle) • 160mm W X 422mm D X 388mm H • 20.7 lb (9.4 kg) in maximum configuration • Handle on top front • Highlighted optical drive button for easy access 														
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, opt disk* Bay 3: 3.5", 1" high, no access, std disk Bay 4: 1.5", .35" high, access, opt reader* *bay only available on models with HDD/SSD/reader installed														
Slot	Slot 1: half-length, full-height, PCIe 3.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x1											Security <ul style="list-style-type: none"> • One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Serial port I/O control • Individual USB port disablement • Chassis intrusion switch on selected model(s) 			
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											EPEAT™ Gold rating ENERGY STAR® 6.0-compliant Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies			

See footnotes for important warranty information



Lenovo ThinkCentre M72z with Frame Stand



Lenovo ThinkCentre M72z with Frame Stand



Lenovo ThinkCentre M72z with Monitor Stand



Lenovo ThinkCentre M72z with Monitor Stand



Dual Independent Display with Optional Lenovo ThinkVision Monitor

ThinkCentre M72z (3543) - TopSeller (Win 8)

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ^a	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Chassis intrusion switch	Serial port	PS/2 port	Stand type	Key-board/Mouse Global	Preload	Ann date (mm/dd/yy)	
3543-A6G	G645	4GBx1	None	500G 7200	Intel HD	11b/g/n	Media	Switch	None	None	Frame	USB	None	Win8 Pro64	10/23/12
3543-A9G	G645	4GBx1	None	500G 7200	Intel HD	11b/g/n	Media	Switch	None	None	Frame	USB	None	Win7 Pro64	10/23/12
3543-B1G	i3-3220	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	Media	Switch	Serial	None	Monitor	2.4G	None	Win7 Pro64	11/13/12
3543-B4G	G2020	4GBx1	None	500G 7200	Intel HD	11b/g/n	Media	Switch	None	None	Frame	USB	None	Win7 Pro64	03/05/13
3543-B5G	G2020	4GBx1	None	500G 7200	Intel HD	11b/g/n	Media	Switch	None	None	Frame	USB	None	Win8 Pro64	03/05/13
3543-C5G	i3-3240	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	Media	Switch	None	None	Monitor	2.4G	None	Win7 Pro64	05/28/13
3543-C8G	G2030	4GBx1	None	500G 7200	Intel HD	11b/g/n	Media	Switch	None	None	Frame	USB	None	Win7 Pro64	06/11/13
3543-C9G	G2030	4GBx1	None	500G 7200	Intel HD	11b/g/n	Media	Switch	None	None	Frame	USB	None	Win8 Pro64	06/11/13
Positioning Processor	Mainstream All-In-One PC for the enterprise Intel® Pentium® G645 Processor (2 cores / 2 threads, 2.9GHz, 3MB cache), integrated Intel HD Graphics, integrated DDR3 memory controller (up to 1066MHz) Intel Pentium G2020 Processor (2 cores / 2 threads, 2.9GHz, 3MB cache), integrated Intel HD Graphics, integrated DDR3 memory controller (up to 1333MHz) Intel Pentium G2030 Processor (2 cores / 2 threads, 3.0GHz, 3MB cache), integrated Intel HD Graphics, integrated DDR3 memory controller (up to 1333MHz) Intel Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated DDR3 memory controller (up to 1600MHz) Intel Core i3-3240 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated DDR3 memory controller (up to 1066MHz) Processor in LGA1155 socket											Preloaded operating system²⁰ <i>Some:</i> Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit <i>Some:</i> Windows 8 Pro 64-bit Preloaded applications (only some listed) - Windows 7 models <ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage Communication Utility ThinkVantage Power Manager Lenovo® Message Center Plus RapidBoot HDD Accelerator Lenovo SimpleTap Adobe® Reader® Corel® Burn.Now™ (DVD±RW) Corel DVD MovieFactory® (DVD±RW) InterVideo WinDVD® (DVD, DVD±RW) - Windows 8 models <ul style="list-style-type: none"> Lenovo Support Lenovo Settings Lenovo Companion Lenovo Cloud Storage Norton™ Studio AccuWeather Evernote® Cyberlink Power2Go (DVD±RW) Cyberlink PowerProducer (DVD±RW) - All models <ul style="list-style-type: none"> ThinkVantage System Update ThinkVantage Automatic lock Utility Lenovo Solution Center View Management Utility Norton Internet Security (30 days of virus definitions) Microsoft® Office preloaded; purchase a product key to activate Skype™ 			
Implementation	Processor in LGA1155 socket														
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook) <i>System automatically clocks down for processors with 1066MHz or 1333MHz DDR3 memory controller</i>														
Graphics	Intel HD Graphics or Intel HD Graphics 2500 in processor, uses main memory, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>														
DP dongle	None														
Display	20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 dynamic contrast ratio														
Multi-touch	None														
Camera	<i>Some:</i> Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, physical switch on/off														
Controls	Front facing buttons for brightness up/auto, brightness down, and power on/off														
Disk	SATA 3.0Gb/s, 3.5" Wide, 7200 rpm														
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable														
Media reader	7-in-1 Single Slot SD media reader														
Chipset	Intel H61 Express Chipset														
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort connector, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)														
Side ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
PCIe Mini Card	One PCI Express® Mini Card slot														
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2														
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter														
Ethernet	One gigabit ethernet port, Realtek® RTL8111E-VB														
Audio	High Definition (HD) Audio, Realtek ALC269Q														
Speaker	Two internal stereo speakers (2watt x 2)														
Intel AMT	None														
Modem	None														
IEEE 1394	None														
Security chip	Trusted Platform Module (TPM 1.2-compliant)														
Keyboard	<i>Some:</i> Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo <i>Some:</i> Ultralim Plus Wireless Keyboard (2.4GHz via USB receiver), black											Security <ul style="list-style-type: none"> Security chip (see information on left) Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse USB port disablement Chassis intrusion switch on selected model(s) 			
Mouse	<i>Some:</i> Enhanced Optical USB Mouse, black, Lenovo logo <i>Some:</i> Ultralim Plus Wireless Mouse (2.4GHz via USB receiver), black														
Power supply	150 watts, autosensing, 85% PSU														
Machine	Model(s) with Non multi-touch, Frame stand: <ul style="list-style-type: none"> Business black color 20.0" W X 4.0" D X 16.2" H 507mm W X 101mm D X 411mm H (including stand) 14.6 lb (6.6 kg) in maximum configuration Handle in rear, removable feet Support VESA mount (100mm) Model(s) with Non multi-touch, Monitor stand: <ul style="list-style-type: none"> Business black color 20.0" W X 8.9" D X 17.0" H 507mm W X 227mm D X 431mm H (including stand) 18.5 lb (8.4 kg) in maximum configuration Tilt: 25° back, -5° forward; Lift: 110mm; Swivel: +/-45° Support VESA mount (100mm) 											EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant			
Limited Warranty	1-year, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											Supports ThinkVantage Technologies			

ThinkCentre M72z (3549)

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ^a	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Chassis intrusion switch	Serial port	PS/2 port	Stand type	Key-board/Mouse Global	Win7 preload	Ann date (mm/dd/yy)
3549-C2G	G640	4GBx1 1600MHz	None	500G 7200	Intel HD	11b/g/n	Media	Switch	None	None	Frame	USB	None	Pro 64 06/19/12
3549-C3G	i3-2130	4GBx1 1600MHz	2.0M	500G 7200	HD 2000	11b/g/n	Media	Switch	Serial	None	Frame	2.4G	None	Pro 64 06/19/12
3549-C6G	i3-2120	4GBx1 1600MHz	2.0M	500G 7200	HD 2000	11b/g/n	Media	Switch	Serial	None	Frame	2.4G	None	Pro 64 06/19/12

• 1-year limited warranty

Positioning Processor	<i>Mainstream All-In-One PC for the enterprise</i> Intel® Pentium® G640 Processor (2 cores / 2 threads, 2.8GHz, 3MB cache) , integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core™ i3-2120 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache) , integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i3-2130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache) , integrated Intel HD 2000 Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket										Preloaded operating system²⁰ Genuine Windows® 7 Professional 64 Ready to install applications (only some listed) • Rescue and Recovery™ • Password Manager • Business-in-a-Box Preloaded applications (only some listed) • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Automatic Lock Utility • ThinkVantage Power Manager • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • RapidBoot HDD Accelerator • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) • InterVideo WinDVD® (DVD, DVD±RW)			
Implementation														
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)													
Graphics	Intel HD Graphics or Intel HD Graphics 2000 in processor, uses main memory, DirectX® 10.1, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>													
DP dongle	None													
Display	20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 dynamic contrast ratio													
Multi-touch	None													
Camera	<i>Some:</i> Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, physical switch on/off													
Controls	Front facing buttons for brightness up/auto, brightness down, and power on/off													
Disk	SATA 3.0Gb/s, 3.5" Wide, 7200 rpm													
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable													
Media reader	7-in-1 Single Slot SD media reader													
Chipset	Intel H61 Express Chipset													
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort connector, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)													
Side ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
PCIe Mini Card	One PCI Express® Mini Card slot													
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2													
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter													
Ethernet	One gigabit ethernet port, Realtek® RTL8111E-VB													
Audio	High Definition (HD) Audio, Realtek ALC269Q													
Speaker	Two internal stereo speakers (2watt x 2)													
Intel AMT	None													
Modem	None													
IEEE 1394	None													
Security chip	Trusted Platform Module (TPM 1.2-compliant)													
Keyboard	<i>Some:</i> Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo <i>Some:</i> Ultralim Plus Wireless Keyboard (2.4GHz via USB receiver), black <i>Some:</i> Enhanced Optical USB Mouse, black, Lenovo logo <i>Some:</i> Ultralim Plus Wireless Mouse (2.4GHz via USB receiver), black													
Mouse														
Power supply	150 watts, autosensing, 85% PSU													
Machine	<i>Model(s) with Non multi-touch, Frame stand:</i> • Business black color • 20.0" W X 4.0" D X 16.2" H • 507mm W X 101mm D X 411mm H (including stand) • 14.6 lb (6.6 kg) in maximum configuration • Handle in rear, removable feet • Support VESA mount (100mm)										Security • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • <i>Chassis intrusion switch on selected model(s)</i>			
Limited Warranty	1-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available										EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies			

ThinkCentre M72z (3554)

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ⁸	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Chassis intrusion switch	Serial port	PS/2 port	Stand type	Key-board/Mouse	Global	Win7 preload	Ann date (mm/dd/yy)
3554-C8G	i3-2130	4GBx1 1600MHz	2.0M	500G 7200	HD 2000	11b/g/n	Media	Switch	Serial	None	Frame	USB	None	Pro 64	06/05/12
3554-G2G	G640	4GBx1 1600MHz	None	500G 7200	Intel HD	11b/g/n	Media	Switch	Serial	None	Frame	USB	None	Pro 64	06/19/12
3554-G3G	i3-2120	4GBx1 1600MHz	2.0M	500G 7200	HD 2000	11b/g/n	Media	Switch	Serial	None	Frame	2.4G	None	Pro 64	06/19/12

●3-year limited warranty

Positioning Processor	<i>Mainstream All-In-One PC for the enterprise</i> Intel® Pentium® G640 Processor (2 cores / 2 threads, 2.8GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core™ i3-2120 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i3-2130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), integrated Intel HD 2000 Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket	Preloaded operating system²⁰ Genuine Windows® 7 Professional 64 Ready to install applications (only some listed) ● Rescue and Recovery™ ● Password Manager ● Business-in-a-Box Preloaded applications (only some listed) ● ThinkVantage® Product Recovery ● ThinkVantage System Update ● ThinkVantage Communication Utility ● ThinkVantage Automatic Lock Utility ● ThinkVantage Power Manager ● View Management Utility ● Lenovo Solution Center ● Lenovo Message Center Plus ● RapidBoot HDD Accelerator ● Lenovo SimpleTap ● Norton™ Internet Security (30 days of virus definitions) ● Adobe® Reader® ● Skype™ for Windows ● Windows Live™ Essentials ● Microsoft® Office preloaded; purchase a product key to activate ● Corel® Burn.Now™ (DVD±RW) ● Corel DVD MovieFactory® (DVD±RW) ● InterVideo WinDVD® (DVD, DVD±RW)
Implementation		
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)	
Graphics	Intel HD Graphics or Intel HD Graphics 2000 in processor, uses main memory, DirectX® 10.1, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>	
DP dongle	None	
Display	20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 dynamic contrast ratio	
Multi-touch	None	
Camera	<i>Some:</i> Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, physical switch on/off	
Controls	Front facing buttons for brightness up/auto, brightness down, and power on/off	
Disk	SATA 3.0Gb/s, 3.5" Wide, 7200 rpm	
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable	
Media reader	7-in-1 Single Slot SD media reader	
Chipset	Intel H61 Express Chipset	
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort connector, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)	
Side ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)	
PCIe Mini Card	One PCI Express® Mini Card slot	
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2	
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter	
Ethernet	One gigabit ethernet port, Realtek® RTL8111E-VB	
Audio	High Definition (HD) Audio, Realtek ALC269Q	
Speaker	Two internal stereo speakers (2watt x 2)	
Intel AMT	None	
Modem	None	
IEEE 1394	None	
Security chip	Trusted Platform Module (TPM 1.2-compliant)	Security ● Security chip (see information on left) ● Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) ● Power-on password ● Administrator password ● Hard disk password ● Boot sequence control ● Boot without keyboard and mouse ● USB port disablement ● <i>Chassis intrusion switch on selected model(s)</i>
Keyboard	<i>Some:</i> Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo <i>Some:</i> Ultralim Plus Wireless Keyboard (2.4GHz via USB receiver), black	
Mouse	<i>Some:</i> Enhanced Optical USB Mouse, black, Lenovo logo <i>Some:</i> Ultralim Plus Wireless Mouse (2.4GHz via USB receiver), black	
Power supply	150 watts, autosensing, 85% PSU	
Machine	<i>Model(s) with Non multi-touch, Frame stand:</i> ● Business black color ● 20.0" W X 4.0" D X 16.2" H ● 507mm W X 101mm D X 411mm H (including stand) ● 14.6 lb (6.6 kg) in maximum configuration ● Handle in rear, removable feet ● Support VESA mount (100mm)	EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available	Supports ThinkVantage Technologies

See footnotes for important warranty information
WE models announced June 5 or June 19, 2012

©Lenovo
(G-MTGI1-3) March 2013

ThinkCentre M72z (3554) - Windows 8

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ¹	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Chassis intrusion switch	Serial port	PS/2 port	Stand type	Key-board/Mouse	Global	Preload	Ann date (mm/dd/yy)
3554-J3G	i3-2130	4GBx1	2.0M	500G 7200	HD 2000	11b/g/n	Media	Switch	None	None	Frame	USB	None	Win8 Pro64	10/23/12
3554-J4G	G645	4GBx1	None	500G 7200	Intel HD	11b/g/n	Media	Switch	None	None	Frame	USB	None	Win8 Pro64	10/23/12
3554-K1G	G645	4GBx1	2.0M	500G 7200	Intel HD	11b/g/n	Media	Switch	Serial	None	Monitor	USB	None	Win7 Pro64	10/23/12
3554-K2G	i3-3220	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	Media	Switch	Serial	None	Monitor	2.4G	None	Win7 Pro64	11/13/12

●3-year limited warranty

Positioning Processor	<p><i>Mainstream All-In-One PC for the enterprise</i> Intel® Pentium® G645 Processor (2 cores / 2 threads, 2.9GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core™ i3-2130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), integrated Intel HD 2000 Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Processor in LGA1155 socket</p>											<p>Preloaded operating system²⁰ Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit</p> <p>Preloaded applications (only some listed) - Windows 7 models</p> <ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage Communication Utility ThinkVantage Power Manager Lenovo® Message Center Plus RapidBoot HDD Accelerator Lenovo SimpleTap Adobe® Reader® Corel® Burn.Now™ (DVD±RW) Corel DVD MovieFactory® (DVD±RW) InterVideo WinDVD® (DVD, DVD±RW) <p>- Windows 8 models</p> <ul style="list-style-type: none"> Lenovo Support Lenovo Settings Lenovo Companion Lenovo Cloud Storage Norton™ Studio AccuWeather Evernote® Cyberlink Power2Go (DVD±RW) Cyberlink PowerProducer (DVD±RW) <p>- All models</p> <ul style="list-style-type: none"> ThinkVantage System Update ThinkVantage Automatic lock Utility Lenovo Solution Center View Management Utility Norton Internet Security (30 days of virus definitions) Microsoft® Office preloaded; purchase a product key to activate Skype™ 			
Implementation	Processor in LGA1155 socket														
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)														
Graphics	<p>Intel HD Graphics / 2000 / 2500 in processor, uses main memory, external digital monitor support via DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort)@60Hz</p>														
DP dongle	None														
Display	<p>20.0" (508mm) HD+ (1600x900) TFT color, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 dynamic contrast ratio</p>														
Multi-touch	None														
Camera	<p>Some: Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, physical switch on/off</p>														
Controls	Front facing buttons for brightness up/auto, brightness down, and power on/off														
Disk	SATA 3.0Gb/s, 3.5" Wide, 7200 rpm														
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable														
Media reader	7-in-1 Single Slot SD media reader														
Chipset	Intel H61 Express Chipset														
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort connector, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)														
Side ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
PCIe Mini Card	One PCI Express® Mini Card slot														
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2														
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter														
Ethernet	One gigabit ethernet port, Realtek® RTL8111E-VB														
Audio	High Definition (HD) Audio, Realtek ALC269Q														
Speaker	Two internal stereo speakers (2watt x 2)														
Intel AMT	None														
Modem	None														
IEEE 1394	None														
Security chip	Trusted Platform Module (TPM 1.2-compliant)														
Keyboard	<p>Some: Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo Some: Ultralim Plus Wireless Keyboard (2.4GHz via USB receiver), black</p>											<p>Security</p> <ul style="list-style-type: none"> Security chip (see information on left) Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse USB port disablement Chassis intrusion switch on selected model(s) 			
Mouse	<p>Some: Enhanced Optical USB Mouse, black, Lenovo logo Some: Ultralim Plus Wireless Mouse (2.4GHz via USB receiver), black</p>														
Power supply	150 watts, autosensing, 85% PSU														
Machine	<p><i>Model(s) with Non multi-touch, Frame stand:</i></p> <ul style="list-style-type: none"> Business black color 20.0" W X 4.0" D X 16.2" H 507mm W X 101mm D X 411mm H (including stand) 14.6 lb (6.6 kg) in maximum configuration Handle in rear, removable feet Support VESA mount (100mm) <p><i>Model(s) with Non multi-touch, Monitor stand:</i></p> <ul style="list-style-type: none"> Business black color 20.0" W X 8.9" D X 17.0" H 507mm W X 227mm D X 431mm H (including stand) 18.5 lb (8.4 kg) in maximum configuration Tilt: 25° back, -5° forward; Lift: 110mm; Swivel: +/-45° Support VESA mount (100mm) 											<p>EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant</p>			
Limited Warranty	<p>3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available</p>											<p>Supports ThinkVantage Technologies</p>			

ThinkCentre M72z (3558) - GMP

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ⁸	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Chassis intrusion switch	Serial port	PS/2 port	Stand type	Key-board/ Mouse	Global (G) GMP (P)	Win7 preload	Ann date (mm/dd/yy)
3558-A2G	i5-3550S	4GBx1 1600MHz	2.0M	250G 7200	HD 2500	11b/g/n	Media	Switch	None	None	Frame	USB	G P	Pro 64	06/05/12
3558-A4G	i5-3570S	4GBx1 1600MHz	2.0M	500G 7200	HD 2500	11b/g/n	Media	Switch	None	None	Frame	USB	G P	Pro 64	08/14/12

●Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning Processor	<i>Mainstream All-In-One PC for the enterprise</i> Intel® Core™ i5-3550S Processor (4 cores / 4 threads, 3.0GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3570S Processor (4 cores / 4 threads, 3.1GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket										Preloaded operating system²⁰ Genuine Windows® 7 Professional 64 Ready to install applications (only some listed) ● Rescue and Recovery™ ● Password Manager ● Business-in-a-Box				
Implementation	Processor in LGA1155 socket										Preloaded applications (only some listed) ● ThinkVantage® Product Recovery ● ThinkVantage System Update ● ThinkVantage Communication Utility ● ThinkVantage Automatic Lock Utility ● ThinkVantage Power Manager ● View Management Utility ● Lenovo Solution Center ● Lenovo Message Center Plus ● RapidBoot HDD Accelerator ● Lenovo SimpleTap ● Norton™ Internet Security (30 days of virus definitions) ● Adobe® Reader® ● Skype™ for Windows ● Windows Live™ Essentials ● Microsoft® Office preloaded; purchase a product key to activate ● Corel® Burn.Now™ (DVD±RW) ● Corel DVD MovieFactory® (DVD±RW) ● InterVideo WinDVD® (DVD, DVD±RW)				
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)														
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>														
DP dongle	None														
Display	20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 dynamic contrast ratio														
Multi-touch	None														
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, physical switch on/off														
Controls	Front facing buttons for brightness up/auto, brightness down, and power on/off														
Disk	SATA 3.0Gb/s, 3.5" Wide, 7200 rpm														
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable														
Media reader	7-in-1 Single Slot SD media reader														
Chipset	Intel H61 Express Chipset										Security ● Security chip (see information on left) ● Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) ● Power-on password ● Administrator password ● Hard disk password ● Boot sequence control ● Boot without keyboard and mouse ● USB port disablement ● <i>Chassis intrusion switch on selected model(s)</i>				
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort connector, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)														
Side ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
PCIe Mini Card	One PCI Express® Mini Card slot														
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2														
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter														
Ethernet	One gigabit ethernet port, Realtek® RTL8111E-VB														
Audio	High Definition (HD) Audio, Realtek ALC269Q														
Speaker	Two internal stereo speakers (2watt x 2)														
Intel AMT	None														
Modem	None														
IEEE 1394	None														
Security chip	Trusted Platform Module (TPM 1.2-compliant)														
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo														
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo														
Power supply	150 watts, autosensing, 85% PSU														
Machine	<i>Model(s) with Non multi-touch, Frame stand:</i> ● Business black color ● 20.0" W X 4.0" D X 16.2" H ● 507mm W X 101mm D X 411mm H (including stand) ● 14.6 lb (6.6 kg) in maximum configuration ● Handle in rear, removable feet ● Support VESA mount (100mm)										EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant				
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available														

ThinkCentre M72z (3558) - GMP (Thin Client)

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ^a	Camera (mega-pixel)	Disk SATA GB	SATA rpm optical	Graphics	PCIe Mini Card WLAN	Media reader	Chassis intrusion switch	Serial port	PS/2 port	Stand type	Key-board/Mouse	Global (G) GMP (P)	Win7 preload (mm/dd/yy)	Ann date	
3558-A5G	G460	2GBx1	1600MHz	None	8G SSD	None	Intel HD	11b/g/n	None	Switch	Serial	None	Frame	USB	G P	Emb 32	11/20/12
3558-A7G	G465	2GBx1	1600MHz	None	8G SSD	None	Intel HD	11b/g/n	None	Switch	Serial	None	Frame	USB	G P	Emb 32	01/08/13
3558-A8G	G470	2GBx1	1600MHz	None	8G SSD	None	Intel HD	11b/g/n	None	Switch	Serial	None	Frame	USB	G P	Emb 32	06/11/13

●Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning Processor	<i>Mainstream All-In-One PC for the enterprise</i> Intel® Celeron® G460 Processor (1 core / 2 threads, 1.8GHz, 1.5MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller Intel Celeron G465 Processor (1 core / 2 threads, 1.9GHz, 1.5MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller Intel Celeron G470 Processor (1 core / 2 threads, 2.0GHz, 1.5MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller	Preloaded operating system²⁰ Genuine Windows® 7 Embedded 32 Preloaded applications (only some listed) <ul style="list-style-type: none"> ● Adobe® Reader® ● Adobe Flash® Player ● Citrix® Receiver ● IIS Web Server ● Microsoft® Management Console ● Microsoft Silverlight ● Remote Desktop Protocol ● ThinPrint .print Client ● TightVNC Viewer ● VMware® View Client ● vWorkspace ● Windows Media Player
Implementation	Processor in LGA1155 socket	Security <ul style="list-style-type: none"> ● Security chip (see information on left) ● Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) ● Power-on password ● Administrator password ● Hard disk password ● Boot sequence control ● Boot without keyboard and mouse ● USB port disablement ● Chassis intrusion switch on selected model(s)
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook), <i>System automatically clocks down for processors with 1066MHz DDR3 memory controller</i>	
Graphics	Intel HD Graphics in processor, uses main memory, HDCP, DirectX® 10.1, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>	
DP dongle	None	
Display	20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 dynamic contrast ratio	
Multi-touch	None	
Camera	None	
Controls	Front facing buttons for brightness up/auto, brightness down, and power on/off	
Disk	Solid State Drive (SSD) / SATA 3.0Gb/s, 2.5" Wide	
Optical	None	
Media reader	None	
Chipset	Intel H61 Express Chipset	
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort connector, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)	
Side ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)	
PCIe Mini Card	One PCI Express® Mini Card slot	
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2	
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter	
Ethernet	One gigabit ethernet port, Realtek® RTL8111E-VB	
Audio	High Definition (HD) Audio, Realtek ALC269Q	
Speaker	Two internal stereo speakers (2watt x 2)	
Intel AMT	None	
Modem	None	
IEEE 1394	None	
Security chip	Trusted Platform Module (TPM 1.2-compliant)	
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo	
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo	
Power supply	150 watts, autosensing, 85% PSU	
Machine	<i>Model(s) with Non multi-touch, Frame stand:</i> <ul style="list-style-type: none"> ● Business black color ● 20.0" W X 4.0" D X 16.2" H ● 507mm W X 101mm D X 411mm H (including stand) ● 14.6 lb (6.6 kg) in maximum configuration ● Handle in rear, removable feet ● Support VESA mount (100mm) 	EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available	For compatible accessories, please go to O-M72Z sheet; For Lenovo service upgrade options, please go to S-TC sheet

ThinkCentre M72z (3558) - GMP (Win 8)

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ⁸	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Chassis intrusion switch	Serial port	PS/2 port	Stand type	Key-board/ Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)	
3558-A3G	i5-3470S	4GBx1	1600MHz	2.0M	500G 7200 HD 2500	11b/g/n	Media	Switch	None	None	Frame	USB	G P	Win8 Pro64	10/23/12
3558-A6G	i5-3470S	4GBx1	1600MHz	2.0M	500G 7200 HD 2500	11b/g/n	Media	None	None	None	Frame	USB	G P	Win7 Pro64	10/23/12

●Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning Processor	<i>Mainstream All-In-One PC for the enterprise</i>											Preloaded operating system²⁰		
Implementation	Intel® Core™ i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit		
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)											Some: Windows 8 Pro 64-bit		
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>											Preloaded applications (only some listed)		
DP dongle	None											- Windows 7 models		
Display	20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 dynamic contrast ratio											<ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage Communication Utility ThinkVantage Power Manager Lenovo® Message Center Plus RapidBoot HDD Accelerator Lenovo SimpleTap Adobe® Reader® Corel® Burn.Now™ (DVD±RW) Corel DVD MovieFactory® (DVD±RW) InterVideo WinDVD® (DVD, DVD±RW) 		
Multi-touch	None											- Windows 8 models		
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, physical switch on/off											<ul style="list-style-type: none"> Lenovo Support Lenovo Settings Lenovo Companion Lenovo Cloud Storage Norton™ Studio AccuWeather Evernote® Cyberlink Power2Go (DVD±RW) Cyberlink PowerProducer (DVD±RW) 		
Controls	Front facing buttons for brightness up/auto, brightness down, and power on/off											- All models		
Disk	SATA 3.0Gb/s, 3.5" Wide, 7200 rpm											<ul style="list-style-type: none"> ThinkVantage System Update ThinkVantage Automatic lock Utility Lenovo Solution Center View Management Utility Norton Internet Security (30 days of virus definitions) Microsoft® Office preloaded; purchase a product key to activate Skype™ 		
Optical Media reader	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable													
Chipset	Intel H61 Express Chipset													
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort connector, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)													
Side ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
PCIe Mini Card	One PCI Express® Mini Card slot													
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2													
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter													
Ethernet	One gigabit ethernet port, Realtek® RTL8111E-VB													
Audio	High Definition (HD) Audio, Realtek ALC269Q													
Speaker	Two internal stereo speakers (2watt x 2)													
Intel AMT	None													
Modem	None													
IEEE 1394	None													
Security chip	Trusted Platform Module (TPM 1.2-compliant)													
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo													
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Power supply	150 watts, autosensing, 85% PSU													
Machine	<i>Model(s) with Non multi-touch, Frame stand:</i> <ul style="list-style-type: none"> Business black color 20.0" W X 4.0" D X 16.2" H 507mm W X 101mm D X 411mm H (including stand) 14.6 lb (6.6 kg) in maximum configuration Handle in rear, removable feet Support VESA mount (100mm) 											Security <ul style="list-style-type: none"> Security chip (see information on left) Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse USB port disablement Chassis intrusion switch on selected model(s) 		
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies		

ThinkCentre M72z (3512) - Multi-touch (TopSeller)

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ⁸	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Chassis intrusion switch	Serial port	PS/2 port	Stand type	Key-board/Mouse	Win7 Global preload	Ann date (mm/dd/yy)
3512-A1G	i3-3220	4GBx1 1600MHz	2.0M	500G 7200	HD 2500	11b/g/n	Media	Switch	Serial	None	Frame	2.4G	None	Pro 64 09/04/12

- Small and medium business (SMB) model(s), part of the Western Europe TopSeller™ Program
- 1-year limited warranty

Positioning Processor	<i>Mainstream All-In-One PC for the enterprise</i> Intel® Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Processor in LGA1155 socket										Preloaded operating system²⁰ Genuine Windows® 7 Professional 64			
Implementation											Ready to install applications (only some listed)			
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)										<ul style="list-style-type: none"> • Rescue and Recovery™ • Passport Manager • Business-in-a-Box Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Automatic Lock Utility • ThinkVantage Power Manager • View Management Utility • Microsoft Touch Pack • Lenovo Solution Center • Lenovo Message Center Plus • RapidBoot HDD Accelerator • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) • InterVideo WinDVD® (DVD, DVD±RW) 			
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>													
DP dongle	None													
Display	20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 dynamic contrast ratio													
Multi-touch	Multi-touch, 2-point support													
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, physical switch on/off													
Controls	Front facing buttons for brightness up/auto, brightness down, and power on/off													
Disk	SATA 3.0Gb/s, 3.5" Wide, 7200 rpm													
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable													
Media reader	7-in-1 Single Slot SD media reader													
Chipset	Intel H61 Express Chipset													
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort connector, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)													
Side ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
PCIe Mini Card	One PCI Express® Mini Card slot													
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2													
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter													
Ethernet	One gigabit ethernet port, Realtek® RTL8111E-VB													
Audio	High Definition (HD) Audio, Realtek ALC269Q													
Speaker	Two internal stereo speakers (2watt x 2)													
Intel AMT	None													
Modem	None													
IEEE 1394	None													
Security chip	Trusted Platform Module (TPM 1.2-compliant)													
Keyboard	Ultraslim Plus Wireless Keyboard (2.4GHz via USB receiver), black													
Mouse	Ultraslim Plus Wireless Mouse (2.4GHz via USB receiver), black													
Power supply	150 watts, autosensing, 85% PSU													
Machine	<i>Model(s) with multi-touch, Frame stand:</i> <ul style="list-style-type: none"> • Business black color • 20.0" W X 4.2" D X 16.2" H • 507mm W X 107mm D X 411mm H (including stand) • 17.5 lb (7.9 kg) in maximum configuration • Handle in rear, removable feet • Support VESA mount (100mm) 										Security <ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • <i>Chassis intrusion switch on selected model(s)</i> 			
Limited Warranty	1-year, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available										EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies			

ThinkCentre M72z (3528) - Multi-touch (TopSeller)

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ⁸	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Chassis intrusion switch	Serial port	PS/2 port	Stand type	Key-board/Mouse	Win7 Global preload	Ann date (mm/dd/yy)
3528-A4G	i5-3470S	4GBx1 1600MHz	2.0M	128G SSD	HD 2500	11b/g/n	Media	Switch	Serial	None	Frame	USB	None	Pro 64 03/05/13

- Small and medium business (SMB) model(s), part of the Western Europe TopSeller™ Program
- 3-year limited warranty

Positioning Processor	<i>Mainstream All-In-One PC for the enterprise</i> Intel® Core™ i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket										Preloaded operating system²⁰ Genuine Windows® 7 Professional 64			
Implementation	Processor in LGA1155 socket										Ready to install applications (only some listed)			
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)										<ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager • Business-in-a-Box 			
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>										Preloaded applications (only some listed)			
DP dongle	None										<ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Automatic Lock Utility • ThinkVantage Power Manager • View Management Utility • Microsoft Touch Pack • Lenovo Solution Center • Lenovo Message Center Plus • RapidBoot HDD Accelerator • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) • InterVideo WinDVD® (DVD, DVD±RW) 			
Display	20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 dynamic contrast ratio													
Multi-touch	Multi-touch, 2-point support													
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, physical switch on/off													
Controls	Front facing buttons for brightness up/auto, brightness down, and power on/off													
Disk	Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide													
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable													
Media reader	7-in-1 Single Slot SD media reader													
Chipset	Intel H61 Express Chipset													
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort connector, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)													
Side ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
PCIe Mini Card	One PCI Express® Mini Card slot													
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2													
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter													
Ethernet	One gigabit ethernet port, Realtek® RTL8111E-VB													
Audio	High Definition (HD) Audio, Realtek ALC269Q													
Speaker	Two internal stereo speakers (2watt x 2)													
Intel AMT	None													
Modem	None													
IEEE 1394	None													
Security chip	Trusted Platform Module (TPM 1.2-compliant)													
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo													
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Power supply	150 watts, autosensing, 85% PSU													
Machine	<i>Model(s) with multi-touch, Frame stand:</i> <ul style="list-style-type: none"> • Business black color • 20.0" W X 4.2" D X 16.2" H • 507mm W X 107mm D X 411mm H (including stand) • 17.5 lb (7.9 kg) in maximum configuration • Handle in rear, removable feet • Support VESA mount (100mm) 										Security <ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • <i>Chassis intrusion switch on selected model(s)</i> 			
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available										EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies			

ThinkCentre M72z (3535) - Multi-touch

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ⁸	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Chassis intrusion switch	Serial port	PS/2 port	Stand type	Key-board/ Mouse	Global	Win7 preload	Ann date (mm/dd/yy)
3535-C6G	G640	4GBx1 1600MHz	2.0M	500G 7200	Intel HD	11b/g/n	Media	Switch	Serial	None	Frame	USB	None	Pro 64	06/19/12
3535-C7G	i3-2120	4GBx1 1600MHz	2.0M	500G 7200	HD 2000	11b/g/n	Media	Switch	Serial	None	Frame	2.4G	None	Pro 64	06/19/12

●3-year limited warranty

Positioning Processor	<i>Mainstream All-In-One PC for the enterprise</i> Intel® Pentium® G640 Processor (2 cores / 2 threads, 2.8GHz, 3MB cache) , integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology	Preloaded operating system²⁰ Genuine Windows® 7 Professional 64 Ready to install applications (only some listed) ● Rescue and Recovery™ ● Password Manager ● Business-in-a-Box
Implementation	Intel Core™ i3-2120 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache) , integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket	Preloaded applications (only some listed) ● ThinkVantage® Product Recovery ● ThinkVantage System Update ● ThinkVantage Communication Utility ● ThinkVantage Automatic Lock Utility ● ThinkVantage Power Manager ● View Management Utility ● Microsoft Touch Pack ● Lenovo Solution Center ● Lenovo Message Center Plus ● RapidBoot HDD Accelerator ● Lenovo SimpleTap ● Norton™ Internet Security (30 days of virus definitions) ● Adobe® Reader® ● Skype™ for Windows ● Windows Live™ Essentials ● Microsoft® Office preloaded; purchase a product key to activate ● Corel® Burn.Now™ (DVD±RW) ● Corel DVD MovieFactory® (DVD±RW) ● InterVideo WinDVD® (DVD, DVD±RW)
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)	
Graphics	Intel HD Graphics or Intel HD Graphics 2000 in processor, uses main memory, DirectX® 10.1, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>	
DP dongle	None	
Display	20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 dynamic contrast ratio	
Multi-touch	Multi-touch, 2-point support	
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, physical switch on/off	
Controls	Front facing buttons for brightness up/auto, brightness down, and power on/off	
Disk	SATA 3.0Gb/s, 3.5" Wide, 7200 rpm	
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable	
Media reader	7-in-1 Single Slot SD media reader	
Chipset	Intel H61 Express Chipset	
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort connector, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)	
Side ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)	
PCIe Mini Card	One PCI Express® Mini Card slot	
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2	
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter	
Ethernet	One gigabit ethernet port, Realtek® RTL8111E-VB	
Audio	High Definition (HD) Audio, Realtek ALC269Q	
Speaker	Two internal stereo speakers (2watt x 2)	
Intel AMT	None	
Modem	None	
IEEE 1394	None	
Security chip	Trusted Platform Module (TPM 1.2-compliant)	
Keyboard	<i>Some:</i> Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo <i>Some:</i> Ultralim Plus Wireless Keyboard (2.4GHz via USB receiver), black	Security ● Security chip (see information on left) ● Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) ● Power-on password ● Administrator password ● Hard disk password ● Boot sequence control ● Boot without keyboard and mouse ● USB port disablement ● Chassis intrusion switch on selected model(s)
Mouse	<i>Some:</i> Enhanced Optical USB Mouse, black, Lenovo logo <i>Some:</i> Ultralim Plus Wireless Mouse (2.4GHz via USB receiver), black	
Power supply	150 watts, autosensing, 85% PSU	
Machine	<i>Model(s) with multi-touch, Frame stand:</i> ● Business black color ● 20.0" W X 4.2" D X 16.2" H ● 507mm W X 107mm D X 411mm H (including stand) ● 17.5 lb (7.9 kg) in maximum configuration ● Handle in rear, removable feet ● Support VESA mount (100mm)	EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available	Supports ThinkVantage Technologies

See footnotes for important warranty information
WE models announced June 19, 2012

©Lenovo
(G-MTGI1-5) March 2013

ThinkCentre M72z (3535) - Multi-touch - II

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ^a	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Chassis intrusion switch	Serial port	PS/2 port	Stand type	Key-board/ Mouse	Global	Win7 preload	Ann date (mm/dd/yy)
3535-D1G	i3-3220	4GBx1 1600MHz	2.0M	500G 7200	HD 2500	11b/g/n	Media	Switch	Serial	None	Frame	2.4G	None	Pro 64	09/04/12

●3-year limited warranty

Positioning Processor	<i>Mainstream All-In-One PC for the enterprise</i> Intel® Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Processor in LGA1155 socket										Preloaded operating system²⁰ Genuine Windows® 7 Professional 64				
Implementation											Ready to install applications (only some listed)				
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)										<ul style="list-style-type: none"> ● Rescue and Recovery™ ● Password Manager ● Business-in-a-Box 				
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>										Preloaded applications (only some listed)				
DP dongle Display	None 20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 dynamic contrast ratio										<ul style="list-style-type: none"> ● ThinkVantage® Product Recovery ● ThinkVantage System Update ● ThinkVantage Communication Utility ● ThinkVantage Automatic Lock Utility ● ThinkVantage Power Manager ● View Management Utility ● Microsoft Touch Pack ● Lenovo Solution Center ● Lenovo Message Center Plus ● RapidBoot HDD Accelerator ● Lenovo SimpleTap ● Norton™ Internet Security (30 days of virus definitions) ● Adobe® Reader® ● Skype™ for Windows ● Windows Live™ Essentials ● Microsoft® Office preloaded; purchase a product key to activate ● Corel® Burn.Now™ (DVD±RW) ● Corel DVD MovieFactory® (DVD±RW) ● InterVideo WinDVD® (DVD, DVD±RW) 				
Multi-touch Camera	Multi-touch, 2-point support Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, physical switch on/off														
Controls	Front facing buttons for brightness up/auto, brightness down, and power on/off														
Disk	SATA 3.0Gb/s, 3.5" Wide, 7200 rpm														
Optical Media reader	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable 7-in-1 Single Slot SD media reader														
Chipset	Intel H61 Express Chipset														
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort connector, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)														
Side ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
PCIe Mini Card	One PCI Express® Mini Card slot														
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2														
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter														
Ethernet	One gigabit ethernet port, Realtek® RTL8111E-VB														
Audio	High Definition (HD) Audio, Realtek ALC269Q														
Speaker	Two internal stereo speakers (2watt x 2)														
Intel AMT	None														
Modem	None														
IEEE 1394	None														
Security chip	Trusted Platform Module (TPM 1.2-compliant)														
Keyboard	Ultraslim Plus Wireless Keyboard (2.4GHz via USB receiver), black														
Mouse	Ultraslim Plus Wireless Mouse (2.4GHz via USB receiver), black														
Power supply	150 watts, autosensing, 85% PSU														
Machine	<i>Model(s) with multi-touch, Frame stand:</i> <ul style="list-style-type: none"> ● Business black color ● 20.0" W X 4.2" D X 16.2" H ● 507mm W X 107mm D X 411mm H (including stand) ● 17.5 lb (7.9 kg) in maximum configuration ● Handle in rear, removable feet ● Support VESA mount (100mm) 										Security <ul style="list-style-type: none"> ● Security chip (see information on left) ● Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) ● Power-on password ● Administrator password ● Hard disk password ● Boot sequence control ● Boot without keyboard and mouse ● USB port disablement ● <i>Chassis intrusion switch on selected model(s)</i> 				
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available										EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant				
										Supports ThinkVantage Technologies					

See footnotes for important warranty information
WE model announced September 4, 2012

©Lenovo
(G-MTGI1-6) March 2013

ThinkCentre M72z (3538) - Multi-touch (GMP)

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ⁸	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Chassis intrusion switch	Serial port	PS/2 port	Stand type	Key-board/ Mouse	Global (G) GMP (P)	Win7 preload	Ann date (mm/dd/yy)
3538-A2G	i5-3550S	4GBx1 1600MHz	2.0M	250G 7200	HD 2500	11b/g/n	Media	Switch	None	None	Frame	USB	G P	Pro 64	06/05/12
3538-A3G	i5-3570S	4GBx1 1600MHz	2.0M	500G 7200	HD 2500	11b/g/n	Media	Switch	None	None	Frame	USB	G P	Pro 64	08/14/12

●Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning Processor	<i>Mainstream All-In-One PC for the enterprise</i> Intel® Core™ i5-3550S Processor (4 cores / 4 threads, 3.0GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3570S Processor (4 cores / 4 threads, 3.1GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket	Preloaded operating system²⁰ Genuine Windows® 7 Professional 64 Ready to install applications (only some listed) ● Rescue and Recovery™ ● Password Manager ● Business-in-a-Box
Implementation	Processor in LGA1155 socket	Preloaded applications (only some listed) ● ThinkVantage® Product Recovery ● ThinkVantage System Update ● ThinkVantage Communication Utility ● ThinkVantage Automatic Lock Utility ● ThinkVantage Power Manager ● View Management Utility ● Microsoft Touch Pack ● Lenovo Solution Center ● Lenovo Message Center Plus ● RapidBoot HDD Accelerator ● Lenovo SimpleTap ● Norton™ Internet Security (30 days of virus definitions) ● Adobe® Reader® ● Skype™ for Windows ● Windows Live™ Essentials ● Microsoft® Office preloaded; purchase a product key to activate ● Corel® Burn.Now™ (DVD±RW) ● Corel DVD MovieFactory® (DVD±RW) ● InterVideo WinDVD® (DVD, DVD±RW)
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)	
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>	
DP dongle	None	
Display	20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 dynamic contrast ratio	
Multi-touch	Multi-touch, 2-point support	
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, physical switch on/off	
Controls	Front facing buttons for brightness up/auto, brightness down, and power on/off	
Disk	SATA 3.0Gb/s, 3.5" Wide, 7200 rpm	
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable	
Media reader	7-in-1 Single Slot SD media reader	
Chipset	Intel H61 Express Chipset	
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort connector, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)	
Side ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)	
PCIe Mini Card	One PCI Express® Mini Card slot	
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2	
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter	
Ethernet	One gigabit ethernet port, Realtek® RTL8111E-VB	
Audio	High Definition (HD) Audio, Realtek ALC269Q	
Speaker	Two internal stereo speakers (2watt x 2)	
Intel AMT	None	
Modem	None	
IEEE 1394	None	
Security chip	Trusted Platform Module (TPM 1.2-compliant)	
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo	
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo	
Power supply	150 watts, autosensing, 85% PSU	
Machine	<i>Model(s) with multi-touch, Frame stand:</i> ● Business black color ● 20.0" W X 4.2" D X 16.2" H ● 507mm W X 107mm D X 411mm H (including stand) ● 17.5 lb (7.9 kg) in maximum configuration ● Handle in rear, removable feet ● Support VESA mount (100mm)	Security ● Security chip (see information on left) ● Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) ● Power-on password ● Administrator password ● Hard disk password ● Boot sequence control ● Boot without keyboard and mouse ● USB port disablement ● <i>Chassis intrusion switch on selected model(s)</i>
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available	EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies

ThinkCentre M72z (3538) - Multi-touch (GMP) - Thin Client

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ^a	Camera (mega-pixel)	Disk SATA GB rpm	SATA optical	Graphics	PCIe Mini Card WLAN	Media reader	Chassis intrusion switch	Serial port	PS/2 port	Stand type	Key-board/Mouse	Global (G) GMP (P)	Win7 preload (mm/dd/yy)	Ann date	
3538-A5G	G460	2GBx1	1600MHz	2.0M	8G SSD	None	Intel HD	11b/g/n	None	Switch	Serial	None	Frame	USB	G P	Emb 32	11/20/12
3538-A6G	G465	2GBx1	1600MHz	2.0M	8G SSD	None	Intel HD	11b/g/n	None	Switch	Serial	None	Frame	USB	G P	Emb 32	01/08/13
3538-A7G	G470	2GBx1	1600MHz	2.0M	8G SSD	None	Intel HD	11b/g/n	None	Switch	Serial	None	Frame	USB	G P	Emb 32	07/23/13

●Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning Processor	<p><i>Mainstream All-In-One PC for the enterprise</i></p> <p>Intel® Celeron® G460 Processor (1 core / 2 threads, 1.8GHz, 1.5MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller</p> <p>Intel Celeron G465 Processor (1 core / 2 threads, 1.9GHz, 1.5MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller</p> <p>Intel Celeron G470 Processor (1 core / 2 threads, 2.0GHz, 1.5MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller</p>	<p>Preloaded operating system²⁰</p> <p>Genuine Windows® 7 Embedded 32</p> <p>Preloaded applications (only some listed)</p> <ul style="list-style-type: none"> ● Adobe® Reader® ● Adobe Flash® Player ● Citrix® Receiver ● IIS Web Server ● Microsoft® Management Console ● Microsoft Silverlight ● Remote Desktop Protocol ● ThinPrint .print Client ● TightVNC Viewer ● VMware® View Client ● vWorkspace ● Windows Media Player
Implementation	Processor in LGA1155 socket	
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook), <i>System automatically clocks down for processors with 1066MHz DDR3 memory controller</i>	
Graphics	Intel HD Graphics in processor, uses main memory, HDCP, DirectX® 10.1, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>	
DP dongle	None	
Display	20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 dynamic contrast ratio	
Multi-touch	Multi-touch, 2-point support	
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, physical switch on/off	
Controls	Front facing buttons for brightness up/auto, brightness down, and power on/off	
Disk	Solid State Drive (SSD) / SATA 3.0Gb/s, 2.5" Wide	
Optical	None	
Media reader	None	
Chipset	Intel H61 Express Chipset	
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort connector, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)	
Side ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)	
PCIe Mini Card	One PCI Express® Mini Card slot	
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2	
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter	
Ethernet	One gigabit ethernet port, Realtek® RTL8111E-VB	
Audio	High Definition (HD) Audio, Realtek ALC269Q	
Speaker	Two internal stereo speakers (2watt x 2)	
Intel AMT	None	
Modem	None	
IEEE 1394	None	
Security chip	Trusted Platform Module (TPM 1.2-compliant)	<p>Security</p> <ul style="list-style-type: none"> ● Security chip (see information on left) ● Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) ● Power-on password ● Administrator password ● Hard disk password ● Boot sequence control ● Boot without keyboard and mouse ● USB port disablement ● <i>Chassis intrusion switch on selected model(s)</i>
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo	
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo	
Power supply	150 watts, autosensing, 85% PSU	
Machine	<p><i>Model(s) with multi-touch, Frame stand:</i></p> <ul style="list-style-type: none"> ● Business black color ● 20.0" W X 4.2" D X 16.2" H ● 507mm W X 107mm D X 411mm H (including stand) ● 17.5 lb (7.9 kg) in maximum configuration ● Handle in rear, removable feet ● Support VESA mount (100mm) 	<p>EPEAT™ Gold rating</p> <p>ENERGY STAR® 5.2-compliant</p> <p>TCO Certified Edge</p> <p>Cisco EnergyWise compatible</p> <p>GREENGUARD® certified</p> <p>RoHS-compliant</p>
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available	Supports ThinkVantage Technologies

See footnotes for important warranty information
WE models announced November 20, 2012 or January 8 or July 23, 2013

©Lenovo
(G-MTGI1-12) August 2013



ThinkCentre M73z with Frame Stand and optional wireless keyboard and mouse



ThinkCentre M73z with Monitor Stand and optional wireless keyboard and mouse



ThinkCentre M73z with Frame Stand with optional PS/2 and Serial ports



ThinkCentre M73z with Monitor Stand with optional PS/2 and Serial ports



ThinkCentre M73z with Frame Stand with optional wireless keyboard and mouse



ThinkCentre M73z with Monitor Stand with optional wireless keyboard and mouse

ThinkCentre M73z (10BC) - TopSeller (1-year Onsite)

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ⁵	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Chassis intrusion switch	Serial & PS/2 port	Stand type	Key-board/Mouse	Global	Preload	Ann date (mm/dd/yy)
10BC000J++	G3220	4GBx1	None	500G 7200	Intel HD	N2230	Media	Switch	None	Frame	USB	None	Win7 Pro64 DG	09/24/13
10BC000K++	i3-4130	4GBx1	720p	500G 7200	HD 4400	N2230	Media	Switch	None	Monitor	USB	None	Win7 Pro64 DG	09/24/13
10BC000L++	i3-4130	4GBx1	720p	500G Hybrid	HD 4400	N2230	Media	Switch	None	Monitor	2.4G	None	Win7 Pro64 DG	09/24/13
10BC000MIX	G3220	4GBx1	None	500G 7200	Intel HD	N2230	Media	Switch	None	Frame	USB	None	Win7 Pro64 DG	11/12/13
10BC000NIX	i3-4130	4GBx1	720p	500G 7200	HD 4400	N2230	Media	Switch	None	Monitor	USB	None	Win7 Pro64 DG	11/12/13
10BC000PIX	i3-4130	4GBx1	720p	500G Hybrid	HD 4400	N2230	Media	Switch	None	Monitor	2.4G	None	Win7 Pro64 DG	11/12/13
10BC0017++	i3-4150	4GBx1	720p	500G Hybrid	HD 4400	N7260	Media	Switch	None	Monitor	2.4G	None	Win7 P64 DG Win8.1	07/15/14
10BC0018++	i3-4150	4GBx1	720p	500G 7200	HD 4400	N7260	Media	Switch	None	Monitor	USB	None	Win7 P64 DG Win8.1	07/15/14
10BC0019++	G3240	4GBx1	None	500G 7200	Intel HD	N7260	Media	Switch	None	Frame	USB	None	Win7 P64 DG Win8.1	07/15/14

Country Code⁺⁺: AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)
 Note: models listed above might not be available in all WE countries

Positioning	Mainstream All-In-One PC for the enterprise											Preloaded operating system²⁰		
Processor	Intel® Pentium® G3220 Processor (2 cores / 2 threads, 3.0GHz, 3MB cache), Intel HD Graphics, 1333MHz DDR3 memory controller Intel Pentium G3240 Processor (2 cores / 2 threads, 3.1GHz, 3MB cache), Intel HD Graphics, 1333MHz DDR3 memory controller Intel Core™ i3-4130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller Intel Core i3-4150 Processor (2 cores / 4 threads, 3.5GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller Processor in LGA1150 socket											Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit		
Implementation	Processor in LGA1150 socket											Ready to install applications (only some listed)		
Memory	16GB max, 1600MHz DDR3L , two 204-pin SODIMM sockets (notebook) *System automatically clocks down for processors with 1333MHz memory controller											<ul style="list-style-type: none"> ● Rescue and Recovery™ ● Password Manager 		
Graphics	Intel HD Graphics or Intel HD Graphics 4400/4600 in processor, uses main memory, external digital monitor support via VGA, supports dual independent display; <i>Maximum resolution:</i> 1600x900 (panel) @60Hz; 1920x1200 (VGA) @60Hz (Reduced Blanking)											Preloaded applications (only some listed)		
DP dongle	None											<ul style="list-style-type: none"> ● ThinkVantage® Product Recovery ● ThinkVantage System Update ● ThinkVantage Communication Utility ● ThinkVantage Device Experience ● ThinkVantage AutoLock ● Desktop Power Manager ● View Management Utility ● Lenovo Cloud Storage by SugarSync ● Lenovo Solution Center ● Lenovo Message Center Plus ● Norton™ Internet Security (30 days of virus definitions) ● Adobe® Reader® ● Skype™ ● Microsoft Office preloaded; purchase a product key to activate ● Cyberlink Power2Go (DVD±RW) ● Cyberlink PowerProducer (DVD±RW) ● Evernote ● Intel AppUp ● Nitro Pro 		
Display	20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio													
Multi-touch	None													
Camera	Optional camera on top of screen, 1.0-megapixel, fixed focus, supports 720p, with digital microphone, physical switch on/off													
Controls	Side buttons for brightness up, brightness down, and power on/off													
Disk	Some: SATA 6.0Gb/s, 3.5" Wide, 7200 rpm Some: 500GB (5400 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 2.5" wide													
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high													
Media reader	Optional 7-in-1 Single Slot media reader, via internal USB 2.0													
Chipset	Intel H81 Express Chipset													
Rear ports	Four USB 2.0, ethernet (RJ-45), VGA out connector, optional serial (9-pin), two optional PS/2 ports (keyboard and mouse)													
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
PCIe Mini Card	One PCI Express® Mini Card slot													
PCIe WLAN	Some: 11b/g/n wireless, Intel Centrino® Wireless-N 2230, Wi-Fi + BT4.0 combo, 2x2 Some: 11b/g/n wireless, Intel Wireless-N 7260, Wi-Fi + BT4.0 combo, 2x2													
Bluetooth	Some: Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter													
Ethernet	One gigabit ethernet port, Intel I217-V													
Audio	High Definition (HD) Audio, Realtek ALC269VC													
Speaker	Two internal stereo speakers (2watt x 2)													
Intel AMT	None													
Modem	None													
IEEE 1394	None													
Security chip	Trusted Platform Module (TPM 1.2-compliant)											Security		
Keyboard	Some: Preferred Pro USB Keyboard (USB connector), Lenovo® logo Some: Ultralim Plus Wireless Keyboard (2.4GHz via USB receiver), black											<ul style="list-style-type: none"> ● Security chip (see information on left) ● Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) ● Power-on password ● Administrator password ● Hard disk password ● Boot sequence control ● Boot without keyboard and mouse ● USB port disablement ● Chassis intrusion switch on selected model(s) 		
Mouse	Some: Enhanced Optical USB Mouse, Lenovo logo Some: Ultralim Plus Wireless Mouse (2.4GHz via USB receiver), black													
Power supply	150 watts, autosensing, 85% PSU													
Mechanical	<ul style="list-style-type: none"> ● Business black color ● Carry handle in rear ● Support VESA mount (100mm) With Frame stand: 19.9" W X 3.56" D X 15.9" H 506mm W X 90.5mm D X 404.75mm H 16.4 lb (7.46 kg) in maximum configuration Adjustable stand (between 10° and 35°) With Monitor stand: 19.9" W X 9.83" D X 16.7" H 506mm W X 249.8mm D X 423.9mm H 19.5 lb (8.84 kg) in maximum configuration Tilt: 10° to 25°; Lift: 110mm; Swivel: +/-45°											EPEAT™ Gold rating ENERGY STAR® 6.0-compliant Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant EuP 2013 Certified		
Limited Warranty	1-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											Supports ThinkVantage Technologies		

See footnotes for important warranty information

©Lenovo
(G-MDST1-1) July 2014

ThinkCentre M73z (10BC) - TopSeller

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ^a	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Chassis intrusion switch	Serial PS/2 port	Stand type	Key-board/Mouse	Global	Preload	Ann date (mm/dd/yy)
10BC0012++	i5-4430S	8GBx1	720p	500G 7200	HD 4600	N7260	Media	Switch	None	Frame	2.4G	None	Win7 P64 DG	Win8.1 02/11/14
10BC0016++	i5-4460S	8GBx1	720p	500G 7200	HD 4600	N7260	Media	Switch	None	Frame	2.4G	None	Win7 P64 DG	Win8.1 07/15/14

Country Code^{a++}: AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)
 Note: models listed above might not be available in all WE countries

- Small and medium business (SMB) model(s), part of the Westen Europe TopSeller™ Program
- 3-year limited warranty

Positioning	<i>Mainstream All-In-One PC for the enterprise</i>										
Processor	Intel® Core™ i5-4430S Processor (4 cores / 4 threads, 2.7GHz, 6MB cache), Turbo Boost 2.0 (3.2GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i5-4460S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.4GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller										
Implementation	Processor in LGA1150 socket										
Memory	16GB max, 1600MHz DDR3L , two 204-pin SODIMM sockets (notebook) *System automatically clocks down for processors with 1333MHz memory controller										
Graphics	Intel HD Graphics or Intel HD Graphics 4400/4600 in processor, uses main memory, external digital monitor support via VGA, supports dual independent display; <i>Maximum resolution: 1600x900 (panel) @60Hz; 1920x1200 (VGA) @60Hz (Reduced Blanking)</i>										
DP dongle	None										
Display	20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio										
Multi-touch	None										
Camera	Optional camera on top of screen, 1.0-megapixel, fixed focus, supports 720p, with digital microphone, physical switch on/off										
Controls	Side buttons for brightness up, brightness down, and power on/off										
Disk	<i>Some:</i> SATA 6.0Gb/s, 3.5" Wide, 7200 rpm										
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high										
Media reader	Optional 7-in-1 Single Slot media reader, via internal USB 2.0										
Chipset	Intel H81 Express Chipset										
Rear ports	Four USB 2.0, ethernet (RJ-45), VGA out connector, optional serial (9-pin), two optional PS/2 ports (keyboard and mouse)										
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)										
PCIe Mini Card	One PCI Express [®] Mini Card slot										
PCIe WLAN	<i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Intel Wireless-N 7260, Wi-Fi + Bluetooth combo adapter, 2x2										
Bluetooth	<i>Some:</i> Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter										
Ethernet	One gigabit ethernet port, Intel I217-V										
Audio	High Definition (HD) Audio, Realtek ALC269VC										
Speaker	Two internal stereo speakers (2watt x 2)										
Intel AMT	None										
Modem	None										
IEEE 1394	None										
Security chip	Trusted Platform Module (TPM 1.2-compliant)										
Keyboard	<i>Some:</i> Ultralim Plus Wireless Keyboard (2.4GHz via USB receiver), black										
Mouse	<i>Some:</i> Ultralim Plus Wireless Mouse (2.4GHz via USB receiver), black										
Power supply	150 watts, autosensing, 85% PSU										
Mechanical	<ul style="list-style-type: none"> • Business black color • Carry handle in rear • Support VESA mount (100mm) <i>With Frame stand:</i> 19.9" W X 3.56" D X 15.9" H 506mm W X 90.5mm D X 404.75mm H 16.4 lb (7.46 kg) in maximum configuration Adjustable stand (between 10° and 35°) <i>With Monitor stand:</i> 19.9" W X 9.83" D X 16.7" H 506mm W X 249.8mm D X 423.9mm H 19.5 lb (8.84 kg) in maximum configuration Tilt: 10° to 25°; Lift: 110mm; Swivel: +/-45°										
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available										
	Preloaded operating system²⁰ Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Device Experience • ThinkVantage AutoLock • Desktop Power Manager • View Management Utility • Lenovo Cloud Storage by SugarSync • Lenovo Solution Center • Lenovo Message Center Plus • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ • Microsoft Office preloaded; purchase a product key to activate • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) • Evernote • Intel AppUp • Nitro Pro Security <ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • Chassis intrusion switch on selected model(s) EPEAT™ Gold rating ENERGY STAR® 6.0-compliant Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant EuP 2013 Certified Supports ThinkVantage Technologies										

See footnotes for important warranty information

©Lenovo
(G-MDST1-4) July 2014

ThinkCentre M73z (10BB) - GMP

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ^a	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Chassis intrusion switch	Serial & PS/2 port	Stand type	Key-board/Mouse	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)
10BB000E++	i5-4570S	4GBx1 1600MHz	720p	500G 7200	HD 4600	N2230	Media	Switch	None	Monitor	USB	G P	Win7 Pro64 DG	09/24/13
10BB001D++	i5-4570S	4GBx1 1600MHz	720p	500G 7200	HD 4600	N2230	Media	Switch	None	Frame	USB	G P	Win7 Pro64	09/24/13
10BB002V++	i3-4130	4GBx1 1600MHz	720p	500G 7200	HD 4400	N2230	Media	Switch	None	Monitor	USB	G P	Win7 Pro64 DG	09/24/13
10BB004Q++	i5-4590S	4GBx1 1600MHz	720p	500G 7200	HD 4600	N2230	Media	Switch	None	Frame	USB	G P	Win7 Pro64	06/24/14
10BB004T++	i5-4590S	4GBx1 1600MHz	720p	500G 7200	HD 4600	N7260	Media	Switch	None	Frame	USB	G P	Win7 Pro64	06/24/14
10BB004R++	i3-4150	4GBx1 1600MHz	720p	500G 7200	HD 4400	N7260	Media	Switch	None	Monitor	USB	G P	Win7 P64 DG Win 8.1	07/15/14
10BB004S++	i5-4590S	4GBx1 1600MHz	720p	500G 7200	HD 4600	N7260	Media	Switch	None	Monitor	USB	G P	Win7 P64 DG Win 8.1	07/15/14

Country Code^a++: AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)

Note: models listed above might not be available in all WE countries

Positioning	<i>Mainstream All-In-One PC for the enterprise</i>											Preloaded operating system²⁰ <i>Some:</i> Windows 7 Professional 64 <i>Some:</i> Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit <i>Some:</i> Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit
Processor	Intel® Core™ i3-4130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller Intel Core i3-4150 Processor (2 cores / 4 threads, 3.5GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller Intel Core i5-4570S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i5-4590S Processor (4 cores / 4 threads, 3.0GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Processor in LGA1150 socket											
Implementation	16GB max, 1600MHz DDR3L , two 204-pin SODIMM sockets (notebook)											Ready to install applications (only some listed) ● Rescue and Recovery™ ● Password Manager Preloaded applications (only some listed) ● ThinkVantage® Product Recovery ● ThinkVantage System Update ● ThinkVantage Communication Utility ● ThinkVantage Device Experience ● ThinkVantage AutoLock ● Desktop Power Manager ● View Management Utility ● Lenovo Cloud Storage by SugarSync ● Lenovo Solution Center ● Lenovo Message Center Plus ● Norton™ Internet Security (30 days of virus definitions) ● Adobe® Reader® ● Skype™ ● Microsoft Office preloaded; purchase a product key to activate ● Cyberlink Power2Go (DVD±RW) ● Cyberlink PowerProducer (DVD±RW) ● Evernote ● Intel AppUp ● Nitro Pro
Memory	16GB max, 1600MHz DDR3L , two 204-pin SODIMM sockets (notebook)											
Graphics	Intel HD Graphics or Intel HD Graphics 4400/4600 in processor, uses main memory, external digital monitor support via VGA, supports dual independent display; <i>Maximum resolution:</i> 1600x900 (panel) @ 60Hz; 1920x1200 (VGA) @ 60Hz (Reduced Blanking)											
DP dongle	None											
Display	20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio											
Multi-touch	None											
Camera	Optional camera on top of screen, 1.0-megapixel, fixed focus, supports 720p, with digital microphone, physical switch on/off											
Controls	Side buttons for brightness up, brightness down, and power on/off											
Disk	<i>Some:</i> SATA 6.0Gb/s, 3.5" Wide, 7200 rpm											
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high											
Media reader	Optional 7-in-1 Single Slot media reader, via internal USB 2.0											
Chipset	Intel H81 Express Chipset											
Rear ports	Four USB 2.0, ethernet (RJ-45), VGA out connector, optional serial (9-pin), two optional PS/2 ports (keyboard and mouse)											
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)											
PCIe Mini Card	One PCI Express® Mini Card slot											
PCIe WLAN	<i>Some:</i> 11b/g/n wireless, Intel Centrino® Wireless-N 2230, Wi-Fi + BT4.0 combo, 2x2 <i>Some:</i> 11b/g/n wireless, Intel Wireless-N 7260, Wi-Fi + BT4.0 combo, 2x2 <i>Some:</i> Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter											
Bluetooth	One gigabit ethernet port, Intel I217-V											
Ethernet	High Definition (HD) Audio, Realtek ALC269VC											
Audio	Two internal stereo speakers (2watt x 2)											
Speaker	None											
Intel AMT	None											
Modem	None											
IEEE 1394	None											
Security chip	Trusted Platform Module (TPM 1.2-compliant)											
Keyboard	Preferred Pro USB Keyboard (USB connector), Lenovo® logo											
Mouse	Enhanced Optical USB Mouse, Lenovo logo											
Power supply	150 watts, autosensing, 85% PSU											
Mechanical	● Business black color ● Carry handle in rear ● Support VESA mount (100mm) <i>With Frame stand:</i> 19.9" W X 3.56" D X 15.9" H 506mm W X 90.5mm D X 404.75mm H 16.4 lb (7.46 kg) in maximum configuration Adjustable stand (between 10° and 35°) <i>With Monitor stand:</i> 19.9" W X 9.83" D X 16.7" H 506mm W X 249.8mm D X 423.9mm H 19.5 lb (8.84 kg) in maximum configuration Tilt: 10° to 25°; Lift: 110mm; Swivel: +/-45°											
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											

See footnotes for important warranty information

©Lenovo
(G-MDST1-2) July 2014

ThinkCentre M73z (10BB) - GMP (Win8/8.1)

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ^a	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Chassis Media intrusion reader switch	Serial & PS/2 port	Stand type	Key-board/ Mouse	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)
10BB001C++	i5-4570S	4GBx1 1600MHz	720p	500G 7200	HD 4600	N2230	Media Switch	None	Frame	USB	G P	Win8 Pro64	09/24/13
10BB003V++	i5-4570S	4GBx1 1600MHz	720p	500G 7200	HD 4600	N7260	Media Switch	None	Frame	USB	G P	Win8.1 Pro64	02/25/14
10BB004P++	i5-4590S	4GBx1 1600MHz	720p	500G 7200	HD 4600	N7260	Media Switch	None	Frame	USB	G P	Win8.1 Pro64	06/24/14

Country Code"+-": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)

Note: models listed above might not be available in all WE countries

- Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning	<i>Mainstream All-In-One PC for the enterprise</i>										
Processor	Intel® Core™ i5-4570S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i5-4590S Processor (4 cores / 4 threads, 3.0GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Processor in LGA1150 socket										
Implementation	Processor in LGA1150 socket										
Memory	16GB max, 1600MHz DDR3L , two 204-pin SODIMM sockets (notebook)										
Graphics	Intel HD Graphics or Intel HD Graphics 4400/4600 in processor, uses main memory, external digital monitor support via VGA, supports dual independent display; <i>Maximum resolution:</i> 1600x900 (panel) @60Hz; 1920x1200 (VGA) @60Hz (Reduced Blanking)										
DP dongle	None										
Display	20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio										
Multi-touch	None										
Camera	Optional camera on top of screen, 1.0-megapixel, fixed focus, supports 720p, with digital microphone, physical switch on/off										
Controls	Side buttons for brightness up, brightness down, and power on/off										
Disk	<i>Some:</i> SATA 6.0Gb/s, 3.5" Wide, 7200 rpm										
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high										
Media reader	Optional 7-in-1 Single Slot media reader, via internal USB 2.0										
Chipset	Intel H81 Express Chipset										
Rear ports	Four USB 2.0, ethernet (RJ-45), VGA out connector, optional serial (9-pin), two optional PS/2 ports (keyboard and mouse)										
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)										
PCIe Mini Card	One PCI Express® Mini Card slot										
PCIe WLAN	<i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2 <i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Intel Wireless-N 7260, Wi-Fi + Bluetooth combo adapter, 2x2										
Bluetooth	<i>Some:</i> Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter										
Ethernet	One gigabit ethernet port, Intel I217-V										
Audio	High Definition (HD) Audio, Realtek ALC269VC										
Speaker	Two internal stereo speakers (2watt x 2)										
Intel AMT	None										
Modem	None										
IEEE 1394	None										
Security chip	Trusted Platform Module (TPM 1.2-compliant)										
Keyboard	Preferred Pro USB Keyboard (USB connector), Lenovo® logo										
Mouse	Enhanced Optical USB Mouse, Lenovo logo										
Power supply	150 watts, autosensing, 85% PSU										
Mechanical	<ul style="list-style-type: none"> • Business black color • Carry handle in rear • Support VESA mount (100mm) <i>With Frame stand:</i> 19.9" W X 3.56" D X 15.9" H 506mm W X 90.5mm D X 404.75mm H 16.4 lb (7.46 kg) in maximum configuration Adjustable stand (between 10° and 35°) <i>With Monitor stand:</i> 19.9" W X 9.83" D X 16.7" H 506mm W X 249.8mm D X 423.9mm H 19.5 lb (8.84 kg) in maximum configuration Tilt: 10° to 25°; Lift: 110mm; Swivel: +/-45°										
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available										
	Preloaded operating system <i>Some:</i> Windows® 8 Pro 64-bit <i>Some:</i> Windows 8.1 Pro 64-bit Web install applications (only some listed) <ul style="list-style-type: none"> • Password Manager Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage System Update • ThinkVantage AutoLock • Desktop Power Manager • View Management Utility (for Windows 8 only) • Lenovo Cloud Storage by SugarSync (for Windows 8 only) • Lenovo Solution Center • Lenovo Support • Lenovo Companion • Norton Internet Security (30 days of virus definitions) • Skype™ • Microsoft Office preloaded; purchase a product key to activate • Cyberlink Power2Go (DVD±RW, DVD) • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) • Evernote® • Intel AppUp • Nitro Pro • AccuWeather • Norton™ Studio • Pokki (for Windows 8.1 only) • Hightail (for Windows 8.1 only) Security <ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) <ul style="list-style-type: none"> • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • Chassis intrusion switch on selected model(s) EPEAT™ Gold rating ENERGY STAR® 6.0-compliant Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant EuP 2013 Certified Supports ThinkVantage Technologies										

See footnotes for important warranty information

©Lenovo
(G-MDST1-3) July 2014

ThinkCentre M78 Small and Tower

ThinkCentre®



Lenovo ThinkCentre M78
Small and Tower



Lenovo ThinkCentre M78 Tower
with Lenovo ThinkVision Monitor



Lenovo ThinkCentre M78 Small



Lenovo ThinkCentre M78 Small
with Lenovo ThinkVision Monitor



Lenovo ThinkCentre M78 Tower



Lenovo ThinkCentre M78 Tower

ThinkCentre M78 Small (10BS) - ES 5.2 (GMP)


Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory ^a	SATA disk GB rpm	SATA optical	PCIe WLAN	Media reader	Graphics	Chassis Intrusion switch	PS/2 port	Floor stand	DP to Cable	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)
10BS0006++	4x3	A6-5400B	4GBx1	500G 7200	DVD±RW	None	None	HD 7540D	Switch	None	Stand	None	G P	Win7 Pro64 (DG)	10/01/13
10BS0007++	4x3	A4-5300B	2GBx1	500G 7200	DVD	None	None	HD 7480D	Switch	None	Stand	None	G P	Win7 Pro64	10/01/13
10BS000B++	4x3	A8-5500B	4GBx1	1TB 7200	DVD±RW	N105	None	HD 8470	Switch	None	Stand	None	G P	Win7 Pro64 (DG)	10/01/13

Country Code"+": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)

Note: models listed above might not be available in all WE countries

●Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning	<i>Mainstream enterprise stability and manageability</i>											Preloaded operating system			
Processor	AMD APU A4-5300B (dual-core, 3.4GHz, 1MB L2 cache), Turbo Core (up to 3.6GHz), AMD Radeon™ HD 7480D Graphics, DDR3 memory controller (up to 1600MHz) AMD APU A6-5400B (dual-core, 3.6GHz, 1MB L2 cache), Turbo Core (up to 3.8GHz), AMD Radeon HD 7540D Graphics, DDR3 memory controller (up to 1866MHz) AMD APU A8-5500B (quad-core, 3.2GHz, 4MB L2 cache), Turbo Core (up to 3.7GHz), AMD Radeon HD 7560D Graphics, DDR3 memory controller (up to 1866MHz)											Some: Windows® 7 Professional 64 Some: Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit			
Implementation	Processor in Socket FM2											Ready to install applications (only some listed)			
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets											<ul style="list-style-type: none"> Rescue and Recovery™ Password Manager 			
Graphics	AMD Radeon HD Graphics , integrated in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display, works along with optional discrete graphics to support up to four independent monitors; Maximum resolution: 1920x1200 (VGA)@60Hz; 2560x2048 (DisplayPort)@60Hz Some: AMD Radeon™ HD 8470 , DirectX 11, 3D Hardware Acceleration, 512MB, PCI Express® 2.0 x16 adapter, one VGA, one DisplayPort, 25 watts, Max resolution: 2560x1600 (DisplayPort)@60Hz; 2048x1536 (VGA)@85Hz											Preloaded applications (only some listed) <ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage System Update ThinkVantage Communication Utility ThinkVantage Power Manager View Management Utility PC Device Stage Lenovo Cloud Storage by SugarSync Lenovo Solution Center Lenovo Message Center Plus Norton™ Internet Security (30 days of virus definitions) Adobe® Reader® Skype™ Evernote® Microsoft® Office preloaded; purchase a product key to activate Cyberlink Power2Go (DVD±RW) Cyberlink PowerProducer (DVD±RW) Nitro Pro 			
DP cable	None														
Disk	SATA 6.0Gb/s 7200 rpm														
Optical	Some: DVD-ROM DL SATA 1.5Gb/s Drive Some: Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive														
SATA controller	Serial ATA, SATA 6.0Gb/s, integrated in chipset, RAID 0/1														
Onboard SATA	Two SATA cables (each 1-drop to device), four SATA 6.0Gb/s connectors on planar														
eSATA port	None														
Media reader	None														
Chipset	AMD A75 Chipset														
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort, optional keyboard (PS/2), optional mouse (PS/2)														
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)														
PCIe WLAN	Some: 11b/g/n wireless, Intel Centrino® Wireless-N 105, 1x1														
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB device)														
Audio	High Definition (HD) Audio, Realtek® ALC662 codec														
Speaker	Internal speaker for business audio														
IEEE 1394	None														
Ethernet	One gigabit ethernet port, Realtek RTL8111E, Wake on LAN®														
Modem	None														
Security chip	Trusted Platform Module (TPM 1.2-compliant)														
Keyboard	Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo														
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo														
Floor Stand	System floor stand for vertical orientation														
Power supply	240 watts, autosensing, 85% PSU														
Machine	<ul style="list-style-type: none"> Business black color; metal case 13.3" W X 15.0" D X 3.9" H 339mm W X 381mm D X 100mm H 16.5 lb (7.5 kg) in maximum configuration Toolless cover flips up and tilts backward on rear hinges Toolless disk and optical drive removal Toolless adapter retention 											Security <ul style="list-style-type: none"> Security chip (see information on left) Security slot (in rear for attachment of optional Kensington® MicroSaver® cable) Cable lock Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse Individual USB port disablement Chassis intrusion switch on selected model(s) 			
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 3.5", .5" high, access, opt reader														
Slot	Slot 1: Low Profile, PCI Express 2.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, 32-bit PCI 2.3 Slot 4: Low Profile, 32-bit PCI 2.3														
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											EPEAT™ Gold rating ENERGY STAR 5.2-compliant ULE Gold RoHS-compliant Supports ThinkVantage Technologies			

See footnotes for important warranty information
WE model(s) announced October 1, 2013

©Lenovo
(G-ADR1S-1) October 2013

ThinkCentre M78 Tower (10BN) - ES 5.2


Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	PCIe WLAN	Media reader	Graphics	Chassis intrusion switch	PS/2 port	DP to DP Cable	Global	Preload	Ann date (mm/dd/yy)
10BN0000++	4x5	A6-5400B	4GBx1	500G 7200	DVD±RW	N105	None	HD 7540D	Switch	None	None	None	Win7 Pro64	10/01/13

Country Code^{9,10}: AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)
 Note: models listed above might not be available in all WE countries

●3-year limited warranty

Positioning	<i>Mainstream enterprise stability and manageability</i>										Preloaded operating system			
Processor	AMD APU A6-5400B (dual-core, 3.6GHz, 1MB L2 cache), Turbo Core (up to 3.8GHz), AMD Radeon™ HD 7540D Graphics, DDR3 memory controller (up to 1866MHz)										Windows® 7 Professional 64			
Implementation	Processor in Socket FM2										Ready to install applications (only some listed)			
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets										<ul style="list-style-type: none"> ● Rescue and Recovery™ ● Password Manager 			
Graphics	AMD Radeon HD Graphics, integrated in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; <i>Maximum resolution: 1920x1200 (VGA) @60Hz; 2560x2048 (DisplayPort) @60Hz</i>										Preloaded applications (only some listed)			
DP cable	None										<ul style="list-style-type: none"> ● ThinkVantage® Product Recovery ● ThinkVantage System Update ● ThinkVantage Communication Utility ● ThinkVantage Power Manager ● View Management Utility ● PC Device Stage ● Lenovo Cloud Storage by SugarSync ● Lenovo Solution Center ● Lenovo Message Center Plus ● Norton™ Internet Security (30 days of virus definitions) ● Adobe® Reader® ● Skype™ ● Evernote® ● Microsoft® Office preloaded; purchase a product key to activate ● Cyberlink Power2Go (DVD±RW) ● Cyberlink PowerProducer (DVD±RW) ● Nitro Pro 			
Disk	Some: SATA 6.0Gb/s 7200 rpm													
Optical	Some: Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive													
SATA controller	Serial ATA, SATA 6.0Gb/s, integrated in chipset, RAID 0/1													
Onboard SATA	Two SATA cables (each 1-drop to device), four SATA 6.0Gb/s connectors on planar													
eSATA port	None													
Media reader	None													
Chipset	AMD A75 Chipset													
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort, optional keyboard (PS/2), optional mouse (PS/2)													
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)													
PCIe WLAN	Some: 11b/g/n wireless, Intel Centrino® Wireless-N 105, 1x1													
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB device)													
Audio	High Definition (HD) Audio, Realtek® ALC662 codec													
Speaker	Internal speaker for business audio													
IEEE 1394	None													
Ethernet	One gigabit ethernet port, Realtek RTL8111E, Wake on LAN®													
Modem	None													
Security chip	Trusted Platform Module (TPM 1.2-compliant)													
Keyboard	Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo													
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Power supply	280 watts, autosensing, 85% PSU													
Machine	<ul style="list-style-type: none"> ● Business black color; metal case ● 6.9" W X 17.4" D X 16.3" H ● 175mm W X 442mm D X 414mm H ● 27.5 lb (12.5 kg) in maximum configuration ● Toolless cover removal, toolless adapter retention ● Toolless disk, optical drive removal 										Security			
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader* Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk* *bay only available on models with HDD/SSD/reader installed										<ul style="list-style-type: none"> ● Security chip (see information on left) ● One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) ● Cable lock ● Power-on password ● Administrator password ● Hard disk password ● Boot sequence control ● Boot without keyboard and mouse ● Individual USB port disablement ● Chassis intrusion switch on selected model(s) 			
Slot	Slot 1: half-length, full-height, PCI Express 2.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, 32-bit PCI 2.3 Slot 4: half-length, full-height, 32-bit PCI 2.3										EPEAT™ Gold rating ENERGY STAR 5.2-compliant ULE Gold RoHS-compliant			
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available										Supports ThinkVantage Technologies			



See footnotes for important warranty information

WE model(s) announced October 1, 2013

©Lenovo
(G-ADR1T-1) October 2013

ThinkCentre M78 Tower (10BN) - ES 5.2 (GMP)


Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	PCIe WLAN	Media reader	Graphics	Chassis intrusion switch	PS/2 port	DP to DP Cable	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)
10BN0005++	4x5	A4-5300B	2GBx1	500G 7200	DVD	None	None	HD 7480D	Switch	None	None	G P	Win7 Pro64	10/01/13
10BN0007++	4x5	A6-5400B	4GBx1	500G 7200	DVD±RW	None	None	HD 7540D	Switch	None	None	G P	Win7 Pro64 (DG)	10/01/13
10BN000B++	4x5	A8-5500B	4GBx1	1TB 7200	DVD±RW	N105	None	HD 8470	Switch	None	None	G P	Win7 Pro64 (DG)	10/01/13

Country Code⁹++ : AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)
 Note: models listed above might not be available in all WE countries

● Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning	<i>Mainstream enterprise stability and manageability</i>											Preloaded operating system
Processor	AMD APU A4-5300B (dual-core, 3.4GHz, 1MB L2 cache), Turbo Core (up to 3.6GHz), AMD Radeon™ HD 7480D Graphics, DDR3 memory controller (up to 1600MHz) AMD APU A6-5400B (dual-core, 3.6GHz, 1MB L2 cache), Turbo Core (up to 3.8GHz), AMD Radeon HD 7540D Graphics, DDR3 memory controller (up to 1866MHz) AMD APU A8-5500B (quad-core, 3.2GHz, 4MB L2 cache), Turbo Core (up to 3.7GHz), AMD Radeon HD 7560D Graphics, DDR3 memory controller (up to 1866MHz)											Some: Windows® 7 Professional 64 Some: Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit
Implementation	Processor in Socket FM2											Ready to install applications (only some listed)
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets											<ul style="list-style-type: none"> Rescue and Recovery™ Password Manager
Graphics	AMD Radeon HD Graphics , integrated in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display, works along with optional discrete graphics to support up to four independent monitors; Maximum resolution: 1920x1200 (VGA)@60Hz; 2560x2048 (DisplayPort)@60Hz Some: AMD Radeon™ HD 8470 , DirectX 11, 3D Hardware Acceleration, 512MB, PCI Express® 2.0 x16 adapter, one VGA, one DisplayPort, 25 watts, Max resolution: 2560x1600 (DisplayPort)@60Hz; 2048x1536 (VGA)@85Hz											Preloaded applications (only some listed)
DP cable	None											<ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage System Update ThinkVantage Communication Utility ThinkVantage Power Manager View Management Utility PC Device Stage Lenovo Cloud Storage by SugarSync Lenovo Solution Center Lenovo Message Center Plus Norton™ Internet Security (30 days of virus definitions) Adobe® Reader® Skype™ Evernote® Microsoft® Office preloaded; purchase a product key to activate Cyberlink Power2Go (DVD±RW) Cyberlink PowerProducer (DVD±RW) Nitro Pro
Disk	Some: SATA 6.0Gb/s 7200 rpm											
Optical	Some: DVD-ROM DL SATA 1.5Gb/s Drive Some: Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive											
SATA controller	Serial ATA, SATA 6.0Gb/s, integrated in chipset, RAID 0/1											
Onboard SATA	Two SATA cables (each 1-drop to device), four SATA 6.0Gb/s connectors on planar											
eSATA port	None											
Media reader	None											
Chipset	AMD A75 Chipset											
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)											
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort, optional keyboard (PS/2), optional mouse (PS/2)											
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)											
PCIe WLAN	Some: 11b/g/n wireless, Intel Centrino® Wireless-N 105, 1x1											
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB device)											
Audio	High Definition (HD) Audio, Realtek® ALC662 codec											
Speaker	Internal speaker for business audio											
IEEE 1394	None											
Ethernet	One gigabit ethernet port, Realtek RTL8111E, Wake on LAN®											
Modem	None											
Security chip	Trusted Platform Module (TPM 1.2-compliant)											
Keyboard	Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo											
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo											
Power supply	280 watts, autosensing, 85% PSU											
Machine	<ul style="list-style-type: none"> Business black color; metal case 6.9" W X 17.4" D X 16.3" H 175mm W X 442mm D X 414mm H 27.5 lb (12.5 kg) in maximum configuration Toolless cover removal, toolless adapter retention Toolless disk, optical drive removal 											Security
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader* Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk* *bay only available on models with HDD/SSD/reader installed											<ul style="list-style-type: none"> Security chip (see information on left) One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) Cable lock Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse Individual USB port disablement Chassis intrusion switch on selected model(s)
Slot	Slot 1: half-length, full-height, PCI Express 2.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, 32-bit PCI 2.3 Slot 4: half-length, full-height, 32-bit PCI 2.3											EPEAT™ Gold rating ENERGY STAR 5.2-compliant ULE Gold RoHS-compliant
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											Supports ThinkVantage Technologies



See footnotes for important warranty information
 WE model(s) announced October 1, 2013

©Lenovo
 (G-ADR1T-2) October 2013



ThinkCentre M79
SFF and Tower



ThinkCentre M79 SFF with
optional monitor



ThinkCentre M79 Tower with
optional monitor



ThinkCentre M79 SFF
front and back view




ThinkCentre M79 Tower
front and back view



ThinkCentre M79 SFF
inside view

ThinkCentre M79 SFF Platform Specifications


Product Specifications Reference (PSREF)

Processor	AMD A4, A6, A8, or A10 series APUs						Keyboard	<i>Some:</i> Preferred Pro USB Keyboard (USB connector), Lenovo logo <i>Some:</i> Lenovo USB Fingerprint Keyboard (USB connector) <i>Some:</i> Ultralim Plus Wireless Keyboard (2.4GHz via USB receiver), black <i>Some:</i> Enhanced Optical USB Mouse, black, Lenovo logo <i>Some:</i> Ultralim Plus Wireless Mouse (2.4GHz via USB receiver), black
	APU	Cores	Frequency (Max/Base)	L2 Cache	Memory Types	Integrated Graphics	Mouse	
	A4-6300B	2	3.9 / 3.7	1MB	DDR3-1600	HD 8370D		
	A6-6400B	2	4.1 / 3.9	1MB	DDR3-1866	HD 8470D		
	A8-6500B	4	4.1 / 3.5	4MB	DDR3-1866	HD 8570D		
	A6 PRO-7400B	2	3.9 / 3.5	1MB	DDR3-1866	Radeon R5 Series		
	A8 PRO-7600B	4	3.8 / 3.1	4MB	DDR3-2133	Radeon R7 Series		
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3, four 240-pin DIMM sockets						Mechanical	<ul style="list-style-type: none"> Business black color; metal case, 11L 13.2" W X 15.0" D X 3.9" H 335mm W X 382mm D X 101mm H 14.6 lb (6.6 kg) in maximum configuration Bay 1: N/A, N/A, internal, opt SSD Bay 2: 5.25", 1.6" high, external, std disk Bay 3: N/A, N/A, external, opt reader Bay 4: 3.5", 1" high, internal, std disk *bay only available on models with HDD/SSD/reader installed Slot 1: Low Profile, PCI Express 3.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 2: Low Profile, PCIe 2.0 x1 Slot 4: Low Profile, 32-bit PCI 2.3 Optional system floor stand for vertical orientation
Disk	<i>Some:</i> SATA 6.0Gb/s, 3.5" Wide, 7200 rpm <i>Some:</i> 500GB (5400 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 2.5" wide <i>Some:</i> 1TB (7200 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 3.5" wide <i>Some:</i> Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide <i>Some:</i> DVD-ROM SATA 1.5Gb/s Drive <i>Some:</i> Super Multi-Burner DVD±RW SATA 1.5Gb/s Drive							
Optical	SATA 6.0Gb/s controller, three connectors on planar, RAID 0/1 support Optional 7-in-1 single slot media card reader							
Onboard SATA Media reader	Optional 7-in-1 single slot media card reader						Floor Stand	Optional system floor stand for vertical orientation
Graphics	AMD Radeon™ Graphics in processor, uses main memory, one VGA, one DisplayPort™, one optional DP, supports up to three independent displays, works along with optional discrete graphics to support up to five independent displays; <i>Maximum resolution:</i> 1920x1200 (VGA) @60Hz; 2560x2048 (DisplayPort) @60Hz <i>Some:</i> AMD Radeon HD 8570 , DirectX 11, 3D Hardware Acceleration, 2GB, PCI Express 3.0 x16 adapter (8x elec), one VGA, one HDMI, 40W; <i>Max resolution:</i> 4096x2160 (HDMI) @24Hz; 2048x1536 (VGA) @85Hz <i>Some:</i> NVIDIA® GeForce® GT 620 , DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express 2.0 x16 adapter, one VGA, one DisplayPort, 30 watts; <i>Max resolution:</i> 2560x1600 (DisplayPort) @60Hz; 2048x1536 (VGA) @85Hz <i>Some:</i> AMD Radeon™ HD 7450 , DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort, 25 watts; <i>Max resolution:</i> 2560x1600 (DisplayPort, DVI-I) @60Hz						Power supply	<i>Some:</i> 180 watts, autosensing, 100-240V (50-60Hz) <i>Some:</i> 240 watts, autosensing, 100-240V (50-60Hz) <i>Some:</i> 240 watts, autosensing, 85% PSU, 100-240V (50-60Hz)
DP cable	Optional DisplayPort to DVI-D monitor cable						Limited warranty ³	<i>Some:</i> 3-years, limited onsite service / service upgrades available <i>Some:</i> 3-years, limited onsite service, IWS (International Warranty Service ⁹) / service upgrades available <i>For Lenovo service upgrade options, please go to S-TC sheet</i>
Chipset	AMD A78 FCH						Preload	<i>Some:</i> Windows® 7 Professional 32/64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit <i>Some:</i> Windows 7 Professional 32 <i>Some:</i> Windows 7 Professional 64 Ready to install applications (only some listed) <ul style="list-style-type: none"> Rescue and Recovery™ Password Manager Preloaded applications (only some listed) <ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage System Update ThinkVantage Communication Utility ThinkVantage Device Experience Desktop Power Manager View Management Utility Lenovo Solution Center Lenovo Message Center Plus Norton™ Internet Security (30 days of virus definitions) Adobe® Reader® Skype™ Microsoft Office preloaded; purchase a product key to activate Cyberlink Power2Go (DVD±RW) Cyberlink PowerProducer (DVD±RW) Evernote® Nitro Pro
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)						Web install applications (only some listed) <ul style="list-style-type: none"> Password Manager Preloaded applications ThinkVantage System Update Desktop Power Manager Microsoft Office preloaded; purchase a product key to activate Cyberlink PowerDVD (DVD±RW, DVD) Cyberlink Power2Go (DVD±RW) Cyberlink PowerProducer (DVD±RW) Evernote® Nitro Pro AccuWeather Norton™ Studio Pokki Hightail 	
Rear ports	Up to six USB ports (2x USB 3.0 + 2x USB 2.0 + 2x optional USB 2.0), serial (9-pin), optional 2nd serial (9-pin), optional parallel (25-pin), ethernet (RJ-45), VGA, DisplayPort (1x standard + 1x optional), optional PS/2 ports							
Rear audio ports IEEE 1394	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm) Optional FireWire PCIe adapter, 1394a-2000, 400Mbps, two 6-pin ports on rear						Environment	ENERGY STAR® 6.0 (Need 85% PSU and Windows OS); EPEAT™ Gold rating (Need 85% PSU and Windows OS); GREENGUARD®; RoHS-compliant; Cisco EnergyWise compatible; ErP Lot 3
Audio support	High Definition (HD) Audio, Realtek ALC662 / internal speaker (1watt)						Accessories	For compatible accessories, please go to TC-AQP sheet
WLAN ¹³	<i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Realtek RTL8723BE, Wi-Fi + Bluetooth 4.0 combo adapter, 1x1 <i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Realtek RTL8192EE, Wi-Fi + Bluetooth 4.0 combo adapter, 2x2 <i>Some:</i> 11ac/b/g/n wireless, PCIe Half Mini Card, Broadcom BCM4352, dual band (2.4/5GHz), Wi-Fi + Bluetooth 4.0 combo adapter, 2x2							
Bluetooth™	<i>Some:</i> Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter							
Ethernet	One gigabit ethernet port, Realtek 8111EPV, Wake on LAN®							
Modem	None							
Manageability Security chip	Enhanced Manageability with DASH 1.1 Trusted Platform Module, TCG 1.2-compliant							
Security features	<ul style="list-style-type: none"> Padlock loop (in rear for opt padlock) Security slot (in rear for optional Kensington® MicroSaver® cable) Cable lock to physically lock both keyboard and mouse (optional) Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse Individual USB port disablement Optional Chassis intrusion switch 							

See footnotes for more detailed information

ThinkCentre M79 Tower Platform Specifications

Product Specifications Reference (PSREF)

Processor	AMD A4, A6, A8, or A10 series APUs	Keyboard	Some: Preferred Pro USB Keyboard (USB connector), Lenovo logo Some: Lenovo USB Fingerprint Keyboard (USB connector) Some: Ultralim Plus Wireless Keyboard (2.4GHz via USB receiver), black Some: Enhanced Optical USB Mouse, black, Lenovo logo Some: Ultralim Plus Wireless Mouse (2.4GHz via USB receiver), black																																				
	<table border="1"> <thead> <tr> <th>APU</th> <th>Cores</th> <th>Frequency (Max/Base)</th> <th>L2 Cache</th> <th>Memory Types</th> <th>Integrated Graphics</th> </tr> </thead> <tbody> <tr> <td>A4-6300B</td> <td>2</td> <td>3.9 / 3.7</td> <td>1MB</td> <td>DDR3-1600</td> <td>HD 8370D</td> </tr> <tr> <td>A6-6400B</td> <td>2</td> <td>4.1 / 3.9</td> <td>1MB</td> <td>DDR3-1866</td> <td>HD 8470D</td> </tr> <tr> <td>A8-6500B</td> <td>4</td> <td>4.1 / 3.5</td> <td>4MB</td> <td>DDR3-1866</td> <td>HD 8570D</td> </tr> <tr> <td>A6 PRO-7400B</td> <td>2</td> <td>3.9 / 3.5</td> <td>1MB</td> <td>DDR3-1866</td> <td>Radeon R5 Series</td> </tr> <tr> <td>A8 PRO-7600B</td> <td>4</td> <td>3.8 / 3.1</td> <td>4MB</td> <td>DDR3-2133</td> <td>Radeon R7 Series</td> </tr> </tbody> </table>	APU	Cores	Frequency (Max/Base)	L2 Cache	Memory Types	Integrated Graphics	A4-6300B	2	3.9 / 3.7	1MB	DDR3-1600	HD 8370D	A6-6400B	2	4.1 / 3.9	1MB	DDR3-1866	HD 8470D	A8-6500B	4	4.1 / 3.5	4MB	DDR3-1866	HD 8570D	A6 PRO-7400B	2	3.9 / 3.5	1MB	DDR3-1866	Radeon R5 Series	A8 PRO-7600B	4	3.8 / 3.1	4MB	DDR3-2133	Radeon R7 Series	Mouse	
APU	Cores	Frequency (Max/Base)	L2 Cache	Memory Types	Integrated Graphics																																		
A4-6300B	2	3.9 / 3.7	1MB	DDR3-1600	HD 8370D																																		
A6-6400B	2	4.1 / 3.9	1MB	DDR3-1866	HD 8470D																																		
A8-6500B	4	4.1 / 3.5	4MB	DDR3-1866	HD 8570D																																		
A6 PRO-7400B	2	3.9 / 3.5	1MB	DDR3-1866	Radeon R5 Series																																		
A8 PRO-7600B	4	3.8 / 3.1	4MB	DDR3-2133	Radeon R7 Series																																		
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3, four 240-pin DIMM sockets	Mechanical	<ul style="list-style-type: none"> Business black color; metal case, 20L 6.3" W X 16.6" D X 15.3" H (with handle) 160mm W X 422mm D X 388mm H 20.7 lb (9.4 kg) in maximum configuration Bay 1: 5.25", 1.6" high, access, std optical Bay 2: N/A, N/A, access, opt reader Bay 3: 3.5", 1" high, no access, std disk Bay 4: 3.5", 1" high, no access, opt disk *bay only available on models with HDD/SSD/reader installed Slot 1: half-length, full-height, PCIe 3.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x1 Slot 4: half-length, full-height, 32-bit PCI 2.3 																																				
Disk	Some: SATA 6.0Gb/s, 3.5" Wide, 7200 rpm Some: 500GB (5400 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 2.5" wide Some: 1TB (7200 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 3.5" wide	Power supply	Some: 180 watts, autosensing, 100-240V (50-60Hz) Some: 280 watts, autosensing, 100-240V (50-60Hz) Some: 280 watts, autosensing, 85% PSU, 100-240V (50-60Hz)																																				
Optical	Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide Some: DVD-ROM SATA 1.5Gb/s Drive Some: Super Multi-Burner DVD±RW SATA 1.5Gb/s Drive	Limited warranty ³	Some: 3-years, limited onsite service / service upgrades available Some: 3-years, limited onsite service, IWS (International Warranty Service ⁹) / service upgrades available <i>For Lenovo service upgrade options, please go to S-TC sheet</i>																																				
Onboard SATA Media reader	SATA 6.0Gb/s controller, three connectors on planar, RAID 0/1 support Optional 7-in-1 single slot media card reader	Preload	Some: Windows [®] 7 Professional 32/64 preinstalled through downgrade Some: Windows 7 Professional 32 Some: Windows 7 Professional 64 Ready to install applications (only some listed) <ul style="list-style-type: none"> Rescue and Recovery™ Password Manager Preloaded applications (only some listed) <ul style="list-style-type: none"> ThinkVantage[®] Product Recovery ThinkVantage System Update ThinkVantage Communication Utility ThinkVantage Device Experience Desktop Power Manager View Management Utility Lenovo Solution Center Lenovo Message Center Plus Norton™ Internet Security (30 days of virus definitions) Adobe[®] Reader[®] Skype™ Microsoft Office preloaded; purchase a product key to activate Cyberlink Power2Go (DVD±RW) Cyberlink PowerProducer (DVD±RW) Evernote[®] Nitro Pro 																																				
Graphics	AMD Radeon™ Graphics in processor, uses main memory, one VGA, one DisplayPort™, one optional DP, supports up to three independent displays, works along with optional discrete graphics to support up to five independent displays; <i>Maximum resolution: 1920x1200 (VGA) @60Hz; 2560x2048 (DisplayPort) @60Hz</i> Some: AMD Radeon HD 8570 , DirectX 11, 3D Hardware Acceleration, 2GB, PCI Express 3.0 x16 adapter (8x elec), one VGA, one HDMI, 40W; <i>Max resolution: 4096x2160 (HDMI) @24Hz; 2048x1536 (VGA) @85Hz</i> Some: NVIDIA[®] GeForce[®] GT 620 , DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express 2.0 x16 adapter, one VGA, one DisplayPort, 30 watts; <i>Max resolution: 2560x1600 (DisplayPort) @60Hz; 2048x1536 (VGA) @85Hz</i> Some: AMD Radeon™ HD 7450 , DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort, 25 watts; <i>Max resolution: 2560x1600 (DisplayPort, DVI-I) @60Hz</i>	DP cable	Optional DisplayPort to DVI-D monitor cable																																				
Chipset	AMD A78 FCH	Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)																																				
Rear ports	Up to six USB ports (2x USB 3.0 + 2x USB 2.0 + 2x optional USB 2.0), serial (9-pin), optional 2nd serial (9-pin), optional parallel (25-pin), ethernet (RJ-45), VGA, DisplayPort (1x standard + 1x optional), optional PS/2 ports	Rear ports	Up to six USB ports (2x USB 3.0 + 2x USB 2.0 + 2x optional USB 2.0), serial (9-pin), optional 2nd serial (9-pin), optional parallel (25-pin), ethernet (RJ-45), VGA, DisplayPort (1x standard + 1x optional), optional PS/2 ports																																				
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)	Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)																																				
IEEE 1394	Optional FireWire PCIe adapter, 1394a-2000, 400Mbps, two 6-pin ports on rear	IEEE 1394	Optional FireWire PCIe adapter, 1394a-2000, 400Mbps, two 6-pin ports on rear																																				
Audio support	High Definition (HD) Audio, Realtek ALC662 / internal speaker (1.5watt)	Audio support	High Definition (HD) Audio, Realtek ALC662 / internal speaker (1.5watt)																																				
WLAN ¹³	Some: 11b/g/n wireless, PCIe Half Mini Card, Realtek RTL8723BE, Wi-Fi + Bluetooth 4.0 combo adapter, 1x1 Some: 11b/g/n wireless, PCIe Half Mini Card, Realtek RTL8192EE, Wi-Fi + Bluetooth 4.0 combo adapter, 2x2 Some: 11ac/b/g/n wireless, PCIe Half Mini Card, Broadcom BCM4352, dual band (2.4/5GHz), Wi-Fi + Bluetooth 4.0 combo adapter, 2x2	WLAN ¹³	Some: 11b/g/n wireless, PCIe Half Mini Card, Realtek RTL8723BE, Wi-Fi + Bluetooth 4.0 combo adapter, 1x1 Some: 11b/g/n wireless, PCIe Half Mini Card, Realtek RTL8192EE, Wi-Fi + Bluetooth 4.0 combo adapter, 2x2 Some: 11ac/b/g/n wireless, PCIe Half Mini Card, Broadcom BCM4352, dual band (2.4/5GHz), Wi-Fi + Bluetooth 4.0 combo adapter, 2x2																																				
Bluetooth™	Some: Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter	Bluetooth™	Some: Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter																																				
Ethernet	One gigabit ethernet port, Realtek 8111EPV, Wake on LAN [®]	Ethernet	One gigabit ethernet port, Realtek 8111EPV, Wake on LAN [®]																																				
Modem	None	Modem	None																																				
Manageability	Enhanced Manageability with DASH 1.1	Manageability	Enhanced Manageability with DASH 1.1																																				
Security chip	Trusted Platform Module, TCG 1.2-compliant	Security chip	Trusted Platform Module, TCG 1.2-compliant																																				
Security features	<ul style="list-style-type: none"> Padlock loop (in rear for opt padlock) Security slot (in rear for optional Kensington[®] MicroSaver[®] cable) Cable lock to physically lock both keyboard and mouse (optional) Power-on password 	Security features	<ul style="list-style-type: none"> Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse Individual USB port disablement Optional <i>Chassis intrusion switch</i> 																																				
Environment	ENERGY STAR [®] 6.0 (Need 85% PSU and Windows OS); EPEAT™ Gold rating (Need 85% PSU and Windows OS); GREENGUARD [®] ; RoHS-compliant; Cisco EnergyWise compatible; ErP Lot 3	Environment	ENERGY STAR [®] 6.0 (Need 85% PSU and Windows OS); EPEAT™ Gold rating (Need 85% PSU and Windows OS); GREENGUARD [®] ; RoHS-compliant; Cisco EnergyWise compatible; ErP Lot 3																																				
Accessories	For compatible accessories, please go to TC-AQP sheet	Accessories	For compatible accessories, please go to TC-AQP sheet																																				

See footnotes for more detailed information

ThinkCentre M79 SFF (10CU) - TopSeller

Product Specifications Reference (PSREF)

Type-model	Processor	Memory	Graphics	Storage	Optical	WLAN	Media reader	2nd Serial Parallel	PS/2 Ports	2nd DP Port	Optional 2 rear USB	IEEE 1394	Chassis intrusion switch	Cable lock	Floor Stand	Key-board/ Mouse	Power Supply	Preload	Base Warranty (year)	Global	Ann Date (mm/yy)
10CU0000++	A4 6300B	4Gx1	HD 8370D	500G 7200	DVD±RW	None	None	None	None	None	None	None	None	None	None	USB	240W ES Win7 P64 DG Win8.1	3-onsite	No	07/14	
10CU0001++	A4 6300B	4Gx1	HD 8370D	500G 7200	DVD±RW	None	None	None	None	None	None	None	Switch	None	None	Finger	240W ES Win7 P64 DG Win8.1	3-onsite	No	07/14	

Country Code"++": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)

Note: models listed above might not be available in all WE countries

• For detailed platform specifications, please see [ThinkCentre M79 SFF Platform Specifications sheet](#)

Processor	AMD A4, A6, A8, or A10 series APUs						Manageability Security chip Security features Keyboard Mouse Mechanical Floor Stand Power supply Limited warranty ³ Preload Environment Accessories	Enhanced Manageability with DASH 1.1 Trusted Platform Module, TCG 1.2-compliant • Padlock loop (in rear for opt padlock) • Security slot (in rear for optional Kensington® MicroSaver® cable) • Cable lock to physically lock both keyboard and mouse (optional) • Power-on, Admin, Hard Disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement • Optional <i>Chassis intrusion switch</i> USB: Preferred Pro USB Keyboard (USB connector), Lenovo logo Finger: Lenovo USB Fingerprint Keyboard (USB connector) 2.4G: Ultralim Plus Wireless Keyboard (2.4GHz via USB receiver), black USB: Enhanced Optical USB Mouse, black, Lenovo logo 2.4G: Ultralim Plus Wireless Mouse (2.4GHz via USB receiver), black • Business black color; metal case, 11L • 13.2" W X 15.0" D X 3.9" H • 335mm W X 382mm D X 101mm H • 14.6 lb (6.6 kg) in maximum configuration Bay: 5.25" x1, 3.5"x1, SSD bay x1, MCR bay x1 *SSD bay only available on models with 2nd SSD installed Slot (Low Profile): one PCIe 3.0 x16 (40w max), two PCIe 2.0 x1, one PCI 2.3 Optional system floor stand for vertical orientation 180W: 180 watts, autosensing, 100-240V (50-60Hz) 240W: 240 watts, autosensing, 100-240V (50-60Hz) 240W ES: 240 watts, autosensing, 85% PSU, 100-240V (50-60Hz) Some: 3-years, limited onsite service / service upgrades available Some: 3-years, limited onsite service, IWS (International Warranty Service ⁹) / service upgrades available <i>For Lenovo service upgrade options, please go to S-TC sheet</i> Some: Windows [®] 7 Professional 32/64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit Some: Windows 7 Professional 32 Some: Windows 7 Professional 64 Some: Windows 8.1 64-bit Some: Windows 8.1 Pro 64-bit ENERGY STAR [®] 6.0 (Need 85% PSU and Windows OS); EPEAT [™] Gold rating (Need 85% PSU and Windows OS); GREENGUARD [®] ; RoHS-compliant; Cisco EnergyWise compatible; ErP Lot 3 For compatible accessories, please go to TC-AQP sheet
	APU	Cores	Frequency (Max/Base)	L2 Cache	Memory Types	Integrated Graphics		
	A4-6300B	2	3.9 / 3.7	1MB	DDR3-1600	HD 8370D		
	A6-6400B	2	4.1 / 3.9	1MB	DDR3-1866	HD 8470D		
	A8-6500B	4	4.1 / 3.5	4MB	DDR3-1866	HD 8570D		
A6 PRO-7400B	2	3.9 / 3.5	1MB	DDR3-1866	Radeon R5 Series			
A8 PRO-7600B	4	3.8 / 3.1	4MB	DDR3-2133	Radeon R7 Series			
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3, four 240-pin DIMM sockets							
Disk	Some: SATA 6.0Gb/s, 3.5" Wide, 7200 rpm Some: 500GB (5400 rpm) hybrid hard disk / with 8GB flash, SATA 6.0Gb/s, 2.5" Some: 1TB (7200 rpm) hybrid hard disk / with 8GB flash, SATA 6.0Gb/s, 3.5" wide Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide							
Optical	Some: DVD-ROM SATA 1.5Gb/s Drive Some: Super Multi-Burner DVD±RW SATA 1.5Gb/s Drive							
Onboard SATA Media reader	SATA 6.0Gb/s controller, three connectors on planar, RAID 0/1 support Optional 7-in-1 single slot media card reader							
Graphics	AMD Radeon™ Graphics in processor, uses main memory, one VGA, one DisplayPort™, one optional DP, supports up to three independent displays, works along with optional discrete graphics to support up to five independent displays; Some: AMD Radeon HD 8570, DirectX 11, one VGA, one HDMI, 40W; Some: NVIDIA® GeForce® GT 620, DirectX 11, one VGA, one DisplayPort, 30W; Some: AMD Radeon™ HD 7450, DirectX 11, one DVI-I one DisplayPort, 25W; Optional DisplayPort to DVI-D monitor cable							
DP cable	Optional DisplayPort to DVI-D monitor cable							
Chipset	AMD A78 FCH							
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)							
Rear ports	Up to six USB ports (2x USB 3.0 + 2x USB 2.0 + 2x optional USB 2.0), serial (9-pin), optional 2nd serial (9-pin), optional parallel (25-pin), ethernet (RJ-45), VGA, DisplayPort (1x standard + 1x optional), optional PS/2 ports							
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)							
IEEE 1394	Optional FireWire PCIe adapter, 1394a-2000, 400Mbps, two 6-pin ports on rear							
Audio support	High Definition (HD) Audio, Realtek ALC662 / internal speaker (1watt)							
WLAN ¹³	Some: 11b/g/n wireless, Realtek RTL8723BE, Wi-Fi + BT 4.0 combo, 1x1 Some: 11b/g/n wireless, Realtek RTL8192EE, Wi-Fi + BT 4.0 combo, 2x2 Some: 11ac/b/g/n wireless, Broadcom BCM4352, 2.4/5GHz, Wi-Fi + BT 4.0, 2x2							
Bluetooth™	Some: Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter							
Ethernet	One gigabit ethernet port, Realtek 8111EPV, Wake on LAN [®]							
Modem	None							

See footnotes for more detailed information

ThinkCentre M79 SFF (10CT)

Product Specifications Reference (PSREF)

Type-model	Processor	Memory	Graphics	Storage	Optical	WLAN	Media reader	2nd Serial / Parallel	PS/2 Ports	2nd DP Port	Optional 2 rear USB	IEEE 1394	Chassis intrusion switch	Cable lock	Floor Stand	Key-board/ Mouse	Power Supply	Preload	Base Warranty (year)	Global	Ann Date (mm/yy)
10CT0006++	A4 6300B	2Gx1	HD 8370D	250G 7200	DVD	None	None	None	None	None	None	None	Switch	None	None	USB	240W ES	Win7 Pro32	3-onsite	G	07/14
10CT0007++	A6 7400B	2Gx1	Radeon R5	500G 7200	DVD±RW	None	None	None	None	None	None	None	Switch	None	None	USB	240W ES	Win7 Pro32	3-onsite	G	07/14

Country Code"+": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)

Note: models listed above might not be available in all WE countries

• For detailed platform specifications, please see [ThinkCentre M79 SFF Platform Specifications sheet](#)

Processor	AMD A4, A6, A8, or A10 series APUs						Manageability Security chip Security features Keyboard Mouse Mechanical Floor Stand Power supply Limited warranty ³ Preload Environment Accessories	Enhanced Manageability with DASH 1.1 Trusted Platform Module, TCG 1.2-compliant ● Padlock loop (in rear for opt padlock) ● Security slot (in rear for optional Kensington® MicroSaver® cable) ● Cable lock to physically lock both keyboard and mouse (optional) ● Power-on, Admin, Hard Disk password ● Boot sequence control ● Boot without keyboard and mouse ● Individual USB port disablement ● Optional <i>Chassis intrusion switch</i> USB: Preferred Pro USB Keyboard (USB connector), Lenovo logo Finger: Lenovo USB Fingerprint Keyboard (USB connector) 2.4G: Ultralim Plus Wireless Keyboard (2.4GHz via USB receiver), black USB: Enhanced Optical USB Mouse, black, Lenovo logo 2.4G: Ultralim Plus Wireless Mouse (2.4GHz via USB receiver), black ● Business black color; metal case, 11L ● 13.2" W X 15.0" D X 3.9" H ● 335mm W X 382mm D X 101mm H ● 14.6 lb (6.6 kg) in maximum configuration Bay: 5.25" x1, 3.5"x1, SSD bay x1, MCR bay x1 *SSD bay only available on models with 2nd SSD installed Slot (Low Profile): one PCIe 3.0 x16 (40w max), two PCIe 2.0 x1, one PCI 2.3 Optional system floor stand for vertical orientation 180W: 180 watts, autosensing, 100-240V (50-60Hz) 240W: 240 watts, autosensing, 100-240V (50-60Hz) 240W ES: 240 watts, autosensing, 85% PSU, 100-240V (50-60Hz) Some: 3-years, limited onsite service / service upgrades available Some: 3-years, limited onsite service, IWS (International Warranty Service®) / service upgrades available <i>For Lenovo service upgrade options, please go to S-TC sheet</i> Some: Windows® 7 Professional 32/64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit Some: Windows 7 Professional 32 Some: Windows 7 Professional 64 Some: Windows 8.1 64-bit Some: Windows 8.1 Pro 64-bit ENERGY STAR® 6.0 (Need 85% PSU and Windows OS); EPEAT™ Gold rating (Need 85% PSU and Windows OS); GREENGUARD®; RoHS-compliant; Cisco EnergyWise compatible; ErP Lot 3 For compatible accessories, please go to TC-AQP sheet
	APU	Cores	Frequency (Max/Base)	L2 Cache	Memory Types	Integrated Graphics		
	A4-6300B	2	3.9 / 3.7	1MB	DDR3-1600	HD 8370D		
	A6-6400B	2	4.1 / 3.9	1MB	DDR3-1866	HD 8470D		
	A8-6500B	4	4.1 / 3.5	4MB	DDR3-1866	HD 8570D		
A6 PRO-7400B	2	3.9 / 3.5	1MB	DDR3-1866	Radeon R5 Series			
A8 PRO-7600B	4	3.8 / 3.1	4MB	DDR3-2133	Radeon R7 Series			
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3, four 240-pin DIMM sockets							
Disk	Some: SATA 6.0Gb/s, 3.5" Wide, 7200 rpm Some: 500GB (5400 rpm) hybrid hard disk / with 8GB flash, SATA 6.0Gb/s, 2.5" Some: 1TB (7200 rpm) hybrid hard disk / with 8GB flash, SATA 6.0Gb/s, 3.5" wide Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide							
Optical	Some: DVD-ROM SATA 1.5Gb/s Drive Some: Super Multi-Burner DVD±RW SATA 1.5Gb/s Drive							
Onboard SATA Media reader	SATA 6.0Gb/s controller, three connectors on planar, RAID 0/1 support Optional 7-in-1 single slot media card reader							
Graphics	AMD Radeon™ Graphics in processor, uses main memory, one VGA, one DisplayPort™, one optional DP, supports up to three independent displays, works along with optional discrete graphics to support up to five independent displays; Some: AMD Radeon HD 8570, DirectX 11, one VGA, one HDMI, 40W; Some: NVIDIA® GeForce® GT 620, DirectX 11, one VGA, one DisplayPort, 30W; Some: AMD Radeon™ HD 7450, DirectX 11, one DVI-I one DisplayPort, 25W; Optional DisplayPort to DVI-D monitor cable							
DP cable	Optional DisplayPort to DVI-D monitor cable							
Chipset	AMD A78 FCH							
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)							
Rear ports	Up to six USB ports (2x USB 3.0 + 2x USB 2.0 + 2x optional USB 2.0), serial (9-pin), optional 2nd serial (9-pin), optional parallel (25-pin), ethernet (RJ-45), VGA, DisplayPort (1x standard + 1x optional), optional PS/2 ports							
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)							
IEEE 1394	Optional FireWire PCIe adapter, 1394a-2000, 400Mbps, two 6-pin ports on rear							
Audio support	High Definition (HD) Audio, Realtek ALC662 / internal speaker (1watt)							
WLAN ¹³	Some: 11b/g/n wireless, Realtek RTL8723BE, Wi-Fi + BT 4.0 combo, 1x1 Some: 11b/g/n wireless, Realtek RTL8192EE, Wi-Fi + BT 4.0 combo, 2x2 Some: 11ac/b/g/n wireless, Broadcom BCM4352, 2.4/5GHz, Wi-Fi + BT 4.0, 2x2							
Bluetooth™	Some: Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter							
Ethernet	One gigabit ethernet port, Realtek 8111EPV, Wake on LAN®							
Modem	None							

See footnotes for more detailed information

ThinkCentre M79 Tower (10CR) - TopSeller

Product Specifications Reference (PSREF)

Type-model	Processor	Memory	Graphics	Storage	Optical	WLAN	Media reader	2nd Serial / Parallel	PS/2 Ports	2nd DP Port	Optional 2 rear USB	IEEE 1394	Chassis intrusion switch	Cable lock	Floor Stand	Key-board/ Mouse	Power Supply	Preload	Base Warranty (year)	Global	Ann Date (mm/yy)
10CR0000++	A4 6300B	4Gx1	HD 8370D	500G 7200	DVD±RW	None	None	None	None	None	None	None	None	None	None	USB	280W ES	Win7 P64 DG Win8.1	3-onsite	No	07/14
10CR0001++	A4 6300B	4Gx1	HD 8370D	500G 7200	DVD±RW	None	None	None	None	None	None	1394	Switch	None	None	USB	280W ES	Win7 P64 DG Win8.1	3-onsite	No	07/14
10CR0002++	A8 6500B	8Gx1	HD 8570D	500G 7200	DVD±RW	None	None	None	None	None	None	None	None	None	None	USB	280W ES	Win7 P64 DG Win8.1	3-onsite	No	08/14

Country Code"++": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)
 Note: models listed above might not be available in all WE countries

• For detailed platform specifications, please see [ThinkCentre M79 Tower Platform Specifications sheet](#)

Processor	AMD A4, A6, A8, or A10 series APUs						Manageability Security chip Security features	Enhanced Manageability with DASH 1.1 Trusted Platform Module, TCG 1.2-compliant	
	APU	Cores	Frequency (Max/Base)	L2 Cache	Memory Types	Integrated Graphics		<ul style="list-style-type: none"> • Padlock loop (in rear for opt padlock) • Security slot (in rear for optional Kensington® MicroSave® cable) • Cable lock to physically lock both keyboard and mouse (optional) • Power-on, Admin, Hard Disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement • Optional <i>Chassis intrusion switch</i> 	
	A4-6300B	2	3.9 / 3.7	1MB	DDR3-1600	HD 8370D			
	A6-6400B	2	4.1 / 3.9	1MB	DDR3-1866	HD 8470D			
	A8-6500B	4	4.1 / 3.5	4MB	DDR3-1866	HD 8570D			
A6 PRO-7400B	2	3.9 / 3.5	1MB	DDR3-1866	Radeon R5 Series				
A8 PRO-7600B	4	3.8 / 3.1	4MB	DDR3-2133	Radeon R7 Series				
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3, four 240-pin DIMM sockets						Keyboard	<i>USB:</i> Preferred Pro USB Keyboard (USB connector), Lenovo logo <i>Finger:</i> Lenovo USB Fingerprint Keyboard (USB connector)	
Disk	<i>Some:</i> SATA 6.0Gb/s, 3.5" Wide, 7200 rpm <i>Some:</i> 500GB (5400 rpm) hybrid hard disk / with 8GB flash, SATA 6.0Gb/s, 2.5" <i>Some:</i> 1TB (7200 rpm) hybrid hard disk / with 8GB flash, SATA 6.0Gb/s, 3.5" wide <i>Some:</i> Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide <i>Some:</i> DVD-ROM SATA 1.5Gb/s Drive <i>Some:</i> Super Multi-Burner DVD±RW SATA 1.5Gb/s Drive						Mouse	<i>2.4G:</i> Ultraslim Plus Wireless Keyboard (2.4GHz via USB receiver), black <i>USB:</i> Enhanced Optical USB Mouse, black, Lenovo logo <i>2.4G:</i> Ultraslim Plus Wireless Mouse (2.4GHz via USB receiver), black	
Optical	SATA 6.0Gb/s controller, three connectors on planar, RAID 0/1 support						Mechanical	<ul style="list-style-type: none"> • Business black color; metal case, 20L • 6.3" W X 16.6" D X 15.3" H (with handle) • 160mm W X 422mm D X 388mm H • 20.7 lb (9.4 kg) in maximum configuration Bay: 5.25" x1, 3.5" x2, MCR Bay x1 Slot (half-length): one PCIe 2.0 x16 (60w max), two PCIe 2.0 x1, one PCI 2.3	
Onboard SATA Media reader	Optional 7-in-1 single slot media card reader						Power supply	<i>180W:</i> 180 watts, autosensing, 100-240V (50-60Hz) <i>280W:</i> 280 watts, autosensing, 100-240V (50-60Hz) <i>280W ES:</i> 280 watts, autosensing, 85% PSU, 100-240V (50-60Hz)	
Graphics	AMD Radeon™ Graphics in processor, uses main memory, one VGA, one DisplayPort™, one optional DP, supports up to three independent displays, works along with optional discrete graphics to support up to five independent displays; <i>Some:</i> AMD Radeon HD 8570 , DirectX 11, one VGA, one HDMI, 40W; <i>Some:</i> NVIDIA® GeForce® GT 620 , DirectX 11, one VGA, one DisplayPort, 30W; <i>Some:</i> AMD Radeon™ HD 7450 , DirectX 11, one DVI-I one DisplayPort, 25W; Optional DisplayPort to DVI-D monitor cable						Limited warranty ³	<i>Some:</i> 3-years, limited onsite service / service upgrades available <i>Some:</i> 3-years, limited onsite service, IWS (International Warranty Service ⁹) / service upgrades available For Lenovo service upgrade options, please go to S-TC sheet	
DP cable	Optional DisplayPort to DVI-D monitor cable						Preload	<i>Some:</i> Windows® 7 Professional 32/64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit <i>Some:</i> Windows 7 Professional 32 <i>Some:</i> Windows 7 Professional 64 <i>Some:</i> Windows 8.1 64-bit <i>Some:</i> Windows 8.1 Pro 64-bit	
Chipset	AMD A78 FCH						Environment	ENERGY STAR® 6.0 (Need 85% PSU and Windows OS); EPEAT™ Gold rating (Need 85% PSU and Windows OS); GREENGUARD®; RoHS-compliant; Cisco EnergyWise compatible; ErP Lot 3	
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)						Accessories	For compatible accessories, please go to TC-AQP sheet	
Rear ports	Up to six USB ports (2x USB 3.0 + 2x USB 2.0 + 2x optional USB 2.0), serial (9-pin), optional 2nd serial (9-pin), optional parallel (25-pin), ethernet (RJ-45), VGA, DisplayPort (1x standard + 1x optional), optional PS/2 ports								
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)								
IEEE 1394	Optional FireWire PCIe adapter, 1394a-2000, 400Mbps, two 6-pin ports on rear								
Audio support	High Definition (HD) Audio, Realtek ALC662 / internal speaker (1.5watt)								
WLAN ¹³	<i>Some:</i> 11b/g/n wireless, Realtek RTL8723BE, Wi-Fi + BT 4.0 combo, 1x1 <i>Some:</i> 11b/g/n wireless, Realtek RTL8192EE, Wi-Fi + BT 4.0 combo, 2x2 <i>Some:</i> 11ac/b/g/n wireless, Broadcom BCM4352, 2.4/5GHz, Wi-Fi + BT 4.0, 2x2								
Bluetooth™	<i>Some:</i> Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter								
Ethernet	One gigabit ethernet port, Realtek 8111EPV, Wake on LAN®								
Modem	None								

See footnotes for more detailed information

ThinkCentre M79 Tower (10CQ)

Product Specifications Reference (PSREF)

Type-model	Processor	Memory	Graphics	Storage	Optical	WLAN	Media reader	2nd Serial / Parallel	PS/2 Ports	2nd DP Port	Optional 2 rear USB	IEEE 1394	Chassis intrusion switch	Cable lock	Floor Stand	Key-board/ Mouse	Power Supply	Preload	Base Warranty (year)	Global	Ann Date (mm/yy)
10CQ0005++	A4 6300B	2Gx1	HD 8370D	250G 7200	DVD	None	None	None	None	None	None	None	Switch	None	None	USB	280W ES	Win7 Pro32	3-onsite IWS	G	07/14
10CQ0006++	A6 7400B	2Gx1	Radeon R5500G	7200	DVD±RW	None	None	None	None	None	None	None	Switch	None	None	USB	280W ES	Win7 Pro32	3-onsite IWS	G	07/14
10CQ0007++	A8 7600B	4Gx1	HD 8570	1TB 7200	DVD±RW	None	Media	P	None	None	None	None	Switch	None	None	USB	280W ES	Win7 Pro64	3-onsite IWS	G	07/14

Country Code"+": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)
 Note: models listed above might not be available in all WE countries

- For detailed platform specifications, please see [ThinkCentre M79 Tower Platform Specifications sheet](#)

Processor	AMD A4, A6, A8, or A10 series APUs						Manageability	Enhanced Manageability with DASH 1.1																																					
	<table border="1"> <thead> <tr> <th>APU</th> <th>Cores</th> <th>Frequency (Max/Base)</th> <th>L2 Cache</th> <th>Memory Types</th> <th>Integrated Graphics</th> </tr> </thead> <tbody> <tr> <td>A4-6300B</td> <td>2</td> <td>3.9 / 3.7</td> <td>1MB</td> <td>DDR3-1600</td> <td>HD 8370D</td> </tr> <tr> <td>A6-6400B</td> <td>2</td> <td>4.1 / 3.9</td> <td>1MB</td> <td>DDR3-1866</td> <td>HD 8470D</td> </tr> <tr> <td>A8-6500B</td> <td>4</td> <td>4.1 / 3.5</td> <td>4MB</td> <td>DDR3-1866</td> <td>HD 8570D</td> </tr> <tr> <td>A6 PRO-7400B</td> <td>2</td> <td>3.9 / 3.5</td> <td>1MB</td> <td>DDR3-1866</td> <td>Radeon R5 Series</td> </tr> <tr> <td>A8 PRO-7600B</td> <td>4</td> <td>3.8 / 3.1</td> <td>4MB</td> <td>DDR3-2133</td> <td>Radeon R7 Series</td> </tr> </tbody> </table>						APU	Cores	Frequency (Max/Base)	L2 Cache	Memory Types	Integrated Graphics	A4-6300B	2	3.9 / 3.7	1MB	DDR3-1600	HD 8370D	A6-6400B	2	4.1 / 3.9	1MB	DDR3-1866	HD 8470D	A8-6500B	4	4.1 / 3.5	4MB	DDR3-1866	HD 8570D	A6 PRO-7400B	2	3.9 / 3.5	1MB	DDR3-1866	Radeon R5 Series	A8 PRO-7600B	4	3.8 / 3.1	4MB	DDR3-2133	Radeon R7 Series	Security chip	Trusted Platform Module, TCG 1.2-compliant	
	APU	Cores	Frequency (Max/Base)	L2 Cache	Memory Types	Integrated Graphics																																							
	A4-6300B	2	3.9 / 3.7	1MB	DDR3-1600	HD 8370D																																							
	A6-6400B	2	4.1 / 3.9	1MB	DDR3-1866	HD 8470D																																							
	A8-6500B	4	4.1 / 3.5	4MB	DDR3-1866	HD 8570D																																							
A6 PRO-7400B	2	3.9 / 3.5	1MB	DDR3-1866	Radeon R5 Series																																								
A8 PRO-7600B	4	3.8 / 3.1	4MB	DDR3-2133	Radeon R7 Series																																								
						Security features	<ul style="list-style-type: none"> • Padlock loop (in rear for opt padlock) • Security slot (in rear for optional Kensington® MicroSave® cable) • Cable lock to physically lock both keyboard and mouse (optional) • Power-on, Admin, Hard Disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement • Optional <i>Chassis intrusion switch</i> 																																						
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3, four 240-pin DIMM sockets						Keyboard	<i>USB:</i> Preferred Pro USB Keyboard (USB connector), Lenovo logo <i>Finger:</i> Lenovo USB Fingerprint Keyboard (USB connector)																																					
Disk	<i>Some:</i> SATA 6.0Gb/s, 3.5" Wide, 7200 rpm <i>Some:</i> 500GB (5400 rpm) hybrid hard disk / with 8GB flash, SATA 6.0Gb/s, 2.5" <i>Some:</i> 1TB (7200 rpm) hybrid hard disk / with 8GB flash, SATA 6.0Gb/s, 3.5" wide <i>Some:</i> Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide <i>Some:</i> DVD-ROM SATA 1.5Gb/s Drive <i>Some:</i> Super Multi-Burner DVD±RW SATA 1.5Gb/s Drive						Mouse	<i>2.4G:</i> Ultraslim Plus Wireless Keyboard (2.4GHz via USB receiver), black <i>USB:</i> Enhanced Optical USB Mouse, black, Lenovo logo <i>2.4G:</i> Ultraslim Plus Wireless Mouse (2.4GHz via USB receiver), black																																					
Optical	SATA 6.0Gb/s controller, three connectors on planar, RAID 0/1 support						Mechanical	<ul style="list-style-type: none"> • Business black color; metal case, 20L • 6.3" W X 16.6" D X 15.3" H (with handle) • 160mm W X 422mm D X 388mm H • 20.7 lb (9.4 kg) in maximum configuration 																																					
Onboard SATA Media reader	Optional 7-in-1 single slot media card reader						Power supply	<i>180W:</i> 180 watts, autosensing, 100-240V (50-60Hz) <i>280W:</i> 280 watts, autosensing, 100-240V (50-60Hz) <i>280W ES:</i> 280 watts, autosensing, 85% PSU, 100-240V (50-60Hz)																																					
Graphics	AMD Radeon™ Graphics in processor, uses main memory, one VGA, one DisplayPort™, one optional DP, supports up to three independent displays, works along with optional discrete graphics to support up to five independent displays; <i>Some:</i> AMD Radeon HD 8570 , DirectX 11, one VGA, one HDMI, 40W; <i>Some:</i> NVIDIA® GeForce® GT 620 , DirectX 11, one VGA, one DisplayPort, 30W; <i>Some:</i> AMD Radeon™ HD 7450 , DirectX 11, one DVI-I one DisplayPort, 25W; Optional DisplayPort to DVI-D monitor cable						Limited warranty ³	<i>Some:</i> 3-years, limited onsite service / service upgrades available <i>Some:</i> 3-years, limited onsite service, IWS (International Warranty Service ⁹) / service upgrades available For Lenovo service upgrade options, please go to <i>S-TC sheet</i>																																					
DP cable	Optional DisplayPort to DVI-D monitor cable						Preload	<i>Some:</i> Windows® 7 Professional 32/64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit <i>Some:</i> Windows 7 Professional 32 <i>Some:</i> Windows 7 Professional 64 <i>Some:</i> Windows 8.1 64-bit <i>Some:</i> Windows 8.1 Pro 64-bit																																					
Chipset	AMD A78 FCH						Environment	ENERGY STAR® 6.0 (Need 85% PSU and Windows OS); EPEAT™ Gold rating (Need 85% PSU and Windows OS); GREENGUARD®; RoHS-compliant; Cisco EnergyWise compatible; ErP Lot 3																																					
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)						Accessories	For compatible accessories, please go to TC-AQP sheet																																					
Rear ports	Up to six USB ports (2x USB 3.0 + 2x USB 2.0 + 2x optional USB 2.0), serial (9-pin), optional 2nd serial (9-pin), optional parallel (25-pin), ethernet (RJ-45), VGA, DisplayPort (1x standard + 1x optional), optional PS/2 ports																																												
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)																																												
IEEE 1394	Optional FireWire PCIe adapter, 1394a-2000, 400Mbps, two 6-pin ports on rear																																												
Audio support	High Definition (HD) Audio, Realtek ALC662 / internal speaker (1.5watt)																																												
WLAN ¹³	<i>Some:</i> 11b/g/n wireless, Realtek RTL8723BE, Wi-Fi + BT 4.0 combo, 1x1 <i>Some:</i> 11b/g/n wireless, Realtek RTL8192EE, Wi-Fi + BT 4.0 combo, 2x2 <i>Some:</i> 11ac/b/g/n wireless, Broadcom BCM4352, 2.4/5GHz, Wi-Fi + BT 4.0, 2x2																																												
Bluetooth™	<i>Some:</i> Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter																																												
Ethernet	One gigabit ethernet port, Realtek 8111EPV, Wake on LAN®																																												
Modem	None																																												

See footnotes for more detailed information

Lenovo ThinkCentre M83 Small Pro, Mini Tower



Lenovo ThinkCentre M83 Mini Tower with Lenovo ThinkVision Monitor



Lenovo ThinkCentre M83 Mini Tower with optional WLAN and graphic card



Lenovo ThinkCentre M83 Small Pro with Lenovo ThinkVision Monitor



Lenovo ThinkCentre M83 Small Pro with optional dual graphic cards
* Cable lock only available on some special bid models



Lenovo ThinkCentre M83 Small Pro (inside view)



Optional 2.5 inch bay on Lenovo ThinkCentre M83 Small Pro
* Come with optional 2.5 inch 2nd HDD

ThinkCentre M83 SFF Pro (10AJ) - ES 6.0 (TopSeller)


Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	PCIe WLAN	Media reader	Graphics	Additional Front USB 2.0	2nd serial port	Chassis intrusion switch	Floor stand	ENERGY STAR 6.0	Preload	Ann date (mm/dd/yy)
10AJ0001++	3x4	i3-4130	4GBx1	500G 7200	DVD±RW	None	None	HD 4400	None	None	Switch	None	ES6.0	Win7 Pro64 (DG)	09/10/13
10AJ0002++	3x4	i3-4130	4GBx1	500G 7200	DVD±RW	None	Media	HD 4400	None	None	Switch	None	ES6.0	Win7 Pro64 (DG)	09/10/13
10AJ0003++	3x4	i5-4430	4GBx1	500G 7200	DVD±RW	None	None	HD 4600	None	None	Switch	Stand	ES6.0	Win7 Pro64 (DG)	09/10/13
10AJ0004++	3x4	i7-4770	4GBx1	500G 7200	DVD±RW	None	Media	HD 4600	None	None	Switch	Stand	ES6.0	Win7 Pro64 (DG)	09/10/13
10AJ0005++	3x4	i5-4430	4GBx1	500G 7200	DVD±RW	None	Media	HD 4600	None	None	Switch	Stand	ES6.0	Win7 Pro64 (DG)	09/10/13

Country Code"+": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)

Note: models listed above might not be available in all WE countries

• Small and medium business (SMB) model(s), part of the Western Europe TopSeller™ Program

Positioning	Mainstream enterprise stability and manageability											Preloaded operating system			
Processor	Intel® Core™ i3-4130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller Intel Core i5-4430 Processor (4 cores / 4 threads, 3.0GHz, 6MB cache), Turbo Boost 2.0 (3.2GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i7-4770 Processor (4 cores / 8 threads, 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller											Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit			
Implementation	Processor in LGA1150 socket											Ready to install applications (only some listed)			
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets											<ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager 			
Graphics	Intel HD Graphics 4400 or 4600 in processor, uses main memory, DirectX® 11, one VGA, two DisplayPort™, supports three independent displays; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking)</i>											Preloaded applications (only some listed)			
DP dongle	None											<ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • Desktop Power Manager • View Management Utility • Lenovo Cloud Storage by SugarSync • Lenovo Solution Center • Lenovo Message Center Plus • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ • Microsoft Office preloaded; purchase a product key to activate • Cyberlink PowerDVD (DVD±RW, DVD) • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) • Evernote • Intel AppUp • Intel Small Business Advantage • Nitro Pro 			
Disk	SATA 6.0Gb/s 7200 rpm, 3.5" wide														
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive														
SATA controller	Serial ATA, SATA 6.0Gb/s, integrated in chipset														
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 6.0Gb/s connectors, one eSATA connector (SATA 6.0Gb/s)														
eSATA port	None														
Media reader	Some: 29-in-1 media reader, internal USB 2.0														
Chipset	Intel Q85 Express Chipset														
Front ports	Two USB 3.0, two optional USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
Rear ports	Two USB 3.0, four USB 2.0, serial (9-pin), optional 2nd serial (9-pin), ethernet (RJ-45), one VGA, two DisplayPort, additional VGA, DisplayPort, or HDMI ports on optional graphic card on some models														
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)														
PCIe WLAN	None														
Bluetooth	None														
Audio	High Definition (HD) Audio, Realtek® ALC662 codec														
Speaker	None														
IEEE 1394	None														
Ethernet	One gigabit ethernet port, Intel I217-LM (Clarkville), Wake on LAN®														
Manageability	Intel Standard Manageability														
Modem	None														
Security chip	Trusted Platform Module (TPM1.2-compliant)														
Keyboard	Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo											Security			
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo											<ul style="list-style-type: none"> • Security chip (see information on left) • One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> - Padlock loop (in rear for opt padlock) - Security slot (in rear for optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Serial port I/O control • Individual USB port disablement • Chassis intrusion switch on selected model(s) 			
Floor Stand	Optional system floor stand for vertical orientation														
Power supply	240 watts, autosensing, 85% PSU														
Machine	<ul style="list-style-type: none"> • SFF Pro (12.9L), business black color; metal case • (WxDxH) 13.31" X 14.76" X 4.02"; 338mm X 375mm X 102mm • 17.20 lb (7.8 kg) in maximum configuration • Toolless cover removal, adapter retention • Toolless disk and optical drive removal 														
Bay	Bay 1: 5.25", 1.6" high, external, std optical Bay 2: 3.5", 1" high, internal, std disk Bay 3: 2.5", N/A, internal, opt, come with opt 2.5" 2nd disk Bay 4: 3.5", 0.5" high, external, opt reader														
Slot	Slot 1: Low Profile, PCI Express 3.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, PCIe 2.0 x16 (x4 elec, 40w max)														
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											EPEAT™ Gold rating ENERGY STAR® 6.0-compliant ULE Gold Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant			
Supports ThinkVantage Technologies															

See footnotes for important warranty information
WE model(s) announced September 10, 2013

©Lenovo
(G-MSK1S-2) September 2013


ThinkCentre M83 SFF Pro (10AJ) - ES 6.0 (TopSeller) - II

Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory	SATA disk GB rpm	SATA optical	Optional 2.5" bay	PCIe WLAN	Media reader	Graphics	Additional Front USB 2.0	2nd serial port	Chassis intrusion switch	Floor stand	ENERGY STAR 6.0	Preload	Ann date (mm/dd/yy)
10AJ001M++	3x4 i3-4150	4GBx1	500G 7200	DVD±RW	None	None	None	None	HD 4400	None	None	Switch	None	ES6.0 Win7 P64 DG Win 8.1	07/08/14	
10AJ001N++	3x4 i3-4150	4GBx1	500G 7200	DVD±RW	None	Media	None	None	HD 4400	None	None	Switch	None	ES6.0 Win7 P64 DG Win 8.1	07/08/14	
10AJ001P++	3x4 i5-4460	4GBx1	500G 7200	DVD±RW	None	None	None	None	HD 4600	None	None	Switch	Stand	ES6.0 Win7 P64 DG Win 8.1	07/08/14	
10AJ001Q++	3x4 i5-4460	4GBx1	500G 7200	DVD±RW	None	Media	None	None	HD 4600	None	None	Switch	Stand	ES6.0 Win7 P64 DG Win 8.1	07/08/14	
10AJ001R++	3x4 i5-4590	4GBx1	500G 7200	DVD±RW	None	None	None	None	HD 4600	None	None	Switch	Stand	ES6.0 Win7 P64 DG Win 8.1	07/08/14	
10AJ001S++	3x4 i5-4590	4GBx1	500G 7200	DVD±RW	None	None	None	None	HD 4600	None	None	None	Stand	ES6.0 Win7 P64 DG Win 8.1	07/08/14	
10AJ001T++	3x4 i3-4150	4GBx1	500G 7200	DVD±RW	2.5"	None	Media	None	HD 4400	None	None	Switch	None	ES6.0 Win7 P64 DG Win 8.1	07/08/14	

Country Code "++": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)
 Note: models listed above might not be available in all WE countries

• Small and medium business (SMB) model(s), part of the Western Europe TopSeller™ Program

Positioning	Mainstream enterprise stability and manageability											Preloaded operating system				
Processor	Intel® Core™ i3-4150 Processor (2 cores / 4 threads, 3.5GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller Intel Core i5-4460 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.4GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i5-4590 Processor (4 cores / 4 threads, 3.3GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller											Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit				
Implementation	Processor in LGA1150 socket											Ready to install applications (only some listed)				
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets											<ul style="list-style-type: none"> Rescue and Recovery™ Password Manager 				
Graphics	Intel HD Graphics 4400 or 4600 in processor, uses main memory, DirectX® 11, one VGA, two DisplayPort™, supports three independent displays; Maximum resolution: 2560x1600 (DisplayPort)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking)											Preloaded applications (only some listed)				
DP dongle	None											<ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage System Update ThinkVantage Communication Utility Desktop Power Manager View Management Utility Lenovo Cloud Storage by SugarSync Lenovo Solution Center Lenovo Message Center Plus Norton™ Internet Security (30 days of virus definitions) Adobe® Reader® Skype™ Microsoft Office preloaded; purchase a product key to activate Cyberlink PowerDVD (DVD±RW, DVD) Cyberlink Power2Go (DVD±RW) Cyberlink PowerProducer (DVD±RW) Evernote Intel AppUp Intel Small Business Advantage Nitro Pro 				
Disk	SATA 6.0Gb/s 7200 rpm, 3.5" wide											Security <ul style="list-style-type: none"> Security chip (see information on left) One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse Serial port I/O control Individual USB port disablement Chassis intrusion switch on selected model(s) 				
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive															
SATA controller	Serial ATA, SATA 6.0Gb/s, integrated in chipset															
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 6.0Gb/s connectors, one eSATA connector (SATA 6.0Gb/s)															
eSATA port	None															
Media reader	Some: 29-in-1 media reader, internal USB 2.0															
Chipset	Intel Q85 Express Chipset															
Front ports	Two USB 3.0, two optional USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)															
Rear ports	Two USB 3.0, four USB 2.0, serial (9-pin), optional 2nd serial (9-pin), ethernet (RJ-45), one VGA, two DisplayPort, additional VGA, DisplayPort, or HDMI ports on optional graphic card on some models															
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)															
PCIe WLAN	None															
Bluetooth	None															
Audio	High Definition (HD) Audio, Realtek® ALC662 codec															
Speaker	None															
IEEE 1394	None															
Ethernet	One gigabit ethernet port, Intel I217-LM (Clarkville), Wake on LAN®															
Manageability	Intel Standard Manageability															
Modem	None															
Security chip	Trusted Platform Module (TPM1.2-compliant)															
Keyboard	Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo															
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo															
Floor Stand	Optional system floor stand for vertical orientation															
Power supply	240 watts, autosensing, 85% PSU															
Machine	<ul style="list-style-type: none"> SFF Pro (12.9L), business black color; metal case (WxDxH) 13.31" X 14.76" X 4.02"; 338mm X 375mm X 102mm 17.20 lb (7.8 kg) in maximum configuration Toolless cover removal, adapter retention Toolless disk and optical drive removal 															
Bay	Bay 1: 5.25", 1.6" high, external, std optical Bay 2: 3.5", 1" high, internal, std disk Bay 3: 2.5", N/A, internal, opt, come with opt 2.5" 2nd disk Bay 4: 3.5", 0.5" high, external, opt reader															
Slot	Slot 1: Low Profile, PCI Express 3.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, PCIe 2.0 x16 (x4 elec, 40w max)															
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											EPEAT™ Gold rating ENERGY STAR® 6.0-compliant ULE Gold Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies				

See footnotes for important warranty information
 WE model(s) announced September 10, 2013

©Lenovo
 (G-MSK1S-3) July 2014

ThinkCentre M83 SFF Pro (10AH) - ES 6.0 (GMP)


Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory ⁶	SATA disk GB rpm	SATA optical	PCIe WLAN	Graphics	Additional Front USB 2.0	2nd serial port	Chassis intrusion switch	Floor stand	ENERGY STAR 6.0	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)
10AH0015++	3x4	i5-4570	2GBx1	500G 7200	DVD	None	HD 4600	None	None	Switch	None	ES6.0	G P	Win7 Pro64	07/30/13
10AH0016++	3x4	i5-4570	4GBx1	500G 7200	DVD	None	HD 4600	USB	None	Switch	Stand	ES6.0	G P	Win7 Pro64 (DG)	07/30/13
10AH0017++	3x4	i5-4570	4GBx1	1TB 7200	DVD	Intel 105	HD 8470	USB	None	Switch	Stand	ES6.0	G P	Win7 Pro64 (DG)	07/30/13
10AH001H++	3x4	i5-4570	4GBx1	500G 7200	DVD±RW	None	HD 4600	USB	None	Switch	Stand	ES6.0	G P	Win7 Pro64 (DG)	08/20/13
10AH001J++	3x4	i5-4570	4GBx1	1TB 7200	DVD±RW	Intel 105	HD 8470	USB	None	Switch	Stand	ES6.0	G P	Win7 Pro64 (DG)	08/20/13
10AH0043++	3x4	i5-4570	2GBx1	500G 7200	DVD	None	HD 4600	None	None	Switch	None	ES6.0	G P	Win7 Pro64	03/11/14
10AH005X++	3x4	i5-4590	4GBx1	500G 3.5"	DVD±RW	None	HD 4600	USB	None	Switch	Stand	ES6.0	G P	Win7 P64 DG Win8.1	07/08/14
10AH005Y++	3x4	i5-4590	4GBx1	1TB 3.5"	DVD±RW	8723BE	GT 620	None	None	Switch	Stand	ES6.0	G P	Win7 P64 DG Win8.1	07/08/14

Country Code"+": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)

Note: models listed above might not be available in all WE countries

Positioning	Mainstream enterprise stability and manageability		Preloaded operating system <i>Some:</i> Windows® 7 Professional 64 <i>Some:</i> Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit <i>Some:</i> Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit Ready to install applications (only some listed) <ul style="list-style-type: none"> Rescue and Recovery™ Password Manager Preloaded applications (only some listed) <ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage System Update ThinkVantage Communication Utility Desktop Power Manager View Management Utility Lenovo Cloud Storage by SugarSync Lenovo Solution Center Lenovo Message Center Plus Norton™ Internet Security (30 days of virus definitions) Adobe® Reader® Skype™ Microsoft Office preloaded; purchase a product key to activate Cyberlink PowerDVD (DVD±RW, DVD) Cyberlink Power2Go (DVD±RW) Cyberlink PowerProducer (DVD±RW) Evernote Intel AppUp Intel Small Business Advantage Nitro Pro
Processor	Intel® Core™ i5-4570 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i5-4590 Processor (4 cores / 4 threads, 3.3GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Processor in LGA1150 socket		
Implementation	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets		
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets		
Graphics	Intel HD Graphics 4600 in processor, uses main memory, DirectX® 11, one VGA, two DisplayPort™, supports three independent displays, works along with discrete graphics to support up to five independent monitors; <i>Maximum resolution:</i> 2560x1600 (DisplayPort)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking) <i>Some:</i> AMD Radeon™ HD 8470 , DirectX 11, 3D Hardware Acceleration, 512MB, PCI Express® 2.0 x16 adapter, one VGA, one DisplayPort, 25 watts, <i>Max resolution:</i> 2560x1600 (DisplayPort)@60Hz; 2048x1536 (VGA)@85Hz <i>Some:</i> NVIDIA® GeForce® GT 620 , DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express 2.0 x16 adapter, one VGA, one DisplayPort, 30 watts; <i>Max resolution:</i> 2560x1600 (DisplayPort)@60Hz; 2048x1536 (VGA)@85Hz		
DP dongle	None		
Disk	SATA 6.0Gb/s 7200 rpm, 3.5" wide		
Optical	<i>Some:</i> DVD-ROM DL SATA 1.5Gb/s 16-48X Max ⁴ Drive <i>Some:</i> Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive		
SATA controller	Serial ATA, SATA 6.0Gb/s, integrated in chipset		
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 6.0Gb/s connectors, one eSATA connector (SATA 6.0Gb/s)		
eSATA port	None		
Media reader	None		
Chipset	Intel Q85 Express Chipset		
Front ports	Two USB 3.0, two optional USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)		
Rear ports	Two USB 3.0, four USB 2.0, serial (9-pin), optional 2nd serial (9-pin), ethernet (RJ-45), one VGA, two DisplayPort, additional VGA, DisplayPort, or HDMI ports on optional graphic card on some models		
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)		
PCIe WLAN	<i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 105, 1x1 <i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Realtek RTL8723BE, Wi-Fi/BT 4.0, 1x1 <i>Some:</i> Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter		
Bluetooth	High Definition (HD) Audio, Realtek® ALC662 codec		
Audio	Internal speaker for business audio (1 watt)		
Speaker	None		
IEEE 1394	None		
Ethernet	One gigabit ethernet port, Intel I217-LM (Clarkville), Wake on LAN®		
Manageability	Intel Standard Manageability		
Modem	None		
Security chip	Trusted Platform Module (TPM1.2-compliant)		
Keyboard	Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo		
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo		
Floor Stand	Optional system floor stand for vertical orientation		
Power supply	240 watts, autosensing, 85% PSU		
Machine	<ul style="list-style-type: none"> SFF Pro (12.9L), business black color; metal case (WxDxH) 13.31" X 14.76" X 4.02"; 338mm X 375mm X 102mm 17.20 lb (7.8 kg) in maximum configuration Toolless cover removal, adapter retention Toolless disk and optical drive removal 		
Bay	Bay 1: 5.25", 1.6" high, external, std optical Bay 2: 3.5", 1" high, internal, std disk Bay 3: 2.5", N/A, internal, opt, come with opt 2.5" 2nd disk Bay 4: 3.5", 0.5" high, external, opt reader		
Slot	Slot 1: Low Profile, PCI Express 3.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, PCIe 2.0 x16 (x4 elec, 40w max)		
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available		



See footnotes for important warranty information

ThinkCentre M83 Mini Tower (10BE) - ES 6.0 (TopSeller)


Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory ³	SATA disk GB rpm	SATA optical	PCIe WLAN	Media reader	Graphics	Additional Front USB 2.0	2nd serial port	Chassis intrusion switch	ENERGY STAR 6.0	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)
10BE0000++	3x5	i7-4770	4GBx1	500GB 7200	DVD±RW	None	Media	HD 4600	None	None	Switch	ES6.0	None	Win7 P64 DG Win8	09/10/13
10BE0001++	3x5	i5-4430	4GBx1	500GB 7200	DVD±RW	None	None	HD 4600	None	None	Switch	ES6.0	None	Win7 P64 DG Win8	09/10/13
10BE0002++	3x5	i5-4430	4GBx1	500GB 7200	DVD±RW	None	Media	HD 4600	None	None	Switch	ES6.0	None	Win7 P64 DG Win8	09/10/13
10BE0003++	3x5	i3-4130	4GBx1	500GB 7200	DVD±RW	None	Media	HD 4400	None	None	Switch	ES6.0	None	Win7 P64 DG Win8	09/10/13
10BE0004++	3x5	i3-4130	4GBx1	500GB 7200	DVD±RW	None	None	HD 4400	None	None	Switch	ES6.0	None	Win7 P64 DG Win8	09/10/13
10BE000V++	3x5	i7-4770	4GBx1	128GB SSD	DVD±RW	None	Media	HD 4600	None	None	Switch	ES6.0	None	Win7 P64 DG Win8.1	03/25/14

Country Code "++": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)

Note: models listed above might not be available in all WE countries

• Small and medium business (SMB) model(s), part of the Western Europe TopSeller™ Program

Positioning	Mainstream enterprise stability and manageability											Preloaded operating system			
Processor	Intel® Core™ i3-4130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller Intel Core i5-4430 Processor (4 cores / 4 threads, 3.0GHz, 6MB cache), Turbo Boost 2.0 (3.2GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i7-4770 Processor (4 cores / 8 threads, 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Processor in LGA1150 socket											Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit			
Implementation	Processor in LGA1150 socket											Ready to install applications (only some listed)			
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets											<ul style="list-style-type: none"> Rescue and Recovery™ Password Manager 			
Graphics	Intel HD Graphics 4400 or 4600 in processor, uses main memory, DirectX® 11, one VGA, two DisplayPort™, supports three independent displays; Maximum resolution: 2560x1600 (DisplayPort)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking)											Preloaded applications (only some listed)			
DP dongle	None											<ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage System Update ThinkVantage Communication Utility Desktop Power Manager View Management Utility Lenovo Cloud Storage by SugarSync Lenovo Solution Center Lenovo Message Center Plus Norton™ Internet Security (30 days of virus definitions) Adobe® Reader® Skype™ Microsoft Office preloaded; purchase a product key to activate Cyberlink PowerDVD (DVD±RW, DVD) Cyberlink Power2Go (DVD±RW) Cyberlink PowerProducer (DVD±RW) Evernote Intel AppUp Intel Small Business Advantage Nitro Pro 			
Disk	Some: SATA 6.0Gb/s 7200 rpm, 3.5" wide Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive														
Optical	Serial ATA, SATA 6.0Gb/s, integrated in chipset														
SATA controller	Two SATA cables (each 1-drop to device), three SATA 6.0Gb/s connectors, one eSATA connector (SATA 6.0Gb/s)														
Onboard SATA	None														
eSATA port	None														
Media reader	Some: 29-in-1 media reader, internal USB 2.0														
Chipset	Intel Q85 Express Chipset														
Front ports	Two USB 3.0, two optional USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
Rear ports	Two USB 3.0, four USB 2.0, serial (9-pin), optional 2nd serial (9-pin), ethernet (RJ-45), one VGA, two DisplayPort, additional VGA, DisplayPort, or HDMI ports on optional graphic card on some models														
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)														
PCIe WLAN	None														
Bluetooth	None														
Audio	High Definition (HD) Audio, Realtek® ALC662 codec														
Speaker	None														
IEEE 1394	None														
Ethernet	One gigabit ethernet port, Intel I217-LM (Clarkville), Wake on LAN®														
Manageability	Intel Standard Manageability														
Modem	None														
Security chip	Trusted Platform Module (TPM1.2-compliant)											Security			
Keyboard	Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo											<ul style="list-style-type: none"> Security chip (see information on left) One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse Serial port I/O control Individual USB port disablement Chassis intrusion switch on selected model(s) 			
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo														
Power supply	280 watts, autosensing, 85% PSU														
Machine	<ul style="list-style-type: none"> Mini Tower (25L), business black color, metal case (WxDxH) 6.89" X 17.41" X 16.32"; 175mm X 442.3mm X 414.5mm 24.69 lb (11.20 kg) in maximum configuration Toolless cover removal, adapter retention Toolless disk, optical drive removal 														
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk														
Slot	Slot 1: half-length, full-height, PCIe 3.0 x16 (75w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x16 (x4 elec, 75w max)											EPEAT™ Gold rating ENERGY STAR® 6.0-compliant ULE Gold Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies			
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available														

See footnotes for important warranty information

WE model(s) announced September 10, 2013 or March 25, 2014

©Lenovo

(G-MSK1T-1) March 2014


ThinkCentre M83 Mini Tower (10BE) - ES 6.0 (TopSeller) - II

Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory ^g	SATA disk GB rpm	SATA optical	PCIe WLAN	Media reader	Graphics	Additional Front USB 2.0	2nd serial port	Chassis intrusion switch	ENERGY STAR 6.0	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)
10BE0015++	3x5	i5-4460	4GBx1	500GB 7200	DVD±RW	None	Media	HD 4600	None	None	Switch	ES6.0	None	Win7 P64 DG	Win8.1 07/08/14
10BE0016++	3x5	i7-4790	4GBx1	128GB SSD	DVD±RW	None	Media	HD 4600	None	None	Switch	ES6.0	None	Win7 P64 DG	Win8.1 07/08/14
10BE0017++	3x5	i3-4150	4GBx1	500GB 7200	DVD±RW	None	None	HD 4400	None	None	Switch	ES6.0	None	Win7 P64 DG	Win8.1 07/08/14
10BE0018++	3x5	i3-4150	4GBx1	500GB 7200	DVD±RW	None	Media	HD 4400	None	None	Switch	ES6.0	None	Win7 P64 DG	Win8.1 07/08/14
10BE0019++	3x5	i5-4460	4GBx1	500GB 7200	DVD±RW	None	None	HD 4600	None	None	Switch	ES6.0	None	Win7 P64 DG	Win8.1 07/08/14
10BE001A++	3x5	i7-4790	4GBx1	500GB 7200	DVD±RW	None	Media	HD 4600	None	None	Switch	ES6.0	None	Win7 P64 DG	Win8.1 07/08/14
10BE001B++	3x5	i5-4590	4GBx1	500GB 7200	DVD±RW	None	None	HD 4600	None	None	Switch	ES6.0	None	Win7 P64 DG	Win8.1 07/08/14
10BE001C++	3x5	i5-4590	4GBx1	500GB 7200	DVD±RW	None	None	HD 4600	None	None	None	ES6.0	None	Win7 P64 DG	Win8.1 07/08/14
10BE0025++	3x5	i5-4590	4GBx1	256GB SSD	DVD±RW	None	Media	HD 4600	None	None	None	ES6.0	None	Win7 P64 DG	Win8.1 08/12/14

Country Code "++": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)

Note: models listed above might not be available in all WE countries

Positioning	Mainstream enterprise stability and manageability										Preloaded operating system				
Processor	Intel® Core™ i3-4150 Processor (2 cores / 4 threads, 3.5GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller Intel Core i5-4460 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.4GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i5-4590 Processor (4 cores / 4 threads, 3.3GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i7-4790 Processor (4 cores / 8 threads, 3.6GHz, 8MB cache), Turbo Boost 2.0 (4.0GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Processor in LGA1150 socket										Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit				
Implementation	Processor in LGA1150 socket										Ready to install applications (only some listed)				
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets										Preloaded applications (only some listed)				
Graphics	Intel HD Graphics 4400 or 4600 in processor, uses main memory, DirectX® 11, one VGA, two DisplayPort™, supports three independent displays; Maximum resolution: 2560x1600 (DisplayPort)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking)										<ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage System Update ThinkVantage Communication Utility Desktop Power Manager View Management Utility Lenovo Cloud Storage by SugarSync Lenovo Solution Center Lenovo Message Center Plus Norton™ Internet Security (30 days of virus definitions) Adobe® Reader® Skype™ Microsoft Office preloaded; purchase a product key to activate Cyberlink PowerDVD (DVD±RW, DVD) Cyberlink Power2Go (DVD±RW) Cyberlink PowerProducer (DVD±RW) Evernote Intel AppUp Intel Small Business Advantage Nitro Pro 				
DP dongle	None														
Disk	Some: SATA 6.0Gb/s 7200 rpm, 3.5" wide Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide														
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive														
SATA controller	Serial ATA, SATA 6.0Gb/s, integrated in chipset														
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 6.0Gb/s connectors, one eSATA connector (SATA 6.0Gb/s)														
eSATA port	None														
Media reader	Some: 29-in-1 media reader, internal USB 2.0														
Chipset	Intel Q85 Express Chipset														
Front ports	Two USB 3.0, two optional USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
Rear ports	Two USB 3.0, four USB 2.0, serial (9-pin), optional 2nd serial (9-pin), ethernet (RJ-45), one VGA, two DisplayPort, additional VGA, DisplayPort, or HDMI ports on optional graphic card on some models														
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)														
PCIe WLAN	None														
Bluetooth	None														
Audio	High Definition (HD) Audio, Realtek® ALC662 codec														
Speaker	None														
IEEE 1394	None														
Ethernet	One gigabit ethernet port, Intel I217-LM (Clarkville), Wake on LAN®														
Manageability	Intel Standard Manageability														
Modem	None														
Security chip	Trusted Platform Module (TPM1.2-compliant)										Security				
Keyboard	Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo										<ul style="list-style-type: none"> Security chip (see information on left) One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) 				
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo										<ul style="list-style-type: none"> Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse Serial port I/O control Individual USB port disablement Chassis intrusion switch on selected model(s) 				
Power supply	280 watts, autosensing, 85% PSU														
Machine	<ul style="list-style-type: none"> Mini Tower (25L), business black color, metal case (WxDxH) 6.89" X 17.41" X 16.32"; 175mm X 442.3mm X 414.5mm 24.69 lb (11.20 kg) in maximum configuration Toolless cover removal, adapter retention Toolless disk, optical drive removal 														
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk														
Slot	Slot 1: half-length, full-height, PCIe 3.0 x16 (75w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x16 (x4 elec, 75w max)										EPEAT™ Gold rating ENERGY STAR® 6.0-compliant ULE Gold Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant				
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available										Supports ThinkVantage Technologies				

See footnotes for important warranty information

©Lenovo
(G-MSK1T-3) August 2014

ThinkCentre M83 Mini Tower (10AG) - ES 6.0 (GMP)

Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory ^a	SATA disk GB rpm	SATA optical	PCIe WLAN	Additional Front Graphics	2nd serial port USB 2.0	Chassis intrusion switch	Key-board	ENERGY STAR 6.0	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)
10AG000P++	3x5	i5-4570	4GBx1	1TB 7200	DVD	Intel 105	HD 8470	USB	None	Switch	None	ES6.0	G P Win7 Pro64 (DG)	07/30/13
10AG000Q++	3x5	i5-4570	2GBx1	500GB 7200	DVD	None	HD 4600	None	None	Switch	None	ES6.0	G P Win7 Pro64	07/30/13
10AG000R++	3x5	i5-4570	4GBx1	500GB 7200	DVD	None	HD 4600	USB	None	Switch	None	ES6.0	G P Win7 Pro64 (DG)	07/30/13
10AG000S++	3x5	i5-4570	4GBx1	500GB 7200	DVD±RW	None	HD 4600	USB	None	Switch	Finger	ES6.0	G P Win7 Pro64 (DG)	08/20/13
10AG000T++	3x5	i5-4570	4GBx1	1TB 7200	DVD±RW	Intel 105	HD 8470	USB	None	Switch	USB	ES6.0	G P Win7 Pro64 (DG)	08/20/13
10AG000U++	3x5	i5-4570	4GBx1	500GB 7200	DVD±RW	None	HD 4600	USB	None	Switch	USB	ES6.0	G P Win7 Pro64 (DG)	09/10/13
10AG001K++	3x5	i5-4590	2GBx1	500GB 7200	DVD	None	HD 4600	None	None	Switch	USB	ES6.0	G P Win7 Pro64	06/10/14
10AG001P++	3x5	i5-4590	4GBx1	500GB 7200	DVD±RW	None	HD 4600	USB	None	Switch	USB	ES6.0	G P Win7 P64 DG Win 8.1	07/08/14
10AG001Q++	3x5	i5-4590	4GBx1	1TB 7200	DVD±RW	8723BE	GT 620	None	None	Switch	USB	ES6.0	G P Win7 P64 DG Win 8.1	07/08/14

●Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning	Mainstream enterprise stability and manageability											Preloaded operating system		
Processor	Intel® Core™ i5-4570 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i5-4590 Processor (4 cores / 4 threads, 3.3GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Processor in LGA1150 socket											Some: Windows® 7 Professional 64 Some: Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit		
Implementation	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets											Ready to install applications (only some listed)		
Memory	Intel HD Graphics 4600 in processor, uses main memory, DirectX® 11, one VGA, two DisplayPort™, supports three independent displays, works along with discrete graphics to support up to five independent monitors; Maximum resolution: 2560x1600 (DisplayPort)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking) Some: AMD Radeon™ HD 8470 , DirectX 11, 3D Hardware Acceleration, 512MB, PCI Express® 2.0 x16 adapter, one VGA, one DisplayPort, 25 watts, Max resolution: 2560x1600 (DisplayPort)@60Hz; 2048x1536 (VGA)@85Hz Some: NVIDIA® GeForce® GT 620 , DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express 2.0 x16 adapter, one VGA, one DisplayPort, 30 watts; Max resolution: 2560x1600 (DisplayPort)@60Hz; 2048x1536 (VGA)@85Hz											<ul style="list-style-type: none"> Rescue and Recovery™ Password Manager Preloaded applications (only some listed) <ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage System Update ThinkVantage Communication Utility Desktop Power Manager View Management Utility Lenovo Cloud Storage by SugarSync Lenovo Solution Center Lenovo Message Center Plus Norton™ Internet Security (30 days of virus definitions) Adobe® Reader® Skype™ Microsoft Office preloaded; purchase a product key to activate Cyberlink PowerDVD (DVD±RW, DVD) Cyberlink Power2Go (DVD±RW) Cyberlink PowerProducer (DVD±RW) Evernote Intel AppUp Intel Small Business Advantage Nitro Pro 		
Graphics	DP dongle: None Disk: SATA 6.0Gb/s 7200 rpm, 3.5" wide Optical: Some: DVD-ROM DL SATA 1.5Gb/s 16-48X Max ⁴ Drive Some: Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive SATA controller: Serial ATA, SATA 6.0Gb/s, integrated in chipset Onboard SATA: Two SATA cables (each 1-drop to device), three SATA 6.0Gb/s connectors, one eSATA connector (SATA 6.0Gb/s) eSATA port: None Media reader: None Chipset: Intel Q85 Express Chipset Front ports: Two USB 3.0, two optional USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm) Rear ports: Two USB 3.0, four USB 2.0, serial (9-pin), optional 2nd serial (9-pin), ethernet (RJ-45), one VGA, two DisplayPort, additional VGA, DisplayPort, or HDMI ports on optional graphic card on some models Rear audio ports: Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm) PCIe WLAN: Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 105, 1x1 Some: 11b/g/n wireless, PCIe Half Mini Card, Realtek RTL8723BE, Wi-Fi/BT 4.0, 1x1 Bluetooth: Some: Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter Audio: High Definition (HD) Audio, Realtek® ALC662 codec Speaker: Internal speaker for business audio (1.5 watt) IEEE 1394: None Ethernet: One gigabit ethernet port, Intel I217-LM (Clarkville), Wake on LAN® Manageability: Intel Standard Manageability Modem: None Security chip: Trusted Platform Module (TPM1.2-compliant) Keyboard: Some: Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo Some: Lenovo USB Fingerprint Keyboard (USB connector) Mouse: Enhanced Optical USB Mouse, black, Lenovo logo Power supply: 280 watts, autosensing, 85% PSU Machine: <ul style="list-style-type: none"> Mini Tower (25L), business black color, metal case (WxDxH) 6.89" X 17.41" X 16.32"; 175mm X 442.3mm X 414.5mm 24.69 lb (11.20 kg) in maximum configuration Toolless cover removal, adapter retention Toolless disk, optical drive removal 											Security <ul style="list-style-type: none"> Security chip (see information on left) One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse Serial port I/O control Individual USB port disablement Chassis intrusion switch on selected model(s) 		
DP dongle	None											EPEAT™ Gold rating ENERGY STAR® 6.0-compliant ULE Gold Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies		
Disk	SATA 6.0Gb/s 7200 rpm, 3.5" wide													
Optical	Some: DVD-ROM DL SATA 1.5Gb/s 16-48X Max ⁴ Drive Some: Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive													
SATA controller	Serial ATA, SATA 6.0Gb/s, integrated in chipset													
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 6.0Gb/s connectors, one eSATA connector (SATA 6.0Gb/s)													
eSATA port	None													
Media reader	None													
Chipset	Intel Q85 Express Chipset													
Front ports	Two USB 3.0, two optional USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
Rear ports	Two USB 3.0, four USB 2.0, serial (9-pin), optional 2nd serial (9-pin), ethernet (RJ-45), one VGA, two DisplayPort, additional VGA, DisplayPort, or HDMI ports on optional graphic card on some models													
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)													
PCIe WLAN	Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 105, 1x1 Some: 11b/g/n wireless, PCIe Half Mini Card, Realtek RTL8723BE, Wi-Fi/BT 4.0, 1x1 Some: Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter													
Bluetooth	Some: Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter													
Audio	High Definition (HD) Audio, Realtek® ALC662 codec													
Speaker	Internal speaker for business audio (1.5 watt)													
IEEE 1394	None													
Ethernet	One gigabit ethernet port, Intel I217-LM (Clarkville), Wake on LAN®													
Manageability	Intel Standard Manageability													
Modem	None													
Security chip	Trusted Platform Module (TPM1.2-compliant)													
Keyboard	Some: Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo Some: Lenovo USB Fingerprint Keyboard (USB connector)													
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Power supply	280 watts, autosensing, 85% PSU													
Machine	<ul style="list-style-type: none"> Mini Tower (25L), business black color, metal case (WxDxH) 6.89" X 17.41" X 16.32"; 175mm X 442.3mm X 414.5mm 24.69 lb (11.20 kg) in maximum configuration Toolless cover removal, adapter retention Toolless disk, optical drive removal 													
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk													
Slot	Slot 1: half-length, full-height, PCIe 3.0 x16 (75w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x16 (x4 elec, 75w max)													
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available													

See footnotes for important warranty information

©Lenovo
(G-MSK1T-2) July 2014



ThinkCentre M83z with frame stand and wireless mouse/keyboard



ThinkCentre M83z with monitor stand (tilt-only)



ThinkCentre M83z with monitor stand (full-function)



ThinkCentre M83z with frame stand



ThinkCentre M83z with monitor stand (tilt-only)



ThinkCentre M83z with monitor stand (full-function)

ThinkCentre M83z Platform Specifications

Product Specifications Reference (PSREF)

Processor	Intel® Celeron®, Pentium®, or 4th Generation Core™ i3 / i5 / i7 Processor	Security features	<ul style="list-style-type: none"> Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse USB port disablement Optional Chassis intrusion switch 																																																																						
	<table border="1"> <thead> <tr> <th>Processor</th> <th>Cores / Threads</th> <th>Clock Speed</th> <th>Max Turbo Frequency</th> <th>Cache</th> <th>Memory Types</th> <th>Integrated Graphics</th> </tr> </thead> <tbody> <tr> <td>Pentium G3220</td> <td>2 / 2</td> <td>3.0 GHz</td> <td>-</td> <td>3MB</td> <td>DDR3-1333</td> <td>Intel HD</td> </tr> <tr> <td>Pentium G3240</td> <td>2 / 2</td> <td>3.1 GHz</td> <td>-</td> <td>3MB</td> <td>DDR3-1333</td> <td>Intel HD</td> </tr> <tr> <td>Core i3-4130</td> <td>2 / 4</td> <td>3.4 GHz</td> <td>-</td> <td>3MB</td> <td>DDR3-1600</td> <td>Intel HD 4400</td> </tr> <tr> <td>Core i3-4150</td> <td>2 / 4</td> <td>3.5 GHz</td> <td>-</td> <td>3MB</td> <td>DDR3-1600</td> <td>Intel HD 4400</td> </tr> <tr> <td>Core i5-4430S</td> <td>4 / 4</td> <td>2.7 GHz</td> <td>3.2 GHz</td> <td>6MB</td> <td>DDR3-1600</td> <td>Intel HD 4600</td> </tr> <tr> <td>Core i5-4460S</td> <td>4 / 4</td> <td>2.9 GHz</td> <td>3.4 GHz</td> <td>6MB</td> <td>DDR3-1600</td> <td>Intel HD 4600</td> </tr> <tr> <td>Core i5-4570S</td> <td>4 / 4</td> <td>2.9 GHz</td> <td>3.6 GHz</td> <td>6MB</td> <td>DDR3-1600</td> <td>Intel HD 4600</td> </tr> <tr> <td>Core i5-4590S</td> <td>4 / 4</td> <td>3.0 GHz</td> <td>3.7 GHz</td> <td>6MB</td> <td>DDR3-1600</td> <td>Intel HD 4600</td> </tr> <tr> <td>Core i7-4770S</td> <td>4 / 8</td> <td>3.1 GHz</td> <td>3.9 GHz</td> <td>8MB</td> <td>DDR3-1600</td> <td>Intel HD 4600</td> </tr> </tbody> </table>	Processor	Cores / Threads	Clock Speed	Max Turbo Frequency	Cache	Memory Types	Integrated Graphics	Pentium G3220	2 / 2	3.0 GHz	-	3MB	DDR3-1333	Intel HD	Pentium G3240	2 / 2	3.1 GHz	-	3MB	DDR3-1333	Intel HD	Core i3-4130	2 / 4	3.4 GHz	-	3MB	DDR3-1600	Intel HD 4400	Core i3-4150	2 / 4	3.5 GHz	-	3MB	DDR3-1600	Intel HD 4400	Core i5-4430S	4 / 4	2.7 GHz	3.2 GHz	6MB	DDR3-1600	Intel HD 4600	Core i5-4460S	4 / 4	2.9 GHz	3.4 GHz	6MB	DDR3-1600	Intel HD 4600	Core i5-4570S	4 / 4	2.9 GHz	3.6 GHz	6MB	DDR3-1600	Intel HD 4600	Core i5-4590S	4 / 4	3.0 GHz	3.7 GHz	6MB	DDR3-1600	Intel HD 4600	Core i7-4770S	4 / 8	3.1 GHz	3.9 GHz	8MB	DDR3-1600	Intel HD 4600	Keyboard	<i>Some:</i> Preferred Pro USB Keyboard (USB connector), Lenovo logo <i>Some:</i> UltraSlim Plus Wireless Keyboard (2.4GHz via USB receiver), black <i>Some:</i> Enhanced Optical USB Mouse, black, Lenovo logo <i>Some:</i> UltraSlim Plus Wireless Mouse (2.4GHz via USB receiver), black
Processor	Cores / Threads	Clock Speed	Max Turbo Frequency	Cache	Memory Types	Integrated Graphics																																																																			
Pentium G3220	2 / 2	3.0 GHz	-	3MB	DDR3-1333	Intel HD																																																																			
Pentium G3240	2 / 2	3.1 GHz	-	3MB	DDR3-1333	Intel HD																																																																			
Core i3-4130	2 / 4	3.4 GHz	-	3MB	DDR3-1600	Intel HD 4400																																																																			
Core i3-4150	2 / 4	3.5 GHz	-	3MB	DDR3-1600	Intel HD 4400																																																																			
Core i5-4430S	4 / 4	2.7 GHz	3.2 GHz	6MB	DDR3-1600	Intel HD 4600																																																																			
Core i5-4460S	4 / 4	2.9 GHz	3.4 GHz	6MB	DDR3-1600	Intel HD 4600																																																																			
Core i5-4570S	4 / 4	2.9 GHz	3.6 GHz	6MB	DDR3-1600	Intel HD 4600																																																																			
Core i5-4590S	4 / 4	3.0 GHz	3.7 GHz	6MB	DDR3-1600	Intel HD 4600																																																																			
Core i7-4770S	4 / 8	3.1 GHz	3.9 GHz	8MB	DDR3-1600	Intel HD 4600																																																																			
Memory	16GB max ⁷ / DDR3 Low Voltage, DDR3L-1600*, non-parity, dual-channel capable, two 204-pin SO-DIMM sockets * System automatically clocks down for processors with 1333MHz DDR3 memory controller	Mouse	<i>Some:</i> Enhanced Optical USB Mouse, black, Lenovo logo <i>Some:</i> UltraSlim Plus Wireless Mouse (2.4GHz via USB receiver), black																																																																						
Disk	<i>Some:</i> SATA 6.0Gb/s, 3.5" Wide, 7200 rpm <i>Some:</i> 500GB (5400 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 2.5" wide <i>Some:</i> 1TB (7200 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 3.5" wide <i>Some:</i> Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide	Mechanical	<ul style="list-style-type: none"> Business black color Support VESA mount (100mm) <table border="1"> <thead> <tr> <th>Dimensions (WxDxH)</th> <th>Weight (Maximum)</th> <th>Adjustments</th> </tr> </thead> <tbody> <tr> <td colspan="3">M83z with frame stand</td> </tr> <tr> <td>21.26" X 3.70" X 15.59" 540mm X 94mm X 396mm</td> <td>16.53 lb (7.5 kg)</td> <td>Tilt: 10° to 25° back</td> </tr> <tr> <td colspan="3">M83z with monitor stand (full-function)</td> </tr> <tr> <td>21.26" X 9.84" X 17.56" 540mm X 250mm X 446mm</td> <td>21.93 lb (9.95 kg)</td> <td>Tilt: 25° back, -5° forward Lift: 110mm Swivel: +/-45°</td> </tr> <tr> <td colspan="3">M83z with monitor stand (tilt-only)</td> </tr> <tr> <td>21.26" X 6.89" X 16.85" 540mm X 175mm X 428mm</td> <td>19.82 lb (8.99 kg)</td> <td>Tilt: 45° back, -5° forward</td> </tr> </tbody> </table>	Dimensions (WxDxH)	Weight (Maximum)	Adjustments	M83z with frame stand			21.26" X 3.70" X 15.59" 540mm X 94mm X 396mm	16.53 lb (7.5 kg)	Tilt: 10° to 25° back	M83z with monitor stand (full-function)			21.26" X 9.84" X 17.56" 540mm X 250mm X 446mm	21.93 lb (9.95 kg)	Tilt: 25° back, -5° forward Lift: 110mm Swivel: +/-45°	M83z with monitor stand (tilt-only)			21.26" X 6.89" X 16.85" 540mm X 175mm X 428mm	19.82 lb (8.99 kg)	Tilt: 45° back, -5° forward																																																	
Dimensions (WxDxH)	Weight (Maximum)	Adjustments																																																																							
M83z with frame stand																																																																									
21.26" X 3.70" X 15.59" 540mm X 94mm X 396mm	16.53 lb (7.5 kg)	Tilt: 10° to 25° back																																																																							
M83z with monitor stand (full-function)																																																																									
21.26" X 9.84" X 17.56" 540mm X 250mm X 446mm	21.93 lb (9.95 kg)	Tilt: 25° back, -5° forward Lift: 110mm Swivel: +/-45°																																																																							
M83z with monitor stand (tilt-only)																																																																									
21.26" X 6.89" X 16.85" 540mm X 175mm X 428mm	19.82 lb (8.99 kg)	Tilt: 45° back, -5° forward																																																																							
Optical Media reader	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable Optional 7-in-1 single slot media card reader	Power supply	150 watts, auto-sensing, 85% PSU, 100-240V (50-60Hz)																																																																						
Graphics	Intel HD Graphics or Intel HD Graphics 4400/4600 in processor, uses main memory, DirectX® 11, one VGA-out, supports dual independent display; <i>Maximum resolution:</i> 1920x1200 (VGA)@60Hz (Reduced Blanking)	Limited warranty ³	<i>Some:</i> 3-years, limited onsite service / service upgrades available <i>Some:</i> 3-years, limited onsite service, IWS (International Warranty Service ⁹) / service upgrades available <i>For Lenovo service upgrade options, please go to S-TC sheet</i>																																																																						
Display	21.5" (546.1mm) Full HD 1080p (1920x1080) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, anti-glare	Preload	Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit Ready to install applications (only some listed) <ul style="list-style-type: none"> Rescue and Recovery™ Password Manager Preloaded applications (only some listed) <ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage System Update ThinkVantage Communication Utility ThinkVantage Device Experience ThinkVantage AutoLock Desktop Power Manager View Management Utility Lenovo Solution Center Lenovo Message Center Plus Norton™ Internet Security (30 days of virus definitions) Adobe® Reader® Skype™ Microsoft Office preloaded; purchase a product key to activate Cyberlink Power2Go (DVD±RW) Cyberlink PowerProducer (DVD±RW) Evernote® Nitro Pro 																																																																						
Multi-touch	None		<i>Some:</i> Windows 8.1 64-bit <i>Some:</i> Windows 8.1 Pro 64-bit Web install applications (only some listed) <ul style="list-style-type: none"> Password Manager Preloaded applications (only some listed) <ul style="list-style-type: none"> ThinkVantage System Update ThinkVantage AutoLock Desktop Power Manager Lenovo Solution Center Lenovo Support Lenovo Companion Norton Internet Security (30 days of virus definitions) Skype™ Microsoft Office preloaded; purchase a product key to activate Cyberlink PowerDVD (DVD±RW, DVD) Cyberlink Power2Go (DVD±RW) Cyberlink PowerProducer (DVD±RW) Evernote® Nitro Pro AccuWeather Norton™ Studio Pokki Hightail 																																																																						
Camera	<i>Some:</i> 720p camera, 1.0-megapixel, fixed focus, digital microphone, LED indicator, physical switch on/off <i>Some:</i> 1080p camera, 2.0-megapixel, fixed focus, dual array digital microphone, LED indicator, physical switch on/off	Controls	Brightness up/down and power button on right side																																																																						
Chipset	Intel H81 Express Chipset	Chipset	Intel H81 Express Chipset																																																																						
Rear ports	Four USB 2.0, ethernet (RJ-45), VGA-out, optional serial (9-pin), optional PS/2 ports (mouse / keyboard)	Rear ports	Four USB 2.0, ethernet (RJ-45), VGA-out, optional serial (9-pin), optional PS/2 ports (mouse / keyboard)																																																																						
Side ports	Two USB 3.0, one microphone (stereo, 3.5mm), one headphone (stereo, 3.5mm)	Side ports	Two USB 3.0, one microphone (stereo, 3.5mm), one headphone (stereo, 3.5mm)																																																																						
ExpressCard	None	ExpressCard	None																																																																						
PCIe Mini Card	One PCI Express Mini Card slot (half size, for WLAN)	PCIe Mini Card	One PCI Express Mini Card slot (half size, for WLAN)																																																																						
Audio support	High Definition (HD) Audio, Realtek ALC269VC / internal speakers (2watt x 2)	Audio support	High Definition (HD) Audio, Realtek ALC269VC / internal speakers (2watt x 2)																																																																						
WLAN ¹³	<i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Realtek RTL8723BE, Wi-Fi + Bluetooth combo adapter, 1x1 <i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Realtek RTL8192EE, Wi-Fi + Bluetooth combo adapter, 2x2 <i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino Wireless-N 7260, Wi-Fi + Bluetooth combo adapter, 2x2 <i>Some:</i> 11ac/a/b/g/n wireless, PCIe Half Mini Card, Intel Dual Band Wireless-AC 7260, Wi-Fi + BT combo adapter, 2x2	WLAN ¹³	<i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Realtek RTL8723BE, Wi-Fi + Bluetooth combo adapter, 1x1 <i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Realtek RTL8192EE, Wi-Fi + Bluetooth combo adapter, 2x2 <i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino Wireless-N 7260, Wi-Fi + Bluetooth combo adapter, 2x2 <i>Some:</i> 11ac/a/b/g/n wireless, PCIe Half Mini Card, Intel Dual Band Wireless-AC 7260, Wi-Fi + BT combo adapter, 2x2																																																																						
Bluetooth™	Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter	Bluetooth™	Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter																																																																						
Ethernet	One gigabit ethernet port, Intel I217-V, Wake on LAN	Ethernet	One gigabit ethernet port, Intel I217-V, Wake on LAN																																																																						
vPro & iAMT	None	vPro & iAMT	None																																																																						
Security chip	Trusted Platform Module, TCG 1.2-compliant	Security chip	Trusted Platform Module, TCG 1.2-compliant																																																																						
Environment	EPEAT™ Gold; ENERGY STAR® 6.0; GREENGUARD®; RoHS-compliant; Cisco EnergyWise compatible; EUP Lot 3	Environment	EPEAT™ Gold; ENERGY STAR® 6.0; GREENGUARD®; RoHS-compliant; Cisco EnergyWise compatible; EUP Lot 3																																																																						

See footnotes for more detailed information

ThinkCentre M83z (10C2) - TopSeller

Product Specifications Reference (PSREF)

Type-model	Processor	Memory	Widescreen display	Multi-Touch	Graphics	Camera	Storage	Optical	WLAN	Media reader	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/Mouse	Preload	Base Warranty (year)	Global	Ann Date (mm/yy)
10C20000++	G3220	4GBx1	21.5" FHD	None	Intel HD	720p	500G 7200	DVD±RW	RTL8723BE	Media	None	Switch	Frame	USB	Win7 P64 DG Win8.1	3-onsite	No	04/14
10C20001++	i3-4130	4GBx1	21.5" FHD	None	HD 4400	720p	500G 7200	DVD±RW	7260 b/g/n	Media	None	Switch	Frame	USB	Win7 P64 DG Win8.1	3-onsite	No	04/14
10C20002++	i5-4460S	4GBx1	21.5" FHD	None	HD 4600	720p	500G 7200	DVD±RW	7260 b/g/n	Media	None	Switch	Frame	USB	Win7 P64 DG Win8.1	3-onsite	No	07/14
10C20003++	i3-4150	4GBx1	21.5" FHD	None	HD 4400	720p	500G 7200	DVD±RW	7260 b/g/n	Media	None	Switch	Frame	USB	Win7 P64 DG Win8.1	3-onsite	No	07/14
10C20004++	G3240	4GBx1	21.5" FHD	None	Intel HD	720p	500G 7200	DVD±RW	RTL8723BE	Media	None	Switch	Frame	USB	Win7 P64 DG Win8.1	3-onsite	No	07/14

Country Code"+": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)

Note: models listed above might not be available in all WE countries

• For detailed platform specifications, please see [ThinkCentre M83z Platform Specifications sheet](#)

Processor	Intel® Celeron®, Pentium®, or 4th Generation Core™ i3 / i5 / i7 Processor	Audio support	High Definition (HD) Audio, Realtek ALC269VC / internal speakers (2watt x 2)																																										
	<table border="1"> <thead> <tr> <th>Processor</th> <th>Cores / Threads</th> <th>Clock Speed</th> <th>Max Turbo Frequency</th> <th>Cache</th> <th>Memory Types</th> <th>Integrated Graphics</th> </tr> </thead> <tbody> <tr> <td>Pentium G3220</td> <td>2 / 2</td> <td>3.0 GHz</td> <td>-</td> <td>3MB</td> <td>DDR3-1333</td> <td>Intel HD</td> </tr> <tr> <td>Pentium G3240</td> <td>2 / 2</td> <td>3.1 GHz</td> <td>-</td> <td>3MB</td> <td>DDR3-1333</td> <td>Intel HD</td> </tr> <tr> <td>Core i3-4130</td> <td>2 / 4</td> <td>3.4 GHz</td> <td>-</td> <td>3MB</td> <td>DDR3-1600</td> <td>Intel HD 4400</td> </tr> <tr> <td>Core i3-4150</td> <td>2 / 4</td> <td>3.5 GHz</td> <td>-</td> <td>3MB</td> <td>DDR3-1600</td> <td>Intel HD 4400</td> </tr> <tr> <td>Core i5-4460S</td> <td>4 / 4</td> <td>2.9 GHz</td> <td>3.4 GHz</td> <td>6MB</td> <td>DDR3-1600</td> <td>Intel HD 4600</td> </tr> </tbody> </table>	Processor	Cores / Threads	Clock Speed	Max Turbo Frequency	Cache	Memory Types	Integrated Graphics	Pentium G3220	2 / 2	3.0 GHz	-	3MB	DDR3-1333	Intel HD	Pentium G3240	2 / 2	3.1 GHz	-	3MB	DDR3-1333	Intel HD	Core i3-4130	2 / 4	3.4 GHz	-	3MB	DDR3-1600	Intel HD 4400	Core i3-4150	2 / 4	3.5 GHz	-	3MB	DDR3-1600	Intel HD 4400	Core i5-4460S	4 / 4	2.9 GHz	3.4 GHz	6MB	DDR3-1600	Intel HD 4600	WLAN ⁴	<p>Some: 11a/b/g/n, Realtek RTL8723BE, Wi-Fi + BT combo</p> <p>Some: 11a/b/g/n, Realtek RTL8192EE, Wi-Fi + BT combo</p> <p>Some: 11b/g/n, Intel Centrino Wireless-N 7260, Wi-Fi + BT combo</p> <p>Some: 11ac/a/b/g/n, Intel Dual Band Wireless-AC 7260, Wi-Fi + BT combo</p>
Processor	Cores / Threads	Clock Speed	Max Turbo Frequency	Cache	Memory Types	Integrated Graphics																																							
Pentium G3220	2 / 2	3.0 GHz	-	3MB	DDR3-1333	Intel HD																																							
Pentium G3240	2 / 2	3.1 GHz	-	3MB	DDR3-1333	Intel HD																																							
Core i3-4130	2 / 4	3.4 GHz	-	3MB	DDR3-1600	Intel HD 4400																																							
Core i3-4150	2 / 4	3.5 GHz	-	3MB	DDR3-1600	Intel HD 4400																																							
Core i5-4460S	4 / 4	2.9 GHz	3.4 GHz	6MB	DDR3-1600	Intel HD 4600																																							
		Bluetooth™ Ethernet	Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter One gigabit ethernet port, Intel I217-V, Wake on LAN																																										
Memory	16GB max ⁷ / DDR3 Low Voltage, DDR3L-1600*, non-parity, dual-channel capable, two 204-pin SO-DIMM sockets * System automatically clocks down for processors with 1333MHz DDR3 memory controller	vPro & iAMT Security chip:	None Trusted Platform Module, TCG 1.2-compliant																																										
Disk	<p>Some: SATA 6.0Gb/s, 3.5" Wide, 7200 rpm</p> <p>Some: 500GB (5400 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 2.5" wide</p> <p>Some: 1TB (7200 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 3.5" wide</p> <p>Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide</p>	Security features	<ul style="list-style-type: none"> Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse USB port disablement Chassis intrusion switch on selected model(s) 																																										
Optical Media reader	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable Optional 7-in-1 single slot media card reader	Keyboard	Some: Preferred Pro USB Keyboard (USB connector), Lenovo logo																																										
Graphics	Intel HD Graphics or Intel HD Graphics 4400/4600 in processor, uses main memory, DirectX® 11, one VGA-out, supports dual independent display; Maximum resolution: 1920x1200 (VGA) @60Hz (Reduced Blanking)	Mouse	Some: Ultralim Plus Wireless Keyboard (2.4GHz via USB receiver), black Some: Enhanced Optical USB Mouse, black, Lenovo logo Some: Ultralim Plus Wireless Mouse (2.4GHz via USB receiver), black																																										
Display	21.5" (546.1mm) Full HD 1080p (1920x1080) TFT color, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, anti-glare	Mechanical	<ul style="list-style-type: none"> Business black color Support VESA mount (100mm) With frame stand: <ul style="list-style-type: none"> Adjustable stand (between 10° and 25°) With monitor stand (full-function): <ul style="list-style-type: none"> Tilt: 25° back, -5° forward; Lift: 110mm; Swivel: +/-45° With monitor stand (tilt-only): <ul style="list-style-type: none"> Adjustable stand (between -5° and 45°) 																																										
Multi-touch	None	Power supply	150 watts, autosensing, 85% PSU, 100-240V (50-60Hz)																																										
Camera	Some: 720p camera, 1.0-megapixel, fixed focus, digital microphone, LED indicator, physical switch on/off	Limited warranty ¹²	Some: 3-years, limited onsite service / service upgrades available Some: 3-years, limited onsite service, IWS (International Warranty Service ⁹) / service upgrades available																																										
Controls	Some: 1080p camera, 2.0-megapixel, fixed focus, dual array digital microphone, LED indicator, physical switch on/off Brightness up/down and power button on right side	Preload	Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit Some: Windows 8.1 64-bit Some: Windows 8.1 Pro 64-bit																																										
Chipset	Intel H81 Express Chipset	Environment	EPEAT™ Gold; ENERGY STAR® 6.0; GREENGUARD®; RoHS-compliant; Cisco EnergyWise compatible; EuP Lot 3																																										
Rear ports	Four USB 2.0, ethernet (RJ-45), VGA-out, optional serial (9-pin), optional PS/2 ports (mouse / keyboard)																																												
Side ports	Two USB 3.0, one microphone (stereo, 3.5mm), one headphone (stereo, 3.5mm)																																												
ExpressCard	None																																												
PCIe Mini Card	One PCI Express Mini Card slot (half size, for WLAN)																																												

See footnotes for more detailed information

ThinkCentre M83z (10C3)

Product Specifications Reference (PSREF)

Type-model	Processor	Memory	Widescreen display	Multi-Touch	Graphics	Camera	Storage	Optical	WLAN	Media reader	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/Mouse	Preload	Base Warranty (year)	Global	Ann Date (mm/yy)
10C3001J++	i7-4770S	4GBx1	21.5" FHD	None	HD 4600	720p	1TB 7200	DVD±RW	7260 b/g/n	Media	S P	Switch	Monitor (full)	USB	Win7 P64 DG Win8.1	3-onsite	No	04/14
10C3000V++	i5-4570S	4GBx1	21.5" FHD	None	HD 4600	720p	500G Hybrid	DVD±RW	7260 b/g/n	Media	None	Switch	Monitor (full)	USB	Win7 P64 DG Win8.1	3-onsite IWS	Global	04/14
10C30014++	i3-4130	4GBx1	21.5" FHD	None	HD 4400	720p	500G 7200	DVD±RW	7260 b/g/n	Media	None	Switch	Monitor (full)	USB	Win8.1 Pro64	3-onsite IWS	Global	04/14
10C3000P++	i3-4130	4GBx1	21.5" FHD	None	HD 4400	720p	500G Hybrid	DVD±RW	7260 b/g/n	Media	S P	Switch	Monitor (full)	USB	Win7 P64 DG Win8.1	3-onsite	No	05/14
10C3000Q++	i5-4430S	4GBx1	21.5" FHD	None	HD 4600	720p	500G Hybrid	DVD±RW	7260 b/g/n	Media	None	Switch	Monitor (full)	USB	Win7 P64 DG Win8.1	3-onsite	No	05/14
10C3000U++	i3-4130	4GBx1	21.5" FHD	None	HD 4400	720p	500G 7200	DVD±RW	7260 b/g/n	Media	S P	Switch	Frame	USB	Win7 P64 DG Win8.1	3-onsite	No	05/14
10C30020++	i3-4150	4GBx1	21.5" FHD	None	HD 4400	None	500G 7200	DVD±RW	7260 b/g/n	Media	None	Switch	Frame	USB	Win7 P64	3-onsite IWS	Global	06/14
10C30021++	i5-4590S	4GBx1	21.5" FHD	None	HD 4600	720p	500G 7200	DVD±RW	7260 b/g/n	Media	None	None	Monitor (full)	USB	Win7 P64 DG Win8.1	3-onsite IWS	Global	07/14

Country Code"+": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)

Note: models listed above might not be available in all WE countries

• For detailed platform specifications, please see [ThinkCentre M83z Platform Specifications sheet](#)

Processor	Intel® Celeron®, Pentium®, or 4th Generation Core™ i3 / i5 / i7 Processor	WLAN ⁴	Some: 11a/b/g/n, Realtek RTL8723BE, Wi-Fi + BT combo Some: 11a/b/g/n, Realtek RTL8192EE, Wi-Fi + BT combo Some: 11b/g/n, Intel Centrino Wireless-N 7260, Wi-Fi + BT combo Some: 11ac/a/b/g/n, Intel Dual Band Wireless-AC 7260, Wi-Fi + BT combo																																																								
	<table border="1"> <thead> <tr> <th>Processor</th> <th>Cores / Threads</th> <th>Clock Speed</th> <th>Max Turbo Frequency</th> <th>Cache</th> <th>Memory Types</th> <th>Integrated Graphics</th> </tr> </thead> <tbody> <tr> <td>Pentium G3220</td> <td>2 / 2</td> <td>3.0 GHz</td> <td>-</td> <td>3MB</td> <td>DDR3-1333</td> <td>Intel HD</td> </tr> <tr> <td>Core i3-4130</td> <td>2 / 4</td> <td>3.4 GHz</td> <td>-</td> <td>3MB</td> <td>DDR3-1600</td> <td>Intel HD 4400</td> </tr> <tr> <td>Core i3-4150</td> <td>2 / 4</td> <td>3.5 GHz</td> <td>-</td> <td>3MB</td> <td>DDR3-1600</td> <td>Intel HD 4400</td> </tr> <tr> <td>Core i5-4430S</td> <td>4 / 4</td> <td>2.7 GHz</td> <td>3.2 GHz</td> <td>6MB</td> <td>DDR3-1600</td> <td>Intel HD 4600</td> </tr> <tr> <td>Core i5-4570S</td> <td>4 / 4</td> <td>2.9 GHz</td> <td>3.6 GHz</td> <td>6MB</td> <td>DDR3-1600</td> <td>Intel HD 4600</td> </tr> <tr> <td>Core i5-4590S</td> <td>4 / 4</td> <td>3.0 GHz</td> <td>3.7 GHz</td> <td>6MB</td> <td>DDR3-1600</td> <td>Intel HD 4600</td> </tr> <tr> <td>Core i7-4770S</td> <td>4 / 8</td> <td>3.1 GHz</td> <td>3.9 GHz</td> <td>8MB</td> <td>DDR3-1600</td> <td>Intel HD 4600</td> </tr> </tbody> </table>	Processor	Cores / Threads	Clock Speed	Max Turbo Frequency	Cache	Memory Types	Integrated Graphics	Pentium G3220	2 / 2	3.0 GHz	-	3MB	DDR3-1333	Intel HD	Core i3-4130	2 / 4	3.4 GHz	-	3MB	DDR3-1600	Intel HD 4400	Core i3-4150	2 / 4	3.5 GHz	-	3MB	DDR3-1600	Intel HD 4400	Core i5-4430S	4 / 4	2.7 GHz	3.2 GHz	6MB	DDR3-1600	Intel HD 4600	Core i5-4570S	4 / 4	2.9 GHz	3.6 GHz	6MB	DDR3-1600	Intel HD 4600	Core i5-4590S	4 / 4	3.0 GHz	3.7 GHz	6MB	DDR3-1600	Intel HD 4600	Core i7-4770S	4 / 8	3.1 GHz	3.9 GHz	8MB	DDR3-1600	Intel HD 4600	Bluetooth™ Ethernet	Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter One gigabit ethernet port, Intel I217-V, Wake on LAN
Processor	Cores / Threads	Clock Speed	Max Turbo Frequency	Cache	Memory Types	Integrated Graphics																																																					
Pentium G3220	2 / 2	3.0 GHz	-	3MB	DDR3-1333	Intel HD																																																					
Core i3-4130	2 / 4	3.4 GHz	-	3MB	DDR3-1600	Intel HD 4400																																																					
Core i3-4150	2 / 4	3.5 GHz	-	3MB	DDR3-1600	Intel HD 4400																																																					
Core i5-4430S	4 / 4	2.7 GHz	3.2 GHz	6MB	DDR3-1600	Intel HD 4600																																																					
Core i5-4570S	4 / 4	2.9 GHz	3.6 GHz	6MB	DDR3-1600	Intel HD 4600																																																					
Core i5-4590S	4 / 4	3.0 GHz	3.7 GHz	6MB	DDR3-1600	Intel HD 4600																																																					
Core i7-4770S	4 / 8	3.1 GHz	3.9 GHz	8MB	DDR3-1600	Intel HD 4600																																																					
		vPro & iAMT	None																																																								
		Security chip:	Trusted Platform Module, TCG 1.2-compliant																																																								
		Security features	<ul style="list-style-type: none"> • Security slot (in rear for attachment of optional Kensington® MicroSave® cable; Kensington lock also locks chassis) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • Chassis intrusion switch on selected model(s) 																																																								
Memory	16GB max ⁷ / DDR3 Low Voltage, DDR3L-1600*, non-parity, dual-channel capable, two 204-pin SO-DIMM sockets * System automatically clocks down for processors with 1333MHz DDR3 memory controller	Keyboard	Some: Preferred Pro USB Keyboard (USB connector), Lenovo logo Some: Ultralim Plus Wireless Keyboard (2.4GHz via USB receiver), black																																																								
Disk	Some: SATA 6.0Gb/s, 3.5" Wide, 7200 rpm Some: 500GB (5400 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 2.5" wide Some: 1TB (7200 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 3.5" wide Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide	Mouse	Some: Enhanced Optical USB Mouse, black, Lenovo logo Some: Ultralim Plus Wireless Mouse (2.4GHz via USB receiver), black																																																								
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable	Mechanical	<ul style="list-style-type: none"> • Business black color • Support VESA mount (100mm) With frame stand: <ul style="list-style-type: none"> • Adjustable stand (between 10° and 25°) With monitor stand (full-function): <ul style="list-style-type: none"> • Tilt: 25° back, -5° forward; Lift: 110mm; Swivel: +/-45° With monitor stand (tilt-only): <ul style="list-style-type: none"> • Adjustable stand (between -5° and 45°) 																																																								
Media reader	Optional 7-in-1 single slot media card reader	Power supply	150 watts, autosensing, 85% PSU, 100-240V (50-60Hz)																																																								
Graphics	Intel HD Graphics or Intel HD Graphics 4400/4600 in processor, uses main memory, DirectX® 11, one VGA-out, supports dual independent display; Maximum resolution: 1920x1200 (VGA)@60Hz (Reduced Blanking)	Limited warranty ¹²	Some: 3-years, limited onsite service / service upgrades available Some: 3-years, limited onsite service, IWS (International Warranty Service®) / service upgrades available																																																								
Display	21.5" (546.1mm) Full HD 1080p (1920x1080) TFT color, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, anti-glare	Preload	Some: Windows® 7 Professional 64 Some: Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit																																																								
Multi-touch	None		Some: Windows 8.1 64-bit Some: Windows 8.1 Pro 64-bit																																																								
Camera	Some: 720p camera, 1.0-megapixel, fixed focus, digital microphone, LED indicator, physical switch on/off Some: 1080p camera, 2.0-megapixel, fixed focus, dual array digital microphone, LED indicator, physical switch on/off	Environment	EEPEAT™ Gold; ENERGY STAR® 6.0; GREENGUARD®; RoHS-compliant; Cisco EnergyWise compatible; EuP Lot 3																																																								
Controls	Brightness up/down and power button on right side																																																										
Chipset	Intel H81 Express Chipset																																																										
Rear ports	Four USB 2.0, ethernet (RJ-45), VGA-out, optional serial (9-pin), optional PS/2 ports (mouse / keyboard)																																																										
Side ports	Two USB 3.0, one microphone (stereo, 3.5mm), one headphone (stereo, 3.5mm)																																																										
ExpressCard	None																																																										
PCIe Mini Card	One PCI Express Mini Card slot (half size, for WLAN)																																																										
Audio support	High Definition (HD) Audio, Realtek ALC269VC / internal speakers (2watt x 2)																																																										

See footnotes for more detailed information




Lenovo ThinkCentre M93/M93p Tiny with Lenovo ThinkVision Monitor



Lenovo ThinkCentre M93/M93p Tiny with optional WLAN



Lenovo ThinkCentre M93/M93p Tiny with optional external I/O box



Lenovo ThinkCentre M93/M93p Tiny with optional external optical box



Lenovo ThinkCentre M93/M93p Tiny (inside view)



Lenovo ThinkCentre M93/M93p Tiny

ThinkCentre M93/M93p Tiny, Small Pro, Mini Tower II



Lenovo ThinkCentre M93/M93p Mini Tower with Lenovo ThinkVision Monitor



Lenovo ThinkCentre M93/M93p Mini Tower with optional WLAN and graphic card




Lenovo ThinkCentre M93/M93p Small Pro with Lenovo ThinkVision Monitor



Lenovo ThinkCentre M93/M93p Small Pro with optional dual graphic cards
* Cable lock only available on some special bid models



Lenovo ThinkCentre M93/M93p Small Pro (inside view)



Optional 2.5" bay on
Lenovo ThinkCentre M93/M93p Small Pro
* Come with optional 2.5" 2nd HDD

ThinkCentre M93 Tiny (10A5) - TopSeller

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ^a	SATA disk GB	External optical / I/O box	PCle Mini Card WLAN / BT	Optional port	DP to DVI Dongle	Chassis intrusion switch	Security cable	Floor stand	VESA mount	Keyboard / mouse	Preload	Ann date (mm/dd/yy)
10A50000++	i3-4130T	4GBx1	500G Hybrid	None	Intel 105	2nd DP	2xDongle	None	None	None	Mount	USB	Win7 Pro64 (DG)	09/10/13
10A50001++	i3-4130T	4GBx1	500G Hybrid	None	Intel 105	2nd DP	None	Switch	Cable	None	Mount	USB	Win7 Pro64 (DG)	09/10/13
10A50002++	i3-4130T	4GBx1	500G Hybrid	DVD±RW	Intel 105	2nd DP	None	Switch	Cable	None	Mount	USB	Win7 Pro64 (DG)	09/10/13
10A50005++	i3-4150T	4GBx1	500G Hybrid	None	7260 b/g/n	2nd DP	None	Switch	Cable	None	Mount	USB	Win7 P64 DG Win 8.1	07/08/14
10A50006++	i3-4150T	4GBx1	500G Hybrid	DVD±RW	7260 b/g/n	2nd DP	None	Switch	Cable	None	Mount	USB	Win7 P64 DG Win 8.1	07/08/14

Country Code"++": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)
 Note: models listed above might not be available in all WE countries

• Small and medium business (SMB) model(s), part of the Western Europe TopSeller™ Program

Positioning	<i>Ultimate security, stability, and manageability for the enterprise</i>											Preloaded operating system	
Processor	Intel® Core™ i3-4130T Processor (2 cores / 4 threads, 2.9GHz, 3MB cache) , integrated Intel HD Graphics 4400, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i3-4150T Processor (2 cores / 4 threads, 3.0GHz, 3MB cache) , integrated Intel HD Graphics 4400, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1150 socket											Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit	
Implementation	Processor in LGA1150 socket											Ready to install applications (only some listed)	
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)											<ul style="list-style-type: none"> Rescue and Recovery™ Password Manager 	
Graphics	Intel HD Graphics 4400 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, one optional HDMI or one optional 2nd DisplayPort on select models, supports up to triple independent display; Maximum resolution: 2560x1600 (DisplayPort)@60Hz; 1920x1080 (HDMI)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking)											Preloaded applications (only some listed) <ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage System Update ThinkVantage Communication Utility Desktop Power Manager View Management Utility Lenovo Cloud Storage by SugarSync Lenovo Solution Center Lenovo Message Center Plus Norton™ Internet Security (30 days of virus definitions) Adobe® Reader® Skype™ Microsoft Office preloaded; purchase a product key to activate Cyberlink Power2Go (DVD±RW, DVD) Cyberlink Power2Go (DVD±RW) Cyberlink PowerProducer (DVD±RW) Evernote Intel AppUp Intel Small Business Advantage Nitro Pro 	
DP dongle	Some: DisplayPort to Single-link DVI-D Cable												
Disk	Some: 500GB (5400 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 2.5" wide												
External optical	Some: external optical box with slim DVD burner, 12.7mm high, tray-in, via USB 3.0												
SATA controller	Serial ATA, SATA 6.0Gb/s support, integrated in chipset												
Onboard SATA	One SATA cable (1-drop to device), one SATA 6.0Gb/s connector on planar												
eSATA port	None												
Chipset	Intel Q87 Express Chipset												
Front ports	Two USB 3.0 (one Always On / Powered), one microphone (stereo, 3.5mm), one headphone / microphone combo jack (stereo, 3.5mm)												
Rear ports	Three USB 3.0 (optional external optical box or external I/O box occupies one specific USB 3.0 on some models), ethernet (RJ-45), VGA DB-15, DisplayPort connector, one optional port (USB 2.0 / serial / 2nd DisplayPort / HDMI on selected models)												
I/O box	Optional external I/O box, extends four USB 2.0 (two on front and two on rear), one serial, and two PS/2 (for keyboard and mouse), via USB 3.0 port												
PCle Mini Card	One PCI Express® Mini Card slot (Half Size)												
PCle WLAN	Some: 11b/g/n wireless, PCle Half Mini Card, Intel Centrino® Wireless-N 105, 1x1 Some: 11b/g/n wireless, PCle Half Mini Card, Intel Wireless-N 7260, Wi-Fi + Bluetooth combo adapter, 2x2												
Bluetooth	Some: Bluetooth 4.0 wireless, integrated in Intel Wi-Fi + Bluetooth combo adapter											Security	
Audio	High Definition (HD) Audio, Realtek® ALC283 codec											<ul style="list-style-type: none"> Security chip (see information on left) Security slot (in rear for attachment of optional Kensington® MicroSaver® cable) 	
Speaker	Internal speaker for business audio (1.5 watt)											<ul style="list-style-type: none"> Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse Individual USB port disablement Chassis intrusion switch on selected model(s) 	
IEEE 1394	None												
Ethernet	One gigabit ethernet port, Intel I217-LM (Clarkville), Wake on LAN®												
Intel AMT	Intel Active Management Technology 9.0 (Intel AMT 9.0)												
Modem	None												
Security chip	Trusted Platform Module (TPM1.2-compliant)												
Keyboard	Preferred Pro USB Keyboard (USB connector), Lenovo® logo												
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo												
Floor Stand	Optional system floor stand for vertical orientation												
VESA mount	Optional VESA mount bracket kit, supports VESA 75mm and 100mm mount standard												
Power supply	65 watts AC/DC adapter, autosensing, 88% PSU												
Machine	<ul style="list-style-type: none"> Tiny (1L), business black color; metal case M93/p Tiny only: 7.0" W X 7.2" D X 1.4" H M93/p Tiny only: 179mm W X 182mm D X 34.5mm H M93/p Tiny only: 2.9 lb (1.3 kg), weight may vary by configuration With VESA mount & optical box: 7.2" W X 7.2" D X 2.55" H With VESA mount & optical box: 184mm W X 182mm D X 65mm H With VESA mount & optical box: 5.1 lb (2.3 kg), weight may vary by configuration 											EPEAT™ Gold rating ENERGY STAR® 6.0-compliant ULE Gold Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant	
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											Supports ThinkVantage Technologies For compatible accessories, please go to TC-AQP sheet; For Lenovo service upgrade options, please go to S-TC sheet	

See footnotes for important warranty information

©Lenovo
(G-MSS1N-3) July 2014


ThinkCentre M93 Mini Tower (10A1) - TopSeller

Product Specifications Reference (PSREF)

Type-model	Slot x Pro-processor	Memory ⁸	SATA disk GB rpm	SATA optical	PCIe WLAN	Graphics	Additional Front USB 2.0	2nd serial port	PS/2 ports	Chassis intrusion switch	Intel vPro	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)
10A10000++	4x5 i3-4130	4Gx1	500G 7200	DVD±RW	None	HD 4400	None	None	PS/2	Switch	None	None	None	12/31/14

Country Code^{9,10}: AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)
 Note: models listed above might not be available in all WE countries

• Small and medium business (SMB) model(s), part of the Western Europe TopSeller™ Program

Positioning	<i>Ultimate security, stability, and manageability for the enterprise</i>										Preloaded operating system			
Processor	Intel® Core™ i3-4130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller										Some: No operating system Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit			
Implementation	Processor in LGA1150 socket										Ready to install applications (only some listed)			
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets										<ul style="list-style-type: none"> Rescue and Recovery™ Password Manager 			
Graphics	Intel HD Graphics 4400/4600 in processor, uses main memory, DirectX® 11, one VGA, two DisplayPort™, supports three independent displays; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking)</i>										Preloaded applications (only some listed)			
DP dongle	None										<ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage System Update ThinkVantage Communication Utility Desktop Power Manager View Management Utility Lenovo Cloud Storage by SugarSync Lenovo Solution Center Lenovo Message Center Plus Norton™ Internet Security (30 days of virus definitions) Adobe® Reader® Skype™ Microsoft Office preloaded; purchase a product key to activate Cyberlink PowerDVD (DVD±RW, DVD) Cyberlink Power2Go (DVD±RW) Cyberlink PowerProducer (DVD±RW) Evernote Intel AppUp Intel Small Business Advantage Nitro Pro 			
Disk	Some: SATA 6.0Gb/s 7200 rpm, 3.5" wide													
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive													
SATA controller	Serial ATA, SATA 6.0Gb/s, integrated in chipset, RAID 0/1 support													
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 6.0Gb/s connectors, one eSATA connector (SATA 6.0Gb/s)													
eSATA port	None													
Media reader	None													
Chipset	Intel Q87 Express Chipset													
Front ports	Two USB 3.0, two optional USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), optional 2nd serial (9-pin), ethernet (RJ-45), one VGA, two DisplayPort, optional keyboard (PS/2), optional mouse (PS/2), additional VGA, DisplayPort, or HDMI ports on optional graphic card on some models													
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)													
PCIe WLAN	None													
Bluetooth	None													
Audio	High Definition (HD) Audio, Realtek® ALC662 codec													
Speaker	Internal speaker for business audio (1.5 watt)													
IEEE 1394	None													
Ethernet	One gigabit ethernet port, Intel I217-LM (Clarkville), Wake on LAN®													
Intel AMT	Intel Active Management Technology 9.0 (Intel AMT 9.0)													
Modem	None													
Security chip	Trusted Platform Module (TPM1.2-compliant)													
Keyboard	Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo													
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Power supply	280 watts, autosensing, 85% PSU													
Machine	<ul style="list-style-type: none"> Mini Tower (25L), business black color, metal case (WxDxH) 6.89" X 17.41" X 16.32"; 175mm X 442.3mm X 414.5mm 24.69 lb (11.20 kg) in maximum configuration Toolless cover removal, adapter retention Toolless disk, optical drive removal 													
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk													
Slot	Slot 1: half-length, full-height, PCIe 3.0 x16 (75w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x16 (x4 elec, 75w max) Slot 4: half-length, full-height, 32-bit PCI 2.3													
														
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available										Security <ul style="list-style-type: none"> Security chip (see information on left) One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse Serial port I/O control Individual USB port disablement Chassis intrusion switch on selected model(s) 			
											EPEAT™ Gold rating (for Windows models) ENERGY STAR® 6.0-compliant (for Windows models) ULE Gold Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies			

See footnotes for important warranty information
 WE model(s) announced December 31, 2013

©Lenovo
 (G-MSS1T-4) January 2014

ThinkCentre M93p Tiny (10AB) - TopSeller

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ^a	SATA disk GB rpm	External optical / I/O box	PCIe Mini Card WLAN / BT	Optional port	Chassis intrusion switch	Security cable	Floor stand	VESA mount	Keyboard / mouse	Intel vPro	Preload	Ann date (mm/dd/yy)
10AB000W++	i7-4765T	4GBx1	500G Hybrid	None	Intel 6235	2nd DP	Switch	Cable	None	Mount	USB	vPro	Win7 Pro64 (DG)	07/02/13
10AB000X++	i5-4570T	4GBx1	500G Hybrid	DVD±RW	Intel 6235	2nd DP	Switch	Cable	None	Mount	USB	vPro	Win7 Pro64 (DG)	07/02/13
10AB000Y++	i5-4570T	4GBx1	500G Hybrid	None	Intel 6235	2nd DP	Switch	Cable	None	Mount	USB	vPro	Win7 Pro64 (DG)	07/02/13
10AB001U++	i5-4570T	4GBx1	128G SSD	None	Intel 6235	2nd DP	Switch	Cable	None	Mount	USB	vPro	Win7 Pro64 (DG)	11/26/13
10AB002S++	i5-4570T	4GBx1	128G SSD	DVD±RW	Intel 6235	2nd DP	Switch	Cable	None	Mount	USB	vPro	Win7 Pro64 (DG)	01/14/14
10AB003C++	i5-4590T	4GBx1	500G Hybrid	None	7260 ac	2nd DP	Switch	Cable	None	Mount	USB	vPro	Win7 P64 DG Win 8.1	07/08/14
10AB003D++	i7-4785T	4GBx1	500G Hybrid	None	7260 ac	2nd DP	Switch	Cable	None	Mount	USB	vPro	Win7 P64 DG Win 8.1	07/08/14
10AB003G++	i5-4590T	4GBx1	128G SSD	None	7260 ac	2nd DP	Switch	Cable	None	Mount	USB	vPro	Win7 P64 DG Win 8.1	07/08/14
10AB003H++	i5-4590T	4GBx1	500G Hybrid	DVD±RW	7260 ac	2nd DP	Switch	Cable	None	Mount	USB	vPro	Win7 P64 DG Win 8.1	07/08/14
10AB003L++	i7-4785T	8GBx1	256G SSD	None	7260 ac	2nd DP	Switch	Cable	None	Mount	USB	vPro	Win7 P64 DG Win 8.1	07/08/14

Positioning	<i>Ultimate security, stability, and manageability for the enterprise</i>											Preloaded operating system		
Processor	Intel® Core™ i5-4570T Processor (2 cores / 4 threads, 2.9GHz, 4MB cache), Turbo Boost 2.0 (3.6GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i5-4590T Processor (2 cores / 4 threads, 2.0GHz, 6MB cache), Turbo Boost 2.0 (3.0GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i7-4765T Processor (4 cores / 8 threads, 2.0GHz, 8MB cache), Turbo Boost 2.0 (3.0GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i7-4785T Processor (4 cores / 8 threads, 2.2GHz, 8MB cache), Turbo Boost 2.0 (3.2GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Processor in LGA1150 socket											Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit		
Implementation	Processor in LGA1150 socket											Ready to install applications (only some listed)		
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)											<ul style="list-style-type: none"> Rescue and Recovery™ Password Manager 		
Graphics	Intel HD Graphics 4600 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, one optional HDMI or one optional 2nd DisplayPort on select models, supports up to triple independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz; 1920x1080 (HDMI)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking)</i>											Preloaded applications (only some listed)		
DP dongle	None											<ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage System Update ThinkVantage Communication Utility Desktop Power Manager View Management Utility Lenovo Cloud Storage by SugarSync Lenovo Solution Center Lenovo Message Center Plus Norton™ Internet Security (30 days of virus definitions) Adobe® Reader® Skype™ Microsoft Office preloaded; purchase a product key to activate Cyberlink PowerDVD (DVD±RW, DVD) Cyberlink Power2Go (DVD±RW) Cyberlink PowerProducer (DVD±RW) Evernote Intel AppUp Intel Small Business Advantage Nitro Pro 		
Disk	<i>Some:</i> 500GB (5400 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 2.5" wide <i>Some:</i> Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" wide													
External optical	<i>Some:</i> external optical box with slim DVD burner, 12.7mm high, tray-in, via USB 3.0													
SATA controller	Serial ATA, SATA 6.0Gb/s support, integrated in chipset													
Onboard SATA	One SATA cable (1-drop to device), one SATA 6.0Gb/s connector on planar													
eSATA port	None													
Chipset	Intel Q87 Express Chipset													
Front ports	Two USB 3.0 (one Always On / Powered), one microphone (stereo, 3.5mm), one headphone / microphone combo jack (stereo, 3.5mm)													
Rear ports	Three USB 3.0 (optional external optical box or external I/O box occupies one specific USB 3.0 on some models), ethernet (RJ-45), VGA DB-15, DisplayPort connector, one optional port (USB 2.0 / serial / 2nd DisplayPort / HDMI on selected models)													
I/O box	Optional external I/O box, extends four USB 2.0 (two on front and two on rear), one serial, and two PS/2 (for keyboard and mouse), via USB 3.0 port													
PCIe Mini Card	One PCI Express® Mini Card slot (Half Size)													
PCIe WLAN	<i>Some:</i> 11a/b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Advanced-N 6235, Wi-Fi + Bluetooth combo adapter, 2x2 <i>Some:</i> 11ac/a/b/g/n wireless, PCIe Half Mini Card, Intel Dual Band Wireless-AC 7260, Wi-Fi + BT combo adapter, 2x2													
Bluetooth	<i>Some:</i> Bluetooth 4.0 wireless, integrated in Intel Wi-Fi + Bluetooth combo adapter													
Audio	High Definition (HD) Audio, Realtek® ALC283 codec													
Speaker	Internal speaker for business audio (1.5 watt)													
IEEE 1394	None													
Ethernet	One gigabit ethernet port, Intel I217-LM (Clarkville), Wake on LAN®													
Intel AMT	Intel Active Management Technology 9.0 (Intel AMT 9.0)													
Modem	None													
Security chip	Trusted Platform Module (TPM1.2-compliant)											Security <ul style="list-style-type: none"> Security chip (see information on left) Security slot (in rear for attachment of optional Kensington® MicroSaver® cable) Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse Individual USB port disablement Chassis intrusion switch on selected model(s) 		
Keyboard	Preferred Pro USB Keyboard (USB connector), Lenovo® logo													
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Floor Stand	Optional system floor stand for vertical orientation													
VESA mount	Optional VESA mount bracket kit, supports VESA 75mm and 100mm mount standard													
Power supply	65 watts AC/DC adapter, autosensing, 88% PSU													
Machine	<ul style="list-style-type: none"> Tiny (1L), business black color; metal case <i>M93/p Tiny only:</i> 7.0" W X 7.2" D X 1.4" H <i>M93/p Tiny only:</i> 179mm W X 182mm D X 34.5mm H <i>M93/p Tiny only:</i> 2.9 lb (1.3 kg), weight may vary by configuration <i>With VESA mount & optical box:</i> 7.2" W X 7.2" D X 2.55" H <i>With VESA mount & optical box:</i> 184mm W X 182mm D X 65mm H <i>With VESA mount & optical box:</i> 5.1 lb (2.3 kg), weight may vary by configuration 											EPEAT™ Gold rating ENERGY STAR® 6.0-compliant ULE Gold Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant		
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											Supports ThinkVantage Technologies		

See footnotes for important warranty information

©Lenovo
(G-MSS1N-1) July 2014

ThinkCentre M93p Tiny (10AA) - GMP

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ^a	SATA disk GB rpm	External optical / I/O box	PCIe Mini Card WLAN / BT	Optional port	Chassis intrusion switch	Floor stand	VESA mount / mouse	Keyboard vPro	Intel Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)
10AA0020++	i5-4570T	4GBx1	500G 5400	DVD	Intel 2230	Serial	Switch	None	Mount	USB	vPro G P	Win7 Pro64 (DG)	07/02/13
10AA0021++	i7-4765T	4GBx1	128G SSD	DVD	Intel 2230	2nd DP	Switch	None	Mount	USB	vPro G P	Win7 Pro64 (DG)	07/02/13
10AA0022++	i5-4570T	4GBx1	500G 5400	None	Intel 2230	HDMI	Switch	Stand	None	USB	vPro G P	Win7 Pro64 (DG)	07/02/13
10AA001Y++	i5-4570T	2GBx1	320G 5400	None	Intel 105	None	Switch	Stand	None	USB	vPro G P	Win7 Pro64 (DG)	07/09/13
10AA002R++	i5-4570T	4GBx1	500G 7200	None	Intel 2230	HDMI	Switch	Stand	None	USB	vPro G P	Win7 Pro64 (DG)	10/08/13
10AA002S++	i5-4570T	4GBx1	500G 7200	DVD±RW	Intel 2230	Serial	Switch	None	Mount	USB	vPro G P	Win7 Pro64 (DG)	10/08/13
10AA002U++	i5-4570T	4GBx1	500G Hybrid	None	Intel 2230	HDMI	None	Stand	None	USB	vPro G P	Win7 Pro64 (DG)	11/12/13
10AA002V++	i7-4765T	4GBx1	500G Hybrid	None	Intel 2230	2nd DP	None	Stand	None	USB	vPro G P	Win7 Pro64 (DG)	11/12/13
10AA002W++	i5-4570T	4GBx1	500G 7200	None	Intel 105	2nd DP	None	Stand	None	USB	vPro G P	Win7 Pro64 (DG)	11/12/13
10AA003X++	i5-4570T	8GBx1	128G SSD	None	Intel 6235	2nd DP	None	Stand	None	USB	vPro G P	Win7 Pro64 (DG)	01/14/14
10AA003Y++	i7-4765T	8GBx1	256G SSD	None	Intel 6235	2nd DP	None	Stand	None	USB	vPro G P	Win7 Pro64 (DG)	01/14/14
10AA004J++	i5-4590T	2GBx1	320G 5400	None	Intel 105	None	Switch	Stand	None	USB	vPro G P	Win7 Pro64 (DG)	06/10/14

Positioning	<i>Ultimate security, stability, and manageability for the enterprise</i>										Preloaded operating system		
Processor	Intel® Core™ i5-4570T Processor (2 cores / 4 threads, 2.9GHz, 4MB cache), Turbo Boost 2.0 (3.6GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i5-4590T Processor (2 cores / 4 threads, 2.0GHz, 6MB cache), Turbo Boost 2.0 (3.0GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i7-4765T Processor (4 cores / 8 threads, 2.0GHz, 8MB cache), Turbo Boost 2.0 (3.0GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Processor in LGA1150 socket										Some: Windows® 7 Professional 64 Some: Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit		
Implementation	Processor in LGA1150 socket										Ready to install applications (only some listed)		
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)										<ul style="list-style-type: none"> Rescue and Recovery™ Password Manager 		
Graphics	Intel HD Graphics 4600 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, one optional HDMI or one optional 2nd DisplayPort on select models, supports up to triple independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz; 1920x1080 (HDMI)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking)</i>										Preloaded applications (only some listed)		
DP dongle	None										<ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage System Update ThinkVantage Communication Utility Desktop Power Manager View Management Utility Lenovo Cloud Storage by SugarSync Lenovo Solution Center Lenovo Message Center Plus Norton™ Internet Security (30 days of virus definitions) Adobe® Reader® Skype™ Microsoft Office preloaded; purchase a product key to activate Cyberlink PowerDVD (DVD±RW, DVD) Cyberlink Power2Go (DVD±RW) Cyberlink PowerProducer (DVD±RW) Evernote Intel AppUp Intel Small Business Advantage Nitro Pro 		
Disk	Some: SATA 3.0Gb/s, 2.5" Wide, 5400 rpm Some: SATA 6.0Gb/s, 2.5" Wide, 7200 rpm Some: 500GB (5400 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 2.5" wide Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide												
External optical	Some: external optical box with slim DVD-ROM, 12.7mm high, tray-in, via USB 3.0 Some: external optical box with slim DVD burner, 12.7mm high, tray-in, via USB 3.0												
SATA controller	Serial ATA, SATA 6.0Gb/s support, integrated in chipset												
Onboard SATA eSATA port	One SATA cable (1-drop to device), one SATA 6.0Gb/s connector on planar												
Chipset	Intel Q87 Express Chipset												
Front ports	Two USB 3.0 (one Always On / Powered), one microphone (stereo, 3.5mm), one headphone / microphone combo jack (stereo, 3.5mm)												
Rear ports	Three USB 3.0 (optional external optical box or external I/O box occupies one specific USB 3.0 on some models), ethernet (RJ-45), VGA DB-15, DisplayPort connector, one optional port (USB 2.0 / serial / 2nd DisplayPort / HDMI on selected models)												
I/O box	Optional external I/O box, extends four USB 2.0 (two on front and two on rear), one serial, and two PS/2 (for keyboard and mouse), via USB 3.0 port												
PCIe Mini Card	One PCI Express® Mini Card slot (Half Size)												
PCIe WLAN	Some: 11a/b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Advanced-N 6235, Wi-Fi + Bluetooth combo adapter, 2x2 Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2 Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino Wireless-N 105, 1x1 Some: Bluetooth 4.0 wireless, integrated in Intel Wi-Fi + Bluetooth combo adapter												
Bluetooth	High Definition (HD) Audio, Realtek® ALC283 codec												
Audio	Internal speaker for business audio (1.5 watt)												
Speaker	None												
IEEE 1394	None												
Ethernet	One gigabit ethernet port, Intel I217-LM (Clarkville), Wake on LAN®												
Intel AMT	Intel Active Management Technology 9.0 (Intel AMT 9.0)												
Modem	None												
Security chip	Trusted Platform Module (TPM1.2-compliant)										Security		
Keyboard	Preferred Pro USB Keyboard (USB connector), Lenovo® logo										<ul style="list-style-type: none"> Security chip (see information on left) Security slot (in rear for attachment of optional Kensington® MicroSaver® cable) Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse Individual USB port disablement Chassis intrusion switch on selected model(s) 		
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo												
Floor Stand	Optional system floor stand for vertical orientation												
VESA mount	Optional VESA mount bracket kit, supports VESA 75mm and 100mm mount standard												
Power supply	65 watts AC/DC adapter, autosensing, 88% PSU												
Machine	<ul style="list-style-type: none"> Tiny (1L), business black color; metal case M93/p Tiny only: 7.0" W X 7.2" D X 1.4" H M93/p Tiny only: 179mm W X 182mm D X 34.5mm H M93/p Tiny only: 2.9 lb (1.3 kg), weight may vary by configuration With VESA mount & optical box: 7.2" W X 7.2" D X 2.55" H With VESA mount & optical box: 184mm W X 182mm D X 65mm H With VESA mount & optical box: 5.1 lb (2.3 kg), weight may vary by configuration 										EPEAT™ Gold rating ENERGY STAR® 6.0-compliant ULE Gold Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies		
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available												

See footnotes for important warranty information

©Lenovo
(G-MSS1N-2) June 2014

ThinkCentre M93p Tiny (10AA) - GMP - II

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ⁸	SATA disk GB rpm	External optical / I/O box	Graphics	PCIe Mini Card WLAN / BT	Optional port	Chassis intrusion switch	Floor stand	VESA mount	Intel Global (G) vPro GMP (P)	Preload	Ann date (mm/dd/yy)
10AA004W++	i7-4785T	4GBx1	128G SSD	DVD	HD 4600	7260 b/g/n	2nd DP	Switch	None	Mount	vPro G P	Win7 P64 DG Win 8.1	07/08/14
10AA004X++	i5-4590T	4GBx1	500G 5400	None	HD 4600	7260 b/g/n	HDMI	Switch	Stand	None	vPro G P	Win7 P64 DG Win 8.1	07/08/14
10AA004Y++	i5-4590T	4GBx1	500G 5400	DVD	HD 4600	7260 b/g/n	Serial	Switch	None	Mount	vPro G P	Win7 P64 DG Win 8.1	07/08/14

Country Code"++": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)

Note: models listed above might not be available in all WE countries

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning	<i>Ultimate security, stability, and manageability for the enterprise</i>										
Processor	Intel® Core™ i5-4590T Processor (2 cores / 4 threads, 2.0GHz, 6MB cache), Turbo Boost 2.0 (3.0GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i7-4785T Processor (4 cores / 8 threads, 2.2GHz, 8MB cache), Turbo Boost 2.0 (3.2GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller										
Implementation	Processor in LGA1150 socket										
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)										
Graphics	Intel HD Graphics 4600 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, one optional HDMI or one optional 2nd DisplayPort on select models, supports up to triple independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz; 1920x1080 (HDMI)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking)</i>										
DP dongle	None										
Disk	<i>Some: SATA 3.0Gb/s, 2.5" Wide, 5400 rpm</i> <i>Some: SATA 6.0Gb/s, 2.5" Wide, 7200 rpm</i> <i>Some: 500GB (5400 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 2.5" wide</i> <i>Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide</i>										
External optical	<i>Some: external optical box with slim DVD-ROM, 12.7mm high, tray-in, via USB 3.0</i> <i>Some: external optical box with slim DVD burner, 12.7mm high, tray-in, via USB 3.0</i>										
SATA controller	Serial ATA, SATA 6.0Gb/s support, integrated in chipset										
Onboard SATA	One SATA cable (1-drop to device), one SATA 6.0Gb/s connector on planar										
eSATA port	None										
Chipset	Intel Q87 Express Chipset										
Front ports	Two USB 3.0 (one Always On / Powered), one microphone (stereo, 3.5mm), one headphone / microphone combo jack (stereo, 3.5mm)										
Rear ports	Three USB 3.0 (optional external optical box or external I/O box occupies one specific USB 3.0 on some models), ethernet (RJ-45), VGA DB-15, DisplayPort connector, one optional port (USB 2.0 / serial / 2nd DisplayPort / HDMI on selected models)										
I/O box	Optional external I/O box, extends four USB 2.0 (two on front and two on rear), one serial, and two PS/2 (for keyboard and mouse), via USB 3.0 port										
PCIe Mini Card	One PCI Express® Mini Card slot (Half Size)										
PCIe WLAN	<i>Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Wireless-N 7260, Wi-Fi + Bluetooth combo adapter, 2x2</i>										
Bluetooth	<i>Some: Bluetooth 4.0 wireless, integrated in Intel Wi-Fi + Bluetooth combo adapter</i>										
Audio	High Definition (HD) Audio, Realtek® ALC283 codec										
Speaker	Internal speaker for business audio (1.5 watt)										
IEEE 1394	None										
Ethernet	One gigabit ethernet port, Intel I217-LM (Clarkville), Wake on LAN®										
Intel AMT	Intel Active Management Technology 9.0 (Intel AMT 9.0)										
Modem	None										
Security chip	Trusted Platform Module (TPM1.2-compliant)										
Keyboard	Preferred Pro USB Keyboard (USB connector), Lenovo® logo										
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo										
Floor Stand	Optional system floor stand for vertical orientation										
VESA mount	Optional VESA mount bracket kit, supports VESA 75mm and 100mm mount standard										
Power supply	65 watts AC/DC adapter, autosensing, 88% PSU										
Machine	<ul style="list-style-type: none"> • Tiny (1L), business black color; metal case • <i>M93/p Tiny only:</i> 7.0" W X 7.2" D X 1.4" H • <i>M93/p Tiny only:</i> 179mm W X 182mm D X 34.5mm H • <i>M93/p Tiny only:</i> 2.9 lb (1.3 kg), weight may vary by configuration • <i>With VESA mount & optical box:</i> 7.2" W X 7.2" D X 2.55" H • <i>With VESA mount & optical box:</i> 184mm W X 182mm D X 65mm H • <i>With VESA mount & optical box:</i> 5.1 lb (2.3 kg), weight may vary by configuration 										
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available										
	Preloaded operating system <i>Some: Windows® 7 Professional 64</i> <i>Some: Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit</i>										
	Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager 										
	Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • Desktop Power Manager • View Management Utility • Lenovo Cloud Storage by SugarSync • Lenovo Solution Center • Lenovo Message Center Plus • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ • Microsoft Office preloaded; purchase a product key to activate • Cyberlink PowerDVD (DVD±RW, DVD) • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) • Evernote • Intel AppUp • Intel Small Business Advantage • Nitro Pro 										
	Security <ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement • Chassis intrusion switch on selected model(s) 										
	EPEAT™ Gold rating ENERGY STAR® 6.0-compliant ULE Gold Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies										

See footnotes for important warranty information


©Lenovo
(G-MSS1N-4) July 2014

ThinkCentre M93p SFF Pro (10A9) - TopSeller

Product Specifications Reference (PSREF)

Type-model	Slot x bay	Pro-processor	Memory ³	SATA disk GB rpm	SATA optical	Optional 2.5" Bay	PCIe WLAN	Media reader	Additional Front Graphics	2nd serial port	Chassis intrusion switch	Floor stand	Intel vPro	Preload	Ann date (mm/dd/yy)
10A90011++	4x4	i5-4570	4GBx1	500G Hybrid DVD±RW	None	None	Intel 105	None	HD 4600 USB	None	Switch	None	vPro	Win7 P64 DG Win8	06/18/13
10A90012++	4x4	i5-4570	4GBx1	128G SSD DVD±RW	None	None	Intel 6235	None	HD 4600 None	None	Switch	None	vPro	Win7 P64 DG Win8	06/18/13
10A90013++	4x4	i5-4570	4GBx1	500G 7200 DVD±RW	None	None	Intel 6235	None	HD 4600 None	None	Switch	None	vPro	Win7 P64 DG Win8	06/18/13
10A90033++	4x4	i7-4770	8GBx1	256G SSD DVD±RW	None	None	7260 ac	None	HD 4600 None	None	Switch	None	vPro	Win7 P64 DG Win8.1	03/25/13
10A9003P++	4x4	i5-4590	4GBx1	500G Hybrid DVD±RW	None	None	None	None	HD 4600 USB	None	Switch	None	vPro	Win7 P64 DG Win8.1	07/08/14
10A9003Q++	4x4	i7-4790	8GBx1	256G SSD DVD±RW	None	None	7260 ac	None	HD 4600 None	None	Switch	None	vPro	Win7 P64 DG Win8.1	07/08/14
10A9003R++	4x4	i5-4590	4GBx1	500G 7200 DVD±RW	None	None	7260 ac	None	HD 4600 None	None	Switch	None	vPro	Win7 P64 DG Win8.1	07/08/14
10A9003S++	4x4	i5-4590	4GBx1	128G SSD DVD±RW	None	None	7260 ac	None	HD 4600 None	None	Switch	None	vPro	Win7 P64 DG Win8.1	07/08/14
10A9003V++	4x4	i5-4590	4GBx1	500G 7200 DVD±RW	2.5" bay	None	7260 ac	None	HD 4600 None	None	Switch	None	vPro	Win7 P64 DG Win8.1	08/05/14

Positioning	<i>Ultimate security, stability, and manageability for the enterprise</i>													
Processor	Intel® Core™ i5-4570 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i5-4590 Processor (4 cores / 4 threads, 3.3GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i7-4770 Processor (4 cores / 8 threads, 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i7-4790 Processor (4 cores / 8 threads, 3.6GHz, 8MB cache), Turbo Boost 2.0 (4.0GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller											Preloaded operating system <i>Some:</i> Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit <i>Some:</i> Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit		
Implementation	Processor in LGA1150 socket											Ready to install applications (only some listed)		
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets													
Graphics	Intel HD Graphics 4600 in processor, uses main memory, DirectX® 11, one VGA, two DisplayPort™, supports three independent displays; <i>Maximum resolution:</i> 2560x1600 (DisplayPort)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking)													
DP dongle	None													
Disk	<i>Some:</i> SATA 6.0Gb/s 7200 rpm, 3.5" wide <i>Some:</i> 500GB (5400 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 2.5" wide <i>Some:</i> Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" wide													
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive													
SATA controller	Serial ATA, SATA 6.0Gb/s, integrated in chipset, RAID 0/1 support													
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 6.0Gb/s connectors, one eSATA connector (SATA 6.0Gb/s)													
eSATA port	None													
Media reader	None													
Chipset	Intel Q87 Express Chipset													
Front ports	Two USB 3.0, two optional USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), optional 2nd serial (9-pin), ethernet (RJ-45), one VGA, two DisplayPort, additional VGA, DisplayPort, or HDMI ports on optional graphic card on some models													
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)													
PCIe WLAN	<i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 105, 1x1 <i>Some:</i> 11a/b/g/n wireless, PCIe Half Mini Card, Intel Centrino Advanced-N 6235, Wi-Fi + Bluetooth combo adapter, 2x2 <i>Some:</i> 11ac/a/b/g/n wireless, PCIe Half Mini Card, Intel Dual Band Wireless-AC 7260, Wi-Fi + BT combo adapter, 2x2													
Bluetooth	<i>Some:</i> Bluetooth 4.0 wireless, integrated in Intel Wi-Fi + Bluetooth combo adapter													
Audio	High Definition (HD) Audio, Realtek® ALC662 codec													
Speaker	Internal speaker for business audio (1 watt)													
IEEE 1394	None													
Ethernet	One gigabit ethernet port, Intel I217-LM (Clarkville), Wake on LAN®													
Intel AMT	Intel Active Management Technology 9.0 (Intel AMT 9.0)													
Modem	None													
Security chip	Trusted Platform Module (TPM1.2-compliant)													
Keyboard	Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo													
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Floor Stand	None													
Power supply	240 watts, autosensing, 85% PSU													
Machine	<ul style="list-style-type: none"> SFF Pro (12.9L), business black color; metal case (WxDxH) 13.31" X 14.76" X 4.02"; 338mm X 375mm X 102mm 17.20 lb (7.8 kg) in maximum configuration Toolless cover removal, adapter retention Toolless disk and optical drive removal 													
Bay	Bay 1: 5.25", 1.6" high, external, std optical Bay 2: 3.5", 1" high, internal, std disk Bay 3: 2.5", N/A, internal, opt, come with opt 2.5" 2nd disk Bay 4: 3.5", 0.5" high, external, opt reader													
Slot	Slot 1: Low Profile, PCI Express 3.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, PCIe 2.0 x16 (x4 elec, 40w max) Slot 4: Low Profile, 32-bit PCI 2.3													
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											Security <ul style="list-style-type: none"> Security chip (see information on left) One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse Serial port I/O control Individual USB port disablement Chassis intrusion switch on selected model(s) 		
												EPEAT™ Gold rating ENERGY STAR® 6.0-compliant ULE Gold Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant		
	Supports ThinkVantage Technologies													



See footnotes for important warranty information

©Lenovo
(G-MSS1S-3) August 2014

ThinkCentre M93p SFF Pro (10A8)


Product Specifications Reference (PSREF)

Type-model	Slot x bay	Pro-processor	Memory ⁸	SATA disk GB rpm	SATA optical	PCIe WLAN	Media reader	Graphics	Additional Front USB 2.0	2nd serial port	Chassis intrusion switch	Floor stand	Intel vPro	Preload	Ann date (mm/dd/yy)
10A80003++	4x4	i5-4670	2GBx1	500G 7200	DVD	Intel 105	None	HD 4600	USB	None	Switch	Stand	vPro	Win7 Pro32	06/18/13

Country Code "++": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)

Note: models listed above might not be available in all WE countries

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- 1-year limited warranty

Positioning	<i>Ultimate security, stability, and manageability for the enterprise</i>											Preloaded operating system			
Processor	Intel® Core™ i5-4670 Processor (4 cores / 4 threads, 3.4GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD Graphics 4600, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology											Windows® 7 Professional 32			
Implementation	Processor in LGA1150 socket											Ready to install applications (only some listed)			
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets											<ul style="list-style-type: none"> ● Rescue and Recovery™ ● Password Manager 			
Graphics	Intel HD Graphics 4600 in processor, uses main memory, DirectX® 11, one VGA, two DisplayPort™, supports three independent displays; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking)</i>											Preloaded applications (only some listed)			
DP dongle	None											<ul style="list-style-type: none"> ● ThinkVantage® Product Recovery ● ThinkVantage System Update ● ThinkVantage Communication Utility ● Desktop Power Manager ● View Management Utility ● Lenovo Cloud Storage by SugarSync ● Lenovo Solution Center ● Lenovo Message Center Plus ● Norton™ Internet Security (30 days of virus definitions) ● Adobe® Reader® ● Skype™ ● Microsoft Office preloaded; purchase a product key to activate ● Cyberlink PowerDVD (DVD±RW, DVD) ● Cyberlink Power2Go (DVD±RW) ● Cyberlink PowerProducer (DVD±RW) ● Evernote ● Intel AppUp ● Intel Small Business Advantage ● Nitro Pro 			
Disk	SATA 6.0Gb/s 7200 rpm, 3.5" wide														
Optical	DVD-ROM DL SATA 1.5Gb/s 16-48X Max ⁴ Drive														
SATA controller	Serial ATA, SATA 6.0Gb/s, integrated in chipset, RAID 0/1 support														
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 6.0Gb/s connectors, one eSATA connector (SATA 6.0Gb/s)														
eSATA port	None														
Media reader	None														
Chipset	Intel Q87 Express Chipset														
Front ports	Two USB 3.0, two optional USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), optional 2nd serial (9-pin), ethernet (RJ-45), one VGA, two DisplayPort, additional VGA, DisplayPort, or HDMI ports on optional graphic card on some models														
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)														
PCIe WLAN	<i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 105, 1x1														
Bluetooth	None														
Audio	High Definition (HD) Audio, Realtek® ALC662 codec														
Speaker	Internal speaker for business audio (1 watt)														
IEEE 1394	None														
Ethernet	One gigabit ethernet port, Intel I217-LM (Clarkville), Wake on LAN®														
Intel AMT	Intel Active Management Technology 9.0 (Intel AMT 9.0)														
Modem	None														
Security chip	Trusted Platform Module (TPM1.2-compliant)														
Keyboard	Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo											Security			
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo											<ul style="list-style-type: none"> ● Security chip (see information on left) ● One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) ● Power-on password ● Administrator password ● Hard disk password ● Boot sequence control ● Boot without keyboard and mouse ● Serial port I/O control ● Individual USB port disablement ● Chassis intrusion switch on selected model(s) 			
Floor Stand	System floor stand for vertical orientation														
Power supply	240 watts, autosensing, 85% PSU														
Machine	<ul style="list-style-type: none"> ● SFF Pro (12.9L), business black color; metal case ● (WxDxH) 13.31" X 14.76" X 4.02"; 338mm X 375mm X 102mm ● 17.20 lb (7.8 kg) in maximum configuration ● Toolless cover removal, adapter retention ● Toolless disk and optical drive removal 														
Bay	Bay 1: 5.25", 1.6" high, external, std optical Bay 2: 3.5", 1" high, internal, std disk Bay 3: 2.5", N/A, internal, opt, come with opt 2.5" 2nd disk Bay 4: 3.5", 0.5" high, external, opt reader														
Slot	Slot 1: Low Profile, PCI Express 3.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, PCIe 2.0 x16 (x4 elec, 40w max) Slot 4: Low Profile, 32-bit PCI 2.3														
Limited Warranty	1-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											EPEAT™ Gold rating ENERGY STAR® 6.0-compliant ULE Gold Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies			


See footnotes for important warranty information
WE model(s) announced June 18, 2013

©Lenovo
(G-MSS1S-1) June 2013

ThinkCentre M93p SFF Pro (10A8) - GMP

Product Specifications Reference (PSREF)

Type-model	Slot x bay	Pro-processor	Memory ⁸	SATA disk GB rpm	SATA optical	PCIe WLAN	Media reader	Additional Front Graphics	2nd serial USB 2.0	Chassis intrusion switch	Floor stand	Intel vPro	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)
10A8001G++	4x4	i5-4570	2GBx1	500G 7200	DVD	None	None	HD 4600	None	None	Switch	None	vPro G P	Win7 Pro64	06/18/13
10A8001H++	4x4	i5-4570	4GBx1	500G 7200	DVD	Intel 105	None	HD 4600	USB	None	Switch	Stand	vPro G P	Win7 Pro64 (DG)	06/18/13
10A8001J++	4x4	i7-4770	4GBx1	1TB 7200	DVD	Intel 105	None	HD 8470	USB	None	Switch	Stand	vPro G P	Win7 Pro64 (DG)	06/18/13
10A8002C++	4x4	i5-4570	4GBx1	500G 7200	DVD±RW	None	None	HD 4600	None	None	Stand	vPro G P	Win7 Pro64 (DG)	11/12/13	
10A8002D++	4x4	i7-4770	4GBx1	500G 7200	DVD±RW	None	None	HD 4600	USB	Serial	None	Stand	vPro G P	Win7 Pro64 (DG)	11/12/13
10A8003U++	4x4	i5-4590	2GBx1	500G 7200	DVD	None	None	HD 4600	None	None	Switch	None	vPro G P	Win7 Pro64	06/10/14
10A80049++	4x4	i7-4790	4GBx1	1TB 7200	DVD	8723BE	None	GT 620	None	None	Switch	Stand	vPro G P	Win7 P64 DG Win 8.1	07/08/14
10A8004A++	4x4	i5-4590	4GBx1	500G 7200	DVD	8723BE	None	HD 4600	None	None	Switch	Stand	vPro G P	Win7 P64 DG Win 8.1	07/08/14

Positioning	<i>Ultimate security, stability, and manageability for the enterprise</i>											Preloaded operating system			
Processor	Intel® Core™ i5-4570 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i5-4590 Processor (4 cores / 4 threads, 3.3GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i7-4770 Processor (4 cores / 8 threads, 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i7-4790 Processor (4 cores / 8 threads, 3.6GHz, 8MB cache), Turbo Boost 2.0 (4.0GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller											<i>Some:</i> Windows® 7 Professional 64 <i>Some:</i> Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit <i>Some:</i> Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit			
Implementation	Processor in LGA1150 socket											Ready to install applications (only some listed)			
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets											<ul style="list-style-type: none"> Rescue and Recovery™ Password Manager 			
Graphics	Intel HD Graphics 4600 in processor, uses main memory, DirectX® 11, one VGA, two DisplayPort™, supports three independent displays, works along with discrete graphics to support up to five independent monitors; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz;</i> 1920x1200 (VGA)@60Hz (Reduced Blanking) <i>Some: AMD Radeon™ HD 8470, DirectX 11, 3D Hardware Acceleration, 512MB, PCI Express® 2.0 x16 adapter, one VGA, one DisplayPort, 25 watts, Max resolution: 2560x1600 (DisplayPort)@60Hz; 2048x1536 (VGA)@85Hz</i> <i>Some: NVIDIA® Geforce® GT 620, DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express 2.0 x16 adapter, one VGA, one DisplayPort, 30 watts; Max resolution: 2560x1600 (DisplayPort)@60Hz; 2048x1536 (VGA)@85Hz</i>											Preloaded applications (only some listed) <ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage System Update ThinkVantage Communication Utility Desktop Power Manager View Management Utility Lenovo Cloud Storage by SugarSync Lenovo Solution Center Lenovo Message Center Plus Norton™ Internet Security (30 days of virus definitions) Adobe® Reader® Skype™ Microsoft Office preloaded; purchase a product key to activate Cyberlink PowerDVD (DVD±RW, DVD) Cyberlink Power2Go (DVD±RW) Cyberlink PowerProducer (DVD±RW) Evernote Intel AppUp Intel Small Business Advantage Nitro Pro 			
DP dongle	None														
Disk	SATA 6.0Gb/s 7200 rpm, 3.5" wide														
Optical	<i>Some:</i> DVD-ROM DL SATA 1.5Gb/s 16-48X Max ⁴ Drive <i>Some:</i> Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive														
SATA controller	Serial ATA, SATA 6.0Gb/s, integrated in chipset, RAID 0/1 support														
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 6.0Gb/s connectors, one eSATA connector (SATA 6.0Gb/s)														
eSATA port	None														
Media reader	None														
Chipset	Intel Q87 Express Chipset														
Front ports	Two USB 3.0, two optional USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), optional 2nd serial (9-pin), ethernet (RJ-45), one VGA, two DisplayPort, additional VGA, DisplayPort, or HDMI ports on optional graphic card on some models														
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)														
PCIe WLAN	<i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 105, 1x1 <i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Realtek RTL8723BE, Wi-Fi/BT 4.0, 1x1 <i>Some:</i> Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter														
Bluetooth	High Definition (HD) Audio, Realtek® ALC662 codec														
Audio	Internal speaker for business audio (1 watt)														
Speaker	None														
IEEE 1394	None														
Ethernet	One gigabit ethernet port, Intel I217-LM (Clarkville), Wake on LAN®														
Intel AMT	Intel Active Management Technology 9.0 (Intel AMT 9.0)														
Modem	None														
Security chip	Trusted Platform Module (TPM1.2-compliant)											Security <ul style="list-style-type: none"> Security chip (see information on left) One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse Serial port I/O control Individual USB port disablement Chassis intrusion switch on selected model(s) 			
Keyboard	Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo														
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo														
Floor Stand	<i>Some:</i> System floor stand for vertical orientation														
Power supply	240 watts, autosensing, 85% PSU														
Machine	<ul style="list-style-type: none"> SFF Pro (12.9L), business black color; metal case (WxDxH) 13.31" X 14.76" X 4.02"; 338mm X 375mm X 102mm 17.20 lb (7.8 kg) in maximum configuration Toolless cover removal, adapter retention Toolless disk and optical drive removal 														
Bay	Bay 1: 5.25", 1.6" high, external, std optical Bay 2: 3.5", 1" high, internal, std disk Bay 3: 2.5", N/A, internal, opt, come with opt 2.5" 2nd disk Bay 4: 3.5", 0.5" high, external, opt reader														
Slot	Slot 1: Low Profile, PCI Express 3.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, PCIe 2.0 x16 (x4 elec, 40w max) Slot 4: Low Profile, 32-bit PCI 2.3											EPEAT™ Gold rating ENERGY STAR® 6.0-compliant ULE Gold Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant			
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											Supports ThinkVantage Technologies			


See footnotes for important warranty information

©Lenovo
(G-MSS1S-2) July 2014

ThinkCentre M93p Mini Tower (10A7) - TopSeller

Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	PCIe WLAN	Media reader	Graphics	Additional Front USB 2.0	2nd serial port	PS/2 ports	Chassis intrusion switch	Intel vPro	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)
10A7000L++	4x5	i7-4770	4Gx1	1TB 7200	DVD±RW	Intel 6235	None	HD 4600	None	None	PS/2	Switch	vPro	None	Win7 P64 DG Win 8	06/18/13
10A7000M++	4x5	i5-4570	4Gx1	500G 7200	DVD±RW	Intel 6235	None	HD 4600	None	None	PS/2	Switch	vPro	None	Win7 P64 DG Win 8	06/18/13
10A7000N++	4x5	i5-4570	4Gx1	128G SSD	DVD±RW	Intel 6235	None	HD 4600	None	None	PS/2	Switch	vPro	None	Win7 P64 DG Win 8	06/18/13
10A7000P++	4x5	i5-4570	4Gx1	500G Hybrid	DVD±RW	Intel 105	None	HD 4600	USB	None	PS/2	Switch	vPro	None	Win7 P64 DG Win 8	06/18/13
10A7001T++	4x5	i7-4770	4Gx2	256G SSD	DVD±RW	Intel 6235	None	HD 4600	None	None	PS/2	Switch	vPro	None	Win7 P64 DG Win 8	12/10/13
10A7002J++	4x5	i7-4770	8Gx1	1TB Hybrid	DVD±RW	None	Media	HD 4600	None	None	PS/2	Switch	vPro	None	Win7 P64 DG Win 8.1	03/25/14
10A70036++	4x5	i5-4590	4Gx1	500G 7200	DVD±RW	7260 ac	None	HD 4600	None	None	PS/2	Switch	vPro	None	Win7 P64 DG Win 8.1	07/08/14
10A70037++	4x5	i7-4790	4Gx2	256G SSD	DVD±RW	7260 ac	None	HD 4600	None	None	PS/2	Switch	vPro	None	Win7 P64 DG Win 8.1	07/08/14
10A70038++	4x5	i5-4590	4Gx1	128G SSD	DVD±RW	7260 ac	None	HD 4600	None	None	PS/2	Switch	vPro	None	Win7 P64 DG Win 8.1	07/08/14
10A70039++	4x5	i5-4590	4Gx1	500G Hybrid	DVD±RW	None	None	HD 4600	USB	None	PS/2	Switch	vPro	None	Win7 P64 DG Win 8.1	07/08/14
10A7003A++	4x5	i7-4790	8Gx1	1TB Hybrid	DVD±RW	None	Media	HD 4600	None	None	PS/2	Switch	vPro	None	Win7 P64 DG Win 8.1	07/08/14
10A7003B++	4x5	i7-4790	4Gx1	1TB 7200	DVD±RW	7260 ac	None	HD 4600	None	None	PS/2	Switch	vPro	None	Win7 P64 DG Win 8.1	07/08/14

Positioning	<i>Ultimate security, stability, and manageability for the enterprise</i>											Preloaded operating system									
Processor	Intel® Core™ i5-4570 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i5-4590 Processor (4 cores / 4 threads, 3.3GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i7-4770 Processor (4 cores / 8 threads, 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i7-4790 Processor (4 cores / 8 threads, 3.6GHz, 8MB cache), Turbo Boost 2.0 (4.0GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller											Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit					Some: Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit				
Implementation	Processor in LGA1150 socket											Ready to install applications (only some listed)									
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets											<ul style="list-style-type: none"> Rescue and Recovery™ Password Manager 									
Graphics	Intel HD Graphics 4600 in processor, uses main memory, DirectX® 11, one VGA, two DisplayPort™, supports three independent displays; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking)</i>											Preloaded applications (only some listed)									
Disk	<i>Some:</i> SATA 6.0Gb/s 7200 rpm, 3.5" wide <i>Some:</i> 500GB (5400 rpm) or 1TB (7200 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 2.5" wide <i>Some:</i> Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" wide											<ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage System Update ThinkVantage Communication Utility Desktop Power Manager View Management Utility Lenovo Cloud Storage by SugarSync Lenovo Solution Center Lenovo Message Center Plus Norton™ Internet Security (30 days of virus definitions) Adobe® Reader® Skype™ Microsoft Office preloaded; purchase a product key to activate Cyberlink PowerDVD (DVD±RW, DVD) Cyberlink Power2Go (DVD±RW) Cyberlink PowerProducer (DVD±RW) Evernote Intel AppUp Intel Small Business Advantage Nitro Pro 									
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive											Security <ul style="list-style-type: none"> Security chip (see information on left) One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse Serial port I/O control Individual USB port disablement Chassis intrusion switch on selected model(s) 									
SATA controller	Serial ATA, SATA 6.0Gb/s, integrated in chipset, RAID 0/1 support																				
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 6.0Gb/s connectors, one eSATA connector (SATA 6.0Gb/s)																				
eSATA port	None																				
Media reader	<i>Some:</i> 29-in-1 media reader, internal USB 2.0																				
Chipset	Intel Q87 Express Chipset																				
Front ports	Two USB 3.0, two optional USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)																				
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), optional 2nd serial (9-pin), ethernet (RJ-45), one VGA, two DisplayPort, optional keyboard (PS/2), optional mouse (PS/2), additional VGA, DisplayPort, or HDMI ports on optional graphic card on some models																				
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)																				
PCIe WLAN	<i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 105, 1x1 <i>Some:</i> 11a/b/g/n wireless, PCIe Half Mini Card, Intel Centrino Advanced-N 6235, Wi-Fi + Bluetooth combo adapter, 2x2 <i>Some:</i> 11ac/a/b/g/n wireless, PCIe Half Mini Card, Intel Dual Band Wireless-AC 7260, Wi-Fi + BT combo adapter, 2x2																				
Bluetooth	<i>Some:</i> Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter																				
Audio	High Definition (HD) Audio, Realtek® ALC662 codec																				
Speaker	Internal speaker for business audio (1.5 watt)																				
IEEE 1394	None																				
Ethernet	One gigabit ethernet port, Intel I217-LM (Clarkville), Wake on LAN®																				
Intel AMT	Intel Active Management Technology 9.0 (Intel AMT 9.0)																				
Security chip	Trusted Platform Module (TPM1.2-compliant)																				
Keyboard	Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo																				
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo																				
Power supply	280 watts, autosensing, 85% PSU																				
Machine	<ul style="list-style-type: none"> Mini Tower (25L), business black color, metal case (WxDxH) 6.89" X 17.41" X 16.32"; 175mm X 442.3mm X 414.5mm 24.69 lb (11.20 kg) in maximum configuration Toolless cover removal, adapter retention Toolless disk, optical drive removal 																				
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk																				
Slot	Slot 1: half-length, full-height, PCIe 3.0 x16 (75w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x16 (x4 elec, 75w max) Slot 4: half-length, full-height, 32-bit PCI 2.3																				
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available																				
See footnotes for important warranty information												Supports ThinkVantage Technologies									

ThinkCentre M93p Mini Tower (10A6)


Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	PCIe WLAN	Media reader	Graphics	Additional Front USB 2.0	2nd serial port	Chassis intrusion switch	Intel vPro	Global	Preload	Ann date (mm/dd/yy)
10A60004++	4x5	i7-4770	4GBx1	1TB 7200	DVD	Intel 105	None	HD 8470	USB	None	Switch	vPro	None	Win7 Pro64	06/18/13

Country Code"++": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)
 Note: models listed above might not be available in all WE countries

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- 1-year limited warranty

Positioning	<i>Ultimate security, stability, and manageability for the enterprise</i>											Preloaded operating system
Processor	Intel® Core™ i7-4770 Processor (4 cores / 8 threads, 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4600, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology											Windows® 7 Professional 64
Implementation	Processor in LGA1150 socket											Ready to install applications (only some listed)
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets											<ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager
Graphics	Intel HD Graphics 4600 in processor, uses main memory, DirectX® 11, one VGA, two DisplayPort™, supports three independent displays, works along with discrete graphics to support up to five independent monitors; Maximum resolution: 2560x1600 (DisplayPort)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking) Some: AMD Radeon™ HD 8470, DirectX 11, 3D Hardware Acceleration, 512MB, PCI Express® 2.0 x16 adapter, one VGA, one DisplayPort, 25 watts, Max resolution: 2560x1600 (DisplayPort)@60Hz; 2048x1536 (VGA)@85Hz											Preloaded applications (only some listed)
DP dongle	None											<ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • Desktop Power Manager • View Management Utility • Lenovo Cloud Storage by SugarSync • Lenovo Solution Center • Lenovo Message Center Plus • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ • Microsoft Office preloaded; purchase a product key to activate • Cyberlink PowerDVD (DVD±RW, DVD) • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) • Evernote • Intel AppUp • Intel Small Business Advantage • Nitro Pro
Disk	SATA 6.0Gb/s 7200 rpm, 3.5" wide											Security <ul style="list-style-type: none"> • Security chip (see information on left) • One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Serial port I/O control • Individual USB port disablement • Chassis intrusion switch on selected model(s)
Optical	DVD-ROM DL SATA 1.5Gb/s 16-48X Max ⁴ Drive											
SATA controller	Serial ATA, SATA 6.0Gb/s, integrated in chipset, RAID 0/1 support											
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 6.0Gb/s connectors, one eSATA connector (SATA 6.0Gb/s)											
eSATA port	None											
Media reader	None											
Chipset	Intel Q87 Express Chipset											
Front ports	Two USB 3.0, two optional USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)											
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), optional 2nd serial (9-pin), ethernet (RJ-45), one VGA, two DisplayPort, additional VGA, DisplayPort, or HDMI ports on optional graphic card on some models											
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)											
PCIe WLAN	Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 105, 1x1											
Bluetooth	None											
Audio	High Definition (HD) Audio, Realtek® ALC662 codec											
Speaker	Internal speaker for business audio (1.5 watt)											
IEEE 1394	None											
Ethernet	One gigabit ethernet port, Intel I217-LM (Clarkville), Wake on LAN®											
Intel AMT	Intel Active Management Technology 9.0 (Intel AMT 9.0)											
Modem	None											
Security chip	Trusted Platform Module (TPM 1.2-compliant)											
Keyboard	Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo											
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo											
Power supply	280 watts, autosensing, 85% PSU											
Machine	<ul style="list-style-type: none"> • Mini Tower (25L), business black color, metal case • (WxDxH) 6.89" X 17.41" X 16.32"; 175mm X 442.3mm X 414.5mm • 24.69 lb (11.20 kg) in maximum configuration • Toolless cover removal, adapter retention • Toolless disk, optical drive removal 											
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk											
Slot	Slot 1: half-length, full-height, PCIe 3.0 x16 (75w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x16 (x4 elec, 75w max) Slot 4: half-length, full-height, 32-bit PCI 2.3											
Limited Warranty	1-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											EPEAT™ Gold rating ENERGY STAR® 6.0-compliant ULE Gold Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies




See footnotes for important warranty information
 WE model(s) announced June 18, 2013

©Lenovo
 (G-MSS1T-1) June 2013

ThinkCentre M93p Mini Tower (10A6) - GMP

Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory ^a	SATA disk GB rpm	SATA optical	PCIe WLAN	Media reader	Graphics	Additional Front USB 2.0	2nd serial port	Chassis intrusion switch	Intel vPro	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)
10A60017++	4x5	i5-4570	2GBx1	500G 7200	DVD±RW	None	None	HD 4600	None	None	Switch	vPro	G P	Win7 Pro64	06/18/13
10A60018++	4x5	i7-4770	4GBx1	1TB 7200	DVD±RW	Intel 105	None	HD 8470	USB	None	Switch	vPro	G P	Win7 Pro64 (DG)	06/18/13
10A60019++	4x5	i5-4570	4GBx1	500G 7200	DVD±RW	Intel 105	None	HD 4600	USB	None	Switch	vPro	G P	Win7 Pro64 (DG)	06/18/13
10A6001D++	4x5	i5-4570	4GBx1	500G 7200	DVD	Intel 105	None	HD 4600	USB	None	Switch	vPro	G P	Win7 Pro64 (DG)	08/20/13
10A6001E++	4x5	i7-4770	4GBx1	1TB 7200	DVD	Intel 105	None	HD 8470	USB	None	Switch	vPro	G P	Win7 Pro64 (DG)	08/20/13
10A6001F++	4x5	i5-4570	2GBx1	500G 7200	DVD	None	None	HD 4600	None	None	Switch	vPro	G P	Win7 Pro64	08/20/13
10A6001S++	4x5	i7-4770	4GBx1	500G 7200	DVD±RW	None	None	HD 4600	USB	Serial	None	vPro	G P	Win7 Pro64 (DG)	11/12/13
10A6001T++	4x5	i5-4570	4GBx1	500G 7200	DVD±RW	None	None	HD 4600	None	None	None	vPro	G P	Win7 Pro64 (DG)	11/12/13
10A6002S++	4x5	i5-4590	2GBx1	500G 7200	DVD±RW	None	None	HD 4600	None	None	Switch	vPro	G P	Win7 Pro64	06/10/14
10A6002Y++	4x5	i5-4590	4GBx1	500G 7200	DVD±RW	8723BE	None	HD 4600	None	None	Switch	vPro	G P	Win7 P64 DG Win8.1	07/08/14
10A60030++	4x5	i7-4790	4GBx1	1TB 7200	DVD±RW	8723BE	None	GT 620	None	None	Switch	vPro	G P	Win7 P64 DG Win8.1	07/08/14
Positioning	<i>Ultimate security, stability, and manageability for the enterprise</i>											Preloaded operating system			
Processor	Intel® Core™ i5-4570 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i5-4590 Processor (4 cores / 4 threads, 3.3GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i7-4770 Processor (4 cores / 8 threads, 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i7-4790 Processor (4 cores / 8 threads, 3.6GHz, 8MB cache), Turbo Boost 2.0 (4.0GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller											Some: Windows® 7 Professional 64 Some: Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit			
Implementation	Processor in LGA1150 socket											Ready to install applications (only some listed)			
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets											<ul style="list-style-type: none"> Rescue and Recovery™ Password Manager 			
Graphics	Intel HD Graphics 4600 in processor, uses main memory, DirectX® 11, one VGA, two DisplayPort™, supports three independent displays, works along with discrete graphics to support up to five independent monitors; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking)</i> Some: AMD Radeon™ HD 8470 , DirectX 11, 3D Hardware Acceleration, 512MB, PCI Express® 2.0 x16 adapter, one VGA, one DisplayPort, 25 watts, <i>Max resolution: 2560x1600 (DisplayPort)@60Hz; 2048x1536 (VGA)@85Hz</i> Some: NVIDIA® GeForce® GT 620 , DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express 2.0 x16 adapter, one VGA, one DisplayPort, 30 watts; <i>Max resolution: 2560x1600 (DisplayPort)@60Hz; 2048x1536 (VGA)@85Hz</i>											Preloaded applications (only some listed) <ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage System Update ThinkVantage Communication Utility Desktop Power Manager View Management Utility Lenovo Cloud Storage by SugarSync Lenovo Solution Center Lenovo Message Center Plus Norton™ Internet Security (30 days of virus definitions) Adobe® Reader® Skype™ Microsoft Office preloaded; purchase a product key to activate Cyberlink PowerDVD (DVD±RW, DVD) Cyberlink Power2Go (DVD±RW) Cyberlink PowerProducer (DVD±RW) Evernote Intel AppUp Intel Small Business Advantage Nitro Pro 			
Disk	SATA 6.0Gb/s 7200 rpm, 3.5" wide											Security <ul style="list-style-type: none"> Security chip (see information on left) One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse Serial port I/O control Individual USB port disablement Chassis intrusion switch on selected model(s) 			
Optical	Some: DVD-ROM DL SATA 1.5Gb/s 16-48X Max ⁴ Drive Some: Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive														
SATA controller	Serial ATA, SATA 6.0Gb/s, integrated in chipset, RAID 0/1 support											EPEAT™ Gold rating ENERGY STAR® 6.0-compliant ULE Gold Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant			
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 6.0Gb/s connectors, one eSATA connector (SATA 6.0Gb/s)														
eSATA port	None											Supports ThinkVantage Technologies			
Media reader	None														
Chipset	Intel Q87 Express Chipset														
Front ports	Two USB 3.0, two optional USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), optional 2nd serial (9-pin), ethernet (RJ-45), one VGA, two DisplayPort, additional VGA, DisplayPort, or HDMI ports on optional graphic card on some models														
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)														
PCIe WLAN	Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 105, 1x1 Some: 11b/g/n wireless, PCIe Half Mini Card, Realtek RTL8723BE, Wi-Fi/BT 4.0, 1x1 Some: Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter														
Bluetooth	High Definition (HD) Audio, Realtek® ALC662 codec														
Audio	Internal speaker for business audio (1.5 watt)														
Speaker	None														
IEEE 1394	None														
Ethernet	One gigabit ethernet port, Intel I217-LM (Clarkville), Wake on LAN®														
Intel AMT	Intel Active Management Technology 9.0 (Intel AMT 9.0)														
Security chip	Trusted Platform Module (TPM1.2-compliant)														
Keyboard	Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo														
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo														
Power supply	280 watts, autosensing, 85% PSU														
Machine	<ul style="list-style-type: none"> Mini Tower (25L), business black color, metal case (WxDxH) 6.89" X 17.41" X 16.32"; 175mm X 442.3mm X 414.5mm 24.69 lb (11.20 kg) in maximum configuration Toolless cover removal, adapter retention Toolless disk, optical drive removal 														
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk														
Slot	Slot 1: half-length, full-height, PCIe 3.0 x16 (75w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x16 (x4 elec, 75w max) Slot 4: half-length, full-height, 32-bit PCI 2.3														
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available														



See footnotes for important warranty information

ThinkCentre M92z All-In-One



Lenovo ThinkCentre M92z with Frame Stand



Lenovo ThinkCentre M92z with Monitor Stand



Toolless Back Cover Removal



Toolless Stand Removal



Dual Independent Display with Optional Lenovo ThinkVision Monitor

ThinkCentre M92z (3280) - 20" (TopSeller) - Win 8

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ^a	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial port	Chassis intrusion switch	Stand type	Key-board/ Mouse	Intel vPro	Global	Preload	Ann date (mm/dd/yy)
3280-A4G	G645	4GBx1	2.0M	500G 7200	Intel HD	11b/g/n	Media	None	S P	Switch	Frame	USB	None	None	Win7 Pro64	10/23/12

- Small and medium business (SMB) model(s), part of the Western Europe TopSeller™ Program
- 1-year limited warranty

Positioning	<i>Premium All-In-One PC for the enterprise</i>											Preloaded operating system²⁰				
Processor	Intel® Pentium® G645 Processor (2 cores / 2 threads, 2.9GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology											Genuine Windows® 7 Professional 64				
Implementation	Processor in LGA1155 socket											Ready to install applications (only some listed)				
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)											<ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager • Business-in-a-Box 				
Graphics	Intel HD Graphics in processor, uses main memory, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>											Preloaded applications (only some listed)				
DP dongle	None											<ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Automatic Lock Utility • ThinkVantage Power Manager • View Management Utility • Lenovo® Solution Center • Lenovo Message Center Plus • RapidBoot HDD Accelerator • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 				
Display	20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, work as standalone monitor via DisplayPort-in connector															
Light sensor	None															
Multi-touch	None															
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off															
Controls	<i>Front:</i> Microphone mute, speaker mute, monitor mode, OSD menu, and power button <i>Side:</i> Volume up and down buttons															
Disk	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm															
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable															
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar															
Media reader	None															
Chipset	Intel Q77 Express Chipset															
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)															
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)															
ExpressCard	None															
mSATA	One mSATA slot															
PCIe Mini Card	One PCI Express® Mini Card slot															
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2															
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter															
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®															
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified															
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)															
Security chip	Trusted Platform Module (TPM 1.2-compliant)															
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo															
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo															
Power supply	150 watts, autosensing, 85% PSU															
Machine	<i>Model(s) with 20" Non multi-touch, Frame stand:</i> <ul style="list-style-type: none"> • Business black color • 19.8" W X 3.6" D X 16.1" H, • 503mm W X 92.5mm D X 408mm H (including stand) • 18.5 lb (8.4 kg) in maximum configuration • Toolless back cover, stand removal • Toolless disk, optical drive, memory removal • Support VESA mount (100mm) 											Security <ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • Chassis intrusion switch on selected model(s) 				
Limited Warranty	1-year, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge TUV Green Mark ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies				

ThinkCentre M92z (3291) - 20" (TopSeller) - Win 8

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ⁸	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/Mouse	Intel vPro Global	Preload	Ann date (mm/dd/yy)	
3291-E3G	G2020	4GBx1	2.0M	500G 7200	Intel HD	11b/g/n	Media	Sensor	S P	Switch	Frame	USB	None	None	Win7 Pro64	03/26/13
3291-E4G	G2020	4GBx1	2.0M	500G 7200	Intel HD	11b/g/n	Media	Sensor	S P	Switch	Frame	USB	None	None	Win8 Pro64	03/26/13
3291-E5G	G2030	4GBx1	2.0M	500G 7200	Intel HD	11b/g/n	Media	Sensor	None	Switch	Frame	USB	None	None	Win7 Pro64	06/11/13
3291-E6G	G2030	4GBx1	2.0M	500G 7200	Intel HD	11b/g/n	Media	Sensor	S P	Switch	Monitor	USB	None	None	Win8 Pro64	06/11/13

- Small and medium business (SMB) model(s), part of the Western Europe TopSeller™ Program
- 3-year limited warranty

Positioning	<i>Premium All-In-One PC for the enterprise</i>											Preloaded operating system²⁰			
Processor	Intel® Pentium® G2020 Processor (2 cores / 2 threads, 2.9GHz, 3MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Pentium G2030 Processor (2 cores / 2 threads, 3.0GHz, 3MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit			
Implementation	Processor in LGA1155 socket											Preloaded applications (only some listed)			
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)											- Windows 7 models			
Graphics	Intel HD Graphics in processor, uses main memory, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>											<ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage Communication Utility • ThinkVantage Power Manager • RapidBoot HDD Accelerator • Lenovo® SimpleTap • Adobe® Reader® • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 			
DP dongle	None											- Windows 8 models			
Display	20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, work as standalone monitor via DisplayPort-in connector											<ul style="list-style-type: none"> • Lenovo Support • Lenovo Settings • Lenovo Companion • Lenovo Cloud Storage • Lenovo QuickLaunch • Norton™ Studio • AccuWeather • Evernote® • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) 			
Light sensor	Ambient Light Sensor														
Multi-touch	None														
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off														
Controls	<i>Front:</i> Microphone mute, speaker mute, monitor mode, OSD menu, and power button <i>Side:</i> Volume up and down buttons														
Disk	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm														
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable														
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar														
Media reader	None														
Chipset	Intel Q77 Express Chipset											- All models			
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)											<ul style="list-style-type: none"> • ThinkVantage System Update • ThinkVantage Automatic Lock Utility • Lenovo Solution Center • View Management Utility • Norton Internet Security (30 days of virus definitions) • Microsoft® Office preloaded; purchase a product key to activate • Skype™ 			
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
ExpressCard	None														
mSATA	One mSATA slot														
PCIe Mini Card	One PCI Express® Mini Card slot														
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2														
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter														
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®														
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified														
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)														
Security chip	Trusted Platform Module (TPM 1.2-compliant)														
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo														
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo														
Power supply	150 watts, autosensing, 85% PSU														
Machine	<i>Model(s) with 20" Non multi-touch, Frame stand:</i> <ul style="list-style-type: none"> • Business black color • 19.8" W X 3.6" D X 16.1" H, • 503mm W X 92.5mm D X 408mm H (including stand) • 18.5 lb (8.4 kg) in maximum configuration • Toolless back cover, stand removal • Toolless disk, optical drive, memory removal • Support VESA mount (100mm) 											Security <ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • Chassis intrusion switch on selected model(s) 			
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge TUV Green Mark ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies			

ThinkCentre M92z (3296) - 20"

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ^a	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/ Mouse	Intel vPro Global	Win7 preload (mm/dd/yy)	Ann date (mm/dd/yy)
3296-A1G	G630	2GBx1	None	500G 7200	Intel HD	None	None	None	None	Switch	Frame	USB	None	Pro 64	06/05/12
3296-A2G	i3-2130	4GBx1	2.0M	500G 7200	HD 2000	None	Media	None	None	Switch	Frame	USB	None	Pro 64	06/05/12

●3-year limited warranty

Positioning	<i>Premium All-In-One PC for the enterprise</i>											Preloaded operating system²⁰			
Processor	Intel® Pentium® G630 Processor (2 cores / 2 threads, 2.7GHz, 3MB cache) , integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core™ i3-2130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache) , integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Genuine Windows® 7 Professional 64 Ready to install applications (only some listed) <ul style="list-style-type: none"> ● Rescue and Recovery™ ● Password Manager ● Business-in-a-Box 			
Implementation												Preloaded applications (only some listed)			
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)											<ul style="list-style-type: none"> ● ThinkVantage® Product Recovery ● ThinkVantage System Update ● ThinkVantage Communication Utility ● ThinkVantage Automatic Lock Utility ● ThinkVantage Power Manager ● View Management Utility ● Lenovo Solution Center ● Lenovo Message Center Plus ● RapidBoot HDD Accelerator ● Lenovo SimpleTap ● Norton™ Internet Security (30 days of virus definitions) ● Adobe® Reader® ● Skype™ for Windows ● Windows Live™ Essentials ● Microsoft® Office preloaded; purchase a product key to activate ● Corel® Burn.Now™ (DVD±RW) ● Corel DVD MovieFactory® (DVD±RW) 			
Graphics	Intel HD Graphics or Intel HD Graphics 2000 in processor, uses main memory, HDCP, DirectX® 10.1, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort) @60Hz</i>														
DP dongle	None														
Display	20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, work as standalone monitor via DisplayPort-in connector														
Light sensor	None														
Multi-touch	None														
Camera	<i>Some:</i> Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off														
Controls	<i>Front:</i> Microphone mute, speaker mute, monitor mode, OSD menu, and power button <i>Side:</i> Volume up and down buttons														
Disk	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm														
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable														
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar														
Media reader	<i>Some:</i> 11-in-1 Single Slot SD media reader														
Chipset	Intel Q77 Express Chipset														
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)														
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
ExpressCard	None														
mSATA	One mSATA slot														
PCIe Mini Card	One PCI Express® Mini Card slot														
PCIe WLAN	None														
Bluetooth	None														
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®														
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified											Security			
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)											<ul style="list-style-type: none"> ● Security chip (see information on left) ● Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) ● Power-on password ● Hard disk password ● Boot sequence control ● Boot without keyboard and mouse ● USB port disablement ● Chassis intrusion switch on selected model(s) 			
Security chip	Trusted Platform Module (TPM 1.2-compliant)											EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge TUV Green Mark ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant			
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo logo														
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo														
Power supply	150 watts, autosensing, 85% PSU														
Machine	<i>Model(s) with 20" Non multi-touch, Frame stand:</i> <ul style="list-style-type: none"> ● Business black color ● 19.8" W X 3.6" D X 16.1" H, ● 503mm W X 92.5mm D X 408mm H (including stand) ● 18.5 lb (8.4 kg) in maximum configuration ● Toolless back cover, stand removal ● Toolless disk, optical drive, memory removal ● Support VESA mount (100mm) 														
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available														
												Supports ThinkVantage Technologies			

See footnotes for important warranty information
WE models announced June 5, 2012

©Lenovo
(G-MTRL1-4) February 2013

ThinkCentre M92z (3296) - 20" (Win 8)

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ⁹	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/Mouse	Intel vPro	Global	Preload	Ann date (mm/dd/yy)
3296-H4G	i3-3220	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	Media	None	S P	Switch	Monitor	USB	None	None	Win8 Pro64	10/23/12

●3-year limited warranty

Positioning	<i>Premium All-In-One PC for the enterprise</i>											Preloaded operating system²⁰			
Processor	Intel® Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller											Windows® 8 Pro 64-bit			
Implementation	Processor in LGA1155 socket											Preloaded applications (only some listed)			
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)											<ul style="list-style-type: none"> ● ThinkVantage® System Update ● ThinkVantage Automatic Lock Utility ● View Management Utility ● Lenovo® Support ● Lenovo Settings ● Lenovo Companion ● Lenovo Cloud Storage ● Lenovo QuickLaunch ● Lenovo Solution Center ● Microsoft® Office preloaded; purchase a product key to activate ● Norton™ Internet Security (30 days of virus definitions) ● Norton Studio ● Intel AppUp® ● AccuWeather ● PC Device Stage ● Evernote® ● Skype™ ● Cyberlink Power2Go (DVD±RW) ● Cyberlink PowerProducer (DVD±RW) 			
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>														
DP dongle	None														
Display	20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, work as standalone monitor via DisplayPort-in connector														
Light sensor	None														
Multi-touch	None														
Camera	<i>Some:</i> Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off														
Controls	<i>Front:</i> Microphone mute, speaker mute, monitor mode, OSD menu, and power button <i>Side:</i> Volume up and down buttons														
Disk	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm														
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable														
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar														
Media reader	11-in-1 Single Slot SD media reader														
Chipset	Intel Q77 Express Chipset														
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)														
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
ExpressCard	None														
mSATA	One mSATA slot														
PCIe Mini Card	One PCI Express® Mini Card slot														
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2														
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter														
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®														
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified														
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)														
Security chip	Trusted Platform Module (TPM 1.2-compliant)											Security			
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo logo											<ul style="list-style-type: none"> ● Security chip (see information on left) ● Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) ● Power-on password ● Hard disk password ● Boot sequence control ● Boot without keyboard and mouse ● USB port disablement ● <i>Chassis intrusion switch on selected model(s)</i> 			
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo														
Power supply	150 watts, autosensing, 85% PSU														
Machine	<i>Model(s) with 20" Non multi-touch, Monitor stand:</i> <ul style="list-style-type: none"> ● Business black color ● 19.8" W X 5.6" D X 17.6" H ● 503mm W X 143mm D X 448mm H (including stand) ● 23.0 lb (10.5 kg) in maximum configuration ● Tilt: 45° back, -5° forward; Lift: 110mm; Swivel: +/-45° ● Toolless back cover, stand removal ● Toolless disk, optical drive, memory removal ● Support VESA mount (100mm) 											EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge TUV Green Mark ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant			
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											Supports ThinkVantage Technologies			

See footnotes for important warranty information
WE model announced October 23, 2012

©Lenovo
(G-MTRL1-14) February 2013

ThinkCentre M92z (3298) - 20" (GMP)

Product Specifications Reference (PSREF)

Type-model	Processor	Memory	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/ Mouse	Intel Global (G) vPro GMP (P)	Win7 preload (mm/dd/yy)	Ann date
3298-A2G	i7-3770S	4GBx1	2.0M	500G 7200	HD 4000	11b/g/n	Media	Sensor	None	Switch	Frame	USB	vPro G P	Pro 64	06/05/12

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning	<i>Premium All-In-One PC for the enterprise</i>											Preloaded operating system²⁰		
Processor	Intel® Core™ i7-3770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Genuine Windows® 7 Professional 64		
Implementation	Processor in LGA1155 socket											Ready to install applications (only some listed)		
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)											<ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager • Business-in-a-Box 		
Graphics	Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>											Preloaded applications (only some listed)		
DP dongle	None											<ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Automatic Lock Utility • ThinkVantage Power Manager • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • RapidBoot HDD Accelerator • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 		
Display	20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, work as standalone monitor via DisplayPort-in connector													
Light sensor	Ambient Light Sensor													
Multi-touch	None													
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off													
Controls	<i>Front:</i> Microphone mute, speaker mute, monitor mode, OSD menu, and power button <i>Side:</i> Volume up and down buttons													
Disk	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm													
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable													
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar													
Media reader	11-in-1 Single Slot SD media reader													
Chipset	Intel Q77 Express Chipset													
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)													
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
ExpressCard	None													
mSATA	One mSATA slot													
PCIe Mini Card	One PCI Express® Mini Card slot													
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2													
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter													
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®													
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified													
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)													
Security chip	Trusted Platform Module (TPM 1.2-compliant)											Security		
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo logo											<ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • Chassis intrusion switch on selected model(s) 		
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Power supply	150 watts, autosensing, 85% PSU													
Machine	<i>Model(s) with 20" Non multi-touch, Frame stand:</i> <ul style="list-style-type: none"> • Business black color • 19.8" W X 3.6" D X 16.1" H, • 503mm W X 92.5mm D X 408mm H (including stand) • 18.5 lb (8.4 kg) in maximum configuration • Toolless back cover, stand removal • Toolless disk, optical drive, memory removal • Support VESA mount (100mm) 											EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge TUV Green Mark ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant		
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											Supports ThinkVantage Technologies		

See footnotes for important warranty information
WE model announced June 5, 2012

©Lenovo
(G-MTRL1-1) February 2013

ThinkCentre M92z (3298) - 20" (GMP) - Win 8

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ⁸	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/ Mouse	Intel Global (G) vPro GMP (P)	Preload	Ann date (mm/dd/yy)	
3298-A4G	i5-3470S	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	Media	Sensor	None	Switch	Frame	USB	vPro	G P	Win8 Pro64	10/23/12
3298-A6G	i5-3470S	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	Media	Sensor	None	None	Frame	USB	vPro	G P	Win7 Pro64	10/23/12

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning	<i>Premium All-In-One PC for the enterprise</i>											Preloaded operating system²⁰			
Processor	Intel® Core™ i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology											Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit			
Implementation	Processor in LGA1155 socket											Some: Windows 8 Pro 64-bit			
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)											Preloaded applications (only some listed)			
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>											- Windows 7 models			
DP dongle	None											<ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage Communication Utility • ThinkVantage Power Manager • RapidBoot HDD Accelerator • Lenovo® SimpleTap • Adobe® Reader® • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 			
Display	20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, work as standalone monitor via DisplayPort-in connector											- Windows 8 models			
Light sensor	Ambient Light Sensor											<ul style="list-style-type: none"> • Lenovo Support • Lenovo Settings • Lenovo Companion • Lenovo Cloud Storage • Lenovo QuickLaunch • Norton™ Studio • AccuWeather • Evernote® • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) 			
Multi-touch	None											- All models			
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off											<ul style="list-style-type: none"> • ThinkVantage System Update • ThinkVantage Automatic Lock Utility • Lenovo Solution Center • View Management Utility • Norton Internet Security (30 days of virus definitions) • Microsoft® Office preloaded; purchase a product key to activate • Skype™ 			
Controls	<i>Front:</i> Microphone mute, speaker mute, monitor mode, OSD menu, and power button <i>Side:</i> Volume up and down buttons														
Disk	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm														
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable														
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar														
Media reader	11-in-1 Single Slot SD media reader														
Chipset	Intel Q77 Express Chipset														
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)														
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
ExpressCard	None														
mSATA	One mSATA slot														
PCIe Mini Card	One PCI Express® Mini Card slot														
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2														
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter														
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®														
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified														
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)														
Security chip	Trusted Platform Module (TPM 1.2-compliant)														
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo logo														
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo														
Power supply	150 watts, autosensing, 85% PSU														
Machine	<i>Model(s) with 20" Non multi-touch, Frame stand:</i> <ul style="list-style-type: none"> • Business black color • 19.8" W X 3.6" D X 16.1" H, • 503mm W X 92.5mm D X 408mm H (including stand) • 18.5 lb (8.4 kg) in maximum configuration • Toolless back cover, stand removal • Toolless disk, optical drive, memory removal • Support VESA mount (100mm) 														
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											Security <ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • Chassis intrusion switch on selected model(s) 			
												EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge TUV Green Mark ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant			
												Supports ThinkVantage Technologies			

See footnotes for important warranty information
WE models announced October 23, 2012

©Lenovo
(G-MTRL1-15) February 2013

ThinkCentre M92z (3318) - 23" (TopSeller)

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ⁸	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/Mouse	Intel vPro	Global	Win7 preload	Ann date (mm/dd/yy)
3318-C7G	i3-2120	4GBx1	2.0M	500G 7200	HD 2000	11b/g/n	Media	None	None	Switch	Monitor	USB	None	None	Pro 64	07/10/12

- Small and medium business (SMB) model(s), part of the Western Europe TopSeller™ Program
- 3-year limited warranty

Positioning	<i>Premium All-In-One PC for the enterprise</i>											Preloaded operating system²⁰				
Processor	Intel® Core™ i3-2120 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Genuine Windows® 7 Professional 64				
Implementation	Processor in LGA1155 socket											Ready to install applications (only some listed)				
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)											<ul style="list-style-type: none"> ● Rescue and Recovery™ ● Password Manager ● Business-in-a-Box 				
Graphics	Intel HD Graphics 2000 in processor, uses main memory, HDCP, DirectX® 10.1, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>											Preloaded applications (only some listed)				
DP dongle	None											<ul style="list-style-type: none"> ● ThinkVantage® Product Recovery ● ThinkVantage System Update ● ThinkVantage Communication Utility ● ThinkVantage Automatic Lock Utility ● ThinkVantage Power Manager ● View Management Utility ● Lenovo Solution Center ● Lenovo Message Center Plus ● RapidBoot HDD Accelerator ● Lenovo SimpleTap ● Norton™ Internet Security (30 days of virus definitions) ● Adobe® Reader® ● Skype™ for Windows ● Windows Live™ Essentials ● Microsoft® Office preloaded; purchase a product key to activate ● Corel® Burn.Now™ (DVD±RW) ● Corel DVD MovieFactory® (DVD±RW) 				
Display	23.0" (580.4mm) Full HD 1080p (1920x1080) TFT color , IPS wide viewing angle, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, work as standalone monitor via DisplayPort-in connector															
Light sensor	None															
Multi-touch	None															
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off															
Controls	<i>Front:</i> Microphone mute, speaker mute, monitor mode, OSD menu, and power button <i>Side:</i> Volume up and down buttons															
Disk	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm															
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable															
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar															
Media reader	11-in-1 Single Slot SD media reader															
Chipset	Intel Q77 Express Chipset															
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)															
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)															
ExpressCard	None															
mSATA	One mSATA slot															
PCIe Mini Card	One PCI Express® Mini Card slot															
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2															
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter															
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®															
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified											Security				
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)											<ul style="list-style-type: none"> ● Security chip (see information on left) ● Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) ● Power-on password ● Hard disk password ● Boot sequence control ● Boot without keyboard and mouse ● USB port disablement ● Chassis intrusion switch on selected model(s) 				
Security chip	Trusted Platform Module (TPM 1.2-compliant)											EPEAT™ Gold rating				
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo											ENERGY STAR® 5.2-compliant				
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo											TCO Certified Edge				
Power supply	150 watts, autosensing, 85% PSU											TUV Green Mark				
Machine	<i>Model(s) with 23" Non multi-touch, Monitor stand:</i> <ul style="list-style-type: none"> ● Business black color ● 22.4" W X 9.7" D X 17.8" H ● 568mm W X 247mm D X 452mm H (including stand) ● 25.7 lb (11.7 kg) in maximum configuration ● Tilt: 45° back, -5° forward; Lift: 110mm; Swivel: +/-45° ● Toolless back cover, stand removal ● Toolless disk, optical drive, memory removal ● Support VESA mount (100mm) 											ULE Gold				
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											EuP 2013				
												Cisco EnergyWise compatible				
												GREENGUARD® certified				
												RoHS-compliant				
												Supports ThinkVantage Technologies				

See footnotes for important warranty information
WE model announced July 10, 2012

©Lenovo
(G-MTRL1-8) February 2013

ThinkCentre M92z (3318) - 23" (TopSeller) - Win 8

Product Specifications Reference (PSREF)

Type-model	Processor	Memory	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/Mouse	Intel vPro Global	Preload	Ann date (mm/dd/yy)
3318-D3G	i3-3220	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	Media	None	None	Switch	Monitor	USB	None	None	Win8 Pro64 10/23/12
3318-F8G	i3-3220	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	Media	None	None	Switch	Monitor	USB	None	None	Win7 Pro64 10/23/12
3318-J2G	i5-3330S	4GBx1	2.0M	1TB 7200	HD 2500	11b/g/n	Media	None	S P	Switch	Monitor	USB	None	None	Win8 Pro64 12/04/12
3318-K2G	i5-3330S	4GBx1	2.0M	1TB 7200	HD 2500	11b/g/n	Media	None	S P	Switch	Monitor	USB	None	None	Win7 Pro64 03/26/13
3318-K8G	i3-3240	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	Media	None	None	Switch	Monitor	USB	None	None	Win7 Pro64 05/28/13

- Small and medium business (SMB) model(s), part of the Western Europe TopSeller™ Program
- 3-year limited warranty

Positioning	<i>Premium All-In-One PC for the enterprise</i>											Preloaded operating system²⁰			
Processor	Intel® Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i3-3240 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i5-3330S Processor (4 cores / 4 threads, 2.7GHz, 6MB cache), Turbo Boost 2.0 (3.2GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit			
Implementation												Preloaded applications (only some listed) - Windows 7 models			
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)											<ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage Communication Utility • ThinkVantage Power Manager • Lenovo® SimpleTap • Adobe® Reader® • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 			
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>											- Windows 8 models			
DP dongle	None											<ul style="list-style-type: none"> • Lenovo Support • Lenovo Settings • Lenovo Companion • Lenovo Cloud Storage • Norton™ Studio • AccuWeather • Evernote® • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) 			
Display	23.0" (580.4mm) Full HD 1080p (1920x1080) TFT color , IPS wide viewing angle, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, work as standalone monitor via DisplayPort-in connector														
Light sensor	None														
Multi-touch	None														
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off														
Controls	<i>Front:</i> Microphone mute, speaker mute, monitor mode, OSD menu, and power button <i>Side:</i> Volume up and down buttons											- All models			
Disk	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm											<ul style="list-style-type: none"> • ThinkVantage System Update • ThinkVantage Automatic Lock Utility • Lenovo Solution Center • View Management Utility • Norton Internet Security (30 days of virus definitions) • Microsoft® Office preloaded; purchase a product key to activate • Skype™ 			
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable														
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar														
Media reader	11-in-1 Single Slot SD media reader														
Chipset	Intel Q77 Express Chipset														
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)														
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
ExpressCard	None														
mSATA	One mSATA slot														
PCIe Mini Card	One PCI Express® Mini Card slot														
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2											Security			
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter											<ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • Chassis intrusion switch on selected model(s) 			
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®														
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified														
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)														
Security chip	Trusted Platform Module (TPM 1.2-compliant)														
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo														
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo														
Power supply	150 watts, autosensing, 85% PSU														
Machine	<i>Model(s) with 23" Non multi-touch, Monitor stand:</i> <ul style="list-style-type: none"> • Business black color • 22.4" W X 9.7" D X 17.8" H • 568mm W X 247mm D X 452mm H (including stand) • 25.7 lb (11.7 kg) in maximum configuration • Tilt: 45° back, -5° forward; Lift: 110mm; Swivel: +/-45° • Toolless back cover, stand removal • Toolless disk, optical drive, memory removal • Support VESA mount (100mm) 											EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge TUV Green Mark ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant			
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											Supports ThinkVantage Technologies			

See footnotes for important warranty information
 WE models announced October 23, 2012, December 4, 2012, March 26, 2013, May, 28, 2013

©Lenovo
 (G-MTRL1-10) June 2013

ThinkCentre M92z (3322) - 23"

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ⁸	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/ Mouse	Intel vPro	Global	Win7 preload	Ann date (mm/dd/yy)
3322-A1G	G630	2GBx1	None	500G 7200	Intel HD	None	None	None	None	Switch	Frame	USB	None	None	Pro 64	06/05/12

- 1-year limited warranty

Positioning	<i>Premium All-In-One PC for the enterprise</i>											Preloaded operating system²⁰			
Processor	Intel [®] Pentium [®] G630 Processor (2 cores / 2 threads, 2.7GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Genuine Windows [®] 7 Professional 64			
Implementation	Processor in LGA1155 socket											Ready to install applications (only some listed)			
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)											<ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager • Business-in-a-Box 			
Graphics	Intel HD Graphics in processor, uses main memory, HDCP, DirectX [®] 10.1, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>											Preloaded applications (only some listed)			
DP dongle	None											<ul style="list-style-type: none"> • ThinkVantage[®] Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Automatic Lock Utility • ThinkVantage Power Manager • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • RapidBoot HDD Accelerator • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe[®] Reader[®] • Skype™ for Windows • Windows Live™ Essentials • Microsoft[®] Office preloaded; purchase a product key to activate 			
Display	23.0" (580.4mm) Full HD 1080p (1920x1080) TFT color , IPS wide viewing angle, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, work as standalone monitor via DisplayPort-in connector														
Light sensor	None														
Multi-touch	None														
Camera	None														
Controls	<i>Front:</i> Microphone mute, speaker mute, monitor mode, OSD menu, and power button <i>Side:</i> Volume up and down buttons														
Disk	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm														
Optical	DVD-ROM DL SATA 1.5Gb/s 16-48X Max Drive, 12.7mm high, fixed, not removable														
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar														
Media reader	None														
Chipset	Intel Q77 Express Chipset														
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)														
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
ExpressCard	None														
mSATA	One mSATA slot														
PCIe Mini Card	One PCI Express [®] Mini Card slot														
PCIe WLAN	None														
Bluetooth	None														
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN [®]														
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby [®] Advanced Audio™ v2 certified, Microsoft Lync™ certified														
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)														
Security chip	Trusted Platform Module (TPM 1.2-compliant)											Security			
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo [®] logo											<ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington[®] MicroSaver[®] cable; Kensington lock also locks chassis) • Power-on password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • Chassis intrusion switch on selected model(s) 			
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo														
Power supply	150 watts, autosensing, 85% PSU														
Machine	<i>Model(s) with 23" Non multi-touch, Frame stand:</i> <ul style="list-style-type: none"> • Business black color • 22.4" W X 3.7" D X 17.6" H, • 568mm W X 93mm D X 447mm H (including stand) • 21.5 lb (9.8 kg) in maximum configuration • Toolless back cover, stand removal • Toolless disk, optical drive, memory removal • Support VESA mount (100mm) 											EPEAT™ Gold rating ENERGY STAR [®] 5.2-compliant TCO Certified Edge TUV Green Mark ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD [®] certified RoHS-compliant			
Limited Warranty	1-year, customer carry-in service / service upgrades available											Supports ThinkVantage Technologies			

ThinkCentre M92z (3325) - 23"

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ⁸	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/ Intel Mouse vPro	Win7 Global preload	Ann date (mm/dd/yy)
3325-A9G	i7-3770S	4GBx1	2.0M	1TB 7200	HD 4000	11b/g/n	Media	None	S P	Switch	Monitor	2.4G vPro	None	Pro 64 06/05/12

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- 3-year limited warranty

Positioning Processor	<i>Premium All-In-One PC for the enterprise</i>											Preloaded operating system²⁰
Implementation	Intel® Core™ i7-3770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD 4000 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Genuine Windows® 7 Professional 64
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)											Ready to install applications (only some listed)
Graphics	Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>											<ul style="list-style-type: none"> ● Rescue and Recovery™ ● Password Manager ● Business-in-a-Box
DP dongle Display	None											Preloaded applications (only some listed)
Light sensor	None											<ul style="list-style-type: none"> ● ThinkVantage® Product Recovery ● ThinkVantage System Update ● ThinkVantage Communication Utility ● ThinkVantage Automatic Lock Utility ● ThinkVantage Power Manager ● View Management Utility ● Lenovo Solution Center ● Lenovo Message Center Plus ● RapidBoot HDD Accelerator ● Lenovo SimpleTap ● Norton™ Internet Security (30 days of virus definitions) ● Adobe® Reader® ● Skype™ for Windows ● Windows Live™ Essentials ● Microsoft® Office preloaded; purchase a product key to activate ● Corel® Burn.Now™ (DVD±RW) ● Corel DVD MovieFactory® (DVD±RW)
Multi-touch Camera	None											
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off											
Controls	<i>Front:</i> Microphone mute, speaker mute, monitor mode, OSD menu, and power button <i>Side:</i> Volume up and down buttons											
Disk	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm											
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable											
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar											
Media reader	11-in-1 Single Slot SD media reader											
Chipset	Intel Q77 Express Chipset											
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)											
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)											
ExpressCard	None											
mSATA	One mSATA slot											
PCIe Mini Card	One PCI Express® Mini Card slot											
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2											
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter											
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®											
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified											
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)											
Security chip	Trusted Platform Module (TPM 1.2-compliant)											
Keyboard	Ultraslim Plus Wireless Keyboard (2.4GHz via USB receiver), black											Security
Mouse	Ultraslim Plus Wireless Mouse (2.4GHz via USB receiver), black											<ul style="list-style-type: none"> ● Security chip (see information on left) ● Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) ● Power-on password ● Hard disk password ● Boot sequence control ● Boot without keyboard and mouse ● USB port disablement ● Chassis intrusion switch on selected model(s)
Power supply	150 watts, autosensing, 85% PSU											
Machine	<i>Model(s) with 23" Non multi-touch, Monitor stand:</i> <ul style="list-style-type: none"> ● Business black color ● 22.4" W X 9.7" D X 17.8" H ● 568mm W X 247mm D X 452mm H (including stand) ● 25.7 lb (11.7 kg) in maximum configuration ● Tilt: 45° back, -5° forward; Lift: 110mm; Swivel: +/-45° ● Toolless back cover, stand removal ● Toolless disk, optical drive, memory removal ● Support VESA mount (100mm) 											EPEAT™ Gold rating ENERGY STAR® 6.0-compliant TCO Certified Edge TUV Green Mark ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											

See footnotes for important warranty information
 WE model announced June 5, 2012

©Lenovo
 (G-MTRL1-6) February 2013

ThinkCentre M92z (3325) - 23" (Win 8)

Product Specifications Reference (PSREF)

Type-model	Processor	Memory	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	Display-Port dongle	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intru switch	Stand type	Key-board/ Intel vPro	Win8 Global	Ann date (mm/dd/yy)
3325-H6G	i5-3470S	4GBx1	2.0M	500G 7200HD	2500 None	None	11b/g/n	Media	None	S P	Switch	Monitor	USB vPro	None	Win8 Pro64 10/23/12
3325-H9G	i3-3220	4GBx1	2.0M	1TB 7200	HD 2500	DP-to-DVI-D	11b/g/n	Media	None	S P	Switch	Monitor	2.4G	None	Win7 Pro64 10/23/12
3325-K5G	i5-3330S	4GBx1	2.0M	180G SSD	HD 2500	None	11b/g/n	Media	None	S P	Switch	Monitor	USB	None	Win7 Pro64 12/04/12

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- 3-year limited warranty

Positioning	<i>Premium All-In-One PC for the enterprise</i>											Preloaded operating system²⁰
Processor	Intel® Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i5-3330S Processor (4 cores / 4 threads, 2.7GHz, 6MB cache), Turbo Boost 2.0 (3.2GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit
Implementation												Preloaded applications (only some listed)
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)											- Windows 7 models
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i> Some: DisplayPort to Single-link DVI-D Cable											<ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage Communication Utility • ThinkVantage Power Manager • Lenovo® SimpleTap • Adobe® Reader® • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW)
DP dongle	Some: DisplayPort to Single-link DVI-D Cable											- Windows 8 models
Display	23.0" (580.4mm) Full HD 1080p (1920x1080) TFT color , IPS wide viewing angle, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, work as standalone monitor via DisplayPort-in connector											<ul style="list-style-type: none"> • Lenovo Support • Lenovo Settings • Lenovo Companion • Lenovo Cloud Storage • Norton™ Studio • AccuWeather • Evernote® • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW)
Light sensor	None											- All models
Multi-touch	None											<ul style="list-style-type: none"> • ThinkVantage System Update • ThinkVantage Automatic Lock Utility • Lenovo Solution Center • View Management Utility • Norton Internet Security (30 days of virus definitions) • Microsoft® Office preloaded; purchase a product key to activate • Skype™
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off											
Controls	Front: Microphone mute, speaker mute, monitor mode, OSD menu, and power button Side: Volume up and down buttons											
Disk	Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide Some: Hard Disk Drive / SATA 6.0Gb/s, 3.5" Wide, 7200 rpm											
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable											
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar											
Media reader	11-in-1 Single Slot SD media reader											
Chipset	Intel Q77 Express Chipset											
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)											
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)											
ExpressCard	None											
mSATA	One mSATA slot											
PCIe Mini Card	One PCI Express® Mini Card slot											
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2											
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter											
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®											
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified Intel Active Management Technology 8.0 (Intel AMT 8.0)											Security
Intel AMT	Trusted Platform Module (TPM 1.2-compliant)											<ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • Chassis intrusion switch on selected model(s)
Keyboard	Some: Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo Some: Ultralim Plus Wireless Keyboard (2.4GHz via USB receiver), black											
Mouse	Some: Enhanced Optical USB Mouse, black, Lenovo logo Some: Ultralim Plus Wireless Mouse (2.4GHz via USB receiver), black											
Power supply	150 watts, autosensing, 85% PSU											
Machine	Model(s) with 23" Non multi-touch, Monitor stand: <ul style="list-style-type: none"> • Business black color • 22.4" W X 9.7" D X 17.8" H • 568mm W X 247mm D X 452mm H (including stand) • 25.7 lb (11.7 kg) in maximum configuration • Tilt: 45° back, -5° forward; Lift: 110mm; Swivel: +/-45° • Toolless back cover, stand removal • Toolless disk, optical drive, memory removal • Support VESA mount (100mm) 											EPEAT™ Gold rating ENERGY STAR® 6.0-compliant TCO Certified Edge TUV Green Mark ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											

See footnotes for important warranty information
 WE models announced October 23 or December 4, 2012

©Lenovo
 (G-MTRL1-11) February 2013

ThinkCentre M92z (3327) - 23" (GMP)

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ⁸	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/ Mouse vPro	Intel Global (G) GMP (P)	Win7 preload (mm/dd/yy)	Ann date (mm/dd/yy)
3327-A4G	i7-3770S	4GBx1	2.0M	500G 7200	HD 4000	11b/g/n	Media	Sensor	None	Switch	Frame	USB vPro	G P	Pro 64	06/05/12

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning	<i>Premium All-In-One PC for the enterprise</i>											Preloaded operating system²⁰		
Processor	Intel® Core™ i7-3770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD 4000 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Genuine Windows® 7 Professional 64		
Implementation	Integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Ready to install applications (only some listed)		
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)											<ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager • Business-in-a-Box 		
Graphics	Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>											Preloaded applications (only some listed)		
DP dongle	None											<ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Automatic Lock Utility • ThinkVantage Power Manager • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • RapidBoot HDD Accelerator • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 		
Display	23.0" (580.4mm) Full HD 1080p (1920x1080) TFT color , IPS wide viewing angle, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, work as standalone monitor via DisplayPort-in connector													
Light sensor	Ambient Light Sensor													
Multi-touch	None													
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off													
Controls	<i>Front:</i> Microphone mute, speaker mute, monitor mode, OSD menu, and power button <i>Side:</i> Volume up and down buttons													
Disk	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm													
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable													
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar													
Media reader	11-in-1 Single Slot SD media reader													
Chipset	Intel Q77 Express Chipset													
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)													
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
ExpressCard	None													
mSATA	One mSATA slot													
PCIe Mini Card	One PCI Express® Mini Card slot													
PCIe WLAN ⁴	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2													
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter													
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®													
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified													
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)											Security		
Security chip	Trusted Platform Module (TPM 1.2-compliant)											<ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • Chassis intrusion switch on selected model(s) 		
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo											EPEAT™ Gold rating		
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo											ENERGY STAR® 5.2-compliant		
Power supply	150 watts, autosensing, 85% PSU											TCO Certified Edge		
Machine	<i>Model(s) with 23" Non multi-touch, Frame stand:</i> <ul style="list-style-type: none"> • Business black color • 22.4" W X 3.7" D X 17.6" H, • 568mm W X 93mm D X 447mm H (including stand) • 21.5 lb (9.8 kg) in maximum configuration • Toolless back cover, stand removal • Toolless disk, optical drive, memory removal • Support VESA mount (100mm) 											TUV Green Mark		
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											ULE Gold		
												EuP 2013		
												Cisco EnergyWise compatible		
												GREENGUARD® certified		
												RoHS-compliant		
												Supports ThinkVantage Technologies		

See footnotes for important warranty information
WE model announced June 5, 2012

©Lenovo
(G-MTRL1-2) February 2013

ThinkCentre M92z (3327) - 23" (GMP) - Win 8

Product Specifications Reference (PSREF)

Type-model	Processor	Memory	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/ Mouse vPro	Intel Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)
3327-A8G	i5-3470S	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	Media	Sensor	None	Switch	Frame	USB vPro	G P	Win8 Pro64	10/23/12
3327-B2G	i5-3470S	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	Media	Sensor	None	None	Frame	USB vPro	G P	Win7 Pro64	10/23/12

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning	<i>Premium All-In-One PC for the enterprise</i>											Preloaded operating system²⁰			
Processor	Intel® Core™ i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit			
Implementation	Processor in LGA1155 socket											Preloaded applications (only some listed)			
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)											- Windows 7 models			
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort) @60Hz</i>											<ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage Communication Utility • ThinkVantage Power Manager • Lenovo® Message Center Plus • RapidBoot HDD Accelerator • Lenovo SimpleTap • Adobe® Reader® • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 			
DP dongle	None											- Windows 8 models			
Display	23.0" (580.4mm) Full HD 1080p (1920x1080) TFT color , IPS wide viewing angle, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, work as standalone monitor via DisplayPort-in connector											<ul style="list-style-type: none"> • Lenovo Support • Lenovo Settings • Lenovo Companion • Lenovo Cloud Storage • Norton™ Studio • AccuWeather • Evernote® • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) 			
Light sensor	Ambient Light Sensor											- All models			
Multi-touch	None											<ul style="list-style-type: none"> • ThinkVantage System Update • ThinkVantage Automatic Lock Utility • Lenovo Solution Center • View Management Utility • Norton Internet Security (30 days of virus definitions) • Microsoft® Office preloaded; purchase a product key to activate • Skype™ 			
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off														
Controls	<i>Front:</i> Microphone mute, speaker mute, monitor mode, OSD menu, and power button <i>Side:</i> Volume up and down buttons														
Disk	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm														
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable														
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar														
Media reader	11-in-1 Single Slot SD media reader														
Chipset	Intel Q77 Express Chipset														
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)														
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
ExpressCard	None														
mSATA	One mSATA slot														
PCIe Mini Card	One PCI Express® Mini Card slot														
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2														
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter														
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®														
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified														
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)														
Security chip	Trusted Platform Module (TPM 1.2-compliant)														
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo														
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo														
Power supply	150 watts, autosensing, 85% PSU														
Machine	<i>Model(s) with 23" Non multi-touch, Frame stand:</i> <ul style="list-style-type: none"> • Business black color • 22.4" W X 3.7" D X 17.6" H, • 568mm W X 93mm D X 447mm H (including stand) • 21.5 lb (9.8 kg) in maximum configuration • Toolless back cover, stand removal • Toolless disk, optical drive, memory removal • Support VESA mount (100mm) 											Security <ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • Chassis intrusion switch on selected model(s) 			
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge TUV Green Mark ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant			
												Supports ThinkVantage Technologies			

See footnotes for important warranty information
WE models announced October 23, 2012

©Lenovo
(G-MTRL1-12) February 2013

ThinkCentre M92z (3311) - 23" (Multi-touch) - TopSeller

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ^a	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/Mouse	Intel vPro Global	Win7 preload	Ann date (mm/dd/yy)	
3311-B8G	i5-3470S	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	Media	None	None	Switch	Frame	USB	vPro	None	Pro 64	07/10/12

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- Small and medium business (SMB) model(s), part of the Western Europe TopSeller™ Program
- 3-year limited warranty

Positioning	<i>Premium All-In-One PC for the enterprise</i>											Preloaded operating system²⁰			
Processor	Intel® Core™ i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Genuine Windows® 7 Professional 64			
Implementation	Processor in LGA1155 socket											Ready to install applications (only some listed)			
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)											<ul style="list-style-type: none"> ● Rescue and Recovery™ ● Password Manager ● Business-in-a-Box 			
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>											Preloaded applications (only some listed)			
DP dongle	None											<ul style="list-style-type: none"> ● ThinkVantage® Product Recovery ● ThinkVantage System Update ● ThinkVantage Communication Utility ● ThinkVantage Automatic Lock Utility ● ThinkVantage Power Manager ● View Management Utility ● Microsoft Touch Pack ● Lenovo Solution Center ● Lenovo Message Center Plus ● RapidBoot HDD Accelerator ● Lenovo SimpleTap ● Norton™ Internet Security (30 days of virus definitions) ● Adobe® Reader® ● Skype™ for Windows ● Windows Live™ Essentials ● Microsoft® Office preloaded; purchase a product key to activate ● Corel® Burn.Now™ (DVD±RW) ● Corel DVD MovieFactory® (DVD±RW) 			
Display	23.0" (580.4mm) Full HD 1080p (1920x1080) TFT color , IPS wide viewing angle, anti-glare, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, work as standalone monitor via DisplayPort-in connector														
Light sensor	None														
Multi-touch	Multi-touch, 2-point support														
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off														
Controls	<i>Front:</i> Microphone mute, speaker mute, monitor mode, OSD menu, and power button <i>Side:</i> Volume up and down buttons														
Disk	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm														
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable														
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar														
Media reader	11-in-1 Single Slot SD media reader														
Chipset	Intel Q77 Express Chipset														
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)														
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
ExpressCard	None														
mSATA	One mSATA slot														
PCIe Mini Card	One PCI Express® Mini Card slot														
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2														
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter														
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®														
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified														
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)														
Security chip	Trusted Platform Module (TPM 1.2-compliant)														
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo											Security			
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo											<ul style="list-style-type: none"> ● Security chip (see information on left) ● Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) ● Power-on password ● Hard disk password ● Boot sequence control ● Boot without keyboard and mouse ● USB port disablement ● Chassis intrusion switch on selected model(s) 			
Power supply	150 watts, autosensing, 85% PSU														
Machine	<i>Model(s) with 23" multi-touch, Frame stand:</i> <ul style="list-style-type: none"> ● Business black color ● 22.4" W X 3.9" D X 17.6" H, ● 568mm W X 100mm D X 447mm H (including stand) ● 23.9 lb (10.9 kg) in maximum configuration ● Toolless back cover, stand removal ● Toolless disk, optical drive, memory removal ● Support VESA mount (100mm) 														
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge TUV Green Mark ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant			
												Supports ThinkVantage Technologies			

See footnotes for important warranty information
WE model announced July 10, 2012

©Lenovo
(G-MTRL1-9) February 2013

ThinkCentre M92z (3314) - 23" (Multi-touch)

Product Specifications Reference (PSREF)

Type-model	Processor	Memory	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	Display-Port dongle	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/ Intel vPro	Win7 Globalpreload(mm/dd/yy)	Ann date	
3314-B1G	i5-3550S	4GBx1	2.0M	500G 7200	HD 2500	DP-to-DVI-D	11b/g/n	Media	None	None	Switch	Frame	2.4G vPro	None	Pro 64	06/05/12
3314-B3G	i7-3770S	4GBx1	2.0M	1TB 7200	HD 4000	None	11b/g/n	Media	None	None	Switch	Frame	USB vPro	None	Pro 64	06/05/12
3314-E8G	i3-3220	4GBx1	2.0M	500G 7200	HD 2500	None	11b/g/n	Media	None	S P	Switch	Monitor	USB	None	Pro 64	09/04/12

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- 3-year limited warranty

Positioning Processor	<i>Premium All-In-One PC for the enterprise</i> Intel® Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i5-3550S Processor (4 cores / 4 threads, 3.0GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Preloaded operating system²⁰ Genuine Windows® 7 Professional 64 Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager • Business-in-a-Box Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Automatic Lock Utility • ThinkVantage Power Manager • View Management Utility • Microsoft Touch Pack • Lenovo Solution Center • Lenovo Message Center Plus • RapidBoot HDD Accelerator • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW)
Implementation												
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)											
Graphics	Intel HD Graphics 2500 / 4000 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i> <i>Some: DisplayPort to Single-link DVI-D Cable</i> 23.0" (580.4mm) Full HD 1080p (1920x1080) TFT color , IPS wide viewing angle, anti-glare, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, work as standalone monitor via DisplayPort-in connector											
DP dongle												
Display												
Light sensor	None											
Multi-touch	Multi-touch, 2-point support											
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off											
Controls	<i>Front:</i> Microphone mute, speaker mute, monitor mode, OSD menu, and power button <i>Side:</i> Volume up and down buttons											
Disk	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm											
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable											
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar											
Media reader	11-in-1 Single Slot SD media reader											
Chipset	Intel Q77 Express Chipset											
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)											
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)											
ExpressCard	None											
mSATA	One mSATA slot											
PCIe Mini Card	One PCI Express® Mini Card slot											
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2											
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter											
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®											
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified											
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)											
Security chip	Trusted Platform Module (TPM 1.2-compliant)											Security <ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • Chassis intrusion switch on selected model(s)
Keyboard	<i>Some:</i> Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo <i>Some:</i> Ultralim Plus Wireless Keyboard (2.4GHz via USB receiver), black											
Mouse	<i>Some:</i> Enhanced Optical USB Mouse, black, Lenovo logo <i>Some:</i> Ultralim Plus Wireless Mouse (2.4GHz via USB receiver), black											
Power supply	150 watts, autosensing, 85% PSU											
Machine	<i>All:</i> <ul style="list-style-type: none"> • Business black color • Toolless back cover, stand removal • Toolless disk, optical drive, memory removal • Support VESA mount (100mm) <i>Model(s) with 23" multi-touch, Frame stand:</i> <ul style="list-style-type: none"> • 22.4" W X 3.9" D X 17.6" H, • 568mm W X 100mm D X 447mm H (including stand) • 23.9 lb (10.9 kg) in maximum configuration <i>Model(s) with 23" multi-touch, Monitor stand:</i> <ul style="list-style-type: none"> • 22.4" W X 10.0" D X 17.8" H • 568mm W X 254mm D X 452mm H (including stand) • 28.2 lb (12.8 kg) in maximum configuration • Tilt: 45° back, -5° forward; Lift: 110mm; Swivel: +/-45° 											EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge TUV Green Mark ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											Supports ThinkVantage Technologies

ThinkCentre M92z (3329) - 23" Multi-touch (GMP)

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ⁸	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/ Intel vPro	Global (G) GMP (P)	Win7 preload (mm/dd/yy)	Ann date
3329-A4G	i7-3770S	4GBx1	2.0M	500G 7200	HD 4000	11b/g/n	Media	Sensor	None	Switch	Frame	USB vPro	G P	Pro 64	06/05/12

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning	<i>Premium All-In-One PC for the enterprise</i>											Preloaded operating system²⁰			
Processor	Intel® Core™ i7-3770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD 4000 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Genuine Windows® 7 Professional 64			
Implementation												Ready to install applications (only some listed)			
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)											<ul style="list-style-type: none"> ● Rescue and Recovery™ ● Password Manager ● Business-in-a-Box 			
Graphics	Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>											Preloaded applications (only some listed)			
DP dongle	None											<ul style="list-style-type: none"> ● ThinkVantage® Product Recovery ● ThinkVantage System Update ● ThinkVantage Communication Utility ● ThinkVantage Automatic Lock Utility ● ThinkVantage Power Manager ● View Management Utility ● Microsoft Touch Pack ● Lenovo Solution Center ● Lenovo Message Center Plus ● RapidBoot HDD Accelerator ● Lenovo SimpleTap ● Norton™ Internet Security (30 days of virus definitions) ● Adobe® Reader® ● Skype™ for Windows ● Windows Live™ Essentials ● Microsoft® Office preloaded; purchase a product key to activate ● Corel® Burn.Now™ (DVD±RW) ● Corel DVD MovieFactory® (DVD±RW) 			
Display	23.0" (580.4mm) Full HD 1080p (1920x1080) TFT color , IPS wide viewing angle, anti-glare, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, work as standalone monitor via DisplayPort-in connector														
Light sensor	Ambient Light Sensor														
Multi-touch	Multi-touch, 2-point support														
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off														
Controls	<i>Front:</i> Microphone mute, speaker mute, monitor mode, OSD menu, and power button <i>Side:</i> Volume up and down buttons														
Disk	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm														
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable														
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar														
Media reader	11-in-1 Single Slot SD media reader														
Chipset	Intel Q77 Express Chipset														
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)														
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
ExpressCard	None														
mSATA	One mSATA slot														
PCIe Mini Card	One PCI Express® Mini Card slot														
PCIe WLAN ⁴	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2														
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter														
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®														
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified														
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)														
Security chip	Trusted Platform Module (TPM 1.2-compliant)											Security			
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo											<ul style="list-style-type: none"> ● Security chip (see information on left) ● Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) ● Power-on password ● Hard disk password ● Boot sequence control ● Boot without keyboard and mouse ● USB port disablement ● Chassis intrusion switch on selected model(s) 			
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo														
Power supply	150 watts, autosensing, 85% PSU														
Machine	<i>Model(s) with 23" multi-touch, Frame stand:</i> <ul style="list-style-type: none"> ● Business black color ● 22.4" W X 3.9" D X 17.6" H, ● 568mm W X 100mm D X 447mm H (including stand) ● 23.9 lb (10.9 kg) in maximum configuration ● Toolless back cover, stand removal ● Toolless disk, optical drive, memory removal ● Support VESA mount (100mm) 											EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge TUV Green Mark ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant			
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											Supports ThinkVantage Technologies			

ThinkCentre M93z All-In-One



ThinkCentre M93z (Multi-touch) with Frame Stand and optional wireless keyboard and mouse



ThinkCentre M93z (Non-touch) with Monitor Stand and optional wireless keyboard and mouse



ThinkCentre M93z with Monitor Stand with optional PS/2 and Serial ports



ThinkCentre M93z with Frame Stand with optional PS/2 and Serial ports



Frame Stand
(Adjustable between 10° and 45°)



Monitor Stand
(Tilt: 45° back, -5° forward; Lift: 110mm; Swivel: +/-45°)

ThinkCentre M93z (10AF) - TopSeller

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ^a	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/ Mouse	Intel vPro	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)	
10AF0009++	i5-4570S	4GBx1	2.0M	500G Hybrid	HD 4600	N6235	Media	Sensor	None	Switch	Monitor	USB	vPro	None	Win7 Pro64 DG	07/09/13	
10AF000A++	i5-4430S	4GBx1	2.0M	500G Hybrid	HD 4600	N2230	Media	Sensor	None	Switch	Frame	USB	None	None	Win7 Pro64 DG	07/09/13	
10AF000M++	i3-4130	4GBx1	2.0M	500G 7200	HD 4400	N2230	Media	Sensor	None	Switch	Monitor	USB	None	None	Win7 Pro64 DG	09/10/13	
10AF0014++	i3-4150	4GBx1	None	500G 7200	HD 4400	7260 b/g/n	Media	Sensor	None	Switch	Monitor	USB	None	None	Win7 P64 DG Win8.1	07/08/14	
10AF0015++	i5-4460S	4GBx1	None	500G 7200	HD 4600	7260 b/g/n	Media	Sensor	None	Switch	Frame	USB	None	None	Win7 P64 DG Win8.1	07/08/14	
10AF0016++	i5-4590S	4GBx1	None	500G Hybrid	HD 4600	7260 ac	Media	Sensor	None	Switch	Monitor	USB	vPro	None	Win7 P64 DG Win8.1	07/08/14	
10AF0017++	i5-4460S	4GBx1	2.0M	500G 7200	HD 4600	7260 b/g/n	Media	Sensor	None	Switch	Frame	USB	None	None	Win7 P64 DG Win8.1	07/08/14	
10AF0018++	i3-4150	4GBx1	2.0M	500G 7200	HD 4400	7260 b/g/n	Media	Sensor	None	Switch	Monitor	USB	None	None	Win7 P64 DG Win8.1	07/08/14	
10AF0019++	i5-4590S	4GBx1	2.0M	500G Hybrid	HD 4600	7260 ac	Media	Sensor	None	Switch	Monitor	USB	vPro	None	Win7 P64 DG Win8.1	07/08/14	
Positioning Processor	<p><i>Premium All-In-One PC for the enterprise</i></p> <p>Intel® Core™ i3-4130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller</p> <p>Intel Core i3-4150 Processor (2 cores / 4 threads, 3.5GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller</p> <p>Intel Core i5-4430S Processor (4 cores / 4 threads, 2.7GHz, 6MB cache), Turbo Boost 2.0 (3.2GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller</p> <p>Intel Core i5-4460S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.4GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller</p> <p>Intel Core i5-4570S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller</p> <p>Intel Core i5-4590S Processor (4 cores / 4 threads, 3.0GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller</p> <p>Processor in LGA1150 socket</p>											<p>Preloaded operating system</p> <p><i>Some:</i> Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit</p> <p><i>Some:</i> Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit</p> <p>Ready to install applications (only some listed)</p> <ul style="list-style-type: none"> ● Rescue and Recovery™ ● Password Manager <p>Preloaded applications (only some listed)</p> <ul style="list-style-type: none"> ● ThinkVantage® Product Recovery ● ThinkVantage System Update ● ThinkVantage Communication Utility ● ThinkVantage Device Experience ● ThinkVantage AutoLock ● Desktop Power Manager ● View Management Utility ● Lenovo Cloud Storage by SugarSync ● Lenovo Solution Center ● Lenovo Message Center Plus ● Norton™ Internet Security (30 days of virus definitions) ● Adobe® Reader® ● Skype™ ● Microsoft Office preloaded; purchase a product key to activate ● Cyberlink PowerDVD (DVD±RW, DVD) ● Cyberlink Power2Go (DVD±RW) ● Cyberlink PowerProducer (DVD±RW) ● Evernote ● Intel AppUp ● Lenovo Solutions for Small Business ● Nitro Pro 					
Implementation	Processor in LGA1150 socket																
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)																
Graphics	Intel HD Graphics 4400/4600 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 3840x2160 (DisplayPort)@60Hz</i>																
Display	23.0" (584.2mm) Full HD 1080p (1920x1080) TFT color , IPS panel, wide viewing angle (+/- 89°), LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, anti-glare, work as standalone monitor via VGA-in connector																
Light sensor	Optional ambient light sensor																
Multi-touch	None																
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, supports 1080p, with dual array digital microphone, LED indicator, physical switch on/off																
Controls	Microphone mute (OSD exit), monitor mode switch (OSD enter), volume up/down buttons (OSD left/right buttons), and power button																
Disk	<i>Some:</i> SATA 6.0Gb/s, 3.5" Wide, 7200 rpm <i>Some:</i> 500GB (5400 rpm) hybrid hard disk / with 8GB flash, SATA 6.0Gb/s, 2.5" wide DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable																
Optical	Two SATA cables (each 1-drop to device), two SATA 6.0Gb/s connectors on planar																
Onboard SATA	Optional 11-in-1 media card reader																
Media reader																	
Chipset	Intel Q87 Express Chipset																
Rear ports	Four USB 3.0, ethernet (RJ-45), DisplayPort-out, VGA-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)																
Side ports	Two USB 3.0 (one Always On / Powered), one mic, one headphone / mic combo jack																
mSATA	One mSATA slot																
PCIe Mini Card	One PCI Express® Mini Card slot																
PCIe WLAN	<i>Some:</i> 11b/g/n wireless, Intel Centrino® Wireless-N 2230, Wi-Fi + BT4.0 combo, 2x2 <i>Some:</i> 11a/b/g/n wireless, Intel Centrino Advanced-N 6235, Wi-Fi + BT4.0 combo, 2x2 <i>Some:</i> 11b/g/n wireless, Intel Wireless-N 7260, Wi-Fi + BT4.0 combo, 2x2 <i>Some:</i> 11ac/a/b/g/n wireless, Intel Dual Band Wireless-AC 7260, Wi-Fi + BT4.0, 2x2																
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel Wi-Fi + Bluetooth combo adapter																
Ethernet	One gigabit ethernet port, Intel I217-LM (Clarkville), Wake on LAN®																
Audio support	High Definition (HD) Audio, Realtek ALC283 / two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified																
Intel AMT	Intel Active Management Technology 9.0 (Intel AMT 9.0)																
Security chip	Trusted Platform Module (TPM 1.2-compliant)																
Keyboard	Preferred Pro USB Keyboard (USB connector), Lenovo® logo																
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo																
Power supply	150 watts, autosensing, 85% PSU																
Machine	<ul style="list-style-type: none"> ● Business black color ● Toolless back cover, stand, disk, optical drive, memory removal ● Support VESA mount (100mm) <p><i>Non-touch model(s) with frame stand:</i></p> <ul style="list-style-type: none"> ● (WxDxH) 22.4" X 3.6" X 17.6"; 568mm X 92.5mm X 447.3 mm ● 21.3 lb (9.68 kg) in maximum configuration ● Adjustable stand (between 10° and 45°) <p><i>Non-touch model(s) with monitor stand:</i></p> <ul style="list-style-type: none"> ● (WxDxH) 22.4" X 9.7" X 17.4" to 21.7"; 568mm X 247mm X 441.2mm to 551.2mm ● 25.5 lb (11.58 kg) in maximum configuration ● Tilt: 45° back, -5° forward; Lift: 110mm; Swivel: +/-45° 																
Limited Warranty	<p>3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available</p>											<p>Security</p> <ul style="list-style-type: none"> ● Security chip (see information on left) ● Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) ● Power-on password ● Administrator password ● Hard disk password ● Boot sequence control ● Boot without keyboard and mouse ● USB port disablement ● Chassis intrusion switch on selected model(s) <p>EPEAT™ Gold rating ENERGY STAR® 6.0-compliant TCO Certified Edge TUV Green Mark ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies</p>					

See footnotes for important warranty information

ThinkCentre M93z (10AE) - GMP

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ⁸	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/Mouse	Intel vPro	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)
10AE001F++	i5-4570S	4GBx1	2.0M	500G 7200	HD 4600	N2230	Media	Sensor	None	Switch	Monitor	USB	vPro	G P	Win7 Pro64	07/09/13
10AE001D++	i5-4570S	4GBx1	2.0M	500G 7200	HD 4600	N6235	Media	Sensor	None	Switch	Monitor	USB	vPro	G P	Win7 P64 DG Win8	07/09/13
10AE001R++	i7-4770S	4GBx1	2.0M	500G Hybrid	HD 4600	N6235	Media	Sensor	S P	Switch	Monitor	USB	vPro	G P	Win7 P64 DG Win8	09/10/13
10AE0022++	i5-4570S	4GBx1	2.0M	500G 7200	HD 4600	7260 b/g/n	Media	Sensor	None	Switch	Monitor	USB	vPro	G P	Win7 P64 DG Win8.1	02/25/14
10AE002G++	i5-4590S	4GBx1	2.0M	500G 7200	HD 4600	N2230	Media	Sensor	None	Switch	Monitor	USB	vPro	G P	Win7 Pro64	06/10/14
10AE002L++	i5-4590S	4GBx1	2.0M	500G 7200	HD 4600	7260 ac	Media	Sensor	None	Switch	Monitor	USB	vPro	G P	Win7 P64 DG Win8.1	07/08/14
10AE002M++	i5-4590S	4GBx1	2.0M	500G 7200	HD 4600	7260 b/g/n	Media	Sensor	None	Switch	Monitor	USB	vPro	G P	Win7 Pro64	07/08/14
Positioning	<i>Premium All-In-One PC for the enterprise</i>											Preloaded operating system				
Processor	Intel® Core™ i5-4570S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i5-4590S Processor (4 cores / 4 threads, 3.0GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i7-4770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Processor in LGA1150 socket											Some: Windows® 7 Professional 64 Some: Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit				
Implementation	Processor in LGA1150 socket											Ready to install applications (only some listed)				
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)															
Graphics	Intel HD Graphics 4600 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 3840x2160 (DisplayPort)@60Hz</i>											Preloaded applications (only some listed) <ul style="list-style-type: none"> ● Rescue and Recovery™ ● Password Manager ● ThinkVantage® Product Recovery ● ThinkVantage System Update ● ThinkVantage Communication Utility ● ThinkVantage Device Experience ● ThinkVantage AutoLock ● Desktop Power Manager ● View Management Utility ● Lenovo Cloud Storage by SugarSync ● Lenovo Solution Center ● Lenovo Message Center Plus ● Norton™ Internet Security (30 days of virus definitions) ● Adobe® Reader® ● Skype™ ● Microsoft Office preloaded; purchase a product key to activate ● Cyberlink PowerDVD (DVD±RW, DVD) ● Cyberlink Power2Go (DVD±RW) ● Cyberlink PowerProducer (DVD±RW) ● Evernote ● Intel AppUp ● Lenovo Solutions for Small Business ● Nitro Pro 				
Display	23.0" (584.2mm) Full HD 1080p (1920x1080) TFT color , IPS panel, wide viewing angle (+/- 89°), LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, anti-glare, work as standalone monitor via VGA-in connector															
Light sensor	Optional ambient light sensor															
Multi-touch	None															
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, supports 1080p, with dual array digital microphone, LED indicator, physical switch on/off															
Controls	Microphone mute (OSD exit), monitor mode switch (OSD enter), volume up/down buttons (OSD left/right buttons), and power button															
Disk	Some: SATA 6.0Gb/s, 3.5" Wide, 7200 rpm Some: 500GB (5400 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 2.5" wide															
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable															
Onboard SATA	Two SATA cables (each 1-drop to device), two SATA 6.0Gb/s connectors on planar															
Media reader	Optional 11-in-1 media card reader															
Chipset	Intel Q87 Express Chipset															
Rear ports	Four USB 3.0, ethernet (RJ-45), DisplayPort-out, VGA-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)															
Side ports	Two USB 3.0 (one Always On / Powered), one microphone (stereo, 3.5mm), one headphone / microphone combo jack (stereo, 3.5mm)															
ExpressCard	None															
mSATA	One mSATA slot															
PCIe Mini Card	One PCI Express® Mini Card slot															
PCIe WLAN	Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2 Some: 11a/b/g/n wireless, PCIe Half Mini Card, Intel Centrino Advanced-N 6235, Wi-Fi + Bluetooth combo adapter, 2x2 Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Wireless-N 7260, Wi-Fi + Bluetooth combo adapter, 2x2 Some: 11ac/a/b/g/n wireless, PCIe Half Mini Card, Intel Dual Band Wireless-AC 7260, Wi-Fi + BT combo adapter, 2x2															
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel Wi-Fi + Bluetooth combo adapter															
Ethernet	One gigabit ethernet port, Intel I217-LM (Clarkville), Wake on LAN®															
Audio support	High Definition (HD) Audio, Realtek ALC283 / two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified															
Intel AMT	Intel Active Management Technology 9.0 (Intel AMT 9.0)															
Security chip	Trusted Platform Module (TPM 1.2-compliant)															
Keyboard	Preferred Pro USB Keyboard (USB connector), Lenovo® logo															
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo															
Power supply	150 watts, autosensing, 85% PSU															
Machine	<ul style="list-style-type: none"> ● Business black color ● Toolless back cover, stand removal ● Toolless disk, optical drive, memory removal ● Support VESA mount (100mm) Non-touch model(s) with frame stand: <ul style="list-style-type: none"> ● (WxDxH) 22.4" X 3.6" X 17.6"; 568mm X 92.5mm X 447.3 mm ● 21.3 lb (9.68 kg) in maximum configuration ● Adjustable stand (between 10° and 45°) Non-touch model(s) with monitor stand: <ul style="list-style-type: none"> ● (WxDxH) 22.4" X 9.7" X 17.4" to 21.7"; 568mm X 247mm X 441.2mm to 551.2mm ● 25.5 lb (11.58 kg) in maximum configuration ● Tilt: 45° back, -5° forward; Lift: 110mm; Swivel: +/-45° 											Security <ul style="list-style-type: none"> ● Security chip (see information on left) ● Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) ● Power-on password ● Administrator password ● Hard disk password ● Boot sequence control ● Boot without keyboard and mouse ● USB port disablement ● Chassis intrusion switch on selected model(s) 				
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											EPEAT™ Gold rating ENERGY STAR® 6.0-compliant TCO Certified Edge TUV Green Mark ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies				

See footnotes for important warranty information

©Lenovo
(G-MPHS1-10) June 2014

ThinkCentre M93z (10AE) - GMP (Windows 8/8.1)

Product Specifications Reference (PSREF)

Type-model	Pro-processor	Memory	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/ Mouse vPro	Intel Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)
10AE001E++	i5-4570S	4GBx1	2.0M	500G 7200	HD 4600	N2230	Media	Sensor	None	Switch	Monitor	USB vPro	G P	Win8 Pro64	07/09/13
10AE0023++	i5-4570S	4GBx1	2.0M	500G 7200	HD 4600	N7260	Media	Sensor	None	Switch	Monitor	USB vPro	G P	Win8.1 Pro64	02/25/14
10AE002K++	i5-4590S	4GBx1	2.0M	500G 7200	HD 4600	N7260	Media	Sensor	None	Switch	Monitor	USB vPro	G P	Win8.1 Pro64	06/10/14

Country Code⁺⁺: AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)

Note: models listed above might not be available in all WE countries

●Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning Processor	<p><i>Premium All-In-One PC for the enterprise</i></p> <p>Intel® Core™ i5-4570S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 4600, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Core i5-4590S Processor (4 cores / 4 threads, 3.0GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), integrated Intel HD Graphics 4600, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Processor in LGA1150 socket</p>											<p>Preloaded operating system</p> <p>Some: Windows® 8 Pro 64-bit</p> <p>Some: Windows 8.1 Pro 64-bit</p> <p>Web install applications (only some listed)</p> <ul style="list-style-type: none"> ● Password Manager
Implementation	Processor in LGA1150 socket											<p>Preloaded applications (only some listed)</p> <ul style="list-style-type: none"> ● ThinkVantage System Update ● ThinkVantage AutoLock ● Desktop Power Manager ● View Management Utility (for Windows 8 only) ● Lenovo Cloud Storage by SugarSync (for Windows 8 only) ● Lenovo Solution Center ● Lenovo Support ● Lenovo Companion ● Norton Internet Security (30 days of virus definitions) ● Skype™ ● Microsoft Office preloaded; purchase a product key to activate ● Cyberlink PowerDVD (DVD±RW, DVD) ● Cyberlink Power2Go (DVD±RW) ● Cyberlink PowerProducer (DVD±RW) ● Evernote® ● Intel AppUp ● Lenovo Solutions for Small Business ● Nitro Pro ● AccuWeather ● Norton™ Studio ● Pokki (for Windows 8.1 only) ● Hightail (for Windows 8.1 only)
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)											
Graphics	Intel HD Graphics 4600 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution</i> : 3840x2160 (DisplayPort)@60Hz											
Display	23.0" (584.2mm) Full HD 1080p (1920x1080) TFT color , IPS panel, wide viewing angle (+/- 89°), LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, anti-glare, work as standalone monitor via VGA-in connector											
Light sensor	Optional ambient light sensor											
Multi-touch	None											
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, supports 1080p, with dual array digital microphone, LED indicator, physical switch on/off											
Controls	Microphone mute (OSD exit), monitor mode switch (OSD enter), volume up/down buttons (OSD left/right buttons), and power button											
Disk	Some: SATA 6.0Gb/s, 3.5" Wide, 7200 rpm											
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable											
Onboard SATA	Two SATA cables (each 1-drop to device), two SATA 6.0Gb/s connectors on planar											
Media reader	Optional 11-in-1 media card reader											
Chipset	Intel Q87 Express Chipset											
Rear ports	Four USB 3.0, ethernet (RJ-45), DisplayPort-out, VGA-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)											
Side ports	Two USB 3.0 (one Always On / Powered), one microphone (stereo, 3.5mm), one headphone / microphone combo jack (stereo, 3.5mm)											
ExpressCard	None											
mSATA	One mSATA slot											
PCIe Mini Card	One PCI Express® Mini Card slot											
PCIe WLAN	Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2											
	Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Wireless-N 7260, Wi-Fi + Bluetooth combo adapter, 2x2											
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel Wi-Fi + Bluetooth combo adapter											
Ethernet	One gigabit ethernet port, Intel I217-LM (Clarkville), Wake on LAN®											
Audio support	High Definition (HD) Audio, Realtek ALC283 / two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified											
Intel AMT	Intel Active Management Technology 9.0 (Intel AMT 9.0)											
Security chip	Trusted Platform Module (TPM 1.2-compliant)											
Keyboard	Preferred Pro USB Keyboard (USB connector), Lenovo® logo											
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo											
Power supply	150 watts, autosensing, 85% PSU											
Machine	<ul style="list-style-type: none"> ● Business black color ● Toolless back cover, stand removal ● Toolless disk, optical drive, memory removal ● Support VESA mount (100mm) <p><i>Non-touch model(s) with frame stand:</i></p> <ul style="list-style-type: none"> ● (WxDxH) 22.4" X 3.6" X 17.6"; 568mm X 92.5mm X 447.3 mm ● 21.3 lb (9.68 kg) in maximum configuration ● Adjustable stand (between 10° and 45°) <p><i>Non-touch model(s) with monitor stand:</i></p> <ul style="list-style-type: none"> ● (WxDxH) 22.4" X 9.7" X 17.4" to 21.7"; 568mm X 247mm X 441.2mm to 551.2mm ● 25.5 lb (11.58 kg) in maximum configuration ● Tilt: 45° back, -5° forward; Lift: 110mm; Swivel: +/-45° 											
Limited Warranty	<p>3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available</p>											<p>Security</p> <ul style="list-style-type: none"> ● Security chip (see information on left) ● Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) ● Power-on password ● Administrator password ● Hard disk password ● Boot sequence control ● Boot without keyboard and mouse ● USB port disablement ● Chassis intrusion switch on selected model(s) <p>EPEAT™ Gold rating ENERGY STAR® 6.0-compliant TCO Certified Edge TUV Green Mark ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant</p>
	Supports ThinkVantage Technologies											

See footnotes for important warranty information

©Lenovo
(G-MPHS1-11) June 2014

ThinkCentre M93z (10AD) - Multi-touch (TopSeller)

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ^a	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial port	Chassis intrusion switch	Stand type	Key-board/ Intel Mouse	Global (G) vPro	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)	
10AD000A++	i5-4570S	4GBx1	2.0M	128G SSD	HD 4600	N6235	Media	Sensor	None	Switch	Monitor	USB	vPro	None	Win7 Pro64	DG	07/09/13
10AD000D++	i5-4570S	4GBx1	2.0M	500G Hybird	HD 4600	N6235	Media	Sensor	None	Switch	Frame	USB	vPro	None	Win7 Pro64	DG	07/09/13
10AD002B++	i5-4590S	4GBx1	2.0M	500G Hybird	HD 4600	7260 ac	Media	Sensor	None	Switch	Frame	USB	vPro	None	Win7 P64	DG	Win8.1 07/08/14

Country Code"+": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)

Note: models listed above might not be available in all WE countries

- Small and medium business (SMB) model(s), part of the Westen Europe TopSeller™ Program
- 3-year limited warranty

Positioning Processor	<i>Premium All-In-One PC for the enterprise</i> Intel® Core™ i5-4570S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 4600, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-4590S Processor (4 cores / 4 threads, 3.0GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), integrated Intel HD Graphics 4600, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1150 socket	Preloaded operating system Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Ready to install applications (only some listed) • Rescue and Recovery™ • Password Manager
Implementation		Preloaded applications (only some listed) • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Device Experience • ThinkVantage AutoLock • Desktop Power Manager • View Management Utility • Lenovo Cloud Storage by SugarSync • Lenovo Solution Center • Lenovo Message Center Plus • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ • Microsoft Office preloaded; purchase a product key to activate • Cyberlink PowerDVD (DVD±RW, DVD) • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) • Evernote • Intel AppUp • Lenovo Solutions for Small Business • Nitro Pro
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)	
Graphics	Intel HD Graphics 4600 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 3840x2160 (DisplayPort)@60Hz</i>	
Display	23.0" (584.2mm) Full HD 1080p (1920x1080) TFT color , IPS panel, wide viewing angle (+/- 89°), LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, anti-glare, work as standalone monitor via VGA-in connector	
Light sensor	Optional ambient light sensor	
Multi-touch	Projected Capacitive Touch (PCT) technology, supports 10-point multi-touch	
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, supports 1080p, with dual array digital microphone, LED indicator, physical switch on/off	
Controls	Microphone mute (OSD exit), monitor mode switch (OSD enter), volume up/down buttons (OSD left/right buttons), and power button	
Disk	<i>Some:</i> 500GB (5400 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 2.5" wide <i>Some:</i> Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide	
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable	
Onboard SATA	Two SATA cables (each 1-drop to device), two SATA 6.0Gb/s connectors on planar	
Media reader	Optional 11-in-1 media card reader	
Chipset	Intel Q87 Express Chipset	
Rear ports	Four USB 3.0, ethernet (RJ-45), DisplayPort-out, VGA-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)	
Side ports	Two USB 3.0 (one Always On / Powered), one microphone (stereo, 3.5mm), one headphone / microphone combo jack (stereo, 3.5mm)	
ExpressCard	None	
mSATA	One mSATA slot	
PCIe Mini Card	One PCI Express® Mini Card slot	
PCIe WLAN	<i>Some:</i> 11a/b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Advanced-N 6235, Wi-Fi + Bluetooth combo adapter, 2x2 <i>Some:</i> 11ac/a/b/g/n wireless, PCIe Half Mini Card, Intel Dual Band Wireless-AC 7260, Wi-Fi + BT combo adapter, 2x2	
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel Wi-Fi + Bluetooth combo adapter	
Ethernet	One gigabit ethernet port, Intel I217-LM (Clarkville), Wake on LAN®	
Audio support	High Definition (HD) Audio, Realtek ALC283 / two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified	
Intel AMT	Intel Active Management Technology 9.0 (Intel AMT 9.0)	
Security chip	Trusted Platform Module (TPM 1.2-compliant)	
Keyboard	Preferred Pro USB Keyboard (USB connector), Lenovo® logo	
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo	
Power supply	150 watts, autosensing, 85% PSU	
Machine	<ul style="list-style-type: none"> • Business black color • Toolless back cover, stand removal • Toolless disk, optical drive, memory removal • Support VESA mount (100mm) <i>Multi-touch model(s) with frame stand:</i> <ul style="list-style-type: none"> • (WxDxH) 22.4" X 3.7" X 17.6"; 568mm X 93.1mm X 447.3 mm • 24.7 lb (11.22 kg) in maximum configuration • Adjustable stand (between 10° and 45°) <i>Multi-touch model(s) with monitor stand:</i> <ul style="list-style-type: none"> • (WxDxH) 22.4" X 9.7" X 17.4" to 21.7"; 568mm X 247mm X 441.2mm to 551.2mm • 28.9 lb (13.12 kg) in maximum configuration • Tilt: 45° back, -5° forward; Lift: 110mm; Swivel: +/-45° 	
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available	Security • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • Chassis intrusion switch on selected model(s) EPEAT™ Gold rating ENERGY STAR® 6.0-compliant TCO Certified Edge TUV Green Mark ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies

See footnotes for important warranty information

ThinkCentre M93z (10AD) - Multi-touch (TopSeller) - Win 8/8.1

Product Specifications Reference (PSREF)

Type-model	Pro-processor	Memory	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/ Intel vPro	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)	
10AD000B++	i5-4570S	4GBx1	2.0M	128G SSD	HD 4600	N6235	Media	Sensor	None	Switch	Monitor	USB	vPro	None	Win8 Pro64	07/09/13
10AD000C++	i5-4570S	4GBx1	2.0M	500G Hybrid	HD 4600	N6235	Media	Sensor	None	Switch	Frame	USB	vPro	None	Win8 Pro64	07/09/13
10AD002C++	i5-4590S	4GBx1	2.0M	500G Hybrid	HD 4600	7260 ac	Media	Sensor	None	Switch	Frame	USB	vPro	None	Win8.1 Pro64	06/10/14
10AD002D++	i5-4590S	4GBx1	2.0M	128G SSD	HD 4600	7260 ac	Media	Sensor	None	Switch	Monitor	USB	vPro	None	Win8.1 Pro64	06/10/14

- Small and medium business (SMB) model(s), part of the Western Europe TopSeller™ Program
- 3-year limited warranty

Positioning Processor	<i>Premium All-In-One PC for the enterprise</i> Intel® Core™ i5-4570S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i5-4590S Processor (4 cores / 4 threads, 3.0GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller	Preloaded operating system <i>Some:</i> Windows® 8 Pro 64-bit <i>Some:</i> Windows 8.1 Pro 64-bit
Implementation	Processor in LGA1150 socket	Web install applications (only some listed)
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)	<ul style="list-style-type: none"> • Password Manager
Graphics	Intel HD Graphics 4600 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution:</i> 3840x2160 (DisplayPort)@60Hz	Preloaded applications (only some listed)
Display	23.0" (584.2mm) Full HD 1080p (1920x1080) TFT color , IPS panel, wide viewing angle (+/- 89°), LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, anti-glare, work as standalone monitor via VGA-in connector	<ul style="list-style-type: none"> • ThinkVantage System Update • ThinkVantage AutoLock • Desktop Power Manager • View Management Utility (for Windows 8 only) • Lenovo Cloud Storage by SugarSync (for Windows 8 only) • Lenovo Solution Center • Lenovo Support • Lenovo Companion • Norton Internet Security (30 days of virus definitions) • Skype™ • Microsoft Office preloaded; purchase a product key to activate • Cyberlink PowerDVD (DVD±RW, DVD) • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) • Evernote® • Intel AppUp • Lenovo Solutions for Small Business • Nitro Pro • AccuWeather • Norton™ Studio • Pokki (for Windows 8.1 only) • Hightail (for Windows 8.1 only)
Light sensor	Optional ambient light sensor	
Multi-touch	Projected Capacitive Touch (PCT) technology, supports 10-point multi-touch	
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, supports 1080p, with dual array digital microphone, LED indicator, physical switch on/off	
Controls	Microphone mute (OSD exit), monitor mode switch (OSD enter), volume up/down buttons (OSD left/right buttons), and power button	
Disk	<i>Some:</i> 500GB (5400 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 2.5" wide <i>Some:</i> Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide	
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable	
Onboard SATA	Two SATA cables (each 1-drop to device), two SATA 6.0Gb/s connectors on planar	
Media reader	Optional 11-in-1 media card reader	
Chipset	Intel Q87 Express Chipset	
Rear ports	Four USB 3.0, ethernet (RJ-45), DisplayPort-out, VGA-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)	
Side ports	Two USB 3.0 (one Always On / Powered), one microphone (stereo, 3.5mm), one headphone / microphone combo jack (stereo, 3.5mm)	
ExpressCard	None	
mSATA	One mSATA slot	
PCIe Mini Card	One PCI Express® Mini Card slot	
PCIe WLAN	<i>Some:</i> 11a/b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Advanced-N 6235, Wi-Fi + Bluetooth combo adapter, 2x2 <i>Some:</i> 11ac/a/b/g/n wireless, PCIe Half Mini Card, Intel Dual Band Wireless-AC 7260, Wi-Fi + BT combo adapter, 2x2	
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel Wi-Fi + Bluetooth combo adapter	
Ethernet	One gigabit ethernet port, Intel I217-LM (Clarkville), Wake on LAN®	
Audio support	High Definition (HD) Audio, Realtek ALC283 / two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified	
Intel AMT	Intel Active Management Technology 9.0 (Intel AMT 9.0)	
Security chip	Trusted Platform Module (TPM 1.2-compliant)	Security
Keyboard	Preferred Pro USB Keyboard (USB connector), Lenovo® logo	<ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • Chassis intrusion switch on selected model(s)
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo	
Power supply	150 watts, autosensing, 85% PSU	
Machine	<ul style="list-style-type: none"> • Business black color • Toolless back cover, stand removal • Toolless disk, optical drive, memory removal • Support VESA mount (100mm) <p><i>Multi-touch model(s) with frame stand:</i></p> <ul style="list-style-type: none"> • (WxDxH) 22.4" X 3.7" X 17.6"; 568mm X 93.1mm X 447.3 mm • 24.7 lb (11.22 kg) in maximum configuration • Adjustable stand (between 10° and 45°) <p><i>Multi-touch model(s) with monitor stand:</i></p> <ul style="list-style-type: none"> • (WxDxH) 22.4" X 9.7" X 17.4" to 21.7"; 568mm X 247mm X 441.2mm to 551.2mm • 28.9 lb (13.12 kg) in maximum configuration • Tilt: 45° back, -5° forward; Lift: 110mm; Swivel: +/-45° 	<ul style="list-style-type: none"> • EPEAT™ Gold rating • ENERGY STAR® 6.0-compliant • TCO Certified Edge • TUV Green Mark • ULE Gold • EuP 2013 • Cisco EnergyWise compatible • GREENGUARD® certified • RoHS-compliant
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available	Supports ThinkVantage Technologies

See footnotes for important warranty information

©Lenovo
(G-MPHS1-6) July 2014

ThinkCentre M93z (10AC) - Multi-touch (GMP)

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ⁸	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/ mouse	Intel vPro	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)
10AC001G++	i5-4570S	4GBx1	2.0M	500G 7200	HD 4600	N2230	Media	Sensor	None	Switch	Monitor	USB	vPro	G P	Win7 Pro64	07/09/13
10AC001E++	i5-4570S	4GBx1	2.0M	500G 7200	HD 4600	N6235	Media	Sensor	None	Switch	Monitor	USB	vPro	G P	Win7 P64 DG Win8	07/09/13
10AC001T++	i7-4770S	4GBx1	2.0M	500G Hybrid	HD 4600	N6235	Media	Sensor	S P	Switch	Frame	USB	vPro	G P	Win7 P64 DG Win8	09/10/13
10AC002C++	i5-4570S	4GBx1	2.0M	500G 7200	HD 4600	7260 b/g/n	Media	Sensor	None	Switch	Monitor	USB	vPro	G P	Win7 P64 DG Win8.1	02/25/14
10AC002Y++	i5-4590S	4GBx1	2.0M	500G 7200	HD 4600	N2230	Media	Sensor	None	Switch	Monitor	USB	vPro	G P	Win7 Pro64	06/10/14
10AC0031++	i5-4590S	4GBx1	2.0M	500G 7200	HD 4600	7260 ac	Media	Sensor	None	Switch	Monitor	USB	vPro	G P	Win7 P64 DG Win8.1	07/08/14
10AC0033++	i5-4590S	4GBx1	2.0M	500G 7200	HD 4600	7260 b/g/n	Media	Sensor	None	Switch	Monitor	USB	vPro	G P	Win7 Pro64	07/08/14
Positioning Processor	Premium All-In-One PC for the enterprise Intel® Core™ i5-4570S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i5-4590S Processor (4 cores / 4 threads, 3.0GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i7-4770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Processor in LGA1150 socket											Preloaded operating system Some: Windows® 7 Professional 64 Some: Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit				
Implementation	Processor in LGA1150 socket											Ready to install applications (only some listed) • Rescue and Recovery™ • Password Manager Preloaded applications (only some listed) • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Device Experience • ThinkVantage AutoLock • Desktop Power Manager • View Management Utility • Lenovo Cloud Storage by SugarSync • Lenovo Solution Center • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ • Microsoft Office preloaded; purchase a product key to activate • Cyberlink PowerDVD (DVD±RW, DVD) • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) • Evernote • Intel AppUp • Lenovo Solutions for Small Business • Nitro Pro				
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)															
Graphics	Intel HD Graphics 4600 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 3840x2160 (DisplayPort)@60Hz</i>											Preloaded applications (only some listed) • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Device Experience • ThinkVantage AutoLock • Desktop Power Manager • View Management Utility • Lenovo Cloud Storage by SugarSync • Lenovo Solution Center • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ • Microsoft Office preloaded; purchase a product key to activate • Cyberlink PowerDVD (DVD±RW, DVD) • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) • Evernote • Intel AppUp • Lenovo Solutions for Small Business • Nitro Pro				
Display	23.0" (584.2mm) Full HD 1080p (1920x1080) TFT color , IPS panel, wide viewing angle (+/- 89°), LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, anti-glare, work as standalone monitor via VGA-in connector															
Light sensor	Optional ambient light sensor											Security • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • Chassis intrusion switch on selected model(s)				
Multi-touch Camera	Projected Capacitive Touch (PCT) technology, supports 10-point multi-touch Camera on top of screen, 2.0-megapixel, fixed focus, supports 1080p, with dual array digital microphone, LED indicator, physical switch on/off															
Controls	Microphone mute (OSD exit), monitor mode switch (OSD enter), volume up/down buttons (OSD left/right buttons), and power button											• Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • Chassis intrusion switch on selected model(s)				
Disk	Some: SATA 6.0Gb/s, 3.5" Wide, 7200 rpm Some: 500GB (5400 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 2.5" wide															
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable											• Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • Chassis intrusion switch on selected model(s)				
Onboard SATA Media reader	Two SATA cables (each 1-drop to device), two SATA 6.0Gb/s connectors on planar Optional 11-in-1 media card reader															
Chipset	Intel Q87 Express Chipset											• Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • Chassis intrusion switch on selected model(s)				
Rear ports	Four USB 3.0, ethernet (RJ-45), DisplayPort-out, VGA-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)															
Side ports	Two USB 3.0 (one Always On / Powered), one microphone (stereo, 3.5mm), one headphone / microphone combo jack (stereo, 3.5mm)											• Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • Chassis intrusion switch on selected model(s)				
ExpressCard mSATA	None															
PCIe Mini Card	One mSATA slot											• Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • Chassis intrusion switch on selected model(s)				
PCIe WLAN	One PCI Express® Mini Card slot Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2 Some: 11a/b/g/n wireless, PCIe Half Mini Card, Intel Centrino Advanced-N 6235, Wi-Fi + Bluetooth combo adapter, 2x2 Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Wireless-N 7260, Wi-Fi + Bluetooth combo adapter, 2x2 Some: 11ac/a/b/g/n wireless, PCIe Half Mini Card, Intel Dual Band Wireless-AC 7260, Wi-Fi + BT combo adapter, 2x2															
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel Wi-Fi + Bluetooth combo adapter											• Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • Chassis intrusion switch on selected model(s)				
Ethernet	One gigabit ethernet port, Intel I217-LM (Clarkville), Wake on LAN®															
Audio support	High Definition (HD) Audio, Realtek ALC283 / two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified Intel Active Management Technology 9.0 (Intel AMT 9.0)											• Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • Chassis intrusion switch on selected model(s)				
Intel AMT Security chip	Trusted Platform Module (TPM 1.2-compliant)															
Keyboard	Preferred Pro USB Keyboard (USB connector), Lenovo® logo											• Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • Chassis intrusion switch on selected model(s)				
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo															
Power supply	150 watts, autosensing, 85% PSU											• Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • Chassis intrusion switch on selected model(s)				
Machine	• Business black color • Toolless back cover, stand removal • Toolless disk, optical drive, memory removal • Support VESA mount (100mm) Multi-touch model(s) with frame stand: • (WxDxH) 22.4" X 3.7" X 17.6"; 568mm X 93.1mm X 447.3 mm • 24.7 lb (11.22 kg) in maximum configuration • Adjustable stand (between 10° and 45°) Multi-touch model(s) with monitor stand: • (WxDxH) 22.4" X 9.7" X 17.4" to 21.7"; 568mm X 247mm X 441.2mm to 551.2mm • 28.9 lb (13.12 kg) in maximum configuration • Tilt: 45° back, -5° forward; Lift: 110mm; Swivel: +/-45°															
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											EPEAT™ Gold rating ENERGY STAR® 6.0-compliant TCO Certified Edge TUV Green Mark ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies				

See footnotes for important warranty information

ThinkCentre M93z (10AC) - Multi-touch (GMP) - Win 8/8.1

Product Specifications Reference (PSREF)

Type-model	Pro-processor	Memory	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/ Mouse	Intel vPro	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)
10AC001F++	i5-4570S	4GBx1	2.0M	500G 7200	HD 4600	N2230	Media	Sensor	None	Switch	Monitor	USB	vPro	G P	Win8 Pro64	07/09/13
10AC002D++	i5-4570S	4GBx1	2.0M	500G 7200	HD 4600	N7260	Media	Sensor	None	Switch	Monitor	USB	vPro	G P	Win8.1 Pro64	02/25/14
10AC0032++	i5-4590S	4GBx1	2.0M	500G 7200	HD 4600	N7260	Media	Sensor	None	Switch	Monitor	USB	vPro	G P	Win8.1 Pro64	06/10/14

Country Code"++": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)

Note: models listed above might not be available in all WE countries

●Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning Processor	<i>Premium All-In-One PC for the enterprise</i> Intel® Core™ i5-4570S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i5-4590S Processor (4 cores / 4 threads, 3.0GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller											Preloaded operating system Some: Windows® 8 Pro 64-bit Some: Windows 8.1 Pro 64-bit				
Implementation	Processor in LGA1150 socket											Web install applications (only some listed)				
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)											● Password Manager				
Graphics	Intel HD Graphics 4600 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 3840x2160 (DisplayPort)@60Hz</i>											Preloaded applications (only some listed)				
Display	23.0" (584.2mm) Full HD 1080p (1920x1080) TFT color , IPS panel, wide viewing angle (+/- 89°), LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, anti-glare, work as standalone monitor via VGA-in connector											● ThinkVantage System Update ● ThinkVantage AutoLock ● Desktop Power Manager ● View Management Utility (for Windows 8 only) ● Lenovo Cloud Storage by SugarSync (for Windows 8 only) ● Lenovo Solution Center ● Lenovo Support ● Lenovo Companion ● Norton Internet Security (30 days of virus definitions) ● Skype™				
Light sensor	Optional ambient light sensor											● Microsoft Office preloaded; purchase a product key to activate				
Multi-touch	Projected Capacitive Touch (PCT) technology, supports 10-point multi-touch											● Cyberlink PowerDVD (DVD±RW, DVD) ● Cyberlink Power2Go (DVD±RW) ● Cyberlink PowerProducer (DVD±RW)				
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, supports 1080p, with dual array digital microphone, LED indicator, physical switch on/off											● Evernote® ● Intel AppUp ● Lenovo Solutions for Small Business ● Nitro Pro ● AccuWeather ● Norton™ Studio ● Pokki (for Windows 8.1 only) ● Hightail (for Windows 8.1 only)				
Controls	Microphone mute (OSD exit), monitor mode switch (OSD enter), volume up/down buttons (OSD left/right buttons), and power button															
Disk	Some: SATA 6.0Gb/s, 3.5" Wide, 7200 rpm															
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable															
Onboard SATA	Two SATA cables (each 1-drop to device), two SATA 6.0Gb/s connectors on planar															
Media reader	Optional 11-in-1 media card reader															
Chipset	Intel Q87 Express Chipset															
Rear ports	Four USB 3.0, ethernet (RJ-45), DisplayPort-out, VGA-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)															
Side ports	Two USB 3.0 (one Always On / Powered), one microphone (stereo, 3.5mm), one headphone / microphone combo jack (stereo, 3.5mm)															
ExpressCard	None															
mSATA	One mSATA slot															
PCIe Mini Card	One PCI Express® Mini Card slot															
PCIe WLAN	Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2 Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Wireless-N 7260, Wi-Fi + Bluetooth combo adapter, 2x2															
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel Wi-Fi + Bluetooth combo adapter															
Ethernet	One gigabit ethernet port, Intel I217-LM (Clarkville), Wake on LAN®															
Audio support	High Definition (HD) Audio, Realtek ALC283 / two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified											Security ● Security chip (see information on left) ● Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) ● Power-on password ● Administrator password ● Hard disk password ● Boot sequence control ● Boot without keyboard and mouse ● USB port disablement ● Chassis intrusion switch on selected model(s)				
Intel AMT	Intel Active Management Technology 9.0 (Intel AMT 9.0)											EPEAT™ Gold rating				
Security chip	Trusted Platform Module (TPM 1.2-compliant)											ENERGY STAR® 6.2-compliant				
Keyboard	Preferred Pro USB Keyboard (USB connector), Lenovo® logo											TCO Certified Edge				
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo											TUV Green Mark				
Power supply	150 watts, autosensing, 85% PSU											ULE Gold				
Machine	<ul style="list-style-type: none"> ● Business black color ● Toolless back cover, stand removal ● Toolless disk, optical drive, memory removal ● Support VESA mount (100mm) Multi-touch model(s) with frame stand: <ul style="list-style-type: none"> ● (WxDxH) 22.4" X 3.7" X 17.6"; 568mm X 93.1mm X 447.3 mm ● 24.7 lb (11.22 kg) in maximum configuration ● Adjustable stand (between 10° and 45°) Multi-touch model(s) with monitor stand: <ul style="list-style-type: none"> ● (WxDxH) 22.4" X 9.7" X 17.4" to 21.7"; 568mm X 247mm X 441.2mm to 551.2mm ● 28.9 lb (13.12 kg) in maximum configuration ● Tilt: 45° back, -5° forward; Lift: 110mm; Swivel: +/-45° 											EuP 2013				
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant				
												Supports ThinkVantage Technologies				

See footnotes for important warranty information

©Lenovo
(G-MPHS1-4) June 2014

ThinkCentre Edge 62z



Lenovo ThinkCentre Edge 62z with Frame Stand



Lenovo ThinkCentre Edge 62z with Frame Stand



Lenovo ThinkCentre Edge 62z with Frame Stand



Handle



Lenovo ThinkCentre Edge 62z with Frame Stand



Lenovo ThinkCentre Edge 62z with Frame Stand

ThinkCentre Edge 62z (2117) - TopSeller

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ⁸	Camera	Disk SATA GB rpm	SATA optical	Graphics	PCIe Mini Card WLAN	Stand type	Global	Preload	Ann date (mm/dd/yy)
2117-GDG	G2030	4GBx1 1600MHz	None	500G 7200	DVD±RW	Intel HD	Intel 105	Frame	None	Win7 Pro64	12/24/13
2117-GEG	G2030	4GBx1 1600MHz	None	500G 7200	DVD±RW	Intel HD	Intel 105	Frame	None	Win7 Pro64 (DG)	12/24/13
2117-GFG	i3-3240	4GBx1 1600MHz	720p	500G 7200	DVD±RW	HD 2500	Intel 105	Frame	None	Win7 Pro64	12/24/13
2117-GGG	i3-3240	4GBx1 1600MHz	720p	500G 7200	DVD±RW	HD 2500	Intel 105	Frame	None	Win7 Pro64 (DG)	12/24/13

- Small and medium business (SMB) model(s), part of the Western Europe TopSeller™ Program
- 1-year limited warranty

Positioning	<i>Essential All-In-One PC for small/medium businesses</i>						Preloaded operating system²⁰					
Processor	Intel® Pentium® G2030 Processor (2 cores / 2 threads, 3.0GHz, 3MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core™ i3-3240 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller						Some: Windows® 7 Professional 64 Some: Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit					
Implementation	Processor in LGA1155 socket						Ready to install applications (only some listed)					
Memory	8GB max, PC3-12800 1600MHz DDR3 , one 204-pin SODIMM sockets (notebook) <i>System automatically clocks down for processors with 1333MHz DDR3 memory controller</i>						<ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager • Lenovo® Message Center Plus 					
Graphics Display	Intel HD Graphics or Intel HD Graphics 2500 in processor, uses system memory 18.5" (470mm) HD (1366x768) TFT color , CCFL backlight, 200 nits, 16:9 aspect ratio, 600:1 dynamic contrast ratio						Preloaded applications (only some listed)					
Multi-touch	None						<ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Automatic Lock Utility • ThinkVantage Power Manager • View Management Utility • Lenovo Solution Center • RapidBoot HDD Accelerator • Lenovo SimpleTap • Lenovo Cloud Storage by SugarSync • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Evernote® • Symantec™ VIP • Intel AppUp® • Nitro PDF Pro • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 					
Camera	Some: HD720p Camera on top of screen, 1.0-megapixel, fixed focus											
Controls	Front facing button for power on/off, side buttons for brightness up and brightness down											
Disk	Hard Disk Drive / SATA 3.0Gb/s, 2.5" Wide											
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable											
Media reader	None											
Chipset	Intel H61 Express Chipset											
Rear ports	Four USB 2.0, ethernet (RJ-45), serial (9-pin)											
Side ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)											
PCIe Mini Card	One PCI Express® Mini Card slot											
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® wireless-N 105, 1x1											
Bluetooth	None											
Ethernet	One gigabit ethernet port, Realtek® RTL8111E-VC											
Audio	High Definition (HD) Audio, Realtek ALC269Q											
Speaker	Two internal stereo speakers (2watt x 2)											
Intel AMT	None											
Security chip	None											
Keyboard	Lenovo® Slim New F5 USB Keyboard (USB connector), black											
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo											
Power supply	120 watts, autosensing, 87% PSU											
Machine	<i>Model(s) with Frame stand:</i> <ul style="list-style-type: none"> • Business black color • 18.5" W X 2.3" D X 14.5" H • 469.7mm W X 59.5mm D X 368.4mm H (including stand) • 11 lb (5 kg) in maximum configuration • Tilt: 10°-20° back; no lift; no swivel; adjustable stand • Supports VESA mount (100mm) 											
Limited Warranty	1-year, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available						Security <ul style="list-style-type: none"> • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement ENERGY STAR® 5.2-compliant EuP 2013 RoHS-compliant Supports ThinkVantage Technologies					

See footnotes for important warranty information
 WE models announced December 24, 2013

©Lenovo
 (G-TAYN1-1) January 2014



ThinkCentre E73 SFF and Tower



ThinkCentre E73 Tower with Dual Lenovo ThinkVision Monitors



ThinkCentre E73 SFF



ThinkCentre E73 SFF



ThinkCentre E73 Tower



ThinkCentre E73 SFF with HDD and optional SSD

ThinkCentre E73 SFF (10AU) - TopSeller

Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory ^a	SATA disk GB rpm	SATA optical	PCIe WLAN	Media reader	Graphics	Parallel port	Serial port	Floor stand	Keyboard / mouse	Global	Preload	Ann date (mm/dd/yy)
10AU003B++	3x4	i7-4770S	4GBx1	1TB 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	None	USB(slim)	None	Win7 Pro64 (DG)	10/22/13
10AU003C++	3x4	i5-4430S	4+2GB	128G SSD	DVD±RW	None	Media	HD 4600	Parallel	Serial	None	USB(slim)	None	Win7 Pro64 (DG)	10/22/13
10AU003D++	3x4	i5-4430S	4GBx1	500G 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	None	USB(slim)	None	Win7 Pro64 (DG)	10/22/13
10AU003E++	3x4	i3-4130	4GBx1	500G 7200	DVD±RW	None	Media	HD 4400	Parallel	Serial	None	USB	None	Win7 Pro64 (DG)	10/22/13
10AU003F++	3x4	i3-4130	4GBx1	500G 7200	DVD±RW	None	Media	HD 4400	Parallel	Serial	None	USB(slim)	None	Win7 Pro64 (DG)	10/22/13
10AU003G++	3x4	G3420	4GBx1	500G 7200	DVD±RW	None	Media	Intel HD	Parallel	Serial	None	USB(slim)	None	Win7 Pro64 (DG)	10/22/13
10AU003H++	3x4	G3220	4GBx1	500G 7200	DVD±RW	None	Media	Intel HD	Parallel	Serial	None	USB	None	Win7 Pro64 (DG)	10/22/13
10AU003J++	3x4	G3220	4GBx1	500G 7200	DVD±RW	None	Media	Intel HD	Parallel	Serial	None	USB(slim)	None	Win7 Pro64 (DG)	10/22/13

Country Code^{a++}: AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)

Note: models listed above might not be available in all WE countries

Positioning	Stylish design, reliability, and productivity for small/medium businesses											Preloaded operating system		
Processor	Intel® Pentium® G3220 Processor (2 cores / 2 threads, 3.0GHz, 3MB cache), Intel HD Graphics, 1333MHz DDR3 memory controller Intel Pentium G3420 Processor (2 cores / 2 threads, 3.2GHz, 3MB cache), Intel HD Graphics, 1600MHz DDR3 memory controller Intel Core™ i3-4130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller Intel Core i5-4430S Processor (4 cores / 4 threads, 2.7GHz, 6MB cache), Turbo Boost 2.0 (3.2GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i7-4770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Processor in LGA1150 socket											Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Power Manager • ThinkVantage Device Experience • View Management Utility • Lenovo Cloud Storage by SugarSync • Lenovo Solution Center • Lenovo Message Center Plus • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ • Evernote® • Microsoft® Office preloaded; purchase a product key to activate • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) • Nitro Pro 		
Implementation	Processor in LGA1150 socket													
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3* , two 240-pin DIMM sockets *System automatically clocks down for processors with 1333MHz memory controller													
Graphics	Intel HD Graphics or Intel HD Graphics 4400/4600 in processor, uses main memory, one VGA, one DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking)</i>													
DP dongle	None													
Disk	Some: SATA 6.0Gb/s, 3.5" Wide, 7200 rpm Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide													
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive													
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset													
Onboard SATA	SATA cables match SATA devices (each 1-drop to device), one SATA 3.0Gb/s connector (for optical) and two SATA 6.0Gb/s connectors (for HDD/SSD) on planar													
eSATA port	None													
Media reader	Optional 9-in-1 media reader, internal USB 2.0													
Chipset	Intel H81 Express Chipset													
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
Rear ports	Two USB 3.0, two USB 2.0, optional serial (9-pin)*, optional parallel (25-pin)*, ethernet (RJ-45), VGA DB-15, DisplayPort * Please see the detailed configuration on top													
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)													
PCIe WLAN	None													
Bluetooth	None													
Audio	High Definition (HD) Audio, Realtek® ALC662 codec													
Speaker	Internal speaker for business audio													
IEEE 1394	None													
Ethernet	Gigabit ethernet port, Realtek RTL8111GN, Wake on LAN													
Manageability	None													
Modem	None													
Security chip	None													
Keyboard	Some: Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo Some: Lenovo® Slim USB Keyboard (USB connector), black, Lenovo logo													
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Floor Stand	Optional system floor stand for vertical orientation													
Power supply	180 watts, universal, autosensing													
Machine	<ul style="list-style-type: none"> • Glossy black bezel; metal case • 13.2" W X 15.0" D X 3.98" H • 336mm W X 382mm D X 101mm H • 13.2 lb (6.0 kg) in maximum configuration • Highlighted optical drive button for easy access 													
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 2.5", N/A, no access, opt 2nd SSD* Bay 4: 1.5", .35" high, access, optnl reader* *bay only available on models with SSD/reader installed													
Slot	Slot 1: Low Profile, PCI Express® 3.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, PCIe 2.0 x1													
Limited Warranty ¹	1-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											Security <ul style="list-style-type: none"> • One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement 		
												GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies		

See footnotes for important warranty information
WE model(s) announced October 22, 2013

©Lenovo
(G-TLS1S-1) October 2013


ThinkCentre E73 SFF (10AU) - TopSeller - II

Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory ^a	SATA disk GB rpm	SATA optical	PCIe WLAN	Media reader	Graphics	Parallel port	Serial port	Floor stand	Keyboard / mouse	Global	Preload	Ann date (mm/dd/yy)
10AU003K++	3x4	i3-4130	4GBx1	500G 7200 DVD±RW	None	Media	HD 4400	Parallel	Serial	None	USB(slim)	None	Win8 64	10/22/13	
10AU003L++	3x4	G3220	4GBx1	500G 7200 DVD±RW	None	Media	Intel HD	Parallel	Serial	None	USB(slim)	None	Win8 64	10/22/13	

Country Code^a++: AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)
 Note: models listed above might not be available in all WE countries

- Small and medium business (SMB) model(s), part of the Westen Europe TopSeller™ Program
- 1-year limited warranty

Positioning	<i>Stylish design, reliability, and productivity for small/medium businesses</i>											Preloaded operating system	
Processor	Intel® Pentium® G3220 Processor (2 cores / 2 threads, 3.0GHz, 3MB cache), Intel HD Graphics, 1333MHz DDR3 memory controller Intel Core™ i3-4130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller											Windows® 8 64-bit	
Implementation	Processor in LGA1150 socket											Ready to install applications (only some listed)	
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3* , two 240-pin DIMM sockets *System automatically clocks down for processors with 1333MHz memory controller											<ul style="list-style-type: none"> • Password Manager 	
Graphics	Intel HD Graphics or Intel HD Graphics 4400/4600 in processor, uses main memory, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking)											Preloaded applications (only some listed)	
DP dongle	None											<ul style="list-style-type: none"> • ThinkVantage® System Update • View Management Utility • Lenovo® Support • Lenovo Companion • Lenovo Cloud Storage by SugarSync • Lenovo Solution Center • Desktop Power Manager • PC Device Stage • Microsoft® Office preloaded; purchase a product key to activate • Norton™ Internet Security (30 days of virus definitions) • Evernote® • Skype™ • Cyberlink PowerDVD (DVD±RW, DVD) • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) • Nitro Pro • AccuWeather • Norton Studio • Intel AppUp® 	
Disk	Some: SATA 6.0Gb/s, 3.5" Wide, 7200 rpm												
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive												
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset												
Onboard SATA	SATA cables match SATA devices (each 1-drop to device), one SATA 3.0Gb/s connector (for optical) and two SATA 6.0Gb/s connectors (for HDD/SSD) on planar												
eSATA port	None												
Media reader	Optional 9-in-1 media reader, internal USB 2.0												
Chipset	Intel H81 Express Chipset												
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)												
Rear ports	Two USB 3.0, two USB 2.0, optional serial (9-pin)*, optional parallel (25-pin)*, ethernet (RJ-45), VGA DB-15, DisplayPort * Please see the detailed configuration on top												
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)												
PCIe WLAN	None												
Bluetooth	None												
Audio	High Definition (HD) Audio, Realtek® ALC662 codec												
Speaker	Internal speaker for business audio												
IEEE 1394	None												
Ethernet	Gigabit ethernet port, Realtek RTL8111GN, Wake on LAN												
Manageability	None												
Modem	None												
Security chip	None												
Keyboard	Lenovo® Slim USB Keyboard (USB connector), black, Lenovo logo												
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo												
Floor Stand	Optional system floor stand for vertical orientation												
Power supply	180 watts, universal, autosensing												
Machine	<ul style="list-style-type: none"> • Glossy black bezel; metal case • 13.2" W X 15.0" D X 3.98" H • 336mm W X 382mm D X 101mm H • 13.2 lb (6.0 kg) in maximum configuration • Highlighted optical drive button for easy access 											Security	
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 2.5", N/A, no access, opt 2nd SSD* Bay 4: 1.5", .35" high, access, optnl reader* *bay only available on models with SSD/reader installed											<ul style="list-style-type: none"> • One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement 	
Slot	Slot 1: Low Profile, PCI Express® 3.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, PCIe 2.0 x1												
Limited Warranty ¹	1-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											GREENGUARD® certified RoHS-compliant	
												Supports ThinkVantage Technologies	

See footnotes for important warranty information
 WE model(s) announced October 22, 2013

©Lenovo
 (G-TLS1S-2) October 2013

ThinkCentre E73 SFF (10AU) - TopSeller - III


Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory ^a	SATA disk GB rpm	SATA optical	PCIe WLAN	Media reader	Graphics	Serial / Parallel port	Floor stand	Keyboard / mouse	Global	Preload	Ann date (mm/dd/yy)
10AU0075++	3x4	i5-4440S	8GBx1	1TB 7200	DVD±RW	None	Media	HD 4600	S P	None	USB(slim)	None	Win7 P64 DG Win8.1	12/24/13
10AU008L++	3x4	i7-4770S	8GBx1	1TB 7200	DVD±RW	None	Media	HD 4600	S P	None	USB(slim)	None	Win7 P64 DG Win8.1	03/18/14

Country Code"+": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)
 Note: models listed above might not be available in all WE countries

- Small and medium business (SMB) model(s), part of the Westen Europe TopSeller™ Program
- 1-year limited warranty

Positioning	Stylish design, reliability, and productivity for small/medium businesses											Preloaded operating system Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit
Processor	Intel® Core™ Core i5-4440S Processor (4 cores / 4 threads, 2.8GHz, 6MB cache), Turbo Boost 2.0 (3.3GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i7-4770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Processor in LGA1150 socket											
Implementation												Preloaded applications (only some listed) • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Power Manager • ThinkVantage Device Experience • View Management Utility • Lenovo Cloud Storage by SugarSync • Lenovo Solution Center • Lenovo Message Center Plus • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ • Evernote® • Microsoft® Office preloaded; purchase a product key to activate • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) • Nitro Pro
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3* , two 240-pin DIMM sockets *System automatically clocks down for processors with 1333MHz memory controller											
Graphics	Intel HD Graphics or Intel HD Graphics 4400/4600 in processor, uses main memory, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking)											
DP dongle	None											
Disk	Some: SATA 6.0Gb/s, 3.5" Wide, 7200 rpm											
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive											
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset											
Onboard SATA	SATA cables match SATA devices (each 1-drop to device), one SATA 3.0Gb/s connector (for optical) and two SATA 6.0Gb/s connectors (for HDD/SSD) on planar											
eSATA port	None											
Media reader	Optional 9-in-1 media reader, internal USB 2.0											
Chipset	Intel H81 Express Chipset											
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)											
Rear ports	Two USB 3.0, two USB 2.0, optional serial (9-pin)*, optional parallel (25-pin)*, ethernet (RJ-45), VGA DB-15, DisplayPort * Please see the detailed configuration on top											
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)											
PCIe WLAN	None											
Bluetooth	None											
Audio	High Definition (HD) Audio, Realtek® ALC662 codec											
Speaker	Internal speaker for business audio											
IEEE 1394	None											
Ethernet	Gigabit ethernet port, Realtek RTL8111GN, Wake on LAN											
Manageability	None											
Modem	None											
Security chip	None											
Keyboard	Lenovo® Slim USB Keyboard (USB connector), black, Lenovo logo											
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo											
Floor Stand	Optional system floor stand for vertical orientation											
Power supply	180 watts, universal, autosensing											
Machine	• Glossy black bezel; metal case • 13.2" W X 15.0" D X 3.98" H • 336mm W X 382mm D X 101mm H • 13.2 lb (6.0 kg) in maximum configuration • Highlighted optical drive button for easy access											
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 2.5", N/A, no access, opt 2nd SSD* Bay 4: 1.5", .35" high, access, optnl reader* *bay only available on models with SSD/reader installed											
Slot	Slot 1: Low Profile, PCI Express® 3.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, PCIe 2.0 x1											
Limited Warranty ¹	1-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											Security • One lock to secure both cover and entire system to fixed object: -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement
												GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies




ThinkCentre E73 SFF (10AW) - ES 6.0 (TopSeller)

Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory ^a	SATA disk GB rpm	SATA optical	PCIe WLAN	Media reader	Graphics	Parallel port	Serial port	Floor stand	Keyboard / mouse	Global	Preload	Ann date (mm/dd/yy)
10AW008B++	3x4	i3-4130	4GBx1	500G 7200	DVD±RW	None	Media	HD 4400	Parallel	Serial	None	USB(slim)	None	Win8.1 64	04/22/14
10AW008C++	3x4	G3220	4GBx1	500G 7200	DVD±RW	None	Media	Intel HD	Parallel	Serial	None	USB(slim)	None	Win8.1 64	04/22/14
10AW008K++	3x4	G3240	4GBx1	500G 7200	DVD±RW	None	Media	Intel HD	Parallel	Serial	None	USB(slim)	None	Win8.1 64	06/24/14
10AW008L++	3x4	i3-4150	4GBx1	500G 7200	DVD±RW	None	Media	HD 4400	Parallel	Serial	None	USB(slim)	None	Win8.1 64	06/24/14

Country Code^{a,+,*}: AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)
 Note: models listed above might not be available in all WE countries

- Small and medium business (SMB) model(s), part of the Westen Europe TopSeller™ Program
- 1-year limited warranty

Positioning	Stylish design, reliability, and productivity for small/medium businesses											Preloaded operating system			
Processor	Intel® Pentium® G3220 Processor (2 cores / 2 threads, 3.0GHz, 3MB cache), Intel HD Graphics, 1333MHz DDR3 memory controller Intel Pentium G3240 Processor (2 cores / 2 threads, 3.1GHz, 3MB cache), Intel HD Graphics, 1333MHz DDR3 memory controller Intel Core™ i3-4130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller Intel Core i3-4150 Processor (2 cores / 4 threads, 3.5GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller											Windows® 8.1 64-bit			
Implementation	Processor in LGA1150 socket											Ready to install applications (only some listed)			
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3* , two 240-pin DIMM sockets *System automatically clocks down for processors with 1333MHz memory controller											<ul style="list-style-type: none"> • Password Manager 			
Graphics	Intel HD Graphics or Intel HD Graphics 4400/4600 in processor, uses main memory, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking)											Preloaded applications (only some listed)			
DP dongle	None											<ul style="list-style-type: none"> • ThinkVantage® System Update • Lenovo® Support • Lenovo Companion • Lenovo Solution Center • Desktop Power Manager • PC Device Stage • Microsoft® Office preloaded; purchase a product key to activate • Norton™ Internet Security (30 days of virus definitions) • Evernote™ • Skype™ • Cyberlink PowerDVD (DVD±RW, DVD) • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) • Nitro Pro • AccuWeather • Norton Studio • Pokki • Hightail 			
Disk	Some: SATA 6.0Gb/s, 3.5" Wide, 7200 rpm														
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive														
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset														
Onboard SATA	SATA cables match SATA devices (each 1-drop to device), one SATA 3.0Gb/s connector (for optical) and two SATA 6.0Gb/s connectors (for HDD/SSD) on planar														
eSATA port	None														
Media reader	Optional 9-in-1 media reader, internal USB 2.0														
Chipset	Intel H81 Express Chipset														
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
Rear ports	Two USB 3.0, two USB 2.0, optional serial (9-pin)*, optional parallel (25-pin)*, ethernet (RJ-45), VGA DB-15, DisplayPort * Please see the detailed configuration on top														
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)														
PCIe WLAN	None														
Bluetooth	None														
Audio	High Definition (HD) Audio, Realtek® ALC662 codec														
Speaker	Internal speaker for business audio														
IEEE 1394	None														
Ethernet	Gigabit ethernet port, Realtek RTL8111GN, Wake on LAN														
Manageability	None														
Modem	None														
Security chip	None														
Keyboard	Lenovo® Slim USB Keyboard (USB connector), black, Lenovo logo														
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo														
Floor Stand	Optional system floor stand for vertical orientation														
Power supply	240 watts, universal, autosensing, 85% PSU														
Machine	<ul style="list-style-type: none"> • Glossy black bezel; metal case • 13.2" W X 15.0" D X 3.98" H • 336mm W X 382mm D X 101mm H • 13.2 lb (6.0 kg) in maximum configuration • Highlighted optical drive button for easy access 														
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 2.5", N/A, no access, opt 2nd SSD* Bay 4: 1.5", .35" high, access, optnl reader* *bay only available on models with SSD/reader installed														
Slot	Slot 1: Low Profile, PCI Express® 3.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, PCIe 2.0 x1											Security <ul style="list-style-type: none"> • One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement 			
Limited Warranty ¹	1-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											EPEAT™ Silver; ENERGY STAR® 6.0 GREENGUARD® certified RoHS-compliant ErP Lot 3 Supports ThinkVantage Technologies			

See footnotes for important warranty information

ThinkCentre E73 SFF (10AW) - ES 6.0 (TopSeller) - II


Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory ^a	SATA disk GB rpm	SATA optical	PCIe WLAN	Media reader	Graphics	Parallel port	Serial port	Floor stand	Keyboard / mouse	Global	Preload	Ann date (mm/dd/yy)
10AW0088++	3x4	G3220	4GBx1	500G 7200	DVD±RW	None	Media	Intel HD	Parallel	Serial	None	USB	None	Win7 P64 DG	Win8.1 04/22/14
10AW0089++	3x4	i3-4130	4GBx1	500G 7200	DVD±RW	None	Media	HD 4400	Parallel	Serial	None	USB	None	Win7 P64 DG	Win8.1 04/22/14
10AW008A++	3x4	G3220	4GBx1	500G 7200	DVD±RW	None	Media	Intel HD	Parallel	Serial	None	USB(slim)	None	Win7 P64 DG	Win8.1 04/22/14
10AW008D++	3x4	i7-4770S	4GBx1	1TB 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	None	USB(slim)	None	Win7 P64 DG	Win8.1 04/22/14
10AW008E++	3x4	i7-4770S	8GBx1	1TB 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	None	USB(slim)	None	Win7 P64 DG	Win8.1 04/22/14
10AW008F++	3x4	i5-4440S	4GBx1	500G 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	None	USB(slim)	None	Win7 P64 DG	Win8.1 04/22/14
10AW008G++	3x4	i5-4440S	8GBx1	1TB 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	None	USB(slim)	None	Win7 P64 DG	Win8.1 04/22/14
10AW008H++	3x4	i3-4130	4GBx1	500G 7200	DVD±RW	None	Media	HD 4400	Parallel	Serial	None	USB(slim)	None	Win7 P64 DG	Win8.1 04/22/14
10AW008J++	3x4	i5-4440S	4+2GB	128G SSD	DVD±RW	None	Media	HD 4600	Parallel	Serial	None	USB(slim)	None	Win7 P64 DG	Win8.1 04/22/14

Country Code"++": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)

Note: models listed above might not be available in all WE countries

● 1-year limited warranty

Positioning	Stylish design, reliability, and productivity for small/medium businesses											Preloaded operating system			
Processor	Intel® Pentium® G3220 Processor (2 cores / 2 threads, 3.0GHz, 3MB cache), Intel HD Graphics, 1333MHz DDR3 memory controller Intel Core™ i3-4130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller Intel Core i5-4440S Processor (4 cores / 4 threads, 2.8GHz, 6MB cache), Turbo Boost 2.0 (3.3GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i7-4770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Processor in LGA1150 socket											Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit Ready to install applications (only some listed) ● Rescue and Recovery™ ● Password Manager			
Implementation	Processor in LGA1150 socket											Preloaded applications (only some listed)			
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3* , two 240-pin DIMM sockets *System automatically clocks down for processors with 1333MHz memory controller											● ThinkVantage® Product Recovery ● ThinkVantage System Update ● ThinkVantage Communication Utility ● ThinkVantage Power Manager ● ThinkVantage Device Experience ● View Management Utility ● Lenovo Cloud Storage by SugarSync ● Lenovo Solution Center ● Lenovo Message Center Plus ● Norton™ Internet Security (30 days of virus definitions) ● Adobe® Reader® ● Skype™ ● Evernote® ● Microsoft® Office preloaded; purchase a product key to activate ● Cyberlink Power2Go (DVD±RW) ● Cyberlink PowerProducer (DVD±RW) ● Nitro Pro			
Graphics	Intel HD Graphics or Intel HD Graphics 4400/4600 in processor, uses main memory, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking)														
DP dongle	None														
Disk	Some: SATA 6.0Gb/s, 3.5" Wide, 7200 rpm Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide														
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive														
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset														
Onboard SATA	SATA cables match SATA devices (each 1-drop to device), one SATA 3.0Gb/s connector (for optical) and two SATA 6.0Gb/s connectors (for HDD/SSD) on planar														
eSATA port	None														
Media reader	Optional 9-in-1 media reader, internal USB 2.0														
Chipset	Intel H81 Express Chipset														
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
Rear ports	Two USB 3.0, two USB 2.0, optional serial (9-pin)*, optional parallel (25-pin)*, ethernet (RJ-45), VGA DB-15, DisplayPort * Please see the detailed configuration on top														
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)														
PCIe WLAN	None														
Bluetooth	None														
Audio	High Definition (HD) Audio, Realtek® ALC662 codec														
Speaker	Internal speaker for business audio														
IEEE 1394	None														
Ethernet	Gigabit ethernet port, Realtek RTL8111GN, Wake on LAN														
Manageability	None														
Modem	None														
Security chip	None														
Keyboard	Some: Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo Some: Lenovo® Slim USB Keyboard (USB connector), black, Lenovo logo														
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo														
Floor Stand	Optional system floor stand for vertical orientation														
Power supply	240 watts, universal, autosensing, 85% PSU														
Machine	● Glossy black bezel; metal case ● 13.2" W X 15.0" D X 3.98" H ● 336mm W X 382mm D X 101mm H ● 13.2 lb (6.0 kg) in maximum configuration ● Highlighted optical drive button for easy access														
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 2.5", N/A, no access, opt 2nd SSD* Bay 4: 1.5", .35" high, access, optnl reader* *bay only available on models with SSD/reader installed														
Slot	Slot 1: Low Profile, PCI Express® 3.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, PCIe 2.0 x1														
Limited Warranty ¹	1-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											Security ● One lock to secure both cover and entire system to fixed object: -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) ● Power-on password ● Administrator password ● Hard disk password ● Boot sequence control ● Boot without keyboard and mouse ● Individual USB port disablement EPEAT™ Silver; ENERGY STAR® 6.0 GREENGUARD® certified RoHS-compliant ErP Lot 3			
Supports ThinkVantage Technologies															

See footnotes for important warranty information

ThinkCentre E73 Tower (10AS) - TopSeller


Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	PCIe WLAN	Media reader	Graphics	Parallel port	Serial port	Keyboard / mouse	Global	Preload	Ann date (mm/dd/yy)
10AS002L++	3x4	i5-4430S	4GBx1	1TB 7200	DVD±RW	None	Media	GT 620	Parallel	Serial	USB	None	Win7 Pro64 (DG)	10/22/13
10AS002M++	3x4	i5-4430S	4GBx1	1TB 7200	DVD±RW	None	Media	GT 620	Parallel	Serial	USB(slim)	None	Win7 Pro64 (DG)	10/22/13
10AS002N++	3x4	i5-4430S	4GBx1	1TB 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB(slim)	None	Win7 Pro64 (DG)	10/22/13
10AS002P++	3x4	i5-4430S	4GBx1	500G 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB	None	Win7 Pro64 (DG)	10/22/13
10AS002Q++	3x4	i3-4130	4GBx1	1TB 7200	DVD±RW	None	Media	HD 4400	Parallel	Serial	USB(slim)	None	Win7 Pro64 (DG)	10/22/13
10AS002R++	3x4	i5-4430S	4GBx1	500G 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB(slim)	None	Win7 Pro64 (DG)	10/22/13
10AS002S++	3x4	i3-4130	4GBx1	1TB 7200	DVD±RW	None	Media	HD 4400	Parallel	Serial	USB	None	Win7 Pro64 (DG)	10/22/13
10AS002T++	3x4	i5-4430S	4GBx1	1TB 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB	None	Win7 Pro64 (DG)	10/22/13
10AS002U++	3x4	i3-4130	4GBx1	500G 7200	DVD±RW	None	Media	HD 4400	Parallel	Serial	USB	None	Win7 Pro64 (DG)	10/22/13
10AS002V++	3x4	i3-4130	4GBx1	500G 7200	DVD±RW	None	Media	HD 4400	Parallel	Serial	USB(slim)	None	Win7 Pro64 (DG)	10/22/13

Country Code⁹++ : AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)

Note: models listed above might not be available in all WE countries

● 1-year limited warranty

Positioning	<i>Stylish design, reliability, and productivity for small/medium businesses</i>										
Processor	Intel® Core™ i3-4130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller Intel Core i5-4430S Processor (4 cores / 4 threads, 2.7GHz, 6MB cache), Turbo Boost 2.0 (3.2GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller										
Implementation	Processor in LGA1150 socket										
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3* , two 240-pin DIMM sockets *System automatically clocks down for processors with 1333MHz memory controller										
Graphics	Intel HD Graphics or Intel HD Graphics 4400/4600 in processor, uses main memory, one VGA, one DisplayPort™, supports dual independent display, works along with discrete graphics to support up to four independent monitors; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking)</i> <i>Some: NVIDIA® Geforce® GT 620, DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express 2.0 x16 adapter, one VGA, one DisplayPort, 30 watts; Max resolution: 2560x1600 (DisplayPort)@60Hz; 2048x1536 (VGA)@85Hz</i>										
DP dongle	None										
Disk	<i>Some: SATA 6.0Gb/s, 3.5" Wide, 7200 rpm</i>										
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive										
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset										
Onboard SATA	SATA cables match SATA devices (each 1-drop to device), one SATA 3.0Gb/s connector (for optical) and two SATA 6.0Gb/s connectors (for HDD/SSD) on planar										
eSATA port	None										
Media reader	Optional 9-in-1 media reader, internal USB 2.0										
Chipset	Intel H81 Express Chipset										
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)										
Rear ports	Two USB 3.0, two USB 2.0, optional serial (9-pin)*, optional parallel (25-pin)*, ethernet (RJ-45), VGA DB-15, DisplayPort * Please see the detailed configuration on top										
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)										
PCIe WLAN	None										
Bluetooth	None										
Audio	High Definition (HD) Audio, Realtek® ALC662 codec										
Speaker	Internal speaker for business audio										
IEEE 1394	None										
Ethernet	Gigabit ethernet port, Realtek RTL8111GN, Wake on LAN										
Manageability	None										
Modem	None										
Security chip	None										
Keyboard	<i>Some: Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo</i> <i>Some: Lenovo® Slim USB Keyboard (USB connector), black, Lenovo logo</i>										
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo										
Power supply	180 watts, universal, autosensing										
Machine	<ul style="list-style-type: none"> ● Glossy black bezel; metal case ● 6.3" W X 15.7" D X 15.6" H (with handle) ● 160mm W X 400mm D X 397mm H ● 16.5 lb (7.5 kg) in maximum configuration ● Ergonomic rubberized handle ● Highlighted optical drive button for easy access 										
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 1.5", .35" high, access, optnl reader* Bay 4: 3.5", 1" high, no access, opt 2nd 2.5" disk** *bay only available on models with media reader installed **3.5" to 2.5" bracket comes with optional 2nd 2.5" disk										
Slot	Slot 1: half-length, full-height, PCI Express® 3.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x1										
Limited Warranty ¹	1-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available										
											
	Preloaded operating system Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Ready to install applications (only some listed) <ul style="list-style-type: none"> ● Rescue and Recovery™ ● Password Manager Preloaded applications (only some listed) <ul style="list-style-type: none"> ● ThinkVantage® Product Recovery ● ThinkVantage System Update ● ThinkVantage Communication Utility ● ThinkVantage Power Manager ● ThinkVantage Device Experience ● View Management Utility ● Lenovo Cloud Storage by SugarSync ● Lenovo Solution Center ● Lenovo Message Center Plus ● Norton™ Internet Security (30 days of virus definitions) ● Adobe® Reader® ● Skype™ ● Evernote® ● Microsoft® Office preloaded; purchase a product key to activate ● Cyberlink Power2Go (DVD±RW) ● Cyberlink PowerProducer (DVD±RW) ● Nitro Pro 										
	Security <ul style="list-style-type: none"> ● One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) ● Power-on password ● Administrator password ● Hard disk password ● Boot sequence control ● Boot without keyboard and mouse ● Individual USB port disablement 										
	GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies										

See footnotes for important warranty information
WE model(s) announced October 22, 2013

©Lenovo
(G-TLS1T-1) October 2013


ThinkCentre E73 Tower (10AS) - TopSeller - II

Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	PCIe WLAN	Media reader	Graphics	Parallel port	Serial port	Keyboard / mouse	Global	Preload	Ann date (mm/dd/yy)
10AS002W++	3x4	G3420	4GBx1	500G 7200	DVD±RW	None	Media	Intel HD	Parallel	Serial	USB	None	Win7 Pro64 (DG)	10/22/13
10AS002X++	3x4	G3220	4GBx1	1TB 7200	DVD±RW	None	Media	Intel HD	Parallel	Serial	USB	None	Win7 Pro64 (DG)	10/22/13
10AS002Y++	3x4	G3220	4GBx1	1TB 7200	DVD±RW	None	Media	Intel HD	Parallel	Serial	USB(slim)	None	Win7 Pro64 (DG)	10/22/13
10AS0030++	3x4	G3220	4GBx1	500G 7200	DVD±RW	None	Media	Intel HD	Parallel	Serial	USB(slim)	None	Win7 Pro64 (DG)	10/22/13
10AS0031++	3x4	G3420	4GBx1	500G 7200	DVD±RW	None	Media	Intel HD	Parallel	Serial	USB(slim)	None	Win7 Pro64 (DG)	10/22/13
10AS0032++	3x4	G3220	4GBx1	500G 7200	DVD±RW	None	Media	Intel HD	Parallel	Serial	USB	None	Win7 Pro64 (DG)	10/22/13
10AS005U++	3x4	i7-4770S	4GBx1	500G 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB	None	Win7 Pro64 (DG)	12/10/13
10AS005V++	3x4	i7-4770S	4GBx1	500G 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB(slim)	None	Win7 Pro64 (DG)	12/10/13

Country Code"+": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)
 Note: models listed above might not be available in all WE countries

- Small and medium business (SMB) model(s), part of the Westen Europe TopSeller™ Program
- 1-year limited warranty

Positioning	<i>Stylish design, reliability, and productivity for small/medium businesses</i>		Preloaded operating system Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Power Manager • ThinkVantage Device Experience • View Management Utility • Lenovo Cloud Storage by SugarSync • Lenovo Solution Center • Lenovo Message Center Plus • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ • Evernote® • Microsoft® Office preloaded; purchase a product key to activate • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) • Nitro Pro
Processor	Intel® Pentium® G3220 Processor (2 cores / 2 threads, 3.0GHz, 3MB cache), Intel HD Graphics, 1333MHz DDR3 memory controller Intel Pentium G3420 Processor (2 cores / 2 threads, 3.2GHz, 3MB cache), Intel HD Graphics, 1600MHz DDR3 memory controller Intel Core™ i7-4770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller		
Implementation	Processor in LGA1150 socket		
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3* , two 240-pin DIMM sockets *System automatically clocks down for processors with 1333MHz memory controller		
Graphics	Intel HD Graphics or Intel HD Graphics 4400/4600 in processor, uses main memory, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking)		
DP dongle	None		
Disk	Some: SATA 6.0Gb/s, 3.5" Wide, 7200 rpm		
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive		
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset		
Onboard SATA	SATA cables match SATA devices (each 1-drop to device), one SATA 3.0Gb/s connector (for optical) and two SATA 6.0Gb/s connectors (for HDD/SSD) on planar		
eSATA port	None		
Media reader	Optional 9-in-1 media reader, internal USB 2.0		
Chipset	Intel H81 Express Chipset		
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)		
Rear ports	Two USB 3.0, two USB 2.0, optional serial (9-pin)*, optional parallel (25-pin)*, ethernet (RJ-45), VGA DB-15, DisplayPort * Please see the detailed configuration on top		
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)		
PCIe WLAN	None		
Bluetooth	None		
Audio	High Definition (HD) Audio, Realtek® ALC662 codec		
Speaker	Internal speaker for business audio		
IEEE 1394	None		
Ethernet	Gigabit ethernet port, Realtek RTL8111GN, Wake on LAN		
Manageability	None		
Modem	None		
Security chip	None		
Keyboard	Some: Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo Some: Lenovo® Slim USB Keyboard (USB connector), black, Lenovo logo		
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo		
Power supply	180 watts, universal, autosensing		
Machine	<ul style="list-style-type: none"> • Glossy black bezel; metal case • 6.3" W X 15.7" D X 15.6" H (with handle) • 160mm W X 400mm D X 397mm H • 16.5 lb (7.5 kg) in maximum configuration • Ergonomic rubberized handle • Highlighted optical drive button for easy access 		
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 1.5", .35" high, access, optnl reader* Bay 4: 3.5", 1" high, no access, opt 2nd 2.5" disk** *bay only available on models with media reader installed **3.5" to 2.5" bracket comes with optional 2nd 2.5" disk		
Slot	Slot 1: half-length, full-height, PCI Express® 3.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x1		
Limited Warranty ¹	1-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available		
			
	Security <ul style="list-style-type: none"> • One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement 		
	GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies		

See footnotes for important warranty information
 WE model(s) announced October 22, 2013 or December 10, 2013

©Lenovo
 (G-TLS1T-2) December 2013

ThinkCentre E73 Tower (10AS) - TopSeller - III


Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	PCIe WLAN	Media reader	Graphics	Parallel port	Serial port	Keyboard / mouse	Global	Preload	Ann date (mm/dd/yy)
10AS0033++	3x4	i5-4430S	4GBx1	500G 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB	None	None	10/22/13
10AS0034++	3x4	i5-4430S	4GBx1	500G 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB(slim)	None	None	10/22/13
10AS0035++	3x4	i3-4130	4GBx1	500G 7200	DVD±RW	None	Media	HD 4400	Parallel	Serial	USB(slim)	None	None	10/22/13
10AS0036++	3x4	i3-4130	4GBx1	500G 7200	DVD±RW	None	Media	HD 4400	Parallel	Serial	USB	None	None	10/22/13
10AS0037++	3x4	G3220	4GBx1	500G 7200	DVD±RW	None	Media	Intel HD	Parallel	Serial	USB	None	None	10/22/13
10AS0038++	3x4	G3220	4GBx1	500G 7200	DVD±RW	None	Media	Intel HD	Parallel	Serial	USB(slim)	None	None	10/22/13
10AS005Y++	3x4	i7-4770S	4GBx1	500G 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB(slim)	None	None	12/10/13
10AS0060++	3x4	i7-4770S	4GBx1	500G 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB	None	None	12/10/13

Country Code"+": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)

Note: models listed above might not be available in all WE countries

- Small and medium business (SMB) model(s), part of the Westen Europe TopSeller™ Program
- 1-year limited warranty

Positioning	Stylish design, reliability, and productivity for small/medium businesses		Preloaded operating system No operating system
Processor	Intel® Pentium® G3220 Processor (2 cores / 2 threads, 3.0GHz, 3MB cache), Intel HD Graphics, 1333MHz DDR3 memory controller Intel Core™ i3-4130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller Intel Core i5-4430S Processor (4 cores / 4 threads, 2.7GHz, 6MB cache), Turbo Boost 2.0 (3.2GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i7-4770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller		
Implementation	Processor in LGA1150 socket		
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3* , two 240-pin DIMM sockets *System automatically clocks down for processors with 1333MHz memory controller		
Graphics	Intel HD Graphics or Intel HD Graphics 4400/4600 in processor, uses main memory, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking)		
DP dongle	None		
Disk	Some: SATA 6.0Gb/s, 3.5" Wide, 7200 rpm		
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive		
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset		
Onboard SATA	SATA cables match SATA devices (each 1-drop to device), one SATA 3.0Gb/s connector (for optical) and two SATA 6.0Gb/s connectors (for HDD/SSD) on planar		
eSATA port	None		
Media reader	Optional 9-in-1 media reader, internal USB 2.0		
Chipset	Intel H81 Express Chipset		
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)		
Rear ports	Two USB 3.0, two USB 2.0, optional serial (9-pin)*, optional parallel (25-pin)*, ethernet (RJ-45), VGA DB-15, DisplayPort * Please see the detailed configuration on top		
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)		
PCIe WLAN	None		
Bluetooth	None		
Audio	High Definition (HD) Audio, Realtek® ALC662 codec		
Speaker	Internal speaker for business audio		
IEEE 1394	None		
Ethernet	Gigabit ethernet port, Realtek RTL8111GN, Wake on LAN		
Manageability	None		
Modem	None		
Security chip	None		
Keyboard	Some: Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo Some: Lenovo® Slim USB Keyboard (USB connector), black, Lenovo logo		
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo		
Power supply	180 watts, universal, autosensing		
Machine	<ul style="list-style-type: none"> • Glossy black bezel; metal case • 6.3" W X 15.7" D X 15.6" H (with handle) • 160mm W X 400mm D X 397mm H • 16.5 lb (7.5 kg) in maximum configuration • Ergonomic rubberized handle • Highlighted optical drive button for easy access 		
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 1.5", .35" high, access, optnl reader* Bay 4: 3.5", 1" high, no access, opt 2nd 2.5" disk** *bay only available on models with media reader installed **3.5" to 2.5" bracket comes with optional 2nd 2.5" disk		
Slot	Slot 1: half-length, full-height, PCI Express® 3.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x1		
Limited Warranty ¹	1-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available		
			
	Security <ul style="list-style-type: none"> • One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement 		
	GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies		

See footnotes for important warranty information
 WE model(s) announced October 22, 2013 or December 10, 2013

©Lenovo
 (G-TLS1T-3) December 2013


ThinkCentre E73 Tower (10AS) - TopSeller - IV

Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	PCIe WLAN	Media reader	Graphics	Parallel port	Serial port	Keyboard / mouse	Cable lock	Warranty (year)	Preload	Ann date (mm/dd/yy)
10AS008D++	3x4	i7-4770S	8GBx1	1TB 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB(slim)	None	1-year	Win7 P64 DG	Win8.1 03/18/14
10AS008E++	3x4	i7-4770S	8GBx1	1TB 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB	None	1-year	Win7 P64 DG	Win8.1 03/18/14
10AS008F++	3x4	i7-4770S	8GBx1	128G SSD +500G 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB	Lock	3-year	Win7 P64 DG	Win8.1 03/18/14
10AS008G++	3x4	i5-4430S	8GBx1	1TB 7200	DVD±RW	None	Media	GT 620	Parallel	Serial	USB(slim)	None	1-year	Win7 P64 DG	Win8.1 03/25/14

Country Code"+": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)
 Note: models listed above might not be available in all WE countries

- Small and medium business (SMB) model(s), part of the Western Europe TopSeller™ Program
- 1-year or 3-year limited warranty

Positioning	<i>Stylish design, reliability, and productivity for small/medium businesses</i>											Preloaded operating system			
Processor	Intel® Core™ i5-4430S Processor (4 cores / 4 threads, 2.7GHz, 6MB cache), Turbo Boost 2.0 (3.2GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i7-4770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Processor in LGA1150 socket											Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit			
Implementation	Processor in LGA1150 socket											Ready to install applications (only some listed)			
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3* , two 240-pin DIMM sockets *System automatically clocks down for processors with 1333MHz memory controller											<ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager 			
Graphics	Intel HD Graphics or Intel HD Graphics 4400/4600 in processor, uses main memory, one VGA, one DisplayPort™, supports dual independent display, works along with discrete graphics to support up to four independent monitors; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking)</i> Some: NVIDIA® GeForce® GT 620 , DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express 2.0 x16 adapter, one VGA, one DisplayPort, 30 watts; <i>Max resolution: 2560x1600 (DisplayPort)@60Hz; 2048x1536 (VGA)@85Hz</i>											Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Power Manager • ThinkVantage Device Experience • View Management Utility • Lenovo Cloud Storage by SugarSync • Lenovo Solution Center • Lenovo Message Center Plus • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ • Evernote® • Microsoft® Office preloaded; purchase a product key to activate • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) • Nitro Pro 			
DP dongle	None														
Disk	Some: SATA 6.0Gb/s, 3.5" Wide, 7200 rpm Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide														
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive														
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset														
Onboard SATA	SATA cables match SATA devices (each 1-drop to device), one SATA 3.0Gb/s connector (for optical) and two SATA 6.0Gb/s connectors (for HDD/SSD) on planar														
eSATA port	None														
Media reader	Optional 9-in-1 media reader, internal USB 2.0														
Chipset	Intel H81 Express Chipset														
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
Rear ports	Two USB 3.0, two USB 2.0, optional serial (9-pin)*, optional parallel (25-pin)*, ethernet (RJ-45), VGA DB-15, DisplayPort * Please see the detailed configuration on top														
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)														
PCIe WLAN	None														
Bluetooth	None														
Audio	High Definition (HD) Audio, Realtek® ALC662 codec														
Speaker	Internal speaker for business audio														
IEEE 1394	None														
Ethernet	Gigabit ethernet port, Realtek RTL8111GN, Wake on LAN														
Manageability	None														
Modem	None														
Security chip	None														
Keyboard	Some: Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo Some: Lenovo® Slim USB Keyboard (USB connector), black, Lenovo logo														
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo														
Power supply	180 watts, universal, autosensing														
Machine	<ul style="list-style-type: none"> • Glossy black bezel; metal case • 6.3" W X 15.7" D X 15.6" H (with handle) • 160mm W X 400mm D X 397mm H • 16.5 lb (7.5 kg) in maximum configuration • Ergonomic rubberized handle • Highlighted optical drive button for easy access 														
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 1.5", .35" high, access, optnl reader* Bay 4: 3.5", 1" high, no access, opt 2nd 2.5" disk** *bay only available on models with media reader installed **3.5" to 2.5" bracket comes with optional 2nd 2.5" disk														
Slot	Slot 1: half-length, full-height, PCI Express® 3.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x1														
Limited Warranty ¹	1-years or 3-year, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											Security <ul style="list-style-type: none"> • One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) • Cable lock to physically lock both keyboard and mouse (optional) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement 			
												GREENGUARD® certified RoHS-compliant			
												Supports ThinkVantage Technologies			

See footnotes for important warranty information
 WE model(s) announced March 18 or 25, 2014

©Lenovo
 (G-TLS1T-4) March 2014


ThinkCentre E73 Tower (10DR) - ES 6.0 (TopSeller)

Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	PCIe WLAN	Media reader	Graphics	Parallel port	Serial port	Keyboard / mouse	Cable lock	Warranty (year)	Preload	Ann date (mm/dd/yy)
10DR0000++	3x4	i7-4770S	4GBx1	500G 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB(slim)	None	1-year	Win7 P64 DG Win8.1	05/06/14
10DR0001++	3x4	i7-4770S	4GBx1	500G 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB	None	1-year	Win7 P64 DG Win8.1	05/06/14
10DR0002++	3x4	i7-4770S	8GBx1	1TB 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB	None	1-year	Win7 P64 DG Win8.1	05/06/14
10DR0003++	3x4	i7-4770S	8GBx1	1TB 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB(slim)	None	1-year	Win7 P64 DG Win8.1	05/06/14
10DR0004++	3x4	i5-4440S	8GBx1	1TB 7200	DVD±RW	None	Media	GT 620	Parallel	Serial	USB(slim)	None	1-year	Win7 P64 DG Win8.1	05/06/14
10DR0005++	3x4	i5-4440S	4GBx1	1TB 7200	DVD±RW	None	Media	GT 620	Parallel	Serial	USB(slim)	None	1-year	Win7 P64 DG Win8.1	05/06/14
10DR0006++	3x4	i5-4440S	4GBx1	1TB 7200	DVD±RW	None	Media	GT 620	Parallel	Serial	USB	None	1-year	Win7 P64 DG Win8.1	05/06/14
10DR0007++	3x4	i3-4130	4GBx1	500G 7200	DVD±RW	None	Media	HD 4400	Parallel	Serial	USB(slim)	None	1-year	Win7 P64 DG Win8.1	05/06/14

Country Code"++": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)

Note: models listed above might not be available in all WE countries

Positioning	<i>Stylish design, reliability, and productivity for small/medium businesses</i>											Preloaded operating system			
Processor	Intel® Core™ i3-4130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller Intel Core i5-4440S Processor (4 cores / 4 threads, 2.8GHz, 6MB cache), Turbo Boost 2.0 (3.3GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i7-4770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller											Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit Ready to install applications (only some listed)			
Implementation	Processor in LGA1150 socket											<ul style="list-style-type: none"> Rescue and Recovery™ Password Manager 			
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3* , two 240-pin DIMM sockets *System automatically clocks down for processors with 1333MHz memory controller											Preloaded applications (only some listed)			
Graphics	Intel HD Graphics or Intel HD Graphics 4400/4600 in processor, uses main memory, one VGA, one DisplayPort™, supports dual independent display, works along with discrete graphics to support up to four independent monitors; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking)</i> Some: NVIDIA® GeForce® GT 620 , DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express 2.0 x16 adapter, one VGA, one DisplayPort, 30 watts; <i>Max resolution: 2560x1600 (DisplayPort)@60Hz; 2048x1536 (VGA)@85Hz</i>											<ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage System Update ThinkVantage Communication Utility ThinkVantage Power Manager ThinkVantage Device Experience View Management Utility Lenovo Cloud Storage by SugarSync Lenovo Solution Center Lenovo Message Center Plus Norton™ Internet Security (30 days of virus definitions) Adobe® Reader® Skype™ Evernote® Microsoft® Office preloaded; purchase a product key to activate Cyberlink Power2Go (DVD±RW) Cyberlink PowerProducer (DVD±RW) Nitro Pro 			
DP dongle	None														
Disk	Some: SATA 6.0Gb/s, 3.5" Wide, 7200 rpm Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide														
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive														
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset														
Onboard SATA	SATA cables match SATA devices (each 1-drop to device), one SATA 3.0Gb/s connector (for optical) and two SATA 6.0Gb/s connectors (for HDD/SSD) on planar														
eSATA port	None														
Media reader	Optional 9-in-1 media reader, internal USB 2.0														
Chipset	Intel H81 Express Chipset														
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
Rear ports	Two USB 3.0, two USB 2.0, optional serial (9-pin)*, optional parallel (25-pin)*, ethernet (RJ-45), VGA DB-15, DisplayPort * Please see the detailed configuration on top														
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)														
PCIe WLAN	None														
Bluetooth	None														
Audio	High Definition (HD) Audio, Realtek® ALC662 codec														
Speaker	Internal speaker for business audio														
IEEE 1394	None														
Ethernet	Gigabit ethernet port, Realtek RTL8111GN, Wake on LAN														
Manageability	None														
Modem	None														
Security chip	None														
Keyboard	Some: Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo Some: Lenovo® Slim USB Keyboard (USB connector), black, Lenovo logo														
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo														
Power supply	280 watts, universal, autosensing, 85% PSU														
Machine	<ul style="list-style-type: none"> Glossy black bezel; metal case 6.3" W X 15.7" D X 15.6" H (with handle) 160mm W X 400mm D X 397mm H 16.5 lb (7.5 kg) in maximum configuration Ergonomic rubberized handle Highlighted optical drive button for easy access 														
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 1.5", .35" high, access, optnl reader* Bay 4: 3.5", 1" high, no access, opt 2nd 2.5" disk** *bay only available on models with media reader installed **3.5" to 2.5" bracket comes with optional 2nd 2.5" disk														
Slot	Slot 1: half-length, full-height, PCI Express® 3.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x1											Security <ul style="list-style-type: none"> One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) Cable lock to physically lock both keyboard and mouse (optional) Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse Individual USB port disablement 			
Limited Warranty ¹	1-years or 3-year, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											EPEAT™ Silver; ENERGY STAR® 6.0 GREENGUARD® certified RoHS-compliant ErP Lot 3			
Supports ThinkVantage Technologies															


See footnotes for important warranty information

©Lenovo
(G-TLS1T-5) May 2014

ThinkCentre E73 Tower (10DR) - ES 6.0 (TopSeller) - II

Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	PCIe WLAN	Media reader	Graphics	Parallel port	Serial port	Keyboard / mouse	Cable lock	Warranty (year)	Preload	Ann date (mm/dd/yy)
10DR000C++	3x4	G3220	4GBx1	500G 7200	DVD±RW	None	Media	Intel HD	Parallel	Serial	USB(slim)	None	1-year	Win7 P64 DG Win8.1	05/06/14
10DR000D++	3x4	i5-4440S	4GBx1	500G 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB(slim)	None	1-year	Win7 P64 DG Win8.1	05/06/14
10DR000E++	3x4	G3220	4GBx1	1TB 7200	DVD±RW	None	Media	Intel HD	Parallel	Serial	USB	None	1-year	Win7 P64 DG Win8.1	05/06/14
10DR000F++	3x4	i3-4130	4GBx1	1TB 7200	DVD±RW	None	Media	HD 4400	Parallel	Serial	USB	None	1-year	Win7 P64 DG Win8.1	05/06/14
10DR000G++	3x4	i5-4440S	4GBx1	1TB 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB	None	1-year	Win7 P64 DG Win8.1	05/06/14
10DR000H++	3x4	i3-4130	4GBx1	1TB 7200	DVD±RW	None	Media	HD 4400	Parallel	Serial	USB(slim)	None	1-year	Win7 P64 DG Win8.1	05/06/14
10DR000K++	3x4	G3220	4GBx1	500G 7200	DVD±RW	None	Media	Intel HD	Parallel	Serial	USB	None	1-year	Win7 P64 DG Win8.1	05/06/14
10DR000M++	3x4	G3220	4GBx1	1TB 7200	DVD±RW	None	Media	Intel HD	Parallel	Serial	USB(slim)	None	1-year	Win7 P64 DG Win8.1	05/06/14
10DR000P++	3x4	i3-4130	4GBx1	500G 7200	DVD±RW	None	Media	HD 4400	Parallel	Serial	USB	None	1-year	Win7 P64 DG Win8.1	05/06/14
10DR000Q++	3x4	i5-4440S	4GBx1	1TB 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB(slim)	None	1-year	Win7 P64 DG Win8.1	05/06/14
10DR000R++	3x4	i5-4440S	4GBx1	500G 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB	None	1-year	Win7 P64 DG Win8.1	05/06/14


Positioning	<i>Stylish design, reliability, and productivity for small/medium businesses</i>											Preloaded operating system			
Processor	Intel® Pentium® G3220 Processor (2 cores / 2 threads, 3.0GHz, 3MB cache), Intel HD Graphics, 1333MHz DDR3 memory controller Intel Core™ i3-4130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller Intel Core i5-4440S Processor (4 cores / 4 threads, 2.8GHz, 6MB cache), Turbo Boost 2.0 (3.3GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller											Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit			
Implementation	Processor in LGA1150 socket											Ready to install applications (only some listed)			
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3* , two 240-pin DIMM sockets *System automatically clocks down for processors with 1333MHz memory controller											<ul style="list-style-type: none"> Rescue and Recovery™ Password Manager 			
Graphics	Intel HD Graphics or Intel HD Graphics 4400/4600 in processor, uses main memory, one VGA, one DisplayPort™, supports dual independent display, works along with discrete graphics to support up to four independent monitors; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz;</i> 1920x1200 (VGA)@60Hz (Reduced Blanking) Some: NVIDIA® GeForce® GT 620 , DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express 2.0 x16 adapter, one VGA, one DisplayPort, 30 watts; <i>Max resolution: 2560x1600 (DisplayPort)@60Hz; 2048x1536 (VGA)@85Hz</i>											<ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage System Update ThinkVantage Communication Utility ThinkVantage Power Manager ThinkVantage Device Experience View Management Utility Lenovo Cloud Storage by SugarSync Lenovo Solution Center Lenovo Message Center Plus Norton™ Internet Security (30 days of virus definitions) Adobe® Reader® Skype™ Evernote® Microsoft® Office preloaded; purchase a product key to activate Cyberlink Power2Go (DVD±RW) Cyberlink PowerProducer (DVD±RW) Nitro Pro 			
DP dongle	None														
Disk	Some: SATA 6.0Gb/s, 3.5" Wide, 7200 rpm Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide														
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive														
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset														
Onboard SATA	SATA cables match SATA devices (each 1-drop to device), one SATA 3.0Gb/s connector (for optical) and two SATA 6.0Gb/s connectors (for HDD/SSD) on planar														
eSATA port	None														
Media reader	Optional 9-in-1 media reader, internal USB 2.0														
Chipset	Intel H81 Express Chipset														
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
Rear ports	Two USB 3.0, two USB 2.0, optional serial (9-pin)*, optional parallel (25-pin)*, ethernet (RJ-45), VGA DB-15, DisplayPort * Please see the detailed configuration on top														
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)														
PCIe WLAN	None														
Bluetooth	None														
Audio	High Definition (HD) Audio, Realtek® ALC662 codec														
Speaker	Internal speaker for business audio														
IEEE 1394	None														
Ethernet	Gigabit ethernet port, Realtek RTL8111GN, Wake on LAN														
Manageability	None														
Modem	None														
Security chip	None														
Keyboard	Some: Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo Some: Lenovo® Slim USB Keyboard (USB connector), black, Lenovo logo														
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo														
Power supply	280 watts, universal, autosensing, 85% PSU														
Machine	<ul style="list-style-type: none"> Glossy black bezel; metal case 6.3" W X 15.7" D X 15.6" H (with handle) 160mm W X 400mm D X 397mm H 16.5 lb (7.5 kg) in maximum configuration Ergonomic rubberized handle Highlighted optical drive button for easy access 														
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 1.5", .35" high, access, optnl reader* Bay 4: 3.5", 1" high, no access, opt 2nd 2.5" disk** *bay only available on models with media reader installed **3.5" to 2.5" bracket comes with optional 2nd 2.5" disk														
Slot	Slot 1: half-length, full-height, PCI Express® 3.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x1											Security <ul style="list-style-type: none"> One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) Cable lock to physically lock both keyboard and mouse (optional) Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse Individual USB port disablement 			
Limited Warranty ¹	1-years or 3-year, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											EPEAT™ Silver; ENERGY STAR® 6.0 GREENGUARD® certified RoHS-compliant ErP Lot 3			
See footnotes for important warranty information											Supports ThinkVantage Technologies				

See footnotes for important warranty information

ThinkCentre E73 Tower (10DR) - ES 6.0 (TopSeller) - III

Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory ^o	SATA disk GB rpm	SATA optical	PCIe WLAN	Media reader	Graphics	Parallel port	Serial port	Keyboard / mouse	Cable lock	Warranty (year)	Preload	Ann date (mm/dd/yy)
10DR000T++	3x4	i3-4150	4GBx1	500G 7200	DVD±RW	None	Media	HD 4400	Parallel	Serial	USB(slim)	None	1-year	Win7 P64 DG Win8.1	07/08/14
10DR000U++	3x4	G3240	4GBx1	1TB 7200	DVD±RW	None	Media	Intel HD	Parallel	Serial	USB(slim)	None	1-year	Win7 P64 DG Win8.1	07/08/14
10DR000V++	3x4	G3240	4GBx1	500G 7200	DVD±RW	None	Media	Intel HD	Parallel	Serial	USB(slim)	None	1-year	Win7 P64 DG Win8.1	07/08/14
10DR0011++	3x4	i7-4790S	8GBx1	1TB 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB(slim)	None	1-year	Win7 P64 DG Win8.1	07/08/14
10DR0013++	3x4	i7-4790S	4GBx1	500G 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB(slim)	None	1-year	Win7 P64 DG Win8.1	07/08/14
10DR0017++	3x4	i7-4790S	8GBx1	1TB 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB	None	1-year	Win7 P64 DG Win8.1	07/08/14
10DR0018++	3x4	i5-4460S	8GBx1	1TB 7200	DVD±RW	None	Media	GT 620	Parallel	Serial	USB(slim)	None	1-year	Win7 P64 DG Win8.1	07/08/14
10DR0019++	3x4	i5-4460S	4GBx1	1TB 7200	DVD±RW	None	Media	GT 620	Parallel	Serial	USB(slim)	None	1-year	Win7 P64 DG Win8.1	07/08/14
10DR001A++	3x4	i5-4460S	4GBx1	1TB 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB(slim)	None	1-year	Win7 P64 DG Win8.1	07/08/14
10DR001B++	3x4	i3-4150	4GBx1	1TB 7200	DVD±RW	None	Media	HD 4400	Parallel	Serial	USB(slim)	None	1-year	Win7 P64 DG Win8.1	07/08/14

Positioning	<i>Stylish design, reliability, and productivity for small/medium businesses</i>											Preloaded operating system			
Processor	Intel® Pentium® G3240 Processor (2 cores / 2 threads, 3.1GHz, 3MB cache), Intel HD Graphics, 1333MHz DDR3 memory controller Intel Core™ i3-4150 Processor (2 cores / 4 threads, 3.5GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller Intel Core i5-4460S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.4GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i7-4790S Processor (4 cores / 8 threads, 3.2GHz, 8MB cache), Turbo Boost 2.0 (4.0GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Processor in LGA1150 socket											Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit Ready to install applications (only some listed) • Rescue and Recovery™ • Password Manager Preloaded applications (only some listed) • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Power Manager • ThinkVantage Device Experience • View Management Utility • Lenovo Cloud Storage by SugarSync • Lenovo Solution Center • Lenovo Message Center Plus • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ • Evernote® • Microsoft® Office preloaded; purchase a product key to activate • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) • Nitro Pro			
Implementation	Processor in LGA1150 socket														
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3* , two 240-pin DIMM sockets *System automatically clocks down for processors with 1333MHz memory controller														
Graphics	Intel HD Graphics or Intel HD Graphics 4400/4600 in processor, uses main memory, one VGA, one DisplayPort™, supports dual independent display, works along with discrete graphics to support up to four independent monitors; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz;</i> <i>1920x1200 (VGA)@60Hz (Reduced Blanking)</i> Some: NVIDIA® GeForce® GT 620 , DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express 2.0 x16 adapter, one VGA, one DisplayPort, 30 watts; <i>Max resolution: 2560x1600 (DisplayPort)@60Hz; 2048x1536 (VGA)@85Hz</i>														
DP dongle	None														
Disk	Some: SATA 6.0Gb/s, 3.5" Wide, 7200 rpm Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide														
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive														
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset														
Onboard SATA	SATA cables match SATA devices (each 1-drop to device), one SATA 3.0Gb/s connector (for optical) and two SATA 6.0Gb/s connectors (for HDD/SSD) on planar														
eSATA port	None														
Media reader	Optional 9-in-1 media reader, internal USB 2.0														
Chipset	Intel H81 Express Chipset														
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
Rear ports	Two USB 3.0, two USB 2.0, optional serial (9-pin)*, optional parallel (25-pin)*, ethernet (RJ-45), VGA DB-15, DisplayPort * Please see the detailed configuration on top														
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)														
PCIe WLAN	None														
Bluetooth	None														
Audio	High Definition (HD) Audio, Realtek® ALC662 codec														
Speaker	Internal speaker for business audio														
IEEE 1394	None														
Ethernet	Gigabit ethernet port, Realtek RTL8111GN, Wake on LAN														
Manageability	None														
Modem	None														
Security chip	None														
Keyboard	Some: Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo Some: Lenovo® Slim USB Keyboard (USB connector), black, Lenovo logo														
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo														
Power supply	280 watts, universal, autosensing, 85% PSU														
Machine	<ul style="list-style-type: none"> Glossy black bezel; metal case 6.3" W X 15.7" D X 15.6" H (with handle) 160mm W X 400mm D X 397mm H 16.5 lb (7.5 kg) in maximum configuration Ergonomic rubberized handle Highlighted optical drive button for easy access 														
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 1.5", .35" high, access, optnl reader* Bay 4: 3.5", 1" high, no access, opt 2nd 2.5" disk** *bay only available on models with media reader installed **3.5" to 2.5" bracket comes with optional 2nd 2.5" disk														
Slot	Slot 1: half-length, full-height, PCI Express® 3.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x1											Security <ul style="list-style-type: none"> One lock to secure both cover and entire system to fixed object: -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) Cable lock to physically lock both keyboard and mouse (optional) Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse Individual USB port disablement EPEAT™ Silver; ENERGY STAR® 6.0 GREENGUARD® certified RoHS-compliant ErP Lot 3			
Limited Warranty ¹	1-years or 3-year, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											Supports ThinkVantage Technologies			


See footnotes for important warranty information

©Lenovo
(G-TLS1T-9) July 2014

ThinkCentre E73 Tower (10DR) - ES 6.0 (TopSeller) - IV

Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	PCIe WLAN	Media reader	Graphics	Parallel port	Serial port	Keyboard / mouse	Cable lock	Warranty (year)	Preload	Ann date (mm/dd/yy)
10DR001C++	3x4	i7-4790S	4GBx1	500G 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB	None	1-year	Win7 P64 DG Win8.1	07/08/14
10DR001D++	3x4	i5-4460S	4GBx1	1TB 7200	DVD±RW	None	Media	GT 620	Parallel	Serial	USB	None	1-year	Win7 P64 DG Win8.1	07/08/14
10DR001E++	3x4	i5-4460S	4GBx1	500G 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB(slim)	None	1-year	Win7 P64 DG Win8.1	07/08/14
10DR001F++	3x4	i5-4460S	4GBx1	1TB 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB	None	1-year	Win7 P64 DG Win8.1	07/08/14
10DR001G++	3x4	i5-4460S	4GBx1	500G 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB	None	1-year	Win7 P64 DG Win8.1	07/08/14
10DR001H++	3x4	i3-4150	4GBx1	1TB 7200	DVD±RW	None	Media	HD 4400	Parallel	Serial	USB	None	1-year	Win7 P64 DG Win8.1	07/08/14
10DR001J++	3x4	i3-4150	4GBx1	500G 7200	DVD±RW	None	Media	HD 4400	Parallel	Serial	USB	None	1-year	Win7 P64 DG Win8.1	07/08/14
10DR001K++	3x4	G3240	4GBx1	1TB 7200	DVD±RW	None	Media	Intel HD	Parallel	Serial	USB	None	1-year	Win7 P64 DG Win8.1	07/08/14
10DR001L++	3x4	G3240	4GBx1	500G 7200	DVD±RW	None	Media	Intel HD	Parallel	Serial	USB	None	1-year	Win7 P64 DG Win8.1	07/08/14

Positioning	<i>Stylish design, reliability, and productivity for small/medium businesses</i>											Preloaded operating system			
Processor	Intel® Pentium® G3240 Processor (2 cores / 2 threads, 3.1GHz, 3MB cache), Intel HD Graphics, 1333MHz DDR3 memory controller Intel Core™ i3-4150 Processor (2 cores / 4 threads, 3.5GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller Intel Core i5-4460S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.4GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i7-4790S Processor (4 cores / 8 threads, 3.2GHz, 8MB cache), Turbo Boost 2.0 (4.0GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller											Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit Ready to install applications (only some listed) ● Rescue and Recovery™ ● Password Manager			
Implementation	Processor in LGA1150 socket											Preloaded applications (only some listed)			
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3* , two 240-pin DIMM sockets *System automatically clocks down for processors with 1333MHz memory controller											● ThinkVantage® Product Recovery ● ThinkVantage System Update ● ThinkVantage Communication Utility ● ThinkVantage Power Manager ● ThinkVantage Device Experience ● View Management Utility ● Lenovo Cloud Storage by SugarSync ● Lenovo Solution Center ● Lenovo Message Center Plus ● Norton™ Internet Security (30 days of virus definitions) ● Adobe® Reader® ● Skype™ ● Evernote® ● Microsoft® Office preloaded; purchase a product key to activate ● Cyberlink Power2Go (DVD±RW) ● Cyberlink PowerProducer (DVD±RW) ● Nitro Pro			
Graphics	Intel HD Graphics or Intel HD Graphics 4400/4600 in processor, uses main memory, one VGA, one DisplayPort™, supports dual independent display, works along with discrete graphics to support up to four independent monitors; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz;</i> 1920x1200 (VGA)@60Hz (Reduced Blanking) Some: NVIDIA® Geforce® GT 620 , DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express 2.0 x16 adapter, one VGA, one DisplayPort, 30 watts; <i>Max resolution: 2560x1600 (DisplayPort)@60Hz; 2048x1536 (VGA)@85Hz</i>														
DP dongle	None														
Disk	Some: SATA 6.0Gb/s, 3.5" Wide, 7200 rpm Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide														
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive														
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset														
Onboard SATA	SATA cables match SATA devices (each 1-drop to device), one SATA 3.0Gb/s connector (for optical) and two SATA 6.0Gb/s connectors (for HDD/SSD) on planar														
eSATA port	None														
Media reader	Optional 9-in-1 media reader, internal USB 2.0														
Chipset	Intel H81 Express Chipset														
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
Rear ports	Two USB 3.0, two USB 2.0, optional serial (9-pin)*, optional parallel (25-pin)*, ethernet (RJ-45), VGA DB-15, DisplayPort * Please see the detailed configuration on top														
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)														
PCIe WLAN	None														
Bluetooth	None														
Audio	High Definition (HD) Audio, Realtek® ALC662 codec														
Speaker	Internal speaker for business audio														
IEEE 1394	None														
Ethernet	Gigabit ethernet port, Realtek RTL8111GN, Wake on LAN														
Manageability	None														
Modem	None														
Security chip	None														
Keyboard	Some: Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo Some: Lenovo® Slim USB Keyboard (USB connector), black, Lenovo logo														
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo														
Power supply	280 watts, universal, autosensing, 85% PSU														
Machine	<ul style="list-style-type: none"> Glossy black bezel; metal case 6.3" W X 15.7" D X 15.6" H (with handle) 160mm W X 400mm D X 397mm H 16.5 lb (7.5 kg) in maximum configuration Ergonomic rubberized handle Highlighted optical drive button for easy access 														
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 1.5", .35" high, access, optnl reader* Bay 4: 3.5", 1" high, no access, opt 2nd 2.5" disk** *bay only available on models with media reader installed **3.5" to 2.5" bracket comes with optional 2nd 2.5" disk														
Slot	Slot 1: half-length, full-height, PCI Express® 3.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x1											Security ● One lock to secure both cover and entire system to fixed object: -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) ● Cable lock to physically lock both keyboard and mouse (optional) ● Power-on password ● Administrator password ● Hard disk password ● Boot sequence control ● Boot without keyboard and mouse ● Individual USB port disablement			
Limited Warranty ¹	1-years or 3-year, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											EPEAT™ Silver; ENERGY STAR® 6.0 GREENGUARD® certified RoHS-compliant ErP Lot 3 Supports ThinkVantage Technologies			

See footnotes for important warranty information

ThinkCentre E73 Tower (10DR) - TopSeller


Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	PCIe WLAN	Media reader	Graphics	Parallel port	Serial port	Keyboard / mouse	Global	Preload	Ann date (mm/dd/yy)
10DR000++	3x4	i3-4130	4GBx1	500G 7200	DVD±RW	None	Media	HD 4400	Parallel	Serial	USB	None	None	05/06/14
10DR0009++	3x4	i5-4440S	4GBx1	500G 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB	None	None	05/06/14
10DR000A++	3x4	G3220	4GBx1	500G 7200	DVD±RW	None	Media	Intel HD	Parallel	Serial	USB	None	None	05/06/14
10DR000B++	3x4	i5-4440S	4GBx1	500G 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB(slim)	None	None	05/06/14
10DR000J++	3x4	i3-4130	4GBx1	500G 7200	DVD±RW	None	Media	HD 4400	Parallel	Serial	USB(slim)	None	None	05/06/14
10DR000L++	3x4	i7-4770S	4GBx1	500G 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB	None	None	05/06/14
10DR000N++	3x4	i7-4770S	4GBx1	500G 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB(slim)	None	None	05/06/14
10DR000S++	3x4	G3220	4GBx1	500G 7200	DVD±RW	None	Media	Intel HD	Parallel	Serial	USB(slim)	None	None	05/06/14

Country Code^{9,10}: AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)
 Note: models listed above might not be available in all WE countries

- Small and medium business (SMB) model(s), part of the Westen Europe TopSeller™ Program
- 1-year limited warranty

Positioning	Stylish design, reliability, and productivity for small/medium businesses											Preloaded operating system		
Processor	Intel® Pentium® G3220 Processor (2 cores / 2 threads, 3.0GHz, 3MB cache), Intel HD Graphics, 1333MHz DDR3 memory controller Intel Core™ i3-4130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller Intel Core i5-4440S Processor (4 cores / 4 threads, 2.8GHz, 6MB cache), Turbo Boost 2.0 (3.3GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i7-4770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Processor in LGA1150 socket											No operating system		
Implementation	Processor in LGA1150 socket													
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3* , two 240-pin DIMM sockets *System automatically clocks down for processors with 1333MHz memory controller													
Graphics	Intel HD Graphics or Intel HD Graphics 4400/4600 in processor, uses main memory, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking)													
DP dongle	None													
Disk	Some: SATA 6.0Gb/s, 3.5" Wide, 7200 rpm													
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive													
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset													
Onboard SATA	SATA cables match SATA devices (each 1-drop to device), one SATA 3.0Gb/s connector (for optical) and two SATA 6.0Gb/s connectors (for HDD/SSD) on planar													
eSATA port	None													
Media reader	Optional 9-in-1 media reader, internal USB 2.0													
Chipset	Intel H81 Express Chipset													
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
Rear ports	Two USB 3.0, two USB 2.0, optional serial (9-pin)*, optional parallel (25-pin)*, ethernet (RJ-45), VGA DB-15, DisplayPort * Please see the detailed configuration on top													
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)													
PCIe WLAN	None													
Bluetooth	None													
Audio	High Definition (HD) Audio, Realtek® ALC662 codec													
Speaker	Internal speaker for business audio													
IEEE 1394	None													
Ethernet	Gigabit ethernet port, Realtek RTL8111GN, Wake on LAN													
Manageability	None													
Modem	None													
Security chip	None													
Keyboard	Some: Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo Some: Lenovo® Slim USB Keyboard (USB connector), black, Lenovo logo													
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Power supply	280 watts, universal, autosensing, 85% PSU													
Machine	<ul style="list-style-type: none"> ● Glossy black bezel; metal case ● 6.3" W X 15.7" D X 15.6" H (with handle) ● 160mm W X 400mm D X 397mm H ● 16.5 lb (7.5 kg) in maximum configuration ● Ergonomic rubberized handle ● Highlighted optical drive button for easy access 													
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 1.5", .35" high, access, optnl reader* Bay 4: 3.5", 1" high, no access, opt 2nd 2.5" disk** *bay only available on models with media reader installed **3.5" to 2.5" bracket comes with optional 2nd 2.5" disk													
Slot	Slot 1: half-length, full-height, PCI Express® 3.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x1													
Limited Warranty ¹	1-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available													
												Security <ul style="list-style-type: none"> ● One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) ● Power-on password ● Administrator password ● Hard disk password ● Boot sequence control ● Boot without keyboard and mouse ● Individual USB port disablement GREENGUARD® certified RoHS-compliant ErP Lot 3		
												Supports ThinkVantage Technologies		



See footnotes for important warranty information


ThinkCentre E73 Tower (10DR) - TopSeller - II

Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	PCIe WLAN	Media reader	Graphics	Parallel port	Serial port	Keyboard / mouse	Global	Preload	Ann date (mm/dd/yy)
10DR000W++	3x4	i7-4790S	4GBx1	500G 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB(slim)	None	None	06/24/14
10DR000X++	3x4	i5-4460S	4GBx1	500G 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB(slim)	None	None	06/24/14
10DR000Y++	3x4	i3-4150	4GBx1	500G 7200	DVD±RW	None	Media	HD 4400	Parallel	Serial	USB(slim)	None	None	06/24/14
10DR0010++	3x4	G3240	4GBx1	500G 7200	DVD±RW	None	Media	Intel HD	Parallel	Serial	USB(slim)	None	None	06/24/14
10DR0012++	3x4	G3240	4GBx1	500G 7200	DVD±RW	None	Media	Intel HD	Parallel	Serial	USB	None	None	06/24/14
10DR0014++	3x4	i3-4150	4GBx1	500G 7200	DVD±RW	None	Media	HD 4400	Parallel	Serial	USB	None	None	06/24/14
10DR0015++	3x4	i7-4790S	4GBx1	500G 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB	None	None	06/24/14
10DR0016++	3x4	i5-4460S	4GBx1	500G 7200	DVD±RW	None	Media	HD 4600	Parallel	Serial	USB	None	None	06/24/14

Country Code⁹++: AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)
 Note: models listed above might not be available in all WE countries

- Small and medium business (SMB) model(s), part of the Westen Europe TopSeller™ Program
- 1-year limited warranty

Positioning	Stylish design, reliability, and productivity for small/medium businesses											Preloaded operating system	
Processor	Intel® Pentium® G3240 Processor (2 cores / 2 threads, 3.1GHz, 3MB cache), Intel HD Graphics, 1333MHz DDR3 memory controller Intel Core™ i3-4150 Processor (2 cores / 4 threads, 3.5GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller Intel Core i5-4460S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.4GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i7-4790S Processor (4 cores / 8 threads, 3.2GHz, 8MB cache), Turbo Boost 2.0 (4.0GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller											No operating system	
Implementation	Processor in LGA1150 socket												
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3* , two 240-pin DIMM sockets *System automatically clocks down for processors with 1333MHz memory controller												
Graphics	Intel HD Graphics or Intel HD Graphics 4400/4600 in processor, uses main memory, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking)												
DP dongle	None												
Disk	Some: SATA 6.0Gb/s, 3.5" Wide, 7200 rpm												
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive												
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset												
Onboard SATA	SATA cables match SATA devices (each 1-drop to device), one SATA 3.0Gb/s connector (for optical) and two SATA 6.0Gb/s connectors (for HDD/SSD) on planar												
eSATA port	None												
Media reader	Optional 9-in-1 media reader, internal USB 2.0												
Chipset	Intel H81 Express Chipset												
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)												
Rear ports	Two USB 3.0, two USB 2.0, optional serial (9-pin)*, optional parallel (25-pin)*, ethernet (RJ-45), VGA DB-15, DisplayPort * Please see the detailed configuration on top												
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)												
PCIe WLAN	None												
Bluetooth	None												
Audio	High Definition (HD) Audio, Realtek® ALC662 codec												
Speaker	Internal speaker for business audio												
IEEE 1394	None												
Ethernet	Gigabit ethernet port, Realtek RTL8111GN, Wake on LAN												
Manageability	None												
Modem	None												
Security chip	None												
Keyboard	Some: Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo Some: Lenovo® Slim USB Keyboard (USB connector), black, Lenovo logo												
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo												
Power supply	280 watts, universal, autosensing, 85% PSU												
Machine	<ul style="list-style-type: none"> • Glossy black bezel; metal case • 6.3" W X 15.7" D X 15.6" H (with handle) • 160mm W X 400mm D X 397mm H • 16.5 lb (7.5 kg) in maximum configuration • Ergonomic rubberized handle • Highlighted optical drive button for easy access 												
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 1.5", .35" high, access, optnl reader* Bay 4: 3.5", 1" high, no access, opt 2nd 2.5" disk** *bay only available on models with media reader installed **3.5" to 2.5" bracket comes with optional 2nd 2.5" disk												
Slot	Slot 1: half-length, full-height, PCI Express® 3.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x1												
Limited Warranty ¹	1-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											Security <ul style="list-style-type: none"> • One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement GREENGUARD® certified RoHS-compliant ErP Lot 3	
Supports ThinkVantage Technologies													

See footnotes for important warranty information



ThinkCentre E93z with Frame Stand



ThinkCentre E93z with Monitor Stand



ThinkCentre E93z with Frame Stand



ThinkCentre E93z with Monitor Stand



ThinkCentre E93z with Frame Stand



ThinkCentre E93z with Monitor Stand

ThinkCentre E93z All-In-One II

ThinkCentre®



ThinkCentre E93z with UltraFlex Stand



ThinkCentre E93z with UltraFlex Stand



ThinkCentre E93z with UltraFlex Stand



ThinkCentre E93z with UltraFlex Stand with optional wireless mouse / keyboard and Lenovo ThinkVision Monitor



ThinkCentre E93z with UltraFlex Stand



ThinkCentre E93z (handle)

ThinkCentre E93z (10B8) - TopSeller

Product Specifications Reference (PSREF)

Type-model	Pro-processor	Memory ^a	Wide-screen display	Multi-Touch	Camera (mega-pixel)	Disk SATA GB rpm	SATA optical	Graphics	PCIe Mini Card	Media reader	Stand type	Key-board/Mouse Global	Preload	Ann date (mm/dd/yy)	
10B8003T++	i5-4430S	4GBx1	21.5" FHD	None	2.0M	500G Hybrid	DVD±RW	HD 4600	N2230	Media	Frame	2.4G	None	Win7 Pro64 DG	08/27/13
10B8003U++	i5-4430S	4GBx1	21.5" FHD	None	2.0M	128G SSD	DVD±RW	HD 4600	N2230	Media	Frame	2.4G	None	Win7 Pro64 DG	08/27/13
10B80043++	i3-4130	4GBx1	21.5" FHD	None	2.0M	500G Hybrid	DVD±RW	HD 4400	N2230	Media	Frame	2.4G	None	Win7 Pro64 DG	09/10/13
10B8007Q++	i3-4150	4GBx1	21.5" FHD	None	2.0M	1TB Hybrid	DVD±RW	HD 4400	7260 ac	Media	UltraFlex	2.4G	None	Win7 P64 DG Win8.1	07/15/14
10B8007R++	i5-4460S	4GBx1	21.5" FHD	None	2.0M	128G SSD	DVD±RW	HD 4600	7260 ac	Media	Frame	2.4G	None	Win7 P64 DG Win8.1	07/15/14
10B8007P++	i5-4460S	4GBx1	21.5" FHD	None	2.0M	500G Hybrid	DVD±RW	HD 4600	7260 ac	Media	UltraFlex	2.4G	None	Win7 P64 DG Win8.1	07/15/14

Country Code "++": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)

Note: models listed above might not be available in all WE countries

Positioning	<i>Premium All-In-One PC for the enterprise</i>	Preloaded operating system Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Ready to install applications (only some listed) ● Rescue and Recovery™ ● Password Manager Preloaded applications (only some listed) ● ThinkVantage® Product Recovery ● ThinkVantage System Update ● ThinkVantage Communication Utility ● ThinkVantage Device Experience ● ThinkVantage AutoLock ● Desktop Power Manager ● View Management Utility ● Lenovo Cloud Storage by SugarSync ● Lenovo Solution Center ● Lenovo Message Center Plus ● Norton™ Internet Security (30 days of virus definitions) ● Adobe® Reader® ● Skype™ ● Microsoft Office preloaded; purchase a product key to activate ● Cyberlink PowerDVD (DVD±RW, DVD) ● Cyberlink Power2Go (DVD±RW) ● Cyberlink PowerProducer (DVD±RW) ● Evernote ● Lenovo Solutions for Small Business ● Nitro Pro
Processor	Intel® Core™ i3-4130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller Intel Core i3-4150 Processor (2 cores / 4 threads, 3.5GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller Intel Core i5-4430S Processor (4 cores / 4 threads, 2.7GHz, 6MB cache), Turbo Boost 2.0 (3.2GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i5-4460S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.4GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Processor in LGA1150 socket	
Implementation		
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)	
Graphics	Intel HD Graphics 4400/4600 in processor, uses main memory, DirectX® 11.1, external digital monitor support via HDMI, supports dual independent display; Max resolution: 1920x1080 (panel) @60Hz; 1920x1200 (HDMI) @60Hz	
Display	21.5" (546.1mm) Full HD 1080p (1920x1080) TFT color , wide viewing angle (+/- 85°), LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, infinity display, work as standalone monitor via HDMI-in connector	
Light sensor	None	
Multi-touch	None	
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, supports 1080p, with dual array digital microphone, LED indicator, physical switch on/off	
Controls	Monitor mode / computer mode button, volume up/down buttons, and power button	
Disk	Some: 500GB (5400 rpm) or 1TB (7200 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 2.5" wide Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable	
Optical	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector and one SATA 3.0Gb/s connector on planar	
Onboard SATA	Optional 11-in-1 media card reader	
Media reader		
Chipset	Intel B85 Express Chipset	
Rear ports	Four USB 2.0, ethernet (RJ-45), HDMI-out, HDMI-in	
Side ports	Two USB 3.0 (one Always On USB 3.0), one headphone / microphone combo jack (stereo, 3.5mm), one optional media card reader	
PCIe Mini Card	Two PCI Express® Mini Card slots	
PCIe WLAN	Some: 11b/g/n wireless, Intel Centrino® Wireless-N 2230, Wi-Fi + BT4.0 combo, 2x2 Some: 11ac/a/b/g/n wireless, Intel Dual Band Wireless-AC 7260, Wi-Fi + BT4.0, 2x2	
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel Wi-Fi + Bluetooth combo adapter	
Ethernet	One gigabit ethernet port, Intel I217-V, Wake on LAN®	
Audio support	High Definition (HD) Audio, Realtek ALC283CG / two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified	
Intel AMT	None	
Security chip	None	
Keyboard	Ultraslim Plus Wireless Keyboard (2.4GHz via USB receiver), black	
Mouse	Ultraslim Plus Wireless Mouse (2.4GHz via USB receiver), black	
Power supply	150 watts, autosensing, 85% PSU	
Color	Business black color	
VESA mount	Support VESA mount (100mm)	
Dimensions and weight (without stand)	Non-touch models (WxDxH): 21.02" X 1.91" X 15.20"; 534mm X 48.5mm X 386 mm 14.55 lb (6.6 kg) in maximum configuration Touch models (WxDxH): 21.02" X 1.95" X 15.20"; 534mm X 49.6mm X 386 mm 16.31 lb (7.4 kg) in maximum configuration	
Stand	Optional Frame Stand: Adjustable between 10° and 65° (Tilt) Optional Monitor Stand: Adjustable between -5° and 45° (Tilt) Optional UltraFlex Stand: Tilt: 65° back, 0° forward; Lift: 110mm; Swivel: +/-90°; supports recline mode (from an upright position to an angled plane) and cable management	
Limited Warranty	1-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available	
		Security ● Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) ● Power-on password ● Administrator password ● Hard disk password ● Boot sequence control ● Boot without keyboard and mouse ● Individual USB port disablement ENERGY STAR® 6.0-compliant EuP 2013 GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies

See footnotes for important warranty information

©Lenovo
(G-TRPL1-1) July 2014

ThinkCentre E93z (10B8) - TopSeller (3-year Onsite)

Product Specifications Reference (PSREF)

Type-model	Pro-processor	Memory ⁸	Wide-screen display	Multi-Touch	Camera (mega-pixel)	Disk SATA GB rpm	SATA optical	Graphics	PCIe Mini Card WLAN	Media reader	Stand type	Key-board/Mouse	Preload	Ann date (mm/dd/yy)
10B80053++	i3-4130	4GBx1	21.5" FHD	None	2.0M	500G Hybrid	DVD±RW	HD 4400	N2230	Media	Monitor	USB(slim)	Win7 Pro64	DG 09/24/13

Country Code"+": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)
 Note: models listed above might not be available in all WE countries

- Small and medium business (SMB) model(s), part of the Western Europe TopSeller™ Program
- 3-year limited warranty

Positioning	<i>Premium All-In-One PC for the enterprise</i>											Preloaded operating system
Processor	Intel® Core™ i3-4130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller											Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit
Implementation	Processor in LGA1150 socket											Ready to install applications (only some listed)
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)											<ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager
Graphics	Intel HD Graphics 4400/4600 in processor, uses main memory, DirectX® 11.1, external digital monitor support via HDMI, supports dual independent display; <i>Max resolution: 1920x1080 (panel) @60Hz; 1920x1080 (HDMI) @60Hz</i>											Preloaded applications (only some listed)
Display	21.5" (546.1mm) Full HD 1080p (1920x1080) TFT color , wide viewing angle (+/- 85°), LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, infinity display, work as standalone monitor via HDMI-in connector											<ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Device Experience • ThinkVantage AutoLock • Desktop Power Manager • View Management Utility • Lenovo Cloud Storage by SugarSync • Lenovo Solution Center • Lenovo Message Center Plus • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ • Microsoft Office preloaded; purchase a product key to activate • Cyberlink PowerDVD (DVD±RW, DVD) • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) • Evernote • Lenovo Solutions for Small Business • Nitro Pro
Light sensor	None											
Multi-touch	None											
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, supports 1080p, with dual array digital microphone, LED indicator, physical switch on/off											
Controls	Monitor mode / computer mode button, volume up/down buttons, and power button											
Disk	<i>Some:</i> 500GB (5400 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 2.5" wide											
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable											
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector and one SATA 3.0Gb/s connector on planar											
Media reader	Optional 11-in-1 media card reader											
Chipset	Intel B85 Express Chipset											
Rear ports	Four USB 2.0, ethernet (RJ-45), HDMI-out, HDMI-in											
Side ports	Two USB 3.0 (one Always On USB 3.0), one headphone / microphone combo jack (stereo, 3.5mm), one optional media card reader											
PCIe Mini Card	Two PCI Express® Mini Card slots											
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2											
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel Wi-Fi + Bluetooth combo adapter											
Ethernet	One gigabit ethernet port, Intel I217-V, Wake on LAN®											
Audio support	High Definition (HD) Audio, Realtek ALC283CG / two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified											
Intel AMT	None											
Security chip	None											
Keyboard	Lenovo® Slim New F5 USB Keyboard (USB connector), black											
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo											
Power supply	150 watts, autosensing, 85% PSU											
Color	Business black color											
VESA mount	Support VESA mount (100mm)											
Dimensions and weight (without stand)	<i>Non-touch models (WxDxH):</i> 21.02" X 1.91" X 15.20"; 534mm X 48.5mm X 386 mm 14.55 lb (6.6 kg) in maximum configuration <i>Touch models (WxDxH):</i> 21.02" X 1.95" X 15.20"; 534mm X 49.6mm X 386 mm 16.31 lb (7.4 kg) in maximum configuration											Security
Stand	<i>Optional Frame Stand:</i> Adjustable between 10° and 65° (Tilt) <i>Optional Monitor Stand:</i> Adjustable between -5° and 45° (Tilt) <i>Optional UltraFlex Stand:</i> Tilt: 65° back, 0° forward; Lift: 110mm; Swivel: +/-90°; supports recline mode (from an upright position to an angled plane) and cable management											<ul style="list-style-type: none"> • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											ENERGY STAR® 6.0-compliant EuP 2013 GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies

See footnotes for important warranty information
 WE model(s) announced September 24, 2013

©Lenovo
 (G-TRPL1-6) September 2013

ThinkCentre E93z (10B8) - TopSeller (3-year Onsite) - Win8

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ^a	Wide-screen display	Multi-Touch	Camera (mega-pixel)	Disk SATA GB rpm	SATA optical	Graphics	PCIe Mini Card WLAN	Media reader	Stand type	Key-board/Mouse	Preload	Ann date (mm/dd/yy)
10B80048++	G3420	4GBx1	21.5" FHD	None	2.0M	500G Hybrid	DVD±RW	Intel HD	N2230	Media	Frame	USB	Win8 Pro64	09/24/13
10B80049++	i3-4130	4GBx1	21.5" FHD	None	2.0M	500G Hybrid	DVD±RW	HD 4400	N2230	Media	UltraFlex	USB	Win8 64	09/24/13

Country Code"+": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)

Note: models listed above might not be available in all WE countries

- Small and medium business (SMB) model(s), part of the Western Europe TopSeller™ Program
- 3-year limited warranty

Positioning	<i>Premium All-In-One PC for the enterprise</i>										Preloaded operating system		
Processor	Intel® Pentium® G3420 Processor (2 cores / 2 threads, 3.2GHz, 3MB cache), Intel HD Graphics, 1600MHz DDR3 memory controller Intel Core™ i3-4130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller										Some: Windows® 8 64-bit Some: Windows® 8 Pro 64-bit		
Implementation	Processor in LGA1150 socket										Web install applications (only some listed)		
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)										<ul style="list-style-type: none"> • Password Manager 		
Graphics	Intel HD Graphics or Intel HD Graphics 4400/4600 in processor, uses main memory, external digital monitor support via HDMI, supports dual independent display; <i>Max resolution: 1920x1080 (panel)@60Hz; 1920x1080 (HDMI)@60Hz</i>										Preloaded applications (only some listed)		
Display	21.5" (546.1mm) Full HD 1080p (1920x1080) TFT color , wide viewing angle (+/- 85°), LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, infinity display, work as standalone monitor via HDMI-in connector										<ul style="list-style-type: none"> • ThinkVantage System Update • ThinkVantage AutoLock • Desktop Power Manager • View Management Utility • Lenovo Cloud Storage by SugarSync • Lenovo Solution Center • Lenovo Support • Lenovo Companion • Norton Internet Security (30 days of virus definitions) • Skype™ 		
Light sensor	None										<ul style="list-style-type: none"> • Microsoft Office preloaded; purchase a product key to activate • Cyberlink PowerDVD (DVD±RW, DVD) • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) • Evernote® • Lenovo Solutions for Small Business • Nitro Pro • AccuWeather • Norton™ Studio 		
Multi-touch	None												
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, supports 1080p, with dual array digital microphone, LED indicator, physical switch on/off												
Controls	Monitor mode / computer mode button, volume up/down buttons, and power button												
Disk	Some: 500GB (5400 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 2.5" wide												
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable												
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector and one SATA 3.0Gb/s connector on planar												
Media reader	Optional 11-in-1 media card reader												
Chipset	Intel B85 Express Chipset												
Rear ports	Four USB 2.0, ethernet (RJ-45), HDMI-out, HDMI-in												
Side ports	Two USB 3.0 (one Always On USB 3.0), one headphone / microphone combo jack (stereo, 3.5mm), one optional media card reader												
PCIe Mini Card	Two PCI Express® Mini Card slots												
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2												
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel Wi-Fi + Bluetooth combo adapter												
Ethernet	One gigabit ethernet port, Intel I217-V, Wake on LAN®												
Audio support	High Definition (HD) Audio, Realtek ALC283CG / two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified												
Intel AMT	None												
Security chip	None												
Keyboard	Preferred Pro USB Keyboard (USB connector), Lenovo® logo												
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo												
Power supply	150 watts, autosensing, 85% PSU												
Color	Business black color										Security		
VESA mount	Support VESA mount (100mm)										<ul style="list-style-type: none"> • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement 		
Dimensions and weight (without stand)	<i>Non-touch models (WxDxH):</i> 21.02" X 1.91" X 15.20"; 534mm X 48.5mm X 386 mm 14.55 lb (6.6 kg) in maximum configuration <i>Touch models (WxDxH):</i> 21.02" X 1.95" X 15.20"; 534mm X 49.6mm X 386 mm 16.31 lb (7.4 kg) in maximum configuration												
Stand	<i>Optional Frame Stand:</i> Adjustable between 10° and 65° (Tilt) <i>Optional Monitor Stand:</i> Adjustable between -5° and 45° (Tilt) <i>Optional UltraFlex Stand:</i> Tilt: 65° back, 0° forward; Lift: 110mm; Swivel: +/-90°; supports recline mode (from an upright position to an angled plane) and cable management										ENERGY STAR® 6.0-compliant		
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available										EuP 2013		
											GREENGUARD® certified		
											RoHS-compliant		
											Supports ThinkVantage Technologies		

See footnotes for important warranty information
 WE model(s) announced September 24, 2013

©Lenovo
 (G-TRPL1-7) September 2013

ThinkCentre E93z (10B9) - NVIDIA (TopSeller)

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ⁸	Wide-screen display	Multi-Touch	Camera (mega-pixel)	Disk SATA GB rpm	SATA optical	Graphics	PCIe Mini Card	Media reader	Stand type	Key-board/Mouse Global	Preload	Ann date (mm/dd/yy)
10B9000X++	i5-4430S	4GBx1	21.5" FHD	None	2.0M	500G Hybrid	DVD±RW	GT 720A	N2230	Media	Monitor	2.4G	None	Win7 Pro64 DG 08/27/13
10B90013++	i3-4130	4GBx1	21.5" FHD	None	2.0M	500G Hybrid	DVD±RW	GT 720A	N2230	Media	Frame	2.4G	None	Win7 Pro64 DG 09/10/13

Country Code"++": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)

Note: models listed above might not be available in all WE countries

- Small and medium business (SMB) model(s), part of the Westen Europe TopSeller™ Program
- 1-year limited warranty

Positioning	<i>Premium All-In-One PC for the enterprise</i>										
Processor	Intel® Core™ i3-4130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller Intel Core i5-4430S Processor (4 cores / 4 threads, 2.7GHz, 6MB cache), Turbo Boost 2.0 (3.2GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller										
Implementation	Processor in LGA1150 socket										
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)										
Graphics	NVIDIA® Optimus™ technology, auto-switch between discrete and integrated graphics, Intel HD Graphics 4400/4600 in processor, and NVIDIA GeForce® GT 720A , PCI Express® x16, 1GB memory, DirectX® 11, external digital monitor support via HDMI, supports dual independent display; <i>Max resolution: 1920x1080 (panel)@60Hz; 1920x1080 (HDMI)@60Hz</i>										
Display	21.5" (546.1mm) Full HD 1080p (1920x1080) TFT color , wide viewing angle (+/- 85°), LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, infinity display, work as standalone monitor via HDMI-in connector										
Light sensor	None										
Multi-touch	None										
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, supports 1080p, with dual array digital microphone, LED indicator, physical switch on/off										
Controls	Monitor mode / computer mode button, volume up/down buttons, and power button										
Disk	500GB (5400 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 2.5" wide										
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable										
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector and one SATA 3.0Gb/s connector on planar										
Media reader	Optional 11-in-1 media card reader										
Chipset	Intel B85 Express Chipset										
Rear ports	Four USB 2.0, ethernet (RJ-45), HDMI-out, HDMI-in										
Side ports	Two USB 3.0 (one Always On USB 3.0), one headphone / microphone combo jack (stereo, 3.5mm), one optional media card reader										
PCIe Mini Card	Two PCI Express® Mini Card slots										
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2										
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel Wi-Fi + Bluetooth combo adapter										
Ethernet	One gigabit ethernet port, Intel I217-V, Wake on LAN®										
Audio support	High Definition (HD) Audio, Realtek ALC283CG / two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified										
Intel AMT Security chip	None										
Keyboard	Ultraslim Plus Wireless Keyboard (2.4GHz via USB receiver), black										
Mouse	Ultraslim Plus Wireless Mouse (2.4GHz via USB receiver), black										
Power supply	180 watts, autosensing, 92% PSU										
Color	Business black color										
VESA mount	Support VESA mount (100mm)										
Dimensions and weight (without stand)	<i>Non-touch models (WxDxH):</i> 21.02" X 1.91" X 15.20"; 534mm X 48.5mm X 386 mm										
	<i>Touch models (WxDxH):</i> 21.02" X 1.95" X 15.20"; 534mm X 49.6mm X 386 mm										
Stand	<i>Optional Frame Stand:</i> Adjustable between 10° and 65° (Tilt)										
	<i>Optional Monitor Stand:</i> Adjustable between -5° and 45° (Tilt)										
	<i>Optional UltraFlex Stand:</i> Tilt: 65° back, 0° forward; Lift: 110mm; Swivel: +/-90°; supports recline mode (from an upright position to an angled plane) and cable management										
Limited Warranty	1-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available										
	Preloaded operating system Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Ready to install applications (only some listed) • Rescue and Recovery™ • Password Manager Preloaded applications (only some listed) • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Device Experience • ThinkVantage AutoLock • Desktop Power Manager • View Management Utility • Lenovo Cloud Storage by SugarSync • Lenovo Solution Center • Lenovo Message Center Plus • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ • Microsoft Office preloaded; purchase a product key to activate • Cyberlink PowerDVD (DVD±RW, DVD) • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) • Evernote • Lenovo Solutions for Small Business • Nitro Pro										
	Security • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement ENERGY STAR® 6.0-compliant EuP 2013 GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies										

See footnotes for important warranty information
WE model(s) announced August 27, 2013 or September 10, 2013

©Lenovo
(G-TRPL1-2) September 2013

ThinkCentre E93z (10B9) - NVIDIA (TopSeller) - 3-year (Win8)

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ⁸	Wide-screen display	Multi-Touch	Camera (mega-pixel)	Disk SATA GB rpm	SATA optical	Graphics	PCIe Mini Card WLAN	Media reader	Stand type	Key-board/Mouse Global	Preload	Ann date (mm/dd/yy)	
10B90015++	i3-4130	4GBx1	21.5" FHD	None	2.0M	500G Hybrid	DVD±RW	GT 720A	N2230	Media	UltraFlex	USB	None	Win8 64	09/24/13

Country Code "++": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)
 Note: models listed above might not be available in all WE countries

- Small and medium business (SMB) model(s), part of the Westen Europe TopSeller™ Program
- 3-year limited warranty

Positioning	<i>Premium All-In-One PC for the enterprise</i>											Preloaded operating system
Processor	Intel® Core™ i3-4130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller											Windows® 8 64-bit
Implementation	Processor in LGA1150 socket											Web install applications (only some listed)
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)											<ul style="list-style-type: none"> • Password Manager
Graphics	NVIDIA® Optimus™ technology, auto-switch between discrete and integrated graphics, Intel HD Graphics 4400/4600 in processor, and NVIDIA GeForce® GT 720A, PCI Express® x16, 1GB memory, DirectX® 11, external digital monitor support via HDMI, supports dual independent display; Max resolution: 1920x1080 (panel)@60Hz; 1920x1080 (HDMI)@60Hz											Preloaded applications (only some listed)
Display	21.5" (546.1mm) Full HD (1920x1080) TFT color, wide viewing angle (+/- 85°), LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, infinity display, work as standalone monitor via HDMI-in connector											<ul style="list-style-type: none"> • ThinkVantage System Update • ThinkVantage AutoLock • Desktop Power Manager • View Management Utility • Lenovo Cloud Storage by SugarSync • Lenovo Solution Center • Lenovo Support • Lenovo Companion • Norton Internet Security (30 days of virus definitions) • Skype™ • Microsoft Office preloaded; purchase a product key to activate • Cyberlink PowerDVD (DVD±RW, DVD) • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) • Evernote® • Lenovo Solutions for Small Business • Nitro Pro • AccuWeather • Norton™ Studio
Light sensor	None											
Multi-touch	None											
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, supports 1080p, with dual array digital microphone, LED indicator, physical switch on/off											
Controls	Monitor mode / computer mode button, volume up/down buttons, and power button											
Disk	500GB (5400 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 2.5" wide											
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable											
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector and one SATA 3.0Gb/s connector on planar											
Media reader	Optional 11-in-1 media card reader											
Chipset	Intel B85 Express Chipset											
Rear ports	Four USB 2.0, ethernet (RJ-45), HDMI-out, HDMI-in											
Side ports	Two USB 3.0 (one Always On USB 3.0), one headphone / microphone combo jack (stereo, 3.5mm), one optional media card reader											
PCIe Mini Card	Two PCI Express® Mini Card slots											
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2											
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel Wi-Fi + Bluetooth combo adapter											
Ethernet	One gigabit ethernet port, Intel I217-V, Wake on LAN®											
Audio support	High Definition (HD) Audio, Realtek ALC283CG / two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified											
Intel AMT	None											
Security chip	None											
Keyboard	Preferred Pro USB Keyboard (USB connector), Lenovo® logo											
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo											
Power supply	180 watts, autosensing, 92% PSU											
Color	Business black color											
VESA mount	Support VESA mount (100mm)											Security
Dimensions and weight (without stand)	<i>Non-touch models (WxDxH):</i> 21.02" X 1.91" X 15.20"; 534mm X 48.5mm X 386 mm 14.55 lb (6.6 kg) in maximum configuration <i>Touch models (WxDxH):</i> 21.02" X 1.95" X 15.20"; 534mm X 49.6mm X 386 mm 16.31 lb (7.4 kg) in maximum configuration											<ul style="list-style-type: none"> • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement
Stand	<i>Optional Frame Stand:</i> Adjustable between 10° and 65° (Tilt) <i>Optional Monitor Stand:</i> Adjustable between -5° and 45° (Tilt) <i>Optional UltraFlex Stand:</i> Tilt: 65° back, 0° forward; Lift: 110mm; Swivel: +/-90°; supports recline mode (from an upright position to an angled plane) and cable management											ENERGY STAR® 6.0-compliant
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											EuP 2013
												GREENGUARD® certified
												RoHS-compliant
												Supports ThinkVantage Technologies

See footnotes for important warranty information
 WE model(s) announced September 24, 2013

©Lenovo
 (G-TRPL1-8) October 2013

ThinkCentre E93z (10CX) - Touch (TopSeller) - Windows 8.1

Product Specifications Reference (PSREF)

Type-model	Processor	Memory ⁸	Wide-screen display	Multi-Touch	Camera (mega-pixel)	Disk SATA GB rpm	SATA optical	Graphics	PCIe Mini Card WLAN	Media reader	Stand type	Key-board/Mouse	Warranty (Year)	Preload	Ann date (mm/dd/yy)
10CX001G++	i3-4150	4GBx1	21.5" FHD	Touch	2.0M	500G Hybrid	DVD±RW	HD 4400	7260 b/g/n	Media	Frame	2.4G	1-onsite	Win8.1 Pro64	07/15/14
10CX001H++	i5-4460S	4GBx1	21.5" FHD	Touch	2.0M	500G Hybrid	DVD±RW	HD 4600	7260 b/g/n	Media	UltraFlex	2.4G	1-onsite	Win8.1 Pro64	07/15/14

Country Code"++": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)

Note: models listed above might not be available in all WE countries

- Small and medium business (SMB) model(s), part of the Western Europe TopSeller™ Program
- 1-year limited warranty

Positioning	<i>Premium All-In-One PC for the enterprise</i>	Preloaded operating system <i>Some:</i> Windows® 8.1 64-bit <i>Some:</i> Windows® 8.1 Pro 64-bit
Processor	Intel® Core™ i3-4150 Processor (2 cores / 4 threads, 3.5GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller Intel Core i5-4460S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.4GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Processor in LGA1150 socket	
Implementation		Web install applications (only some listed) • Password Manager
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)	
Graphics	Intel HD Graphics 4400/4600 in processor, uses main memory, DirectX® 11.1, external digital monitor support via HDMI, supports dual independent display; <i>Max resolution:</i> 1920x1080 (panel)@60Hz; 1920x1080 (HDMI)@60Hz	Preloaded applications (only some listed) • ThinkVantage System Update • ThinkVantage AutoLock • Desktop Power Manager • View Management Utility • Lenovo Cloud Storage by SugarSync • Lenovo Solution Center • Lenovo Support • Lenovo Companion • Norton Internet Security (30 days of virus definitions) • Skype™ • Microsoft Office preloaded; purchase a product key to activate • Cyberlink PowerDVD (DVD±RW, DVD) • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) • Evernote® • Lenovo Solutions for Small Business • Nitro Pro • AccuWeather • Norton™ Studio
Display	21.5" (546.1mm) Full HD 1080p (1920x1080) TFT color , wide viewing angle (+/- 85°), LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, infinity display, work as standalone monitor via HDMI-in connector	
Light sensor	None	
Multi-touch	Projected Capacitive Touch (PCT) technology, supports 10-point multi-touch	
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, supports 1080p, with dual array digital microphone, LED indicator, physical switch on/off	
Controls	Monitor mode / computer mode button, volume up/down buttons, and power button	
Disk	<i>Some:</i> 500GB (5400 rpm) or 1TB (7200 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 2.5" wide <i>Some:</i> Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide	
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable	
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector and one SATA 3.0Gb/s connector on planar	
Media reader	Optional 11-in-1 media card reader	
Chipset	Intel B85 Express Chipset	
Rear ports	Four USB 2.0, ethernet (RJ-45), HDMI-out, HDMI-in	
Side ports	Two USB 3.0 (one Always On USB 3.0), one headphone / microphone combo jack (stereo, 3.5mm), one optional media card reader	
PCIe Mini Card	Two PCI Express® Mini Card slots	
PCIe WLAN	<i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Intel Wireless-N 7260, Wi-Fi + Bluetooth combo adapter, 2x2 <i>Some:</i> 11ac/a/b/g/n wireless, PCIe Half Mini Card, Intel Dual Band Wireless-AC 7260, Wi-Fi + Bluetooth combo adapter, 2x2	
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel Wi-Fi + Bluetooth combo adapter	
Ethernet	One gigabit ethernet port, Intel I217-V, Wake on LAN®	
Audio support	High Definition (HD) Audio, Realtek ALC283CG / two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified	
Intel AMT	None	
Security chip	None	
Keyboard	Ultraslim Plus Wireless Keyboard (2.4GHz via USB receiver), black	
Mouse	Ultraslim Plus Wireless Mouse (2.4GHz via USB receiver), black	
Power supply	150 watts, autosensing, 85% PSU	
Color	Business black color	
VESA mount	Support VESA mount (100mm)	
Dimensions and weight (without stand)	<i>Non-touch models (WxDxH):</i> 21.02" X 1.91" X 15.20"; 534mm X 48.5mm X 386 mm 14.55 lb (6.6 kg) in maximum configuration <i>Touch models (WxDxH):</i> 21.02" X 1.95" X 15.20"; 534mm X 49.6mm X 386 mm 16.31 lb (7.4 kg) in maximum configuration	
Stand	<i>Optional Frame Stand:</i> Adjustable between 10° and 65° (Tilt) <i>Optional Monitor Stand:</i> Adjustable between -5° and 45° (Tilt) <i>Optional UltraFlex Stand:</i> Tilt: 65° back, 0° forward; Lift: 110mm; Swivel: +/-90°; supports recline mode (from an upright position to an angled plane) and cable management	
Limited Warranty	1-year or 3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available	
		Security • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement ENERGY STAR® 6.0-compliant EuP 2013 GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies

See footnotes for important warranty information

©Lenovo
(G-TRPL1-12) August 2014

ThinkCentre E93z (10BA) - Touch (NVIDIA) - TopSeller

Product Specifications Reference (PSREF)

Type-model	Pro-processor	Memory ⁸	Wide-screen display	Multi-Touch	Camera (mega-pixel)	Disk SATA GB rpm	SATA optical	Graphics	PCIe Mini Card WLAN	Media reader	Stand type	Key-board/Mouse Global	Preload	Ann date (mm/dd/yy)
10BA002L++	i5-4430S	4GBx1	21.5" FHD	Touch	2.0M	500G Hybrid	DVD±RW	GT 720A	N2230	Media	UltraFlex	2.4G	None	Win7 Pro64 DG 09/10/13

Country Code"+": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)
 Note: models listed above might not be available in all WE countries

- Small and medium business (SMB) model(s), part of the Westen Europe TopSeller™ Program
- 1-year limited warranty

Positioning	<i>Premium All-In-One PC for the enterprise</i>										
Processor	Intel® Core™ i5-4430S Processor (4 cores / 4 threads, 2.7GHz, 6MB cache), Turbo Boost 2.0 (3.2GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller										
Implementation	Processor in LGA1150 socket										
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)										
Graphics	NVIDIA® Optimus™ technology, auto-switch between discrete and integrated graphics, Intel HD Graphics 4400/4600 in processor, and NVIDIA GeForce® GT 720A , PCI Express® x16, 1GB memory, DirectX® 11, external digital monitor support via HDMI, supports dual independent display; <i>Max resolution: 1920x1080 (panel)@60Hz; 1920x1080 (HDMI)@60Hz</i>										
Display	21.5" (546.1mm) Full HD 1080p (1920x1080) TFT color , wide viewing angle (+/- 85°), LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, infinity display, work as standalone monitor via HDMI-in connector										
Light sensor	None										
Multi-touch	Projected Capacitive Touch (PCT) technology, supports 10-point multi-touch										
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, supports 1080p, with dual array digital microphone, LED indicator, physical switch on/off										
Controls	Monitor mode / computer mode button, volume up/down buttons, and power button										
Disk	500GB (5400 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 2.5" wide										
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable										
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector and one SATA 3.0Gb/s connector on planar										
Media reader	Optional 11-in-1 media card reader										
Chipset	Intel B85 Express Chipset										
Rear ports	Four USB 2.0, ethernet (RJ-45), HDMI-out, HDMI-in										
Side ports	Two USB 3.0 (one Always On USB 3.0), one headphone / microphone combo jack (stereo, 3.5mm), one optional media card reader										
PCIe Mini Card	Two PCI Express® Mini Card slots										
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2										
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel Wi-Fi + Bluetooth combo adapter										
Ethernet	One gigabit ethernet port, Intel I217-V, Wake on LAN®										
Audio support	High Definition (HD) Audio, Realtek ALC283CG / two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified										
Intel AMT	None										
Security chip	None										
Keyboard	Ultraslim Plus Wireless Keyboard (2.4GHz via USB receiver), black										
Mouse	Ultraslim Plus Wireless Mouse (2.4GHz via USB receiver), black										
Power supply	180 watts, autosensing, 92% PSU										
Color	Business black color										
VESA mount	Support VESA mount (100mm)										
Dimensions and weight (without stand)	<i>Non-touch models (WxDxH):</i> 21.02" X 1.91" X 15.20"; 534mm X 48.5mm X 386 mm										
	<i>Touch models (WxDxH):</i> 21.02" X 1.95" X 15.20"; 534mm X 49.6mm X 386 mm										
Stand	<i>Optional Frame Stand:</i> Adjustable between 10° and 65° (Tilt)										
	<i>Optional Monitor Stand:</i> Adjustable between -5° and 45° (Tilt)										
	<i>Optional UltraFlex Stand:</i> Tilt: 65° back, 0° forward; Lift: 110mm; Swivel: +/-90°; supports recline mode (from an upright position to an angled plane) and cable management										
Limited Warranty	1-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available										
Preloaded operating system Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Ready to install applications (only some listed) • Rescue and Recovery™ • Password Manager Preloaded applications (only some listed) • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Device Experience • ThinkVantage AutoLock • Desktop Power Manager • View Management Utility • Lenovo Cloud Storage by SugarSync • Lenovo Solution Center • Lenovo Message Center Plus • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ • Microsoft Office preloaded; purchase a product key to activate • Cyberlink PowerDVD (DVD±RW, DVD) • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) • Evernote • Lenovo Solutions for Small Business • Nitro Pro											
Security • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement ENERGY STAR® 6.0-compliant EuP 2013 GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies											

See footnotes for important warranty information
 WE model(s) announced September 10, 2013

©Lenovo
 (G-TRPL1-3) September 2013

ThinkCentre E93z (10BA) - Touch (NVIDIA) - TopSeller (3-year)

Product Specifications Reference (PSREF)

Type-model	Processor	Memory	Wide-screen display	Multi-Touch	Camera (mega-pixel)	Disk SATA GB rpm	SATA optical	Graphics	PCIe Mini Card WLAN	Media reader	Stand type	Key-board/Mouse Global	Preload	Ann date (mm/dd/yy)
10BA003M++	i5-4430S	4GBx1	21.5" FHD	Touch	2.0M	128G SSD	DVD±RW	GT 720A	N2230	Media	UltraFlex	2.4G None	Win7 Pro64 DG	10/22/13
10BA0091++	i5-4460S	4GBx1	21.5" FHD	Touch	2.0M	128G SSD	DVD±RW	GT 720A	7260 b/g/n	Media	UltraFlex	2.4G None	Win7 P64 DG Win 8.1	07/15/14

Country Code"+": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)
 Note: models listed above might not be available in all WE countries

- Small and medium business (SMB) model(s), part of the Western Europe TopSeller™ Program
- 3-year limited warranty

Positioning	<i>Premium All-In-One PC for the enterprise</i>											Preloaded operating system
Processor	Intel® Core™ i5-4430S Processor (4 cores / 4 threads, 2.7GHz, 6MB cache), Turbo Boost 2.0 (3.2GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Intel Core i5-4460S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.4GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Processor in LGA1150 socket											Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit
Implementation	NVIDIA® Optimus™ technology, auto-switch between discrete and integrated graphics, Intel HD Graphics 4400/4600 in processor, and NVIDIA GeForce® GT 720A, PCI Express® x16, 1GB memory, DirectX® 11, external digital monitor support via HDMI, supports dual independent display; Max resolution: 1920x1080 (panel)@60Hz; 1920x1080 (HDMI)@60Hz											Ready to install applications (only some listed)
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)											<ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager
Graphics	NVIDIA® Optimus™ technology, auto-switch between discrete and integrated graphics, Intel HD Graphics 4400/4600 in processor, and NVIDIA GeForce® GT 720A, PCI Express® x16, 1GB memory, DirectX® 11, external digital monitor support via HDMI, supports dual independent display; Max resolution: 1920x1080 (panel)@60Hz; 1920x1080 (HDMI)@60Hz											Preloaded applications (only some listed)
Display	21.5" (546.1mm) Full HD 1080p (1920x1080) TFT color , wide viewing angle (+/- 85°), LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, infinity display, work as standalone monitor via HDMI-in connector											<ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Device Experience • ThinkVantage AutoLock • Desktop Power Manager • View Management Utility • Lenovo Cloud Storage by SugarSync • Lenovo Solution Center • Lenovo Message Center Plus • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ • Microsoft Office preloaded; purchase a product key to activate • Cyberlink PowerDVD (DVD±RW, DVD) • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) • Evernote • Lenovo Solutions for Small Business • Nitro Pro
Light sensor	None											
Multi-touch	Projected Capacitive Touch (PCT) technology, supports 10-point multi-touch											
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, supports 1080p, with dual array digital microphone, LED indicator, physical switch on/off											
Controls	Monitor mode / computer mode button, volume up/down buttons, and power button											
Disk	Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide											
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable											
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector and one SATA 3.0Gb/s connector on planar											
Media reader	Optional 11-in-1 media card reader											
Chipset	Intel B85 Express Chipset											
Rear ports	Four USB 2.0, ethernet (RJ-45), HDMI-out, HDMI-in											
Side ports	Two USB 3.0 (one Always On USB 3.0), one headphone / microphone combo jack (stereo, 3.5mm), one optional media card reader											
PCIe Mini Card	Two PCI Express® Mini Card slots											
PCIe WLAN	Some: 11b/g/n wireless, Intel Centrino® Wireless-N 2230, Wi-Fi + BT4.0 combo, 2x2 Some: 11b/g/n wireless, Intel Wireless-N 7260, Wi-Fi + BT4.0 combo, 2x2											
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel Wi-Fi + Bluetooth combo adapter											
Ethernet	One gigabit ethernet port, Intel I217-V, Wake on LAN®											
Audio support	High Definition (HD) Audio, Realtek ALC283CG / two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified											
Intel AMT	None											
Security chip	None											
Keyboard	Ultraslim Plus Wireless Keyboard (2.4GHz via USB receiver), black											
Mouse	Ultraslim Plus Wireless Mouse (2.4GHz via USB receiver), black											
Power supply	180 watts, autosensing, 92% PSU											
Color	Business black color											
VESA mount	Support VESA mount (100mm)											
Dimensions and weight (without stand)	<i>Non-touch models (WxDxH):</i> 21.02" X 1.91" X 15.20"; 534mm X 48.5mm X 386 mm 14.55 lb (6.6 kg) in maximum configuration <i>Touch models (WxDxH):</i> 21.02" X 1.95" X 15.20"; 534mm X 49.6mm X 386 mm 16.31 lb (7.4 kg) in maximum configuration											
Stand	<i>Optional Frame Stand:</i> Adjustable between 10° and 65° (Tilt) <i>Optional Monitor Stand:</i> Adjustable between -5° and 45° (Tilt) <i>Optional UltraFlex Stand:</i> Tilt: 65° back, 0° forward; Lift: 110mm; Swivel: +/-90°; supports recline mode (from an upright position to an angled plane) and cable management											
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											ENERGY STAR® 6.0-compliant EuP 2013 GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies

See footnotes for important warranty information

©Lenovo
(G-TRPL1-9) July 2014

ThinkCentre E93z (10BA) - Touch (NVIDIA) - TopSeller (Win8)

Product Specifications Reference (PSREF)

Type-model	Pro-processor	Memory ⁸	Wide-screen display	Multi-Touch	Camera (mega-pixel)	Disk SATA GB rpm	SATA optical	Graphics	PCIe Mini Card	Media reader	Stand type	Key-board/Mouse Global	Preload	Ann date (mm/dd/yy)	
10BA002M++	i5-4330S	4GBx1	21.5" FHD	Touch	2.0M	500G Hybrid	DVD±RW	GT 720A	N2230	Media	UltraFlex	2.4G	None	Win8 Pro64	09/10/13

Country Code^{9,10}: AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)

Note: models listed above might not be available in all WE countries

- Small and medium business (SMB) model(s), part of the Western Europe TopSeller™ Program
- 1-year limited warranty

Positioning	<i>Premium All-In-One PC for the enterprise</i>										Preloaded operating system			
Processor	Intel® Core™ i5-4430S Processor (4 cores / 4 threads, 2.7GHz, 6MB cache), Turbo Boost 2.0 (3.2GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller										Windows® 8 Pro 64-bit			
Implementation	Processor in LGA1150 socket										Web install applications (only some listed)			
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)										<ul style="list-style-type: none"> • Password Manager 			
Graphics	NVIDIA® Optimus™ technology, auto-switch between discrete and integrated graphics, Intel HD Graphics 4400/4600 in processor, and NVIDIA GeForce® GT 720A , PCI Express® x16, 1GB memory, DirectX® 11, external digital monitor support via HDMI, supports dual independent display; <i>Max resolution: 1920x1080 (panel)@60Hz; 1920x1080 (HDMI)@60Hz</i>										Preloaded applications (only some listed)			
Display	21.5" (546.1mm) Full HD 1080p (1920x1080) TFT color , wide viewing angle (+/- 85°), LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, infinity display, work as standalone monitor via HDMI-in connector										<ul style="list-style-type: none"> • ThinkVantage System Update • ThinkVantage AutoLock • Desktop Power Manager • View Management Utility • Lenovo Cloud Storage by SugarSync • Lenovo Solution Center • Lenovo Support • Lenovo Companion • Norton Internet Security (30 days of virus definitions) • Skype™ • Microsoft Office preloaded; purchase a product key to activate • Cyberlink PowerDVD (DVD±RW, DVD) • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) • Evernote® • Lenovo Solutions for Small Business • Nitro Pro • AccuWeather • Norton™ Studio 			
Light sensor	None													
Multi-touch	Projected Capacitive Touch (PCT) technology, supports 10-point multi-touch													
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, supports 1080p, with dual array digital microphone, LED indicator, physical switch on/off													
Controls	Monitor mode / computer mode button, volume up/down buttons, and power button													
Disk	500GB (5400 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 2.5" wide													
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable													
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector and one SATA 3.0Gb/s connector on planar													
Media reader	Optional 11-in-1 media card reader													
Chipset	Intel B85 Express Chipset													
Rear ports	Four USB 2.0, ethernet (RJ-45), HDMI-out, HDMI-in													
Side ports	Two USB 3.0 (one Always On USB 3.0), one headphone / microphone combo jack (stereo, 3.5mm), one optional media card reader													
PCIe Mini Card	Two PCI Express® Mini Card slots													
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2													
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel Wi-Fi + Bluetooth combo adapter													
Ethernet	One gigabit ethernet port, Intel I217-V, Wake on LAN®													
Audio support	High Definition (HD) Audio, Realtek ALC283CG / two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified													
Intel AMT Security chip	None													
Keyboard	Ultraslim Plus Wireless Keyboard (2.4GHz via USB receiver), black													
Mouse	Ultraslim Plus Wireless Mouse (2.4GHz via USB receiver), black													
Power supply	180 watts, autosensing, 92% PSU													
Color	Business black color										Security			
VESA mount	Support VESA mount (100mm)										<ul style="list-style-type: none"> • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement 			
Dimensions and weight (without stand)	<i>Non-touch models (WxDxH):</i> 21.02" X 1.91" X 15.20"; 534mm X 48.5mm X 386 mm 14.55 lb (6.6 kg) in maximum configuration <i>Touch models (WxDxH):</i> 21.02" X 1.95" X 15.20"; 534mm X 49.6mm X 386 mm 16.31 lb (7.4 kg) in maximum configuration										ENERGY STAR® 6.0-compliant			
Stand	<i>Optional Frame Stand:</i> Adjustable between 10° and 65° (Tilt) <i>Optional Monitor Stand:</i> Adjustable between -5° and 45° (Tilt) <i>Optional UltraFlex Stand:</i> Tilt: 65° back, 0° forward; Lift: 110mm; Swivel: +/-90°; supports recline mode (from an upright position to an angled plane) and cable management										EuP 2013			
Limited Warranty	1-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available										GREENGUARD® certified			
											RoHS-compliant			
											Supports ThinkVantage Technologies			

See footnotes for important warranty information
WE model(s) announced September 10, 2013

©Lenovo
(G-TRPL1-4) September 2013

ThinkCentre E93z (10BA) - Touch (NVIDIA) - TS (Win8) - 3-year

Product Specifications Reference (PSREF)

Type-model	Pro-processor	Memory ⁸	Wide-screen display	Multi-Touch	Camera (mega-pixel)	Disk SATA GB rpm	SATA optical	Graphics	PCIe Mini Card WLAN	Media reader	Stand type	Key-board/Mouse Global	Preload	Ann date (mm/dd/yy)	
10BA003C++	i5-4430S	4GBx1	21.5" FHD	Touch	2.0M	500G Hybrid	DVD±RW	GT 720A	N2230	Media	UltraFlex	USB	None	Win8 Pro64	09/10/13

Country Code⁹++ : AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)

Note: models listed above might not be available in all WE countries

- Small and medium business (SMB) model(s), part of the Western Europe TopSeller™ Program
- 3-year limited warranty

Positioning	<i>Premium All-In-One PC for the enterprise</i>											Preloaded operating system
Processor	Intel® Core™ i5-4430S Processor (4 cores / 4 threads, 2.7GHz, 6MB cache), Turbo Boost 2.0 (3.2GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller											Windows® 8 Pro 64-bit
Implementation	Processor in LGA1150 socket											Web install applications (only some listed)
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)											<ul style="list-style-type: none"> • Password Manager
Graphics	NVIDIA® Optimus™ technology, auto-switch between discrete and integrated graphics, Intel HD Graphics 4400/4600 in processor, and NVIDIA GeForce® GT 720A , PCI Express® x16, 1GB memory, DirectX® 11, external digital monitor support via HDMI, supports dual independent display; <i>Max resolution: 1920x1080 (panel)@60Hz; 1920x1080 (HDMI)@60Hz</i>											Preloaded applications (only some listed)
Display	21.5" (546.1mm) Full HD 1080p (1920x1080) TFT color , wide viewing angle (+/- 85°), LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, infinity display, work as standalone monitor via HDMI-in connector											<ul style="list-style-type: none"> • ThinkVantage System Update • ThinkVantage AutoLock • Desktop Power Manager • View Management Utility • Lenovo Cloud Storage by SugarSync • Lenovo Solution Center • Lenovo Support • Lenovo Companion • Norton Internet Security (30 days of virus definitions) • Skype™ • Microsoft Office preloaded; purchase a product key to activate • Cyberlink PowerDVD (DVD±RW, DVD) • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) • Evernote® • Lenovo Solutions for Small Business • Nitro Pro • AccuWeather • Norton™ Studio
Light sensor	None											
Multi-touch	Projected Capacitive Touch (PCT) technology, supports 10-point multi-touch											
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, supports 1080p, with dual array digital microphone, LED indicator, physical switch on/off											
Controls	Monitor mode / computer mode button, volume up/down buttons, and power button											
Disk	500GB (5400 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 2.5" wide											
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable											
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector and one SATA 3.0Gb/s connector on planar											
Media reader	Optional 11-in-1 media card reader											
Chipset	Intel B85 Express Chipset											
Rear ports	Four USB 2.0, ethernet (RJ-45), HDMI-out, HDMI-in											
Side ports	Two USB 3.0 (one Always On USB 3.0), one headphone / microphone combo jack (stereo, 3.5mm), one optional media card reader											
PCIe Mini Card	Two PCI Express® Mini Card slots											
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2											
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel Wi-Fi + Bluetooth combo adapter											
Ethernet	One gigabit ethernet port, Intel I217-V, Wake on LAN®											
Audio support	High Definition (HD) Audio, Realtek ALC283CG / two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified											
Intel AMT Security chip	None											
Keyboard	Preferred Pro USB Keyboard (USB connector), Lenovo® logo											
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo											
Power supply	180 watts, autosensing, 92% PSU											
Color	Business black color											
VESA mount	Support VESA mount (100mm)											
Dimensions and weight (without stand)	<i>Non-touch models (WxDxH):</i> 21.02" X 1.91" X 15.20"; 534mm X 48.5mm X 386 mm 14.55 lb (6.6 kg) in maximum configuration <i>Touch models (WxDxH):</i> 21.02" X 1.95" X 15.20"; 534mm X 49.6mm X 386 mm 16.31 lb (7.4 kg) in maximum configuration											Security <ul style="list-style-type: none"> • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement
Stand	<i>Optional Frame Stand:</i> Adjustable between 10° and 65° (Tilt) <i>Optional Monitor Stand:</i> Adjustable between -5° and 45° (Tilt) <i>Optional UltraFlex Stand:</i> Tilt: 65° back, 0° forward; Lift: 110mm; Swivel: +/-90°; supports recline mode (from an upright position to an angled plane) and cable management											ENERGY STAR® 6.0-compliant EuP 2013
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies

See footnotes for important warranty information
WE model(s) announced September 10, 2013

©Lenovo
(G-TRPL1-5) September 2013

ThinkCentre E93z (10B8) - 3-year Onsite

Product Specifications Reference (PSREF)

Type-model	Pro-processor	Memory ⁸	Wide-screen display	Multi-Touch	Camera (mega-pixel)	Disk SATA GB rpm	SATA optical	Graphics	PCIe Mini Card WLAN	Media reader	Stand type	Key-board/Mouse	Preload	Ann date (mm/dd/yy)
10B8006H++	i7-4770S	4GBx1	21.5" FHD	None	2.0M	500G Hybrid	DVD±RW	HD 4600	N7260	Media	Frame	2.4G Win7 Pro64	DG Win8.1	12/24/13

Country Code"++": AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)

Note: models listed above might not be available in all WE countries

●3-year limited warranty

Positioning	<i>Premium All-In-One PC for the enterprise</i>											Preloaded operating system
Processor	Intel® Core™ i7-4770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller											Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit
Implementation	Processor in LGA1150 socket											Ready to install applications (only some listed)
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)											<ul style="list-style-type: none"> Rescue and Recovery™ Password Manager
Graphics	Intel HD Graphics 4400/4600 in processor, uses main memory, DirectX® 11.1, external digital monitor support via HDMI, supports dual independent display;											Preloaded applications (only some listed)
Display	<i>Max resolution:</i> 1920x1080 (panel) @60Hz; 1920x1080 (HDMI) @60Hz 21.5" (546.1mm) Full HD 1080p (1920x1080) TFT color , wide viewing angle (+/- 85°), LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, infinity display, work as standalone monitor via HDMI-in connector											<ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage System Update ThinkVantage Communication Utility ThinkVantage Device Experience ThinkVantage AutoLock Desktop Power Manager View Management Utility Lenovo Cloud Storage by SugarSync Lenovo Solution Center Lenovo Message Center Plus Norton™ Internet Security (30 days of virus definitions) Adobe® Reader® Skype™ Microsoft Office preloaded; purchase a product key to activate Cyberlink PowerDVD (DVD±RW, DVD) Cyberlink Power2Go (DVD±RW) Cyberlink PowerProducer (DVD±RW) Evernote Lenovo Solutions for Small Business Nitro Pro
Light sensor	None											
Multi-touch	None											
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, supports 1080p, with dual array digital microphone, LED indicator, physical switch on/off											
Controls	Monitor mode / computer mode button, volume up/down buttons, and power button											
Disk	<i>Some:</i> 500GB (5400 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 2.5" wide											
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable											
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector and one SATA 3.0Gb/s connector on planar											
Media reader	Optional 11-in-1 media card reader											
Chipset	Intel B85 Express Chipset											
Rear ports	Four USB 2.0, ethernet (RJ-45), HDMI-out, HDMI-in											
Side ports	Two USB 3.0 (one Always On USB 3.0), one headphone / microphone combo jack (stereo, 3.5mm), one optional media card reader											
PCIe Mini Card	Two PCI Express® Mini Card slots											
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Wireless-N 7260, Wi-Fi + Bluetooth combo adapter, 2x2											
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel Wi-Fi + Bluetooth combo adapter											
Ethernet	One gigabit ethernet port, Intel I217-V, Wake on LAN®											
Audio support	High Definition (HD) Audio, Realtek ALC283CG / two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified											
Intel AMT	None											
Security chip	None											
Keyboard	Ultraslim Plus Wireless Keyboard (2.4GHz via USB receiver), black											
Mouse	Ultraslim Plus Wireless Mouse (2.4GHz via USB receiver), black											
Power supply	150 watts, autosensing, 85% PSU											
Color	Business black color											
VESA mount	Support VESA mount (100mm)											
Dimensions and weight (without stand)	<i>Non-touch models (WxDxH):</i> 21.02" X 1.91" X 15.20"; 534mm X 48.5mm X 386 mm 14.55 lb (6.6 kg) in maximum configuration <i>Touch models (WxDxH):</i> 21.02" X 1.95" X 15.20"; 534mm X 49.6mm X 386 mm 16.31 lb (7.4 kg) in maximum configuration											Security
Stand	<i>Optional Frame Stand:</i> Adjustable between 10° and 65° (Tilt) <i>Optional Monitor Stand:</i> Adjustable between -5° and 45° (Tilt) <i>Optional UltraFlex Stand:</i> Tilt: 65° back, 0° forward; Lift: 110mm; Swivel: +/-90°; supports recline mode (from an upright position to an angled plane) and cable management											<ul style="list-style-type: none"> Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse Individual USB port disablement
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available											ENERGY STAR® 6.0-compliant EuP 2013 GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies

See footnotes for important warranty information
WE model(s) announced December 24, 2013

©Lenovo
(G-TRPL1-11) January 2014

ThinkCentre E93z (10BA) - Touch (NVIDIA) - (Win8.1) - 3-year

Product Specifications Reference (PSREF)

Type-model	Pro-processor	Memory ⁸	Wide-screen display	Multi-Touch	Camera (mega-pixel)	Disk SATA GB rpm	SATA optical	Graphics	PCIe Mini Card WLAN	Media reader	Stand type	Key-board/Mouse Global	Preload	Ann date (mm/dd/yy)	
10BA005N++	i7-4770S	4GBx1	21.5" FHD	Touch	2.0M	500G Hybrid	DVD±RW	GT 720A	N7260	Media	UltraFlex	2.4G	None	Win8.1 Pro64	12/10/13

Country Code⁹++ : AT (Austria), FR (France), GB (Germany w/ English OS), GE (Germany w/ German OS), IV (Israel), IW (Iceland), IX (Italy), MB (Belgium), MD (Denmark), MH (Netherlands), ML (Luxembourg), MN (Norway), MS (Sweden), MZ (Switzerland), NX (Netherlands), PG (Portugal), SP (Spain), UK (United Kingdom)

Note: models listed above might not be available in all WE countries

●3-year limited warranty

Positioning Processor	<i>Premium All-In-One PC for the enterprise</i> Intel® Core™ i7-4770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller	Preloaded operating system Windows® 8.1 Pro 64-bit Web install applications (only some listed) <ul style="list-style-type: none"> • Password Manager Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage System Update • ThinkVantage AutoLock • Desktop Power Manager • Lenovo Solution Center • Lenovo Support • Lenovo Companion • Norton Internet Security (30 days of virus definitions) • Skype™ • Microsoft Office preloaded; purchase a product key to activate • Cyberlink PowerDVD (DVD±RW, DVD) • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) • Evernote® • Lenovo Solutions for Small Business • Nitro Pro • AccuWeather • Norton™ Studio • Pokki • Hightail
Implementation	Processor in LGA1150 socket	
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)	
Graphics	NVIDIA® Optimus™ technology, auto-switch between discrete and integrated graphics, Intel HD Graphics 4400/4600 in processor, and NVIDIA GeForce® GT 720A , PCI Express® x16, 1GB memory, DirectX® 11, external digital monitor support via HDMI, supports dual independent display; <i>Max resolution: 1920x1080 (panel)@60Hz; 1920x1080 (HDMI)@60Hz</i>	
Display	21.5" (546.1mm) Full HD 1080p (1920x1080) TFT color , wide viewing angle (+/- 85°), LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, infinity display, work as standalone monitor via HDMI-in connector	
Light sensor	None	
Multi-touch	Projected Capacitive Touch (PCT) technology, supports 10-point multi-touch	
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, supports 1080p, with dual array digital microphone, LED indicator, physical switch on/off	
Controls	Monitor mode / computer mode button, volume up/down buttons, and power button	
Disk	500GB (5400 rpm) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 2.5" wide	
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable	
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector and one SATA 3.0Gb/s connector on planar	
Media reader	Optional 11-in-1 media card reader	
Chipset	Intel B85 Express Chipset	
Rear ports	Four USB 2.0, ethernet (RJ-45), HDMI-out, HDMI-in	
Side ports	Two USB 3.0 (one Always On USB 3.0), one headphone / microphone combo jack (stereo, 3.5mm), one optional media card reader	
PCIe Mini Card	Two PCI Express® Mini Card slots	
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Wireless-N 7260, Wi-Fi + Bluetooth combo adapter, 2x2	
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel Wi-Fi + Bluetooth combo adapter	
Ethernet	One gigabit ethernet port, Intel I217-V, Wake on LAN®	
Audio support	High Definition (HD) Audio, Realtek ALC283CG / two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified	
Intel AMT Security chip	None	
Keyboard	Ultraslim Plus Wireless Keyboard (2.4GHz via USB receiver), black	
Mouse	Ultraslim Plus Wireless Mouse (2.4GHz via USB receiver), black	
Power supply	180 watts, autosensing, 92% PSU	
Color	Business black color	
VESA mount	Support VESA mount (100mm)	
Dimensions and weight (without stand)	<i>Non-touch models (WxDxH):</i> 21.02" X 1.91" X 15.20"; 534mm X 48.5mm X 386 mm 14.55 lb (6.6 kg) in maximum configuration <i>Touch models (WxDxH):</i> 21.02" X 1.95" X 15.20"; 534mm X 49.6mm X 386 mm 16.31 lb (7.4 kg) in maximum configuration	
Stand	<i>Optional Frame Stand:</i> Adjustable between 10° and 65° (Tilt) <i>Optional Monitor Stand:</i> Adjustable between -5° and 45° (Tilt) <i>Optional UltraFlex Stand:</i> Tilt: 65° back, 0° forward; Lift: 110mm; Swivel: +/-90°; supports recline mode (from an upright position to an angled plane) and cable management	
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding public and national holidays. Calls received after 3 pm will require an additional next business day for service dispatch / service upgrades available	
		Security <ul style="list-style-type: none"> • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement ENERGY STAR® 6.0-compliant EuP 2013 GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies

See footnotes for important warranty information
WE model(s) announced December 10, 2013

©Lenovo
(G-TRPL1-10) December 2013

Disclaimer

Lenovo provides the information in the Product Specifications Reference (PSREF) withdrawn product books on an "AS-IS" basis. Because the actual products have been withdrawn from marketing, the information in these withdrawn product books is no longer maintained or updated. The referenced footnote numbering may not correspond with the listed footnotes.

PSREF books for the withdrawn systems:

http://www.lenovo.com/psref/psrefs_withdrawn.html

- Availability:** All offers subject to availability. Lenovo reserves the right to alter product offerings and specifications at any time, without notice. Lenovo is not responsible for photographic or typographic errors.
- Warranty:** For a copy of applicable product warranties, go to http://support.lenovo.com/en_US/product-service/warranty-status/WarrantyPolicies.page. Lenovo makes no representation or warranty regarding third party products or services.
- ¹ **Limited warranty:** Support unrelated to a warranty issue may be subject to additional charges.
 - ² **Hard drive:** GB = billion bytes, TB = trillion bytes. Accessible capacity is less; up to 4GB is service partition.
 - ³ **Limited onsite service systems** are designed to be repaired during the applicable warranty period primarily with customer-replaceable parts provided by Lenovo. Lenovo will only send a technician onsite to perform a repair if (a) remote telephone diagnosis and/or customer part replacement are unable to resolve the problem, or (b) the part is one of the few designated by Lenovo for onsite replacement. For a list of onsite replaceable parts, contact Lenovo. Support unrelated to a warranty issue may be subject to additional charges. Lenovo onsite repair (LOR), 8 am to 5 pm, Monday through Friday coverage excluding holidays, next business day (NBD) response time.
 - ⁴ **CD and DVD list** maximum rates; rates are variable and are often less than the maximum.
 - ⁵ **Included software** may differ from its retail version (if available), and may not include user manuals or all program functionality. License agreements may apply.
 - ⁷ **Lenovo Services:** These services are available for machines normally used for business, professional, or trade purposes, rather than personal, family, or household purposes. Not all machine types and models are covered. Service period begins with the equipment date of purchase. Service must be purchased during the original limited product warranty period. Service levels are response time objectives and are not guarantees. If the machine problem turns out to be a Customer Replaceable Unit (CRU), a part will be express shipped to you for quick replacement. Onsite 24x7x2-hour service is not available in all locations. P&L means parts and labor. P/U means pick-up. See Lenovo terms and conditions for complete details and restrictions.
 - ⁸ **Memory:** For PCs without a separate graphics card, memory supports both system and video. Accessible system memory may be up to 384MB less than the amount stated, depending on video mode.
 - ⁹ **International Warranty Service** is available in any country in which this product is sold and serviced. Service delivery methods and parts availability vary by country, may be different from that in the country of purchase, and are subject to change without notice. Fees and restrictions may apply in some countries.
 - ¹⁰ **Modem speeds:** Public network download speeds are limited to 53Kbps. Upload speeds are limited to 48Kbps for V.92 modems. Actual speeds depend on many factors and are often less than the maximum possible. V.92 functions and speeds require compatible phone line and server equipment. Check with your telephone and ISP service providers for availability.
 - ¹¹ **For combination drives**, maximum speeds only are given in the following order: CD read, CD write, CD re-write, DVD read.
 - ¹² **The IEEE 802.11n specification (MIMO)** has been finalized and is currently in IEEE 802.11n-2009 release. The maximum speed depends on the access point device and the number of integrated antenna used for connection. An adapter with 11a/b, 11a/b/g, 11b/g/n, or 11a/b/g/n can communicate on any of its supported formats.
 - ¹³ **Wireless capability:** Requires compatible wireless-enabled options sold separately.
 - ¹⁴ **Response times may vary.** May exclude some holidays. Telephone support may be subject to additional charges.
 - ¹⁵ **Update Connector** is available at no charge to registered customers during the limited warranty period. Line charges may apply.
 - ¹⁶ **Embedded Security Subsystem** works with optional VPN software.

- ¹⁸ **Embedded Security Subsystem** may require download of client security software from the Web.
- ¹⁹ **Asset ID** allows system-specific information to be stored in a chip inside the system; it does not have any radio frequency support.
- ²⁰ **Operating System:** Level of support varies by operating system. Operating systems not preloaded on the system may not provide full feature functionality. Refer to lenovo.com/pc/support and enter your machine type and model number for more information.

This publication was developed for products and services offered in the United States. Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifications and other product information at any time without prior notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions; therefore this disclaimer may not apply to you.

ThinkCentre®

Trademarks: Lenovo, the Lenovo logo, New World. New Thinking., Access Connections, Rescue and Recovery, ThinkCentre, ThinkPad, ThinkVantage, and ThinkVision are trademarks of Lenovo. Microsoft, Windows, and Vista are registered trademarks of Microsoft Corporation. Intel, the Intel logo, Intel Inside logo, Intel Core and Core Inside are trademarks of Intel Corporation in the US and other countries. Other company, product, or service names may be trademarks or service marks of others.

Visit www.lenovo.com/safecomputing periodically for the latest information on safe and effective computing.

Visit www.lenovo.com/psref for the latest version of Product Specifications Reference.

© Lenovo, 2014.
All rights reserved.

Lenovo
1009 Think Place
Morrisville, NC 27560
U.S.A.

tcbook_WE.pdf