

Thin Client

# Atomino Series



## Atomino, the smallest Thin Client powered by Intel Atom 1.6 GHz

Ideal Thin Client to access Virtual Desktop Infrastructure requiring high performance

- Ideal workstation to access any centralized infrastructure, integrates support towards **VMware View** with **PCoIP** protocol or **Citrix XenApp, XenDesktop**
- **Very low power consumption**, is a green solution, only **13W**
- **High reliability** and **easy remote management** provide a lower Total Cost of Ownership (TCO) than a traditional PC or laptop
- **Simple and Secure** access to company applications, without the risk of Virus infection
- **Very small dimension**, including DVI-I or VGA with dual monitor support, 4 USB external ports
- **WiFi built-in support**, with external antenna allows you to offer a very compact full optional wireless workstation
- **Display resolution up to 1920 x 1440** with 4:3 and 16:9 wide screen support
- **LCD VESA** mounting on the back of the monitor

### CERTIFIED FOR



### OPERATING SYSTEM



Transforming Enterprise Computing

ITALY (HQ)

PRAIM SRL - VIA EZIO MACCANI, 191  
38121 TRENTO (TN)  
ITALY

p: +39 0461 420517 | f: +39 0461 420581

INFO@PRAIM.COM - WWW.PRAIM.COM

UNITED KINGDOM

PRAIM LTD - LAKESIDE HOUSE, 1 FURZEGROUND WAY  
STOCKLEY PARK, UXBIDGE, UB11 1BD  
UNITED KINGDOM

p: +44 (0)20-8622 3031 | f: +44 (0)20-8622 3303

INFO@PRAIM.COM - WWW.PRAIM.CO.UK

Technical specifications		XT9050-A	XP9400-A	WE9700-A	PX1000-A
P/N		80X9051110	80W9401110	80W9700110	80P1001110
Processor/ Chipset		Intel Atom N270 1.6GHz / Intel 945GSE + ICH7-M			
Power supply		external 100/240VAC 50/60Hz, 12VDC / 4A max			
Power consumption: on / stand-by		13W / 1.95W standard version, 15W / 1.95W with built-in wireless			
Device dim, weight / Packaging dim, weight		15,6(H) x 12,2(P) x 3,6(L) cm, 0,75 Kg / 22,1(H) x 23,2(P) x 8,5(L) cm, 1,520 Kg			
Device certifications / Power Supply certification		CE, FCC Class B, Energy Star 5.0 / CE, FCC Class B, GS TUV,UL			
Temperature range / humidity		0° ÷ 35° / 20% ÷ 80%			
Security lock		kensington			
Operating System		ThinOX V8	XP Embedded SP3	WES7 SP1	PXE Boot
RAM Memory / Flash memory		1GB / 512MB	1GB / 2GB	2GB / 4GB	1GB / --
Display res. with DDC, 4:3, 16:10 WIDE ratio		1920 x 1440			
Colors		from 256 to 16,8 Milion			
Peripherals					
USB ports / LAN Ethernet		4 USB 2.0 ports (2 front + 2 rear) / 10/100/1000 BaseT Ethernet RJ45			
Monitor		1 DVI-I port with DVI to VGA included			
PS/2 Mouse and keyboard		1 PS/2 port, PS/2 mouse and keyboard adapter included, optical mouse included			
Audio In MIC / Audio Out Headphones		1 x 1/8 inch jack / 1 x 1/8 inch jack			
802.11b/g/n built in wireless		Factory Option			
Built-in speaker		Built-in speaker 1 W			
Protocols and resident clients					
TCP/IP, DNS, DHCP, FTP, SNMP MIB II		•	•	•	--
802.1X Ethernet EAP/PEAP MSCHAPV		•	•	•	--
Cisco VPN Client		•	◊	◊	--
Client RDP		7.0	7.0	7.1	--
Client VMware View 5.0		RDP/PCoIP	RDP/PCoIP	RDP/PCoIP	--
Citrix ICA / PN Agent / Receiver		ICA 12	Receiver 3.0	Receiver 3.1	--
Virtual Bridges VERDE 5.5		SPICE	◊	◊	--
Ericom PowerTerm WebConnect Client		•	•	•	--
Leostream Client \ Provision Networks VAS		•	◊	◊	--
Browser		Firefox 11	IE 7.0	IE 8.0	--
Local PDF Viewer		Acrobat 7	Acrobat 7	◊	--
Microsoft .NET Framework			2.0	2.0-3.0-3.5	--
Media Player, Wordpad			•	•	--
E-mail client		Thunderbird 2.0	Outlook express		--
JVM		SUN 1.6	◊	◊	--
Flash Player		Adobe 11	◊	◊	--
Local voip Skype Client		•	◊	◊	--
NX Nomachine Client		•		◊	--
X11 nativo Client		•	◊		--
Propalms TSE Client		•	◊	◊	--
VNC Client		•		◊	--
Shell script sessions		•			--
CUPS printing support		•	•		--
LPD/LPR and RAW		•	•	•	--
User disk partition		50MB	~ 1GB	~ 1.5GB	--
Praim USB re-direction support		□	□	□	
Supported Operating Systems					
Citrix Metaframe 1.7, 1.8, XP, PS 4, 4.5		•	•	•	--
Citrix XenApp 6.0, XenDesktop 4.0, 5.0		•	•	•	--
Microsoft Windows 2000/2003/2008 TS		•	•	•	--
Unix/Linux/AIX, NX NoMachine Server		•	◊	◊	--
IBM AS/400, IBM S/390			Opt Net2000	Opt Net2000	--
Administration					
Remote management via Praim ThinMan		Freeware	Freeware	Freeware	--
FW upgrade / VNC shadowing / Wake On LAN		•	•	•	--
Screen saver with password		•	•	•	--
Options		P/N	P/N	P/N	P/N
External USB WiFi USB 802.11b/g dongle		80AC00031	80AC00031	80AC00031	80AC00031
Built-in wireless 802.11b/g		80AC00060	80AC00060	80AC00060	80AC00060
Built-in wireless 802.11b/g/n		80AC00063	80AC00063	80AC00063	80AC00063
Dual monitor optl cable adapter DVI-I to DVI/VGA		80EC00019	80EC00019	80EC00019	80EC00019
USB to Parallel cable adapter		80EC00012	80EC00012	80EC00012	80EC00012
Flash disk expansion		-	4GB	-	-
RAM memory DDR2 expansion		1GB, 2GB	2GB	-	1GB, 2GB
105 keys PS/2 PC keyboard		89T110001	89T110001	89T110001	89T110001
105 keys PS/2 PC/5250 keyboard		89T110002	89T110002	89T110002	89T110002
Praim Media streaming codecs Add-On		76AC00006	-	-	-
VESA mounting KIT		80EC00027	80EC00027	80EC00027	80EC00027
Warranty					
1 year ex-factory. Free 2 year warranty extension when the product is registered on the Praim web site					
Note:	• Available	◊ Installable from the user based on available free disk space	□	Requires ThinMan Enterprise Edition	

All names and trademarks contained in this document, are property of their respective owners. The information in this document is property of Praim SRL.

Ver. 1.32



Transforming Enterprise Computing

ITALY (HQ)

UNITED KINGDOM

PRAIM SRL - VIA EZIO MACCANI, 191  
38121 TRENTO (TN)  
ITALY

PRAIM LTD - LAKESIDE HOUSE, 1 FURZEGROUND WAY  
STOCKLEY PARK, UXBURIDGE, UB11 1BD  
UNITED KINGDOM

p: +39 0461 420517 | f: +39 0461 420581

p: +44 (0)20-8622 3031 | f: +44 (0)20-8622 3303

INFO@PRAIM.COM - WWW.PRAIM.COM

INFO@PRAIM.COM - WWW.PRAIM.CO.UK