

Rangee LT360



1,6 GHz Intel Atom	1024 MB RAM	8 GB Flash
8 x USB 2.0	DVI-D VGA	external power adapter
Rangee Linux	Dual- monitor	Audio-In Audio-Out

LT360 series

With the LT360 Rangee complies all demands on a modern Thin Client workstation.

It is equipped with a powerful and highly energy-efficient 1.6 GHz Intel Atom processor what makes the LT360 to the ideal Thin Client for all fields of application.

A smartcard-reader can be integrated optionally.

Six different models

	Processor	RAM	Flash/DOM Memory	Operating System	Software-Modules	Price
LT360-PXE	Intel Atom 1,6 GHz	1GB DDR2	-	-	-	235,00€ excl. VAT. 279,65€ incl. VAT.
R-LT360-L	Intel Atom 1,6 GHz	1GB DDR2	8GB	Rangee Linux	one softwaremodule of own choice *	278,00€ excl. VAT. 330,82€ incl. VAT.
S-LT360-L	Intel Atom 1,6 GHz	1GB DDR2	8GB	Rangee Linux	ICA, RDP, VMware View and Mozilla Firefox	296,00€ excl. VAT. 352,24€ incl. VAT.
X-LT360-L	Intel Atom 1,6 GHz	2GB DDR2	8GB	Rangee Linux	all available softwaremodules *	348,00€ excl. VAT. 414,12€ incl. VAT.
R-LT360-STB	Intel Atom 1,6 GHz	1GB DDR2	8GB	Rangee Linux	RDP	310,00€ excl. VAT. 368,90€ incl. VAT.
X-LT360-ES	Intel Atom 1,6 GHz	2GB DDR2	8GB	Windows 7 Embedded Standard	ICA, RDP and Internet Explorer	424,00€ excl. VAT. 504,56€ incl. VAT.

Technical specifications

System

Processor	Intel Atom N270 1,6GHz CPU
RAM	1GB SO DIMM DDR2 RAM
Flash/DOM Memory	8GB (not with PXE-model)

Graphic

Max. Resolution	Up to 1920 x 1200 at 60Hz
Video Memory	32MB shared memory
Graphic Ports	1 x DVI-D, 1 x VGA (DB-15)
Dual-Monitor	Yes (over DVI and VGA)

Audio

Ports	1 x Audio-In, 1 x Audio-Out
-------	-----------------------------

Interfaces

USB 2.0	8 x USB 2.0 (2 x front, 6 x back)
PS/2	1 x PS/2 for keyboard
Serial / Parallel	1 x serial / 1 x parallel

Network

Ethernet	1 x 10/100/1000 Mbit LAN RJ-45 Ethernet
Wireless LAN	Support of USB-Sticks and PCI-Cards up to wireless N-Standard

Data

Size (BxHxD)	45 x 205 x 215 mm
Weight	1,4 kg
Cooling	Fanless
Temperature	5°C to 40°C

Power Supply

Power Adapter	External power adapter
Power Input	12V / 5A, 13 Watt

Configuration

Warranty	2 years, extendable up to 5 years
VESA Mount	-
Remote Management	Over Webbrowser and TCMS (optional)
Operating System	Rangee Linux Thin Client OS



front



back

Software

	LT360-PXE	R-LT360-L	S-LT360-L	X-LT360-L	R-LT360-STB	X-LT360-ES
Clients	Citrix ICA / XenAPP		•	•		•
	Remote Desktop RDP		•		•	•
	Xdmcp / Xephir			•		
	X2go			•		
	2X			•		
	NX Nomachine	PXE		•		
	GoGlobal	boot	One	•		
Virtual Desktop	Ericom Terminal Emulation	solution!	softwaremodule of own	•		
	VMware/ PCoIP		•	•		
	Citrix XenDesktop	Without	choice!	•		
	Ericom Webconnect	operating-system!		•		
Multi-media	Local browser		Mozilla Firefox	Mozilla Firefox		Internet Explorer
	Java/Flash		•	•		
	Media Player (VLC, MPlayer)			•		
	VoIP Client (Skype, Ekiga)			•		
VPN	Cisco VPN			•		
	Open VPN			•		
	Shrew VPN			•		

